

1.5 WATT UNREGULATED DC/DC CONVERTER



PWR1726



FEATURES

- 8000V ISOLATION TEST VOLTAGE
- NO EXTERNAL PARTS REQUIRED
- SYNCHRONIZABLE
- REMOTE ON/OFF
- LOW-BARRIER CAPACITANCE

APPLICATIONS

- BIOMEDICAL DATA ACQUISITION
- INDUSTRIAL PROCESS EQUIPMENT
- DATA ACQUISITION
- TEST EQUIPMENT
- PORTABLE EQUIPMENT

DESCRIPTION

The PWR1726 is a single-channel, dual-output DC/DC converter designed for those applications where high-isolation voltage and low-barrier capacitance are critical for system reliability and integrity.

Calculated mean-time-to-failure (MTTF) is in excess of 100 years at an ambient temperature of +25°C and at rated output power. The performance of the PWR1726 is not derated over its entire specified temperature range of -25°C to +85°C.

Synchronization of the PWR1726 may be accomplished simply by connecting the sync pin of one unit to the sync pin of another unit. In this manner, up to eight converters may be ganged together.

The PWR1726 provides a plus and minus output voltage that is approximately equal to the magnitude of the input voltage. The unit operates over an input voltage range of 7Vdc to 18Vdc.

Each PWR1726 isolation barrier is tested per the method set forth by UL544, VDE750, and CSA C22.2.

Internet: <http://www.cdpowerelectronics.com>

Power Electronics Division, United States
3400 E Britannia Drive, Tucson, Arizona 85706
Phone: 520.295.4100 Fax: 520.770.9369

Power Electronics Division, Europe
C&D Technologies (Power Electronics) Ltd.
132 Shannon Industrial Estate, Shannon, Co. Clare, Ireland
Tel: +353.61.474.133 Fax: +353.61.474.141


COMMON SPECIFICATIONS

Specifications typical at $T_A = +25^{\circ}\text{C}$, $V_{IN} = 15\text{VDC}$, $I_{LOAD} = \pm 50\text{mA}$ and in free-running mode unless otherwise noted.

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
INPUT					
Rated Voltage			15		V _{DC}
Voltage Range		7		18	V _{DC}
Input Current	$I_{LOAD} = 0$		30		mA
	$I_{LOAD} = \text{Rated Load}$		145	165	mA
	Short Circuit		115		mA
Ripple Current	$I_{LOAD} = \text{Rated Load}$		15		mAp-p
ISOLATION					
Voltage Rated Continuous					V _{rms}
AC, 60Hz		3500			V _{DC}
DC		5000			Vpk
Test Voltage	60sec, 60Hz	8000			GΩ
Resistance			10		pF
Capacitance			10		μA
Leakage Current	$V_{ISO} = 240\text{VAC}$, 60Hz		1	2	
OUTPUT					
Rated Voltage	$I_{LOAD} = \text{Rated Load}$		±15		V _{DC}
Voltage Range	$I_{LOAD} = \text{Rated Load}$	±14.25		±15.75	V _{DC}
	$I_{LOAD} = 0\text{mA}$	±16.0	±16.5	±18.0	V _{DC}
Rated Current	Balanced Loads		±50		mA
Current Range	Balanced Loads	0		±90	mA
	Single Ended	0		180	mA
Line Regulation	$7\text{VDC} < V_{IN} < 18\text{VDC}$		1.16		mV/mV
Load Regulation	No Load $< I_{OUT} < \pm 50\text{mA}$			0.3	%/mA
Ripple Voltage	BW = DC to 10MHz				mVp-p
	$I_{LOAD} = 0$		15		mVp-p
	$I_{LOAD} = \text{Rated Load}$		50		mVp-p
GENERAL					
MTTF	Calculated per MIL - HDBK - 217 Rev. E				MHr
	Ground, Benign 25°C		1.2		
Switching Frequency			120		kHz
TEMPERATURE					
Specification		-25	+25	+85	$^{\circ}\text{C}$
Operation		-40		+100	$^{\circ}\text{C}$
Storage		-55		+110	$^{\circ}\text{C}$

NOTE: Other input and output voltages may be available upon request. Please consult the factory.

MECHANICAL



ABSOLUTE MAXIMUM RATINGS



Input Voltage	18V _{DC}
Output Short-Circuit Duration	Continuous
Internal Power Dissipation	2W
Lead Temperature (soldering, 10 seconds max)	+300°C

ORDERING INFORMATION


Device Family	PWR	1726	/H
PWR indicates DC/DC converter			
Model Number			
Screening Option			

TYPICAL PERFORMANCE CURVES

TA = +25°C, Rated Input Voltage, Rated Output Current unless otherwise noted.




REMOTE ON/OFF CONTROL



If no connection is made to "Remote ON/OFF" pin, the converter will operate normally.

SYNCHRONIZATION INFORMATION

The unit may be synchronized to an external clock. Recommended frequency is a minimum of 150KHz and a maximum of 225KHz. The sync signal must be a square wave pulse with an amplitude of 0 to +10V. If some other frequency is required, contact factory.



ENGINEERING NOTES

The information provided herein is believed to be reliable; however, C&D TECHNOLOGIES assumes no responsibility for inaccuracies or omissions. C&D TECHNOLOGIES assumes no responsibility for the use of this information, and all use of such information shall be entirely at the user's own risk. Prices and specifications are subject to change without notice. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. C&D TECHNOLOGIES does not authorize or warrant any C&D TECHNOLOGIES product for use in life support devices/systems or in aircraft control applications.