
PF0311

MOS FET Power Amplifier Module for VHF Band

HITACHI

ADE-208-104B (Z)

3rd Edition

July 1996

Application


VHF Band 150 to 174 MHz

Features

- Small package: $30 \times 10 \times 5.9$ mm
- High efficiency: 50% Typ
- Low power control current: 0.5 mA Max

Pin Arrangement


• RF-J



1: Pin
2: V_{PC}
3: V_{DD}
4: P_{out}
5: GND (Flange)

PF0311

Internal Diagram and External Circuit




Absolute Maximum Ratings (T_c = 25°C)

Item	Symbol	Rating	Unit
Supply voltage	V _{DD}	17	V
Supply current	I _{DD}	3	A
PC voltage	V _{PC}	7	V
Input power	Pin	100	mW
Operating case temperature	T _c (op)	-30 to +100	°C
Storage temperature	T _{stg}	-40 to +110	°C


Electrical Characteristics (T_c = 25°C)



Item	Symbol	Min	Typ	Max	Unit	Test Condition
Frequency range	f	150	—	174	MHz	—
Drain cutoff current	I _{DS}	—	—	100	μA	V _{DD} = 17 V, V _{PC} = 0 V, R _L = R _g = 50 Ω,
Total efficiency	η _T	45	55	—	%	Pin = 20 mW, V _{DD} = 9.6 V, Pout = 6.5 W (at V _{PC} controlled), R _L = R _g = 50 Ω, T _c = 25°C
2nd harmonic distortion	2nd H.D.	—	−25	−15	dBc	
3rd harmonic distortion	3rd H.D.	—	−35	−25	dBc	
4th harmonic distortion	4th H.D.	—	−40	−30	dBc	
Input VSWR	VSWR (in)	—	1.5	3.0	—	
Output power (1)	Pout (1)	6.8	7.5	—	W	Pin = 20 mW, V _{DD} = 9.6 V, V _{PC} = 6 V, R _L = R _g = 50 Ω
Output power (2)	Pout (2)	2	3	—	W	Pin = 20 mW, V _{DD} = 6 V, V _{PC} = 5.5 V, R _L = R _g = 50 Ω
Load VSWR tolerance (1)	—	No degradation			—	Pin = 20 mW, V _{DD} = 15 V, Pout ≤ 6.5 W, (at V _{PC} controlled), Output VSWR = 6:1 All phases
Load VSWR tolerance (2)	—	No degradation			—	Pin = 20 mW, V _{DD} = 9.6 V, Pout ≤ 6.5 W, (at V _{PC} controlled), Output VSWR = 20:1 All phases
Stability	—	No parasitic oscillation			—	Pin = 20 mW, V _{DD} = 6 to 15 V, Pout ≤ 6.5 W, (at V _{PC} controlled), Output VSWR = 3:1 All phases,



Mechanical Characteristics



Item	Measuring Conditions	Spec
Torque for screw up the heatsink flange	M2.6 Screw Bolts	1.5 to 3.5 kg•cm
Warp size of the heatsink flange: S		S = 0 +0.1/−0 mm



Characteristic Curves

















PF0311

Package Dimensions

Unit: mm



Hitachi Code	RF-J
JEDEC	—
EIAJ	—
Weight (reference value)	—

When using this document, keep the following in mind:

1. This document may, wholly or partially, be subject to change without notice.
2. All rights are reserved: No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without Hitachi's permission.
3. Hitachi will not be held responsible for any damage to the user that may result from accidents or any other reasons during operation of the user's unit according to this document.
4. Circuitry and other examples described herein are meant merely to indicate the characteristics and performance of Hitachi's semiconductor products. Hitachi assumes no responsibility for any intellectual property claims or other problems that may result from applications based on the examples described herein.
5. No license is granted by implication or otherwise under any patents or other rights of any third party or Hitachi, Ltd.
6. **MEDICAL APPLICATIONS:** Hitachi's products are not authorized for use in **MEDICAL APPLICATIONS** without the written consent of the appropriate officer of Hitachi's sales company. Such use includes, but is not limited to, use in life support systems. Buyers of Hitachi's products are requested to notify the relevant Hitachi sales offices when planning to use the products in **MEDICAL APPLICATIONS**.

HITACHI

Hitachi, Ltd.

Semiconductor & IC Div.
 Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100, Japan
 Tel: Tokyo (03) 3270-2111
 Fax: (03) 3270-5109

For further information write to:

Hitachi America, Ltd.
 Semiconductor & IC Div.
 2000 Sierra Point Parkway
 Brisbane, CA. 94005-1835
 U S A
 Tel: 415-589-8300
 Fax: 415-583-4207

Hitachi Europe GmbH
 Electronic Components Group
 Continental Europe
 Dornacher StraÙe 3
 D-85622 Feldkirchen
 M nchen
 Tel: 089-9 91 80-0
 Fax: 089-9 29 30 00

Hitachi Europe Ltd.
 Electronic Components Div.
 Northern Europe Headquarters
 Whitebrook Park
 Lower Cookham Road
 Maidenhead
 Berkshire SL6 8YA
 United Kingdom
 Tel: 0628-585000
 Fax: 0628-778322

Hitachi Asia Pte. Ltd.
 16 Collyer Quay #20-00
 Hitachi Tower
 Singapore 0104
 Tel: 535-2100
 Fax: 535-1533

Hitachi Asia (Hong Kong) Ltd.
 Unit 706, North Tower,
 World Finance Centre,
 Harbour City, Canton Road
 Tsim Sha Tsui, Kowloon
 Hong Kong
 Tel: 27359218
 Fax: 27306071

Copyright © Hitachi, Ltd., 1997. All rights reserved. Printed in Japan.