

PM5 SERIES

- Available in a wide range of voltages
- Press fit mounting lowers labor and assembly cost
- 6" 24AWG wire leads at no additional cost
- Wide variety of connectors available

Bivar

PM5 SERIES

Mounting Information:

Press-fit mounting in 0.250 [7.11mm] hole

Panel Thickness: 0.047 [1.2mm] to 0.093 [2.4mm]

Material Specifications:

Housing: UL Rated 94V-0, Black, 6 Nylon per ASTM D4066 PA111

Oxygen Index: +28%

Optional Wire Leads: 24AWG U.L. 1007 Cathode-Black, Anode-Red

Application Notes:

Wire leads from 2.5" to 48" are available subject to special quotation please consult Bivar at 1-800-SPACERS for additional information. Many connectors are available as well as customer specified connectors. Subject to quotation.

Ordering Information:

PM5 G D 5V W6 -CC

Series Color Lens Special Leads Options

Color Options and Suffixes:

Suffix	Color	Peak (nm)	Typ. Vf
G	Green	565nm	2.0
H	High Efficiency Red	635nm	2.0
Y	Yellow	585nm	2.0
SR	Super Red	660nm	2.0
O	Orange	635nm	2.0
A	Amber	610nm	2.0
BW	Blue	430nm	3.5
BC	Red/Green Bi-Color	635/565	2.0

Lens Choices:

D	Color Diffused
C	Water Clear
T	Tinted Non-diffused

Special:

L	2ma Low Current
5V	5 Volt integrated resistor
12V	12 Volt integrated resistor

Leads:

"Blank" Terminal Leads

Wx 24AWG Wire Leads

Replace the "X" with the length in inches

Options:

-CC	Standard 0.100" [2.54mm] pitch header connector
-CC2	Miniature 0.075" [2.54mm] pitch header connector

