


Features

- Near-zero propagation delay
- 5Ω switches connect inputs to outputs
- Fast Switching Speed - 5ns (max.)(16292)
- Internal 500Ω pull-down on A2 ports
- Ultra-low quiescent power (0.2μA typical) – Ideally suited for notebook applications
- Vcc Operating Range : 3.0V to 3.6V
- Industrial operating temperature: -40°C to +85°C
- Make-before-break switching
- Packages available:
 - 56-pin 240-mil wide thin plastic TSSOP (A)
 - 56-pin 300-mil wide plastic SSOP (V)

Applications

- Memory switching

Logic Block Diagram



Truth Table

Function	S0	A1	A2
A1 to B1, A2 to B2	L	B1	B2
A1 to B2, A2 to B1	H	B2	B1

Note:

1. H = High Voltage Level
L = Low Voltage Level
Z = High Impedance

Description

Pericom Semiconductor's PI3B series of logic circuits are produced using the Company's advanced 0.35 micron CMOS technology.

The PI3B16292 and PI3B162292 are 3.3 volt, 12-bit to 24-bit Mux/Demux Bus switches designed with a low ON resistance allowing inputs to be connected directly to outputs.

The PI3B162292 device has a built-in 25-ohm series resistor to reduce noise resulting from reflections, thus eliminating the need for an external terminating resistor.

A2 port is not externally connected and, as a result, has an internal 500-ohm pulldown resistor to ground.

Pin Configuration

S0	1	56	NC
1A1	2	55	NC
NC1	3	54	1B1
2A1	4	53	1B2
NC1	5	52	2B1
3A1	6	51	2B2
NC1	7	50	3B1
GND	8	49	GND
4A1	9	48	3B2
NC1	10	47	4B1
5A1	11	46	4B2
NC1	12	45	5B1
6A1	13	44	5B2
NC1	14	43	6B1
7A1	15	42	6B2
NC1	16	41	7B1
VCC	17	40	7B2
8A1	18	39	8B1
GND	19	38	GND
NC1	20	37	8B2
9A1	21	36	9B1
NC1	22	35	9B2
10A1	23	34	10B1
NC1	24	33	10B2
11A1	25	32	11B1
NC1	26	31	11B2
12A1	27	30	12B1
NC1	28	29	12B2

Product Pin Description

Pin Name	I/O	Description
S0	I	Select Inputs
xA1	I/O	Bus A
xBx	I/O	Bus B
NC		Leave it unconnected
NC1		Leave it unconnected

Maximum Ratings

(Above which the useful life may be impaired. For user guidelines, not tested.)

Storage Temperature	–65°C to +150°C
Ambient Temperature with Power Applied	–0°C to +85°C
Supply Voltage Range	–0.5V to +4.6V
DC Input Voltage	–0.5V to +4.6V
DC Output Current	120 mA
Power Dissipation	0.5Watt

Note:

Stresses greater than those listed under MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

DC Electrical Characteristics (Over the Operating Range, T_A = –40°C to +85°C, V_{CC} = 3.0V to 3.6V)

Parameters	Description	Test Conditions ⁽¹⁾		Min.	Typ ⁽²⁾	Max.	Units
V _{IH}	Input HIGH Voltage	Guaranteed Logic HIGH Level		2.0	—	—	V
V _{IL}	Input LOW Voltage	Guaranteed Logic LOW Level		–0.5	—	0.8	V
I _I	Input Current	V _{CC} = Max., V _{IN} = V _{CC} or GND		—	—	±1	μA
		V _{CC} = 0, V _{IN} = V _{CC}		—	—	10	μA
V _{IK}	Clamp Diode Voltage	V _{CC} = Min., I _{IN} = –18mA		—	–0.7	–1.2	V
R _{ON}	Switch On Resistance ⁽³⁾	V _{CC} = Min., V _{IN} = 0.0V, I _{ON} = 64mA	16292	—	5	8	Ω
			162292	20	28	40	
		V _{CC} = Min., V _{IN} = 2.4V, I _{ON} = 15mA	16292	—	10	15	Ω
			162292	20	35	48	

Capacitance (T_A = 25°C, f = 1 MHz)

Parameters ⁽⁴⁾	Description	Test Conditions	Max.	Units
C _{IN}	Input Capacitance	V _{IN} = 0V	3.0	pF
C _{ON}	A/B Capacitance, Switch On	V _{IN} = 0V	30.0	pF

Notes:

1. For Max. or Min. conditions, use appropriate value specified under Electrical Characteristics for the applicable device.
2. Typical values are at V_{CC} = 3.3V, T_A = 25°C ambient and maximum loading.
3. Measured by the voltage drop between A and B pin at indicated current through the switch. ON resistance is determined by the lower of the voltages on the two (A,B) pins.
4. This parameter is determined by device characterization but is not production tested.

Power Supply Characteristics

Parameters	Description	Test Conditions ⁽¹⁾		Min.	Typ ⁽²⁾	Max.	Units
I _{CC}	Quiescent Power Supply Current	V _{CC} = MAX.	V _{IN} = GND or V _{CC}	—	—	10	μA
ΔI _{CC} ⁽³⁾	Supply Current for S0 @ TTL HIGH	V _{CC} = MAX.	V _{IN} = 3.0 V ⁽⁴⁾ Other Inputs at V _{CC} OR GND	—	—	750	μA
I _{CCD}	Supply Current for S0 per MHz ⁽⁵⁾ Toggling 50% Duty Cycle	V _{CC} = Max., A and B Pins Open		—	—	0.25	mA/ MHz

Notes:

1. For Max. or Min. conditions, use appropriate value specified under Electrical Characteristics for applicable device.
2. Typical values are at V_{CC} = 3.3V, +25°C ambient.
3. This is the increase in supply current for S0 at the specified TTL voltage level rather than V_{CC} or GND.
4. Per driven input (S0 only); A and B pins do not contribute to I_{CC}.
5. This current applies to the control inputs only and represent the current required to switch internal capacitance at the specified frequency. The A and B inputs generate no significant AC or DC currents as they transition. This parameter is not tested, but is guaranteed by design.

PI3B16292 Switching Characteristics over Operating Range

Parameters	Description	Conditions ⁽¹⁾	Com.		Units
			Min.	Max.	
t _{PLH} t _{PHL}	Propagation Delay ^(2,3) xA1 to xBx, xBx to xA1	C _L = 50 pF R _L = 500Ω R = 500Ω to 6V ⁽⁴⁾	—	0.25	ns
t _{PZH} t _{PZL}	Bus Enable time S to xA1 or xBx		1	4.5	
t _{PHZ} t _{PLZ}	Bus Disable time S to xA1 or xBx		1	5.0	
t _m	Make-before-break time ⁽²⁾		0	2	


PI3B162292 Switching Characteristics over Operating Range

Parameters	Description	Conditions ⁽¹⁾	Com.		Units
			Min.	Max.	
t _{PLH} t _{PHL}	Propagation Delay ^(2,3) xA1 to xBx, xBx to xA1	C _L = 50 pF R _L = 500Ω R = 500Ω to 4.6V ⁽⁴⁾	—	1.25	ns
t _{PZH} t _{PZL}	Bus Enable time S to xA1 or xBx		1	5	
t _{PHZ} t _{PLZ}	Bus Disable time S to xA1 or xBx		1	5.5	
t _m	Make-before-break time ⁽²⁾		0	2	

Notes:

1. See test circuit and waveforms.
2. This parameter is guaranteed but not tested.
3. The bus switch contributes no propagational delay other than the RC delay of the ON resistance of the switch and load capacitance. The time constant for the switch alone is of the order of 0.25ns for 50pF load. Since this time constant is much smaller than rise/fall times of typical driving signals, it adds very little propagational delay to the system. Propagational delay of the bus switch, when used in a system, is determined by the driving circuit on the driving side of the switch and its interaction with the load on the driven side.
4. Applies to t_{PLZ} and t_{PZL}.

56-Pin SSOP (300 MIL WIDE) - Package Code: V56



56-Pin TSSOP (240 MIL WIDE) - Package Code: A56

