

FEATURES

- On-chip tunable voltage-controlled crystal oscillator circuitry (VCXO) allows precise system frequency tuning (pull range 300ppm minimum).
- VCXO tuning range: 0-3.3V.
- Uses inexpensive fundamental-mode crystals.
- Integrated phase-locked loop (PLL) multiplies VCXO frequency to the higher system frequencies needed.
- 3.3V supply voltage.
- Small circuit board footprint (8-pin 0.150 SOIC).
- Custom frequency selections available.
- 12mA output drives capability at TTL level.

DESCRIPTIONS

The PLL501-02/04 is a monolithic low Jitter, high performance CMOS clock generator IC. It has a circuitry that implements a voltage-controlled crystal oscillator when an external resonator (nominally 13.5MHz) is attached. The VCXO allows device frequencies to be precisely adjusted for matching requirements.

This product is ideal for Set-Top Box and multimedia synthesizer applications.

PIN CONFIGURATION





Table 1: Crystal / Output Frequencies

DEVICE	F _{XIN} (MHz)	CLK (MHz)
PLL501-02	13.5	27
PLL501-04	13.5	54

Note: Contact PhaseLink for custom PLL Frequencies

BLOCK DIAGRAM



PIN DESCRIPTIONS

Name	Number	Type	Description
XIN	1	I	VCXO Crystal Feedback Connection.
VDD	2	P	3.3V Power Supply.
VIN	3	I	Voltage Input for VCXO Frequency Control.
GND	4	P	Ground for PLL Core.
CLK	5	O	Clock Output.
VDD	6	P	3.3V Power Supply.
GND	7	P	Ground.
XOUT	8	O	VCXO Crystal Drive.

ELECTRICAL SPECIFICATIONS

1. Absolute Maximum Ratings

PARAMETERS	SYMBOL	MIN.	MAX.	UNITS
Supply Voltage	V_{DD}		7	V
Input Voltage, dc	V_I	$V_{SS}-0.5$	$V_{DD}+0.5$	V
Output Voltage, dc	V_O	$V_{SS}-0.5$	$V_{DD}+0.5$	V
Storage Temperature	T_S	-65	150	° C
Ambient Operating Temperature	T_A	0	70	° C
Junction Temperature	T_J		125	° C
Lead Temperature (soldering, 10s)			260	° C
Input Static Discharge Voltage Protection			2	KV

Exposure of the device under conditions beyond the limits specified by Maximum Ratings for extended periods may cause permanent damage to the device and affect product reliability. These conditions represent a stress rating only, and functional operations of the device at these or any other conditions above the operational limits noted in this specification is not implied.

2. DC Electrical Specifications

PARAMETERS	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Supply Current, Dynamic, with Loaded Outputs	I_{DD}	$f_{XTA} = 13.5\text{MHz}; C_L=10\text{pF}$		20		mA
Operating Voltage	V_{DD}		3.13		3.47	V
Output High Voltage	V_{OH}	$I_{OH} = -12\text{mA}$	2.4			V
Output Low Voltage	V_{OL}	$I_{LO} = 12\text{mA}$			0.4	V
Output High Voltage at CMOS level	V_{OHC}	$I_{OH} = -4\text{mA}$	$V_{DD} - 0.4$			V
Operating Supply Current	I_{DD}	No Load		7		mA
Short Circuit Current				± 50		mA
VIN, VCXO Control Voltage			0		3.3	V

3. AC Electrical Specifications

PARAMETERS	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Input Crystal Frequency				13.5		MHz
Input Crystal Accuracy					±30	ppm
Output Clock Rise Time	t_r	0.8V ~ 2.0V			1.5	ns
Output Clock Fall Time	t_f	2.0V ~ 0.8V			1.5	ns
Output Clock Duty Cycle		Measured @ 1.4V	45	50	55	%
Max Absolute Jitter		Short Term		100		ps
Short Circuit Current				±50		mA
CLK output pullability		0V ≤ VIN ≤ 3.3V	±150			ppm

4. Voltage Control Crystal Oscillator


PARAMETERS	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
PLL Stabilization Time *	T_{PLLSTB}	From VCXO stable		500		us
VCXO Stabilization Time *	$T_{VCXOSTB}$	From power valid		10		ms
Output Frequency Synthesis Error		(Unless otherwise noted in Frequency Table)			±30	ppm
Crystal Resonator Frequency	f_{XTAL}	Series Fundamental Mode	10	13.5	15	MHz
Crystal Loading Capacitance		Series Fundamental Mode		N/A		pF
Crystal Resonator Motional Capacitance	$C_{1(xtal)}$	At cut		25		fF
VCXO Tuning Range		$f_{XTA} = 13.5\text{MHz}$; $C_{MOT}=25\text{fF}$		400		ppm
VCXO Tuning Characteristic				200		ppm/V

Note: Parameters denoted with an asterisk (*) represent nominal characterization data and are not production tested to any specific limits.

External Components

The PLL501-02/04 requires a minimum number of external components for proper operation. A decoupling capacitor of 0.01μF should be connected between VDD and GND on pin2 and 4, as close to the PLL501-02/04 as possible. A series termination resistor of 33Ω may be used for the clock output. The input crystal must be connected as close to the chip as possible. The input crystal should be a series mode, pullable, AT cut, 13.5MHz. Consult PhaseLink for recommended suppliers.

PACKAGE INFORMATION



ORDERING INFORMATION

For part ordering, please contact our Sales Department:

47745 Fremont Blvd., Fremont, CA 94538, USA

Tel: (510) 492-0990 Fax: (510) 492-0991

PART NUMBER

The order number for this device is a combination of the following:
Device number, Package type and Operating temperature range

PLL501-02 X C

PART NUMBER

TEMPERATURATRE
C=COMMERCIAL
M=MILITARY
I=INDUSTRIAL

PACKAGE TYPE
X=SSOP

PhaseLink Corporation, reserves the right to make changes in its products or specifications, or both at any time without notice. The information furnished by Phaselink is believed to be accurate and reliable. However, PhaseLink makes no guarantee or warranty concerning the accuracy of said information and shall not be responsible for any loss or damage of whatever nature resulting from the use of, or reliance upon this product.

LIFE SUPPORT POLICY: PhaseLink's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President of PhaseLink Corporation.