

TELECOM DIODE BRIDGE/ TVS ARRAY

APPLICATIONS

- ✓ T1/E1 Line Cards
- ✓ ISDN U-Interfaces & ISDN S/T Interfaces
- ✓ xDSL Interfaces
- ✓ Ethernet - 10/100 Base T
- ✓ RS-485 Data Lines

IEC COMPATIBILITY (EN61000-4)



- ✓ 61000-4-2 (ESD): Air - 15kV, Contact - 8kV
- ✓ 61000-4-4 (EFT): 40A - 5/50ns
- ✓ 61000-4-5 (Surge): 8/20 μ s - L4, 95A(Line-Gnd), L1, 48A(Power) & L4, 48A(Line-Line)

FEATURES

- ✓ **ESD PROTECTION > 40 kilovolts**
- ✓ 2000 Watts Peak Pulse Power per Line (td=8/20 μ s)
- ✓ Low Capacitance - 18pF
- ✓ 100A (2/10 μ s) per Bellcore 1089(Intra-Building)

MECHANICAL CHARACTERISTICS

- ✓ Molded JEDEC SO-8
- ✓ Weight 0.1 grams (Approximate)
- ✓ Flammability Rating UL 94V-0
- ✓ 12mm Tape and Reel Per EIA Standard 481-1-A
- ✓ Device Marking Code & Logo
- ✓ Pin One Defined By DOT on Top of Packag

**CIRCUIT DIAGRAM**

DEVICE CHARACTERISTICS

MAXIMUM RATINGS @ 25°C Unless Otherwise Specified			
PARAMETER	SYMBOL	VALUE	UNITS
Peak Pulse Power ($t_p = 8/20\mu s$) - See Figure 1	P_{PP}	2000	Watts
Operating Temperature	T_J	-55°C to 150°C	°C
Storage Temperature	T_{STG}	-55°C to 150°C	°C

ELECTRICAL CHARACTERISTICS PER LINE @ 25°C Unless Otherwise Specified							
PART NUMBER	DEVICE MARKING CODE	RATED STAND-OFF VOLTAGE	MINIMUM BREAKDOWN VOLTAGE	MAXIMUM CLAMPING VOLTAGE (Note 1 & 2) (See Fig. 2)	MAXIMUM LEAKAGE CURRENT	TYPICAL CAPACITANCE (See Note 3)	MAXIMUM CAPACITANCE (See Note 4)
		V_{WM} VOLTS	@ 1mA $V_{(BR)}$ VOLTS	@8/20μs $V_C @ I_{PP}$	@ V_{WM} I_D μA	0V @ 1 MHz C pF	0V @ 1 MHz C pF
PLC03-6	PBA	6.0	6.8	20.0V @ 100.0A	25	7	15

Note 1: For an 8/20μs waveform, apply positive pulse to pin 1 or 8 to pin 2 or 3(ground).


Note 2: Measured between pin 1 or 8 to pin 2 or 3; pin 1 or 8 to pin 4 or 5.

Note 3: Measured between I/O pins and ground (pin 1 to 2).


Note 4: Measured between I/O pins (pins 1 to 4).

GRAPHS


**FIGURE 1
PEAK PULSE POWER VS PULSE TIME**




**FIGURE 2
PULSE WAVE FORM**



**FIGURE 3
POWER DERATING CURVE**



PACKAGE OUTLINE & DIMENSIONS



TAPE & REEL PACKAGING:

Surface mount product is taped and reeled in accordance with EIA-481, reel quantities and sizes are as follows:

7 Inch Reel - 1,000 pieces per reel; 13 Inch Reel - 2,500 pieces per reel

COPYRIGHT © ProTek Devices 2001

SPECIFICATIONS: ProTek reserves the right to change the electrical and or mechanical characteristics described herein without notice (except JEDEC).

DESIGN CHANGES: ProTek reserves the right to discontinue product lines without notice, and that the final judgement concerning selection and specifications is the buyer's and that in furnishing engineering and technical assistance, ProTek assumes no responsibility with respect to the selection or specifications of such products.

ProTek Devices

2929 South Fair Lane, Tempe, AZ 85282

Tel: 602-431-8101 Fax: 602-431-2288

E-Mail: sales@protekdevices.com

Web Site: www.protekdevices.com