





## TRANSZORB® Transient Voltage Suppressors



Steady State Power 1W  
Peak Pulse Power 300W  
Breakdown Voltage 530, 550V

## DO-204AL (DO-41 Plastic)



Dimensions are in inches and (millimeters)

## Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Protects power IC controllers such as TOPSwitch®
- Glass passivated junction
- High temperature soldering guaranteed: 250°C/10 seconds at terminals
- Excellent clamping capability
- Available in unidirectional only

## Mechanical Data

**Case:** JEDEC DO-204AL molded plastic body over passivated junction

**Terminals:** Axial leads, solderable per MIL-STD-750, Method 2026

**Polarity:** The band denotes the cathode, which is positive with respect to the anode under normal TVS operation

**Mounting Position:** Any **Weight:** 0.012oz., 0.3g

**Packaging Codes – Options (Antistatic):**

51 – 1K per Bulk box, 10K/carton

54 – 5.5K per 13" paper Reel  
(52mm horiz. tape), 16.5K/carton

73 – 3K per horiz. tape & Ammo box, 30K/carton

Maximum Ratings and Thermal Characteristics  $T_A = 25^\circ\text{C}$  unless otherwise noted.

Parameter	Symbol	P4KE530	P4KE550	Unit
Steady state power dissipation (Note 3)	$P_{M(AV)}$	1.0		W
Peak pulse power dissipation (Note 1, 2, Fig. 1)	$P_{PPM}$	Minimum 300		W
Stand-off voltage	$V_{WM}$	477	495	V
Typical thermal resistance junction-to-lead	$R_{\theta JL}$	27		$^\circ\text{C/W}$
Typical thermal resistance junction-to-ambient	$R_{\theta JA}$	75		$^\circ\text{C/W}$
Operating junction and storage temperature range	$T_J, T_{STG}$	-55 to +150		$^\circ\text{C}$

Electrical Characteristics  $T_A = 25^\circ\text{C}$  unless otherwise noted.

Parameter	Symbol	P4KE530	P4KE550	Unit
Minimum breakdown voltage at 100 $\mu\text{A}$	$V_{(BR)}$	530	550	V
Max. clamping voltage at 400mA, 10/1000 $\mu\text{s}$ -waveform	$V_C$	760		V
Maximum DC reverse leakage current at $V_{WM}$	$I_D$	5.0		$\mu\text{A}$
Typical temperature coefficient of $V_{(BR)}$		650		$\text{mV}^\circ\text{C}$
Typical capacitance (Note 4) at 0V at 200V	$C_J$	90 7.5		pF

**Notes:** (1) Non repetitive current pulse per Fig.3 and derated above 25°C per Fig. 2


(2) Peak pulse power waveform is 10/1000 $\mu\text{s}$

(3) Lead temperature at 75°C =  $T_L$


(4) Measured at 1MHz

## Ratings and Characteristic Curves ( $T_A = 25^\circ\text{C}$ unless otherwise noted)


**Fig. 1 – Peak Pulse Power Rating Curve**



**Fig. 2 – Pulse Derating Curve**



**Fig. 3 – Pulse Waveform**



## Application Notes

- Respect Thermal Resistance (PCB Layout) – as the temperature coefficient also contributes to the clamping voltage.
- Select minimum breakdown voltage, so you get acceptable power dissipation and PCB tie point temperature. Devices with higher breakdown voltage will have a shorter conduction time and will dissipate less power.
- Clamping voltage is influenced by internal resistance – design approximation is 7V per 100mA slope.
- Keep temperature of TVS lower than TOPSwitch® as a recommendation.
- Maximum current is determined by the maximum  $T_J$  and can be higher than 300mA. Contact supplier for different clamping voltage / current arrangements.
- Minimum breakdown voltage can be customized for other applications. Contact supplier
- TOPSwitch® is a registered trademark of Power Integrations, Inc.