

## RF Power Source

## RFS 2450 - 20

This solid state RF power source is designed for reliable, trouble-free service. It operates in a class A/AB and includes RF protection circuits, cooling installations and a 230 V AC power supply. The amplifier is accommodated in a 19" system housing.

### Features :

- \* 35 Watts saturated output power
- \* including crystal oscillator
- \* Power variation over more than 15 dB
- \* Output isolator in option
- \* Temperature protection

### Applications :

- \* Microwaves generators
- \* Power sources as a driver
- \* Fields Test
- \* Instrumentations

### Specifications

Characteristics	Data	Units
Frequency	2450	MHz
RF output power CW		
Typ.	30	W
Min	20	W
Class	A/AB	
Crystal oscillator	yes	
Gain control <b>remote</b>	> 15	dB
External power control	0 to 10	V
Out impedance nom.	50	Ohms
Load VSWR for rated output power	up to 1.5 : 1	
VSWR mismatch, with isolator	Infinite	
Protection circuits	Load VSWR, overtemperature	
Harmonics typ.	-20	dBc
Spurious typ.	-60	dBc
Modulation capability	C W	%
RF ON/OFF <b>remote</b>	remote	
P fwd <b>remote</b>	0 to 10	V
P reflect <b>remote</b>	0 to 10	V
RF connector	N female	
Cooling	Forced air (self-contained fans)	
Operating temperature Range	0 °C ... + 40	° C
Power Supply	230 AC +/- 10 % ,47-63 Hz	V
Dimensions (W x L x H)	3 U 19" Rack 490 x 360 x 188	mm

All data at room temperature + 22 °C, into 50 Ohms, subject to change without notice

**remote** : have to be used with an external control circuit

Made in Europeen Union

05/04/2001

**R.F.P.A. S.A.**

Parc d'activité de Fontaudin F33370 Artigues près Bordeaux

France Tél : +33 (0)5 56 86 85 84 Fax: + 33 (0) 5 56 86 55 56