

Technical Specification for 2.5Gbps Fiber Optic Transceiver Module

SDM7108-XC

- | | | |
|--|---|--|
| <input type="checkbox"/> 155.52Mb/s | <input type="checkbox"/> 622.08Mb/s | <input checked="" type="checkbox"/> other <u>2488.32Mbps</u> |
| <input checked="" type="checkbox"/> Short Haul | <input type="checkbox"/> Long Haul | <input type="checkbox"/> other _____ |
| <input checked="" type="checkbox"/> Intermediate Reach | <input type="checkbox"/> Long Reach | <input type="checkbox"/> other _____ |
| <input checked="" type="checkbox"/> Single 5.0 V | <input type="checkbox"/> Single 3.3 V | <input type="checkbox"/> other _____ |
| <input checked="" type="checkbox"/> 1.3 μ m | <input type="checkbox"/> 1.55 μ m | <input type="checkbox"/> other _____ |
| <input type="checkbox"/> Transmitter | <input type="checkbox"/> Receiver | <input checked="" type="checkbox"/> Transceiver |
| | (<input type="checkbox"/> 2R / <input type="checkbox"/> 3R) | (<input checked="" type="checkbox"/> 2R / <input type="checkbox"/> 3R) |



Sumitomo Electric reserves the right to make changes in this specification without prior notice.

#Safety Precaution Symbols This specification uses various picture symbols to prevent possible injury to operator or other persons or damage to properties for appropriate use of the product. The symbols and definitions are as shown below. Be sure to be familiar with these symbols before reading this specification.

	Warning	Wrong operation without following this instruction may lead to human death or serious injury.
	Caution	Wrong operation without following this instruction may lead to human injury or property damage.

Example of picture symbols indicates prohibition of actions. Action details are explained thereafter.

indicates compulsory actions or instructions. Action details are explained thereafter.

1. General

The SDM7108-XC is a fiber optic transceiver module designed for high-speed digital transmission. These products use a 1.3 μm InGaAsP / InP, DFB Laser Diode and InGaAsP, PIN Photodiode as a light source and detector, respectively. The transceiver module is a PC board mountable package with electrical and optical interfaces. These modules are designed for intermediate reach, short haul applications.

Features

- *InGaAsP / InP, DFB Laser Diode 1.3 μm operation
- *Low Profile Plastic Molded Package
- *Automatic Optical Power Control
- *Single +5.0V Power Supply
- *Class 1 Laser Product (IEC 825-1 and FDA 21 CFR 1040.10 and 1040.11)
- *Operating Case Temperature of 0°C to 70°C
- *Low Power Consumption
- *Industrial Standard 1x9 Pin Footprint
- *Signal Detect (FLAG) Function
- *SC Duplex Connector Receptacle

Applications

- *Telecommunications
 - >SONET/IR, SDH/SH Application
 - >ATM Application
 - >156Mbps to 2.5Gbps Shelf-to-Shelf Links
 - >Subscriber Loop
 - >Metropolitan Area Network
- *Data Communications
 - >High Speed Rack-to-Rack Data Links

2. Block Diagram




Figure 1-1. Block Diagram (Transmitter)




Figure 1-2. Block Diagram (Receiver)

3. Package Dimension




Figure 2. External View

⚠ Caution



Do not disassemble this product. Otherwise, failure, electrical shock overheating or fire may occur.

Handle the lead pin carefully. Use assisting tools or prospective aids as required. A lead pin may injure skin or human body

4. Footprint




Figure 3 Footprint

5. Pin Assignment

No.	Symbol	Function
1	Veerx	Power Supply (-) for Receiver : Connected to GND
2	RD	Differential Data Output (Positive)
3	RDb	Differential Data Output (Negative)
4	SD(FLAG)	Signal Detect (FLAG)
5	Vccrx	Power Supply (+) for Receiver : Connected to +5.0V
6	VccTx	Power Supply (+) for Transmitter : Connected to +5.0V
7	TDb	Transmitter Differential Data Input (Negative)
8	TD	Transmitter Differential Data Input (Positive)
9	Veetx	Power Supply (-) for Transmitter : Connected to GND

6. Absolute Maximum Ratings

Parameter	Symbol	min.	Max	Unit	Note
Storage Case Temperature	Ts	-40	85	°C	1
Operating Case Temperature	Tc	0	70	°C	1
Supply Voltage	Vcc-Vee	0.0	6.0	V	2
Input Voltage	Vi	Vee	Vcc+0.5	V	3
Output Current (RD, RDb)	Ioutrd		30	mA	
Output Current (SD)	Ioutsd		20	mA	
Lead Soldering (Temperature)			260	°C	4
(Time)			10	sec.	


Note 1. No condensation allowed. 2. Vcc>Vee

3. TD, TDb 4. Measured on lead pin at 2mm (0.079in.) off the package bottom

Warning

 Use the product with the rated voltage described in the specification. If the voltage exceeds the maximum rating, overheating or fire may occur.

Caution

 Do not store the product in the area where temperature exceeds the maximum rating, where there is too much moisture or dampness, where there is acid gas or corrosive gas, or other extreme conditions. Otherwise, failure, overheating or fire may occur.

7. Electrical Interface

(Unless otherwise specified, Vcc = 4.75 to 5.25 V, Vee = GND, @2488.32Mbps, PRBS2²³-1,50% duty and all operating temperature shall apply.)

7-1. Transmitter side

Parameter	Symbol	min.	Typ.	Max.	Unit	Note
Supply Voltage	Vcc-Vee	4.75	5.00	5.25	V	
Supply Current	I _{dtx}		150	200	mA	1
Input Voltage Swing (TD, TDb)	V _{in}	0.45		1.20	V _{p-p}	2
Input Impedance	R _{in}		100		Ω	3
Signal Input Rise / Fall Time				0.12	nsec.	4

Note 1. Input bias current is not included. 50% duty cycle data. 2488.32Mbps 2. Vcc-Vee=5.0V, Tc=25°C 3. 20 ~ 80%

3. Measured between TD and TDb. 4. 20 ~ 80%

7-2. Receiver side

Parameter	Symbol	min.	Typ.	Max.	Unit	Note
Supply Voltage	Vcc-Vee	4.75	5.00	5.25	V	
Supply Current	I _{drx}		100	200	mA	1
Data Output Voltage	High	V _{ordh}	Vcc-1.10	Vcc-0.65	V	2
	Low	V _{ordl}	Vcc-1.80	Vcc-1.30		
SD Output Voltage	High	V _{osdh}	Vee+2.40		V	2, 3
	Low	V _{osdl}		Vee+0.50		
Data Rise / Fall Time of Output Signal	Trd / Tfd		0.20		nsec	4

Note 1. Output current is not included. 2. Vcc=+5.0V, Tc=25°C, Output load resistance RL=50Ω to Vccrx-2V for RD and RDb.

3. I_{oh} = -0.2mA, I_{ol} = 2mA 4. 20 ~ 80%




Figure 4. Electrical Data Interface

8. Optical Interface

(Unless otherwise specified, Vcc = 4.75 to 5.25 V, Vee = GND, @2488.32Mbps, PRBS2²³-1,50% duty and all operating temperature shall apply.)

8-1. Transmitter side

Parameter	Symbol	min.	Typ.	Max.	Unit	Note
Average Output Power to SMF	Pos	-5.0		0.0	dBm	1
Extinction Ratio	Er	8.2			dB	1
Center Wavelength	λ_c	1266		1360	nm	
Spectral Width (-20dB)	20			1.0	nm	
Side Mode Suppression Ration	Sr	30			dB	1
Eye Mask for Optical Output	compliant with ITU-T recommendation G.957					

Note 1. Measured at 2488.32Mbps PRBS2²³-1, 50% duty cycle data

Relation between Input Signal and Optical Output Signal

Input Signal		Optical Output Signal
TD	TDb	
High	Low	ON (High)
Low	High	OFF (Low)
High	High	Undefined
Low	Low	Undefined

Warning

Do not look at the laser beam projection area (e.g. end of optical connector) with naked eyes or through optical equipment while the power is supplied to this product. Otherwise, your eyes may be injured.

8-2. Receiver side

Parameter	Symbol	min.	Typ.	Max.	Unit	Note
Center Wavelength	-	1260		1580	nm	
Minimum Sensitivity	Pmin		-21.0	-18.0	dBm	1
Overload	Pmax	0.0	1.0		dBm	1
SD Assert Level	Pa		-25		dBm	
SD Deassert Level	Pd		-27		dBm	
Hysteresis	Hys		2.0		dB	
Reflectance	REFr		-14		dB	

Note 1. BER=10⁻¹⁰, 2. Measured at the bit rate of 2488.32Mbps, PRBS 2²³-1, NRZ

9. Laser Safety

This product uses a semiconductor laser system and is a laser class 1 product acc. FDA, complies with 21CFR 1040. 10 and 1040.11. Also this product is a laser class 1 product acc. IEC 825-1.

Class 1 Laser Product

Caution



If this product is used under conditions not recommended in the specification or this product is used with unauthorized revision, classification for laser product safety standard is invalid. Classify the product again at your responsibility and take appropriate actions.

10. Reliability Test (Under Qualification)

Bellcore TA-NWT-000983 Issue 2, December 1993								
Heading	Test	Reference	Condition	Sampling			SEI Plan	
				LTPD	SS	C	SS	F/C
Mechanical Integrity	Mechanical Shock	MIL-STD-883 Method 2002	Condition B					
			5 times/axis					
	Vibration	MIL-STD-883 Method 2007	500G, 1.0 ms	20%	11	0	---	---
			1,500G, 0.5ms	20%	11	0	11	0
			Condition A	20%	11	0	11	0
			20 G					
Endurance	Thermal Shock	MIL-STD-883 Method 1011	ΔT=100°C	20%	11	0	11	0
	Solderability	MIL-STD-883 Method 2003	(steam aging not required)	20%	11	0	11	0
	Fiber Pull		1 Kg; 3 times; 5sec.	20%	11	0	---	---
			2 Kg; 3 times; 5sec.	20%	11	0	---	---
	Accel. Aging (High Temp.)	(R)-453 Section 5.18	+85°C; rated power					
			>5,000hrs.	---	25	---	25	0
	High Temp. Storage	-----	>10,000hrs.	---	10	---	---	---
			max. storage T (T=85°C)	20%	11	0	---	---
	Low Temp. Storage	-----	>2,000	20%	11	0	11	0
			min. storage T (T=-40°C)	20%	11	0	11	0
Special Tests	Temperature Cycling	Section 5.20	- 40°C to +85°C					
			400 times pass/fail	20%	11	0	---	---
	Damp Heat (if using epoxy)	MIL-STD-202 M103 or IEC 68-2-3	500 times for info.	---	11	---	---	---
			500 times pass/fail	20%	11	0	11	0
	Cyclic Moisture Resistance	Section 5.23	1000 times for info.	---	11	---	11	0
			-----	20%	11	0	11	0
Special Tests	Internal Moisture	MIL-STD-883 Method 1018	< 5,000 ppm water vapor	20%	11	0	11	0
	Flammability	TR357:Sec. 4.4.2.5	-----	---	---	---	---	OK
	ESD Threshold	Section 5.22	-----	---	6	---	6	0

11. Ordering Information

Ordering Number	Connector type	Operating Temperature
SDM7108-XC	SC Duplex Connector	Tc = 0 ~ 70°C

12. Other Precaution

Under such a strong vibration environment as in automobile, the performance and reliability are not guaranteed.

The governmental approval is required to export this product to other countries. To dispose of these components, the appropriate procedure should be taken to prevent illegal exportation.

This module must be handled, used and disposed of according to your company's safe working practice.

13. For More Information

U.S.A.

Sumitomo Electric Lightwave Corp, 78 Alexander Drive, Research Triangle Park, NC 27709

Tel. (919)541-8100 / Fax. (919)541-8376

E-mail: info@sumitomoelectric.com

<http://www.sumitomoelectric.com>

Europe

Sumitomo Electric Europe Ltd., Unit 11, Magnolia House, Spring Villa Park, Spring Villa Road

Edgware, Middlesex, HA8 7EB, United Kingdom

Tel. (0181)905-6167

Fax. (0181)905-6120

Japan

Sumitomo Electric Industries, Ltd. (International Business Division), 3-12, Moto-Akasaka 1-chome
Minato-ku Tokyo 107-8468

Tel. (03)3423-5771 / Fax. (03)3423-5099

E-mail: product-info@yfocus.sei.co.jp

http://www.sei.co.jp/Electro-optic/eopd_home_e.html