

Sumitomo Electric Industries, Ltd.  
Part No. SLT1110 Series  
Doc. No. HUW9824103-01B  
Date of Issue. June 14, 1999



Technical Specification  
of  
1.3 $\mu$ m MQW-FP Laser Diode:  
SLT1110 Series

Sumitomo Electric Industries, Ltd.

## 1. General

SLT1110 Series are 1.3 $\mu$ m InGaAsP/InP MQW-FP laser diodes fabricated by OMVPE entirely. These diodes have low threshold current and high performance at high temperature. A laser diode is mounted into a coaxial package integrated with an InGaAs monitor PD and a ball lens cap.

## 2. Package dimension and pin assignment

(See attached appendix)

## 3. Absolute maximum ratings (Tc=+25°C, unless otherwise noted.)

Parameter	Symbol	Ratings	Unit
Storage temperature	Tstg	-40~+100	°C
Operating case temperature	Top	-40~+85	°C
Peak optical output power	Po	10	mW
Forward current (LD)	IfL	150	mA
Reverse voltage (LD)	VrL	2	V
Reverse voltage (PD)	VrP	15	V
Reverse current (PD)	IrP	2	mA
Soldering temperature (<10sec.)	Stemp	260	°C

## 4. Electrical and optical characteristics (Po=5mW, Tc=+25°C, unless otherwise noted.)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Threshold current	Ith	CW	-	8	15	mA
Optical output power	Po	CW, If=Ith+20mA	4.0	5.0	-	mW
Operating voltage	Vf	CW	-	1.2	1.6	V
Central wavelength	$\lambda_c$	CW	1280	1310	1340	nm
Spectral width	$\Delta\lambda$	CW, RMS	-	2	5	nm
Rise time	tr	Ib=Ith, 20-80%	-	0.3	0.5	nsec.
Fall time	tf	Ib=Ith, 80-20%	-	0.3	0.5	nsec.
Monitor current	Im	CW, VrP=5V	200	450	-	pA
Monitor dark current	Id	VrP=5V	-	-	10	nA
Monitor capacitance	C	VrP=5V, f=1 MHz	-	-	10	pF

## 5. Ordering information

Part number	Pin assignment	Pin length
SLT1110	Type A	13.5±0.5mm
SLT1111	Type B	13.5±0.5mm
SLT1112	Type A	18.5±0.5mm
SLT1116	Type C	13.5±0.5mm
SLT1117	Type D	13.5±0.5mm

## 6. Precaution

- (1) Radiation emitted by laser devices can be dangerous to the eyes. Avoid eye or skin exposure to direct or scattered radiation.
- (2) The governmental approval is required to export this product to other countries. To dispose of this product, the appropriate procedure should be taken to prevent illegal exportation.
- (3) The laser diodes should be handled in the same manner as ordinary semiconductor devices to prevent the electro-static damages. For safekeeping and carrying, the modules should be packaged with ESD proof material. To assemble the modules on PCB, the workbench, the soldering iron and the human body should be grounded.
- (4) Please pay special attention to the atmosphere condition because the dew on the module may cause some electrical damages.
- (5) Under such a strong vibration environment as in automobile, the performance and reliability are not guaranteed.

## Appendix

Part No.: SLT1110□/□□□

(Customize code)

Code	Pin assignment	Pin length (L1)
0	Type A	13.5±0.5
1	Type B	13.5±0.5
2	Type A	18.5±0.5
6	Type C	13.5±0.5
7	Type D	13.5±0.5


Pin No.	Pin function for type C
1	(CASE) LD anode
2	LD cathode
3	PD anode
4	LD anode/PD cathode

Pin No.	Pin function for type D
1	(CASE) LD anode
2	PD anode
3	PD cathode
4	LD cathode/PD anode

Pin No.	Pin function for type A
1	LD anode (CASE)
2	LD cathode
3	PD cathode
4	PD anode

Pin No.	Pin function for type B
1	LD anode (CASE)
2	PD anode
3	PD cathode
4	LD cathode

### Pin Assignment



Sumitomo Electric Industries, Ltd.  
Part No. SLT1110 Series  
Doc. No. HUW9824103-01B  
Date of Issue. June 14, 1999

## **7. For More Information**

### **U.S.A.**

Sumitomo Electric Lightwave Corp.  
78 Alexander Drive  
Research Triangle Park, NC 27709  
U.S.A.  
Tel. (919) 541-8100  
Fax. (919) 541-8376

### **Europe**

Sumitomo Electric Europe Ltd.  
Unit 11, Magnolia House  
Spring Villa Park, Spring Villa Road  
Edgware, Middlesex, HA8 7EB  
United Kingdom  
Tel. (0181) 905-6167  
Fax. (0181) 905-6120

### **Japan**

Sumitomo Electric Industries, Ltd.  
( International Business Division)  
3-12, Moto-Akasaka 1-chome  
Minato-ku Tokyo 107  
Japan  
Tel. (03) 3423-5771  
Fax. (03) 3423-5099