



Sumitomo Electric Industries, Ltd.
Part No.: SLT4400-xx-S460 Series
SLT4460-xx-S460 Series
Document No.: HUW0024123-01A
Date of issue: March 20, 2001

Preliminary Specification
of
1.625 μ m MQW-DFB Laser Diode Module:
for up to 622Mb/s transmission

SLT4400-xx-S460 Series
SLT4460-xx-S460 Series



1. General

SLT4400-xx-S460 Series and SLT4460-xx-S460 Series are 1.625μm InGaAsP/InP MQW-DFB laser diode modules designed for fiber optic communication systems. These modules are ideally suitable for long reach and intermediate reach of up to 622Mb/s transmission applications.

A laser diode is mounted into a coaxial package integrated with an InGaAs monitor PD and a single mode fiber pigtail.

Especially SLT4460-xx-S460 Series have a single stage isolator integrated inside.

2. Package dimension and pin assignment

(See attached appendix.)

3. Absolute maximum ratings (Tc=25°C, unless otherwise noted.)

Parameter	Symbol	Ratings	Unit
Storage temperature	Tstg	-40~+85	°C
Operating case temperature	Top	-40~+85	°C
Forward current (LD)	IfL	150	mA
Reverse voltage (LD)	VrL	2	V
Reverse voltage (PD)	VrP	15	V
Reverse current (PD)	IrP	2	mA
Soldering temperature (<10sec.)	Stemp	260	°C

4. Electrical and optical characteristics (Pf=2mW, Tc=25°C, unless otherwise noted.)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Threshold current	Ith	CW	—	10	20	mA
		CW, Tc=-40~+85°C	—	—	50	
Optical output power	Pf	CW, If=Ith+20mA	1.0	2	2.5	mW
		CW, If=Ith+20mA, Tc=-40~+85°C	0.5	—	4.0	
Operating voltage	Vf	CW, Tc=-40~+85°C	—	—	1.7	V
Slope efficiency	Se	CW, Average(Ith to Ith+20mA)	0.050	—	0.125	mW/mA
		CW, Average(Ith to Ith+20mA) Tc=-40~+85°C	0.025	—	0.15	
Peak wavelength	λ_p	CW	1620	1625	1630	nm
		CW, Tc=-40~+85°C	1612	—	1638	
Side-mode suppression ratio	SSR	CW, Tc=-40~+85°C	30	—	—	dB
Tracking error	ΔPf	Im hold(@Pf=2mW(25°C)), CW Tc=-40~+85°C	-1.0	—	1.0	dB
Rise time	tr	Ib=Ith, 20-80%, Tc=-40~+85°C	—	0.05	0.10	nsec.
Fall time	tf	Ib=Ith, 80-20%, Tc=-40~+85°C	—	0.10	0.15	nsec.
Extinction ratio	Er	10log(2mW/Pf(Ith)), Tc=-40~+85°C	10	—	—	dB
Monitor current	Im	CW, VrP=5V, Tc=-40~+85°C	50	—	1500	μ A
Monitor dark current	Id	VrP=5V	—	1	10	nA
Monitor capacitance	C	VrP=5V, f=1MHz	—	—	10	pF

Note: Since the SLT4400-xx-S460 Series have no optical isolator inside, to integrate externally an optical isolator is recommended for long reach of transmission applications.

5. Fiber pigtail specification

Parameter	Min.	Typ.	Max.	Unit
Type	Single Mode			—
Mode field diameter@1310nm	8.5	9.5	10.5	μ m
Cladding diameter	122	125	128	μ m
Outer jacket diameter	0.8	0.9	1.0	mm
Bending radius	30	—	—	mm

6. Ordering Information

Part number	Pin assignment	Optical isolator	Connector type	Flange type (hole pitch)
SLT4400-CN-S460	Type A	No isolator	SC/PC	Flangeless
SLT4400-CP-S460				Vertical (12mm)
SLT4400-CS-S460				Horizontal (12.7mm)
SLT4400-XN-S460			No connector	Flangeless
SLT4400-XP-S460				Vertical (12mm)
SLT4400-XS-S460				Horizontal (12.7mm)
SLT4460-CN-S460	Type A	Single stage isolator	SC/PC	Flangeless
SLT4460-CP-S460				Vertical (12mm)
SLT4460-CS-S460				Horizontal (12.7mm)
SLT4460-XN-S460			No connector	Flangeless
SLT4460-XP-S460				Vertical (12mm)
SLT4460-XS-S460				Horizontal (12.7mm)

7. Precaution

- (1) Radiation emitted by laser devices can be dangerous to the eyes. Avoid eye or skin exposure to direct or scattered radiation.
- (2) The modules should be handled in the same manner as ordinary semiconductor devices to prevent the electro-static damages. For safe keeping and carrying, the modules should be packaged with ESD proof material. To assemble the modules on PCB, the workbench, the soldering iron and the human body should be grounded.
- (3) The stress to the fiber pigtail may cause the damage on the performance. The fiber pigtail may snap off by dropping the module.
- (4) Please pay special attention to the atmosphere condition because the dew on the module may cause some electrical damages.
- (5) Under such a strong vibration environment as in automobile, the performance and reliability are not guaranteed.

Appendix

Part No.: SLT44□□-□□/□□□-S460

Code	Isolator
0	No isolator
6	Single stage


Pin No.	Pin function for type C
1	(CASE)
2	LD cathode
3	PD anode
4	LD anode/PD cathode

Code	Connector type
C	SC/PC
D	FC/PC
X	No connector

Code	Flange type
N	Flangeless
P	Vertical (12.0mm)
S	Horizontal (12.7mm)
X	(Customize)

Code	Pin assignment
0	Type A
6	Type C

Pin No.	Pin function for typeA and typeB
1	LD anode (CASE)
2	LD cathode
3	PD cathode
4	PD anode



Sumitomo Electric Industries, Ltd.
Part No.: SLT4400-xx-S460 Series
SLT4460-xx-S460 Series
Document No.: HUW0024123-01A
Date of issue: March 20, 2001

8. For More Information

U.S.A.

ExceLight Communications Inc.

4021 Stirrup Creek Drive, Suite 200, Durham NC, 27703

U.S.A.

Tel. (919) 361-1600

Fax. (919) 361-1619

E-mail: info@excelight.com

URL: <http://www.excelight.com>

Europe

Sumitomo Electric Europe Ltd.

220 Centennial Park, Centennial Avenue, Elstree, Herts, WD6 3SL

United Kingdom

Tel. (020) 8953-8118

Fax. (020) 8207-5950

URL: <http://www.sumielectric.com>

Japan

Sumitomo Electric Industries, Ltd. (International Business Division)

3-12, Moto-Akasaka 1-chome, Minato-ku Tokyo, 107-8468

Japan

Tel. (03) 3423-5771

Fax. (03) 3423-5099

E-mail: product_info@ppd.sei.co.jp

URL: http://www.sei.co.jp/Electro-optic/index_e.html

Sumitomo Electric Industries, Ltd.
Part No.: SLT4400-xx-S460 Series
SLT4460-xx-S460 Series
Document No.: HUW0024123-01A
Date of issue: March 20, 2001

Revision Record

Document No.	Date of issue	Description	Incorporated by	Checked by	Approved by
HUW0024123-01A	Mar./20/01	Preliminary issue.	R. Shigemoto	T. Nakanishi	M. Yoshimura

Preliminary