

1M X 36 DRAM SIMM Memory Module

FEATURES


- Performance range:

	t_{RAC}	t_{CAC}	t_{RC}
SL...-A60	60ns	15ns	110ns
SL...-A70	70ns	20ns	130ns
SL...-A80	80ns	20ns	150ns

- Fast Page Mode operation
- CAS-before-RAS refresh capability
- RAS-only and Hidden refresh capability
- TTL compatible inputs and outputs
- Single +5V $\pm$ 10% power supply
- 1024 cycles/16ms refresh
- JEDEC standard pinout
- Available in tin or gold edge connectors

PIN CONFIGURATION (Front View)

Pin	Symbol	Pin	Symbol	Pin	Symbol
1	V_{SS}	25	DQ_{24}	49	DQ_9
2	DQ_0	26	DQ_7	50	DQ_{27}
3	DQ_{18}	27	DQ_{25}	51	DQ_{10}
4	DQ_1	28	A_7	52	DQ_{28}
5	DQ_{19}	29	NC	53	DQ_{11}
6	DQ_2	30	V_{CC}	54	DQ_{29}
7	DQ_{20}	31	A_8	55	DQ_{12}
8	DQ_3	32	A_9	56	DQ_{30}
9	DQ_{21}	33	NC	57	DQ_{13}
10	V_{CC}	34	$\overline{\text{RAS}}_2$	58	DQ_{31}
11	NC	35	DQ_{26}	59	V_{CC}
12	A_0	36	DQ_8	60	DQ_{32}
13	A_1	37	DQ_{17}	61	DQ_{14}
14	A_2	38	DQ_{35}	62	DQ_{33}
15	A_3	39	V_{SS}	63	DQ_{15}
16	A_4	40	$\overline{\text{CAS}}_0$	64	DQ_{34}
17	A_5	41	$\overline{\text{CAS}}_2$	65	DQ_{16}
18	A_6	42	$\overline{\text{CAS}}_3$	66	NC
19	NC	43	$\overline{\text{CAS}}_1$	67	PD_1
20	DQ_4	44	$\overline{\text{RAS}}_0$	68	PD_2
21	DQ_{22}	45	NC	69	PD_3
22	DQ_5	46	NC	70	PD_4
23	DQ_{23}	47	$\overline{W}$	71	NC
24	DQ_6	48	NC	72	V_{SS}



0074

GENERAL DESCRIPTION

The SiliconTech SL36(S/T)6A1M1B-Axx is a 1M bits x 36 Dynamic RAM high density memory module. This module consists of two CMOS 1M x 16 DRAMs in 42-pin SOJ package and four CMOS 1M x 1 bit DRAMs in a 20-pin SOJ package mounted on a 72-pin glass epoxy substrate. A 0.1 μ F decoupling capacitor is mounted for each DRAM.

The module is a Single In-line Memory Module with tin (SL36T6A1M1B-Axx) or gold (SL36S6A1M1B-Axx) edge connections and is intended for mounting into 72-pin edge connector sockets.

Pin Names

Pin Name	Pin Function
A_0 - A_9	Address Inputs
DQ_0 - DQ_{35}	Data In/Out
$\overline{W}$	Read/Write Input
$\overline{\text{RAS}}_0$, $\overline{\text{RAS}}_2$	Row Address Strobe
$\overline{\text{CAS}}_0$ - $\overline{\text{CAS}}_3$	Column Address Strobe
PD_1 - PD_4	Presence Detect
V_{CC}	Power (+5V)
V_{SS}	Ground
NC	No Connection

Presence Detect Pins* (Optional)

Pin	60ns	70ns	80ns
PD_1	V_{SS}	V_{SS}	V_{SS}
PD_2	V_{SS}	V_{SS}	V_{SS}
PD_3	NC	V_{SS}	NC
PD_4	NC	NC	V_{SS}


* Pin Connection Changing Available

Units: Inches



TOLERANCES: ± 0.005 UNLESS OTHERWISE SPECIFIED

FUNCTIONAL BLOCK DIAGRAM



0076M