

4M X 72 Bits (32MB) DRAM Buffered 168-Pin DIMM with EDO and ECC (3.3V; 4K Refresh)

FEATURES

- Performance range:

	t_{RAC}	t_{CAC}	t_{RC}	t_{HPC}
SL...-A50V	50ns	18ns	90ns	25ns
SL...-A60V	60ns	20ns	110ns	30ns

- Extended Data Out (EDO) Mode operation
- CAS-before-RAS refresh capability
- RAS-only refresh capability
- LVTTL compatible inputs and outputs
- +3.3V $\pm$ 0.3V power supply
- 4096 cycles/64ms refresh
- JEDEC standard pinout
- ECC Optimized
- Gold edge connectors

GENERAL DESCRIPTION

The SiliconTech SL72B6C4M4F-AxxV is a 4M x 72 bits Dynamic RAM (DRAM) Dual In-line Memory Module (DIMM). This module consists of four 4M x 16 bits DRAMs in 50-pin 400-mil TSOP-II packages and two 4M x 4 bits DRAMs in 24-pin 300-mil TSOP-II packages. The DRAMs are mounted on a 168-pin glass epoxy substrate. A 0.1 μ F decoupling capacitor is mounted for each DRAM. Selected inputs are buffered for improved performance and easier memory subsystem design.

The module is intended for use in 168-pin edge connector sockets keyed for buffered signals and 3.3V power supply.

PIN CONFIGURATION

Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol
1	V_{SS}	25	NC	49	V_{CC}	73	V_{CC}	97	DQ ₄₅	121	A ₉	145	NC
2	DQ ₀	26	V_{CC}	50	NC	74	DQ ₃₂	98	DQ ₄₆	122	A ₁₁	146	NC
3	DQ ₁	27	$\overline{\text{WE}}_0$	51	NC	75	DQ ₃₃	99	DQ ₄₇	123	NC	147	NC
4	DQ ₂	28	$\overline{\text{CAS}}_0$	52	DQ ₁₈	76	DQ ₃₄	100	DQ ₄₈	124	V_{CC}	148	NC
5	DQ ₃	29	NC	53	DQ ₁₉	77	DQ ₃₅	101	DQ ₄₉	125	NC	149	DQ ₆₁
6	V_{CC}	30	$\overline{\text{RAS}}_0$	54	V_{SS}	78	V_{SS}	102	V_{CC}	126	B ₀	150	DQ ₆₂
7	DQ ₄	31	$\overline{\text{OE}}_0$	55	DQ ₂₀	79	PD ₁	103	DQ ₅₀	127	V_{SS}	151	DQ ₆₃
8	DQ ₅	32	V_{SS}	56	DQ ₂₁	80	PD ₃	104	DQ ₅₁	128	NC	152	V_{SS}
9	DQ ₆	33	A ₀	57	DQ ₂₂	81	PD ₅	105	DQ ₅₂	129	NC	153	DQ ₆₄
10	DQ ₇	34	A ₂	58	DQ ₂₃	82	PD ₇	106	DQ ₅₃	130	NC	154	DQ ₆₅
11	DQ ₈	35	A ₄	59	V_{CC}	83	ID ₀	107	V_{SS}	131	NC	155	DQ ₆₆
12	V_{SS}	36	A ₆	60	DQ ₂₄	84	V_{CC}	108	NC	132	$\overline{\text{PDE}}$	156	DQ ₆₇
13	DQ ₉	37	A ₈	61	NC	85	V_{SS}	109	NC	133	V_{CC}	157	V_{CC}
14	DQ ₁₀	38	A ₁₀	62	NC	86	DQ ₃₆	110	V_{CC}	134	NC	158	DQ ₆₈
15	DQ ₁₁	39	NC	63	NC	87	DQ ₃₇	111	NC	135	NC	159	DQ ₆₉
16	DQ ₁₂	40	V_{CC}	64	NC	88	DQ ₃₈	112	NC	136	DQ ₅₄	160	DQ ₇₀
17	DQ ₁₃	41	NC	65	DQ ₂₅	89	DQ ₃₉	113	NC	137	DQ ₅₅	161	DQ ₇₁
18	V_{CC}	42	NC	66	DQ ₂₆	90	V_{CC}	114	NC	138	V_{SS}	162	V_{SS}
19	DQ ₁₄	43	V_{SS}	67	DQ ₂₇	91	DQ ₄₀	115	NC	139	DQ ₅₆	163	PD ₂
20	DQ ₁₅	44	$\overline{\text{OE}}_2$	68	V_{SS}	92	DQ ₄₁	116	V_{SS}	140	DQ ₅₇	164	PD ₄
21	DQ ₁₆	45	$\overline{\text{RAS}}_2$	69	DQ ₂₈	93	DQ ₄₂	117	A ₁	141	DQ ₅₈	165	PD ₆
22	DQ ₁₇	46	$\overline{\text{CAS}}_4$	70	DQ ₂₉	94	DQ ₄₃	118	A ₃	142	DQ ₅₉	166	PD ₈
23	V_{SS}	47	NC	71	DQ ₃₀	95	DQ ₄₄	119	A ₅	143	V_{CC}	167	ID ₁
24	NC	48	$\overline{\text{WE}}_2$	72	DQ ₃₁	96	V_{SS}	120	A ₇	144	DQ ₆₀	168	V_{CC}

continued on the next page


PIN CONFIGURATION (continued)

Pin Names


Pin Name	Pin Function
A ₀ , B ₀ , A ₁ -A ₁₁	Address Inputs (Buffered)
DQ ₀ -DQ ₇₁	Data In/Out
$\overline{WE}_0$, $\overline{WE}_2$	Read/Write Input (Buffered)
$\overline{OE}_0$, $\overline{OE}_2$	Output Enable (Buffered)
$\overline{RAS}_0$, $\overline{RAS}_2$	Row Address Strobe
$\overline{CAS}_0$, $\overline{CAS}_4$	Column Address Strobe (Buffered)
PD ₁ -PD ₈	Presence Detect (Buffered)
$\overline{PDE}$	Presence Detect Enable
ID ₀ -ID ₁	ID Bits
V _{CC}	Power (+3.3V)
V _{SS}	Ground
NC	No Connection

Presence Detect


For 4Mx72 Bits Configuration with 4M x 16 Bits components and 4K Refresh: PD ₁ =NC, PD ₂ =NC, PD ₃ =V _{SS} , PD ₄ =NC		
For EDO: PD ₅ =NC		
Speed:		
Pin	50ns	60ns
PD ₆	V _{SS}	NC
PD ₇	V _{SS}	NC
For x72 ECC: PD ₈ =V _{SS}		
For x72 ECC: ID ₀ =V _{SS}		
For Normal Refresh Mode: ID ₁ =V _{SS}		



FUNCTIONAL BLOCK DIAGRAM



PACKAGE DIMENSIONS



577-1

TOLERANCES: ± 0.005 UNLESS OTHERWISE SPECIFIED