

- **Ideal Front-End Filter for European Wireless Receivers**
- **Low-Loss, Coupled-Resonator Quartz Design**
- **Simple External Impedance Matching**
- **F-712 Package**

SF174

Absolute Maximum Rating (Ta=25°C)		
Parameter	Rating	Unit
CW RF Power Dissipation	+ 0	dBm
DC Voltage V _{DC}	± 10	V
AC Voltage V _{pp}	10 (50Hz/60Hz)	V
Operating Temperature Range	-10 ~ +60	°C
Storage Temperature Range	-45 ~ +85	°C

Specifications					
Parameter	Sym	Minimum	Typical	Maximum	Unit
Center Frequency (25°C)	f _c	NS	174.1125	NS	MHz
Insertion Loss at f _c ± 50KHz	IL	-	-	5.0	dB
3dB Bandwidth	BW ₃	200	-	-	KHz
20dB Bandwidth	BW ₂₀	-	-	500	KHz
40dB Bandwidth	BW ₄₀	-	-	650	KHz
Attenuation f _c ± 1.0 MHz	-	45	-	-	dB
DC Insulation Resistance Between any Two Pins	-	10	-	-	MΩ

NS = Not Specified

Notes	Package Outline (F-712)
-------	-------------------------

1. Static voltage




Static voltage between signal load & ground may cause deterioration & destruction of the component. Please avoid static voltage.

2. Ultrasonic cleaning

Ultrasonic vibration may cause deterioration & destruction of the component. Please avoid ultrasonic cleaning.

3. Soldering

Only leads of component may be solder. Please avoid soldering another part of component.



Pin	Connection
1	Input
2	Ground
3	Ground
4	Output

All dimensions are in mm