


Fast CoolMOS™ Power Transistor

FEATURES:

- New revolutionary high voltage technology
- Ultra low gate charge
- Worlbest $R_{DS(on)}$ per chip area
- Ultra low effective capacitances
- Improved noise immunity

Applications:

- SMPS, resonant applications



Chip Type	V_{DS}	I_D	Die Size	Package	Ordering Code
SIPC06N60C2	600V	4A	2.45 x 2.60 mm ²	sawn on foil	tbd

MECHANICAL PARAMETER:

Raster size	2.45 x 2.60	mm
Source pad size	1.64 x 2.02	
Gate pad size	0.47 x 0.53	
Area total / active	6.37 / 3.96	mm ²
Thickness	175	μm
Wafer size	150	mm
Flat position	0	grd
Max.possible chips per wafer	2388	
Passivation frontside	Photoimide	
Emitter metallization	3200 nm Al Si 1%	
Collector metallization	1400 nm Ni Ag –system suitable for epoxy and soft solder die bonding	
Die bond	electrically conductive glue or solder	
Wire bond (proposed)	Source: Al, ≤ 500μm; Gate: Al, ≤ 125μm	
Reject Ink Dot Size	Ø 0.65mm ; max 1.2mm	
Recommended Storage Environment	store in original container, in dry nitrogen, < 6 month	

MAXIMUM RATINGS:

Parameter	Symbol	Value	Unit
Drain-Source voltage	V_{DS}	600	V
DC drain current, limited by T_{jmax}	I_D	4	A
Pulsed drain current, t_p limited by T_{jmax}	I_{Dpuls}	8	A
Gate source voltage	V_{GS}	± 20	V
Operating junction and storage temperature	T_j, T_{stg}	-55 ... +150	°C
Reverse diode dv/dt $I_S=4A, V_{DS} \leq V_{DSS}, di/dt=100 A/\mu s, T_{jmax}=150^\circ C$	dv/dt	6	KV/ μs

STATIC CHARACTERISTICS (tested on chip), $T_j=25^\circ C$, unless otherwise specified:

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D = 0.25mA$			600	V
Gate-source on-state resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=2.8A$		0.95	1.2 ¹⁾	Ω
Gate threshold voltage	$V_{GS(th)}$	$I_D=191\mu A, V_{GS}=V_{DS}$	3.5	4.5	5.5	V
Zero gate voltage drain current	I_{DSS}	$V_{DS}=600V, V_{GS}=0V$		0.1	25	μA
Gate-source leakage current	I_{GSS}	$V_{DS}=0V, V_{GS}=25V$			100	nA

¹⁾ this correlates to a max. $R_{DS(on)}$ -value of 0.95 Ω at $V_{GS}=10V, I_D=2.8A$ of this chip packaged in a TO220-package


ELECTRICAL CHARACTERISTICS (tested at component):

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
Input capacitance	C_{iss}	$V_{DS}=25V,$	-	580	-	pF
Output capacitance	C_{oss}	$V_{GS}=0V,$	-	220	-	
Reverse transfer capacitance	C_{rss}	$f=1MHz$	-	7	-	

SWITCHING CHARACTERISTICS (tested at component), Inductive Load

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
Turn-on delay time	$t_{d(on)}$	$T_j=25^\circ C$	-	55	-	ns
Rise time	t_r	$V_{DD}=350V,$	-	30	-	
Turn-off delay time	$t_{d(off)}$	$I_D=4.5 A,$	-	60	-	
Fall time	t_f	$V_{GS}=10V,$	-	15	-	
		$R_G= 18\Omega$				

CHIP DRAWING:





Preliminary

SIPC06N60C2

FURTHER ELECTRICAL CHARACTERISTICS:

This chip data sheet refers to the device data sheet		
--	--	--

DESCRIPTION:

AQL 0,65 for visual inspection according to failure catalog

Electrostatic Discharge Sensitive Device according to MIL-STD 883

Test-Normen Villach/Prüffeld

Published by
Infineon Technologies AG i Gr.,
Bereich Kommunikation
St.-Martin-Strasse 53,
D-81541 München
© Infineon Technologies AG 1999
All Rights Reserved.

Attention please!

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office in Germany or our Infineon Technologies Representatives worldwide (see address list).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.