


S2292

Dimming Option



- Note 1 Input by-pass capacitor (25 uf - 100uf) may be required to reduce reflected ripple.
- Note 2 Full brightness with no control requires that pin 3 be tied to pin 2.



Endicott Research Group, Inc.
2601 Wayne St., Endicott NY 13760
607-754-9187



Endicott Research Group, Inc.
2601 Wayne St., Endicott NY 13760
607-754-9187 Fax 607-754-9255
<http://www.ergpower.com>

S2292

Specifications and
Applications Information

9/14/99


Preliminary

8m Class
DC to AC Inverter


The ERG S2292 (*S-Series*) low profile dc to ac inverter is specifically designed to power the Sharp LM057QC1T01 LCD display module to a moderate brightness level from a +5 volt dc source.

This low profile inverter features:

- ✓ LCD Module Specific
- ✓ Display Compatible Output Connector
- ✓ Firm Specifications
- ✓ Application Information
- ✓ Designed, Manufactured and Supported in the USA
- ✓ Custom Input and Output Voltages
- ✓ Flexible System Interface



S-Series



Absolute Maximum Ratings

Rating	Symbol	Value	Units
Input Voltage Range	Vin	-0.3 to +6.0	Vdc
Operating Temperature	To	0 to +70	°C
Storage Temperature	Tstg	-40 to +85	°C

Recommended Operating Conditions

Rating	Symbol	Value	Units
Input Voltage	Vin	+2.5 to 5.5	Vdc

Electrical Characteristics

Unless otherwise noted Vin = 5.00 Volts dc and Ta = 25 °C

Characteristic	Symbol	Min	Typ	Max	Units
Input Current	Iin	-	.63	.70	Adc
Operating Frequency	Fo	30	35	40	KHz
Minimum Output Voltage	Vout (min)	1000	-	-	Vrms
Efficiency	η	-	76	-	%
Output Current	Iout	-	6	-	marms
Output Voltage (when Powering a load simulating the characteristics of the referenced display)	Vout	-	400	-	Vrms

After tube has been allowed to warm-up for 5 minutes


Specifications subject to change without notice



Endicott Research Group, Inc.

Made in USA

Typical Performance Curves



Endicott Research Group, Inc.