




TYPICAL PERFORMANCE



Horizontal: 1.0 MHz/div

Vertical (from top): Magnitude
Magnitude
Phase

10 dB/div
1 dB/div
5 deg/div


SPECIFICATION

Parameter	Min	Typ	Max	Units
Center Frequency (Fc) ¹	623.28	623.38	623.48	MHz
Insertion Loss		7.5	8.0	dB
3 dB Bandwidth	1.00	1.06		MHz
20 dB Bandwidth		2.54		MHz
Phase Linearity (in 3 dB BW)		7	10	deg p-p
Phase Slope (in 3 dB BW)		360		deg
Insertion Phase ²		40		deg
Turn Over Temperature	35	45	55	° C
Source and Load Impedance		50		Ω
Input Power		+10	+15	dBm
Operating Temperature Range	-30		100	° C

Notes: 1. Any specified bandwidths are referenced to this frequency.
2. Parameter measured at Fc.



PACKAGE OUTLINE




Units: mm

Pin Configuration:

Input: 4
Input Return: 5
Output: 8
Output Return: 1
Ground: 2,3,6,7

MATCHING CIRCUIT



Typical component values:

Ls1 = 10 nH
Cp1 = 5.1 pF

Ls2 = 10 nH
Cp2 = 5.1 pF

(minimum inductor Q = 45)

- Notes - Requires 2% matching components.
- Component values may change depending on board layout.

ISO 9001
Registered

Micro Networks Corporation

Worldwide Headquarters ■ 324 Clark Street ■ Worcester, MA 01606 ■ tel: 508-852-5400 ■ fax: 508-852-8456

European Sales Headquarters ■ Hertosingel 20 ■ 6214 AD Maastricht ■ The Netherlands ■ tel: +31-43-32-70915 ■ fax: +31-43-32-70715

www.micronetworks.com