


TYPICAL PERFORMANCE



Horizontal: 2.0 MHz/div

Vertical (from top): Magnitude
Magnitude
Phase


10 dB/div
1 dB/div
5 deg/div

SPECIFICATION

Parameter	Min	Typ	Max	Units
Center Frequency (Fc) ¹	555.61	555.71	555.81	MHz
Insertion Loss		7.5	8.0	dB
3 dB Bandwidth	1.00	1.15		MHz
20 dB Bandwidth		3.30		MHz
Phase Linearity (in 3 dB BW)		2.60	8	deg p-p
Phase Slope (in 3 dB BW)		360		deg
Insertion Phase ²		0		deg
Turn Over Temperature	35	45	55	° C
Source and Load Impedance		50		Ω
Input Power		+10	+15	dBm
Operating Temperature Range	-30		100	° C

Notes: 1. Any specified bandwidths are referenced to this frequency.
2. Parameter measured at Fc.

PACKAGE OUTLINE




Units: mm

Pin Configuration:

Input: 8
Input Return: 1
Output: 4
Output Return: 5
Ground: 2,3,6,7

MATCHING CIRCUIT



Typical component values:

Ls1 = 15 nH
Cp1 = 10 pF

Ls2 = 18 nH
Cp2 = 8.2 pF

(minimum inductor Q = 45)

- Notes
- Requires 2% matching components.
 - Component values may change depending on board layout.

ISO 9001
Registered

Micro Networks Corporation

Worldwide Headquarters ■ 324 Clark Street ■ Worcester, MA 01606 ■ tel: 508-852-5400 ■ fax: 508-852-8456
European Sales Headquarters ■ Hertosingel 20 ■ 6214 AD Maastricht ■ The Netherlands ■ tel: +31-43-32-70915 ■ fax: +31-43-32-70715
www.micronetworks.com