




TYPICAL PERFORMANCE



Horizontal: 2.0 MHz/div

Vertical (from top): Magnitude

10 dB/div


SPECIFICATION

Parameter	Min	Typ	Max	Units
Center Frequency (F_c) ¹	69.01	70	70.09	MHz
1 dB Bandwidth	3.0			MHz
3 dB Bandwidth	3.5			
40 dB Bandwidth			5.6	MHz
Ultimate Rejection ($0.5 * F_c$ to 62 MHz)	50			dB
Ultimate Rejection (78 to $1.5 * F_c$ MHz)	50			dB
Insertion Loss			27	dB
Source and Load Impedance		50		Ω
Passband Amplitude Ripple ²			0.8	dB p-p
Passband Phase Ripple ²			8.0	deg p-p
Passband Group Delay Ripple ^{2, 3}			100	ns p-p
Measurement Temperature		23		° C
Operating Temperature Range ⁴	-30		+70	° C

Notes:

1. Floating reference. All specified bandwidths track with this frequency.
2. Defined over the interval bound by the first local maxima inward from the 3 dB frequencies.
3. A 1% smoothing aperture and an averaging factor of 16 may be used for this measurement.
4. Temperature coefficient of Frequency = $-0.03\text{ppm}/(\Delta^\circ\text{C})^2$ nominal

PACKAGE OUTLINE




Units: mm

Pin Configuration:

Input: 1
Input Return: 14
Output: 8
Output Return: 7
Ground: 2,9

MATCHING CIRCUIT



Typical component values:
(minimum inductor Q = 45)

Ls1 = 425 nH
Lp1 = 68 nH

Ls2 = 455 nH
Lp2 = 68 nH

- Notes
- Requires variable matching components.
 - Coilcraft 1008HT (fixed) and LM2 (7-mm variable) series recommended
 - Component values may change depending on board layout.

ISO 9001
Registered

Micro Networks Corporation

Worldwide Headquarters ■ 324 Clark Street ■ Worcester, MA 01606 ■ tel: 508-852-5400 ■ fax: 508-852-8456

European Sales Headquarters ■ Hertosingel 20 ■ 6214 AD Maastricht ■ The Netherlands ■ tel: +31-43-32-70915 ■ fax: +31-43-32-70715

www.micronetworks.com