


TYPICAL PERFORMANCE




Horizontal: 2.5 MHz/div

Vertical (from top): Magnitude 10 dB/div
 Magnitude 1 dB/div
 Group Delay 50 nsec/div

SPECIFICATION

Parameter	Min.	Typical	Max.	Units.
F_visual		45.75		MHz
F_color		42.17		MHz
F_audio		41.25		MHz
Center Frequency (Nominal)		44.05		MHz
Insertion Loss		23	25	dB
1 dB Lower band edge			41.05	MHz
1 dB upper band edge	46.55			MHz
Passband Ripple(41.05 - 46.55)		0.5	0.8	dB
Phase deviation (41.05-46.55)		8	12	deg p-p
GD Ripple (41.05 - 46.55)		25	50	ns p-p
Rejection at 47.05	20			dB
Rejection (10 - 39.75)	40	45		dB
Rejection (47.25 - 70.0)	40	45		dB
2T K Factor		2		%
Ambient Temperature		25		deg C
Temperature coefficient		-96		ppm/deg C
Source/Load impedance		50		Ω
Tuning	None			
Material	YZ Lithium Niobate			

PACKAGE OUTLINE




Units: mm

Pin Configuration:

Input: 14
 Input Return: 1
 Output: 7
 Output Return: 8
 Ground: All other pins.

MATCHING CIRCUIT



No matching required

ISO 9001
Registered

Micro Networks Corporation

Worldwide Headquarters ■ 324 Clark Street ■ Worcester, MA 01606 ■ tel: 508-852-5400 ■ fax: 508-852-8456
European Sales Headquarters Hertosingel 20 ■ 6214 AD Maastricht ■ The Netherlands ■ tel: +31-43-32-70915 ■ fax: +31-43-32-70715
www.micronetworks.com