


TYPICAL PERFORMANCE




Horizontal: 2.5 MHz/div

Vertical (from top): Magnitude 10 dB/div
 Magnitude 1 dB/div
 Group Delay 50 nsec/div

SPECIFICATION

Parameter	Min.	Typical	Max.	Units.
F_visual		38.9		MHz
F_color		32.9		MHz
F_audio		32.4		MHz
Center Frequency (Nominal)		36		MHz
Insertion Loss	28		32	dB
2 dB Lower band edge			31.95	MHz
2 dB upper band edge	39.35			MHz
Passband Ripple(32.2 - 39.35)		0.3	0.8	dB
Phase deviation (32.2 - 39.35)		2.5	8	deg p-p
GD Ripple (32.2 - 39.35)		30	50	ns p-p
Rejection (20 - 31.10)	45	55		dB
Rejection (31.1 - 31.3)	52	60		dB
Rejection (39.7 - 65.0)	45	55		dB
2T K Factor		1		%
C/L Delay - 12.5 T		5		ns
Delay		4.5		us
Ambient Temperature		40		deg C
Temperature coefficient		-72		ppm/deg C
Source/Load impedance		50		Ω
Tuning	None			
Material	128 Lithium Niobate			

PACKAGE OUTLINE




Units: mm

Pin Configuration:

Input: 3
 Input Return: 22
 Output: 15
 Output Return: 10
 Ground: All other pins.

MATCHING CIRCUIT



No matching required

ISO 9001
Registered

Micro Networks Corporation

Worldwide Headquarters ■ 324 Clark Street ■ Worcester, MA 01606 ■ tel: 508-852-5400 ■ fax: 508-852-8456
European Sales Headquarters Hertosingel 20 ■ 6214 AD Maastricht ■ The Netherlands ■ tel: +31-43-32-70915 ■ fax: +31-43-32-70715
www.micronetworks.com