

## SWITCH-Cubes

### Features

- Bi- or mono-stable fiber-optical switching module
- Low switching power required
- Micro-hybrid construction in a sealed metal housing
- Epoxy-free optical path
- Small Form Factor Components (SFFC), dimensions: 15 x 15 x 15 mm<sup>3</sup>, other dimensions on demand
- Flexible Fiber Connection Technology (FFCT), for details see Products page
- All types of single mode as well as multi mode fibers possible
- Extremely wide band of wavelengths possible (VIS-IR)
- Fiber packaging: loose tube or 250 µm coating

### Applications

- Network switching in central office environments
- Optical network protection and restoration
- Configurable optical add/drop
- Transmitter and receiver protection
- Bi-directional or unidirectional systems
- Cable TV, Metro Core, Metro Access, Metro Enterprise, WAN, RFTS



### Specifications

Parameters	Fiber-optical Switches	
Port configurations	1 x 1 (on / off), 1 x 2, 2 x 2	
Wavelength range	1290-1330 nm and 1525-1575 nm	
Insertion loss*	1 x 1, 1 x 2	< 0.8 dB
	2 x 2	< 1.0 dB
Return loss *	> 50 dB	
Polarization dependent loss	< 0.1 dB	
Crosstalk	> 50 dB	
Switching time	< 10 ms	
Operating temperature	0°C – 70°C	
Storage temperature	-45°C – 85°C	
Package dimensions	15 x 15 x 15 mm <sup>3</sup>	

\* It is the max. loss at entire wavelength range, valid over full temperature range and at all states of polarization but without connector losses.

**Additional components according to your specifications on demand!**

Our SWITCH-Cubes switch and control your data flow.



## Ordering Information

Indicate your requirements by selecting one option from each configuration table. Please print the corresponding codes in the available boxes to form your part number. For more information on this or other products and their availability, please contact Cube Optics AG at +49 - 6131-698510 or via e.mail at sales@cubeoptics.com, or visit our website at www.cubeoptics.com.

Ordering example: S-1-2-A-0-S-3-B-15

S-  -  -  -  -  -  -  -  -  -

no. of input ports	code
1	1
2	2

wavelength	code
1310 nm/1550 nm	A

fiber connection	code
in- and output on same side	S
in- and output on opposite sides	O
rectangular connection	R

fiber length	code
0.5 m	A
1 m	B
1.5 m	C

connector in/ out	code
none	0
SC/PC	1
FC/PC	2
SC/APC	3
FC/APC	4
LC/PC	5
MU/PC	6
E2000/HRL	7

no. of output ports	code
1	1
2	2

optional features	code
none	0

fiber type and packaging	code
Corning SMF-28™ (9,125,250 µm) 900 µm loose tube	1
Corning SMF-28™ (9,125,250µm) 250 µm coating	2
multi mode fiber GI (50,125,250 µm) 900 µm loose tube	3
multi mode fiber GI (50,125,250 µm) 250 µm coating	4

**Corporate Office:**  
Cube Optics AG  
Robert-Koch-Strasse 30  
D-55129 Mainz  
Germany  
Tel.: +49-61 31/ 698 51-0  
Fax: +49-61 31/ 698 51-79  
e.mail: info@cubeoptics.com

**Technical Support**  
Cube Optics AG - Sales Office Munich  
Ganghoferstr. 3a  
D-82216 Maisach-Gerlinden  
Germany  
Tel.: +49-8142/44 53-81  
Fax: +49-8142/44 53-82  
e.mail:sales@cubeoptics.com