

SF5S6

60V 5A


FEATURES

- Tj150°C
- P_{RSSM} avalanche guaranteed
- Fully Isolated Molding
- Dielectric strength 1.5KV guaranteed

APPLICATION

- Switching power supply
- DC/DC converter
- Home Appliances, Office Equipment
- Telecommunication

OUTLINE DIMENSIONS



RATINGS

- Absolute Maximum Ratings (If not specified T_c=25°C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-55~150	°C
Operating Junction Temperature	Tj		150	°C
Maximum Reverse Voltage	V _{RM}		60	V
Repetitive Peak Surge Reverse Voltage	V _{RRSM}	Pulse width 0.5ms, duty 1/40	65	V
Average Rectified Forward Current	I _O	50Hz sine wave, R-load, T _c =134°C	5	A
Peak Surge Forward Current	I _{FSM}	50Hz sine wave, Non-repetitive 1 cycle peak value, T _j =25°C	150	A
Repetitive Peak Surge Reverse Power	P _{RRSM}	Pulse width 10 μs, T _j =25°C	330	W
Dielectric Strength	V _{dis}	Terminals to case, AC 1 minute	1.5	kV
Mounting Torque	TOR	(Recommended torque: 0.3N·m)	0.5	N·m

- Electrical Characteristics (If not specified Tc=25°C)

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	V_F	$I_F=5A$ Pulse measurement	Max.0.58	V
Reverse Current	I_R	$V_R=V_{RM}$ Pulse measurement	Max. 4.5	mA
Junction Capacitance	C_j	$f=1MHz, V_R=10V$	Typ.260	pF
Thermal Resistance	θ_{jc}	junction to case	Max.3.5	°C/W


SF5S6

Forward Voltage




SF5S6

Junction Capacitance




SF5S6

Reverse Current




SF5S6

Reverse Power Dissipation




$T_j = 150^\circ\text{C}$



SF5S6

Forward Power Dissipation




$T_j = 150^\circ\text{C}$



SF5S6

Derating Curve




$V_R = 30V$



SF5S6

Peak Surge Forward Capability



SBD Repetitive Surge Reverse Power Derating Curve



