

SF5SC3L

30V 5A


FEATURES

- Tj150°C
- Low VF=0.45V
- PRRSM avalanche guaranteed
- Fully Isolated Molding
- Dielectric strength 2kV guaranteed

APPLICATION

- Switching power supply
- DC/DC converter
- Home Appliances, Office Equipment
- Telecommunication

OUTLINE DIMENSIONS



RATINGS

● Absolute Maximum Ratings (If not specified Tc=25°C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-55~150	°C
Operating Junction Temperature	Tj		150	°C
Maximum Reverse Voltage	VRM		30	V
Repetitive Peak Surge Reverse Voltage	VRRSM	Pulse width 0.5ms, duty 1/40	35	V
Average Rectified Forward Current	Io	50Hz sine wave, R-load, Rating for each diode Io/2, Tc=143°C	5	A
Peak Surge Forward Current	IFSM	50Hz sine wave, Non-repetitive 1 cycle peak value, Tj=25°C	100	A
Repetitive Peak Surge Reverse Power	PRRSM	Pulse width 10 μs, Rating of per diode, Tj=25°C	330	W
Dielectric Strength	Vdis	Terminals to case, AC 1 minute	2.0	kV
Mounting Torque	TOR	(Recommended torque:0.3N·m)	0.5	N·m

● Electrical Characteristics (If not specified Tc=25°C)


Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	VF	IF=2.5A, Pulse measurement, Rating of per diode	Max.0.45	V
Reverse Current	IR	VR=VRM, Pulse measurement, Rating of per diode	Max.3.5	mA
Junction Capacitance	Cj	f=1MHz, VR=10V, Rating of per diode	Typ.220	pF
Thermal Resistance	θjc	junction to case	Max.2.3	°C/W

SF5SC3L

Forward Voltage




SF5SC3L Junction Capacitance




SF5SC3L

Reverse Current




SF5SC3L Reverse Power Dissipation




$T_j = 150^\circ\text{C}$



SF5SC3L Forward Power Dissipation




$T_j = 150^\circ\text{C}$




SF5SC3L

Derating Curve




$V_R = 15\text{V}$



SF5SC3L

Peak Surge Forward Capability



SBD Repetitive Surge Reverse Power Derating Curve

