

S16L60

600V 16A

FEATURES

- High Voltage
- $\tau_{rr} 100\text{ns}$
- Small θ_{jc}


APPLICATION

- PFC
- Switching power supply
- Free Wheel
- Home Appliances, Office Equipment,
Factory Automation

OUTLINE DIMENSIONS

Case : MTO-3P

(Unit : mm)



RATINGS

●Absolute Maximum Ratings (If not specified Tc=25°C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-55~150	°C
Operating Junction Temperature	Tj		150	°C
Maximum Reverse Voltage	V _{RM}		600	V
Average Rectified Forward Current	I _O	50Hz sine wave, R-load, T _c =122°C	16	A
Peak Surge Forward Current	I _{FSM}	50Hz sine wave, Non-repetitive 1 cycle peak value, T _j =25°C	300	A
Mounting Torque	TOR	(Recommended torque: 0.5N·m)	0.8	N·m

●Electrical Characteristics (If not specified Tc=25°C)

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	V_F	$I_F=16A$, Pulse measurement	Max.1.5	V
Reverse Current	I_R	$V_R=V_{RM}$, Pulse measurement	Max.25	μA
Reverse Recovery Time	t_{rr}	$I_F=0.5A$, $I_R=1A$	Max.100	ns
Thermal Resistance	θ_{jc}	junction to case	Max.1.1	$^{\circ}C/W$


S16L60

Forward Voltage



S16L60

Forward Power Dissipation




$T_j = T_{jmax}$




S16L60

Derating Curve




$$V_R = V_{RM}$$



S16L60

Peak Surge Forward Capability



S16L60 Junction Capacitance

