


Si PIN photodiode array

S8558

Surface mountable 16-element photodiode array



S8558 is a 16-element Si PIN photodiode array in a ceramic chip carrier package suitable for surface mount using solder reflow techniques. S8558 can be used in a wide range of applications including spectrophotometer and position detection.

Features

- Active area: 0.7×2.0 mm ($\times 16$ elements)
- Ceramic chip carrier package for surface mount
- Suitable for solder reflow
- High sensitivity

Applications

- Spectrophotometers
- Position detection


■ Absolute maximum ratings ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Reverse voltage	V_R Max.	30	V
Operating temperature	T_{opr}	-40 to +100	$^\circ\text{C}$
Storage temperature	T_{stg}	-40 to +125	$^\circ\text{C}$


■ Electrical and optical characteristics ($T_a=25^\circ\text{C}$, per 1 element)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Spectral response range	λ		-	320 to 1100	-	nm
Peak sensitivity wavelength	λ_p		-	960	-	nm
Photo sensitivity	S	$\lambda=660$ nm	-	0.45	-	A/W
		$\lambda=780$ nm	-	0.57	-	A/W
		$\lambda=830$ nm	-	0.62	-	A/W
		$\lambda=\lambda_p$	-	0.72	-	A/W
Short circuit current	I_{sc}	100 lx	-	1.0	-	μA
Dark current	I_D	$V_R=10\text{ V}$	-	0.05	1.0	nA
Temperature coefficient of I_D	T_{CID}		-	1.15	-	times/ $^\circ\text{C}$
Cut-off frequency	f_c	$V_R=10\text{ V}$, $R_L=50\ \Omega$ $\lambda=830$ nm, -3 dB	-	25	-	MHz
Terminal capacitance	C_t	$V_R=10\text{ V}$, $f=1\text{ MHz}$	-	5	10	pF
Noise equivalent power	NEP	$\lambda=\lambda_p$	-	5.6×10^{-15}	-	$\text{W/Hz}^{1/2}$


■ Spectral response




■ Dark current vs. reverse voltage




■ Terminal capacitance vs. reverse voltage



■ Cut-off frequency vs. reverse voltage



■ Dimensional outline (unit: mm)

**HAMAMATSU**

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Hamamatsu City, 435-8558 Japan, Telephone: (81) 053-434-3311, Fax: (81) 053-434-5184, <http://www.hamamatsu.com>

U.S.A.: Hamamatsu Corporation, 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658

France: Hamamatsu Photonics France S.A.R.L.: 8, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741

Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2002 Hamamatsu Photonics K.K.