


Si photodiode S2551

For visible to infrared precision photometry



S2551 is a Si photodiode having a long active area of 1.2×29.1 mm, designed for visible to infrared precision photometry.

Features

- Long, narrow active area: 1.2×29.1 mm
- High sensitivity
- Low capacitance

Applications

- Analytical instruments
- Optical measurement equipment


■ Absolute maximum ratings

Parameter	Symbol	Value	Unit
Reverse voltage	V_R Max.	30	V
Operating temperature	T_{opr}	-20 to +60	°C
Storage temperature	T_{stg}	-20 to +80	°C

■ Electrical and optical characteristics ($T_a=25$ °C)


Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Spectral response range	λ		-	320 to 1060	-	nm
Peak sensitivity wavelength	λ_p		-	920	-	nm
Photo sensitivity	S	$\lambda=\lambda_p$	-	0.6	-	A/W
		$\lambda=663$ nm	-	0.37	-	A/W
Short circuit current	I_{sc}	$100 I_x$	24	30	-	μ A
Dark current	I_D	$V_R=10$ mV	-	-	1	nA
Temperature coefficient of I_D	T_{CID}		-	1.15	-	times/°C
Rise time	t_r	$V_R=0$ V, $R_L=1$ k Ω	-	0.6	-	μ s
Terminal capacitance	C_t	$V_R=0$ V, $f=10$ kHz	-	350	-	pF
Shunt resistance	R_{sh}	$V_R=10$ mV	0.01	0.03	-	G Ω
Noise equivalent power	NEP		-	3.9×10^{-14}	-	W/Hz ^{1/2}

■ Spectral response




KSPDB0173EA

■ Photo sensitivity temperature characteristic




KSPDB0053EB

■ Rise time vs. load resistance




KSPDB0174EA

■ Dark current vs. reverse voltage




KSPDB0175EA

■ Shunt resistance vs. ambient temperature



KSPDB0176EA

■ Dimensional outline (unit: mm)



→ The resin coating may extend a maximum of 0.1 mm beyond the upper surface of the package.

KSPDA0116EA

HAMAMATSU

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Hamamatsu City, 435-8558 Japan, Telephone: (81) 053-434-3311, Fax: (81) 053-434-5184, <http://www.hamamatsu.com>

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658

France: Hamamatsu Photonics France S.A.R.L.: 8, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741

Cat. No. KSPD1027E01
Mar. 2001 DN