## **CO Alarm**

**U** Product Information

Model:

S910HA-K2

**Description:** 

| Model                                  | S910HA-K1   |
|--|---|
| Alarm Output                           | When the thickness of CO reaches 50ppm-100ppm, the red lamp will flash to alarm within 2.5 minutes; When the thickness of CO reaches 100ppm-300ppm, the red lamp and green lamp will flash by turns to alarm within 2.5 minutes; alarm buzzer sounds (80dB); Output Signal: No connection of relay; Contact Capacity: DC24V 100mA                   |
| Operating<br>Temperature &<br>Humidity | Temperature: -10℃-±50℃ Humidity: <85%RH   |
| Power Supply                           | AC 220V/50Hz±10%  |
| Power<br>Consumption                   | <4W   |
| Dimension &<br>Weight                  | 140×84×40(mm) Wiehgt: about 400g  |
| Application                            | carbon monoxide in pipe gas carbon monoxide produced when gas doesn't burn fully smell sensitive made in Japan automatic cleaning, failure selfchecking five-year warranty high sensitivity Adapted to Network System   |
|  | Selfchecking: Every time it is switched on, it will simulate alarm for 12 minutes. The buzzer sounds and the red lamp and green lamp flashes by turns to show the alarm works properly. In the case of monitoring, if the buzzer makes a sound once every five seconds, it means the alarm goes wrong. If so, it should be sent to the manufacture. |