



ultrasonic sensor diffuse mode sensor S18UBARQ



- compact housing style
- connection via M12 x 1 connector
- temperature compensation
- very small blind zone
- switching range adjustable via teach-in
- adjustable retroreflective mode

Wiring diagram



Ultrasonic sensors use ultrasonic waves for non-contact and wear-free detection of a large variety of objects. It does not matter whether the object is transparent or opaque, metallic or non-metallic, or of liquid, solid or powdery consistence. Environmental conditions such as spray, dust or rain hardly affect their function.

Type	S18UBARQ
Ident-No.	3002715
Max. sensing range [cm]	3... 30 cm
Operating mode	Ultrasonic sensors with discrete output
Temperature drift	±0,3 % v.E.
Min. absolute repeat accuracy	≥ ± 0,5 mm
Length of nominal target	50 mm
Operating temperature	-20 ...+ 60 °C
Rated operational voltage (DC) U_B	10... 30 VDC
No-load current I ₀	≤ 100 mA
Output function	normally open, PNP/NPN
Short-circuit protection	yes
Reverse polarity protection	complete
Switching frequency	≤ 100 Hz
Wire breakage protection	yes
Housing style	cylindrical/thread; S18U
Dimensions	95,1 mm
Housing diameter	18 mm
Thread length	39,9 mm
Housing material	plastic, PBT
Wiring	connector, M12 x 1
Degree of protection	IP67
Switching status indication	LED yellow
Indication 'object includes'	LED green