



TCS600

600 Watts, 50 Volts, Pulsed
Avionics 1030 MHz

GENERAL DESCRIPTION

The TCS600 is a high power COMMON BASE bipolar transistor. It is designed for pulsed systems in the frequency band 1030/1090 MHz, with the pulse width and duty required for TCAS applications. The device has gold thin-film metallization and diffused ballasting for proven highest MTTF. The transistor includes input and output prematch for broadband capability. Low thermal resistance package reduces junction temperature, extends life.

ABSOLUTE MAXIMUM RATINGS

Maximum Power Dissipation

Device Dissipation @25°C 1458 W

Maximum Voltage and Current

Collector to Base Voltage (BV_{ces}) 65 V

Emitter to Base Voltage (BV_{ebo}) 3.5 V


Collector Current (I_c) 40 A

Maximum Temperatures

Storage Temperature -65 to +200 °C

Operating Junction Temperature +230 °C

CASE OUTLINE 55ST Style 1



ELECTRICAL CHARACTERISTICS @ 25°C

SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
P_{out}	Power Out	F = 1030 MHz	600			W
P_{in}	Power Input	$V_{CC} = 50$ Volts			80	W
P_g	Power Gain	PW = 32 μ sec	8.7			dB
η_c	Collector Efficiency	DF = 1%		50		
Pd	Pulse Droop			0.5		dB
VSWR	Load Mismatch Tolerance	F = 1030 MHz			4:1	

FUNCTIONAL CHARACTERISTICS @ 25°C

BV_{ebo}^*	Emitter to Base Breakdown	$I_e = 50$ mA	3.5			V
BV_{ces}	Collector to Emitter Breakdown	$I_c = 100$ mA	65			V
h_{FE}^*	DC – Current Gain	$V_{ce} = 5V, I_c = 5A$	20			
θ_{jc}^1	Thermal Resistance				0.12	°C/W

NOTE 1: At rated output power and pulse conditions.

*: Not measureable due to internal EB returns.

Initial Issue MAY 1999