

# TLS1255 VIDEO PREAMPLIFIER SYSTEM WITH ON-SCREEN DISPLAY (OSD) MIXER

SLVS142 – DECEMBER 1996

- Wide Bandwidth . . . Typ 100 MHz at –3 dB
- Color Saturation Control Features
- Digital Level Control (0 V to 4 V) for Contrast, Color, and Brightness
- Mixer Function for OSD Applications
- Blanking Function for On-Screen Display (OSD) Applications
- Fewer Peripheral Components Required
- Low-Impedance Output Driver

## description

The TLS1255 is a wide-band video preamplifier system intended for high-resolution red-green-blue (RGB) color monitors with color-saturation control features. The saturation of a color refers to the degree of chroma or purity, or the degree of freedom from admixture with white. In addition to the RGB preamplifier function, the TLS1255 provides color-saturation control and gain control at the video system outputs. Each video amplifier (R, G, and B) contains a gain set for adjusting maximum system gain ( $A_V = 6$  dB). The TLS1255 provides a digital level-operated contrast, brightness, color, and gain adjustment. The video-output stages from TLS1255 directly drive CRT power amplifiers.

The system has been designed to operate from a 12-V supply with all digital level controls operating over a 0-V to 4-V range to make the interface to serial digital buses possible. The TLS1255 also contains a blanking circuit that clamps the video output voltage to within 0.2 V of ground. The mixer circuit required for the OSD application is also integrated into the TLS1255, which makes the design of video boards and other applications easier.

The TLS1255 is characterized for operation from 0°C to 70°C.

## N PACKAGE (TOP VIEW)

R_OSD_IN	1	28	OSD_ADJUST
G_OSD_IN	2	27	R_GAIN_ADJUST
B_OSD_IN	3	26	R_CLAMP(+)
R_VIDEO_IN	4	25	R_VIDEO_OUT
R_CLAMP_CAP	5	24	G_GAIN_ADJUST
G_VIDEO_IN	6	23	V <sub>CC2</sub>
GND	7	22	G_VIDEO_OUT
G_CLAMP_CAP	8	21	G_CLAMP(+)
B_VIDEO_IN	9	20	B_VIDEO_OUT
B_CLAMP_CAP	10	19	B_GAIN_ADJUST
V <sub>CC1</sub>	11	18	GND
CONTRAST	12	17	BLANKING
COLOR	13	16	OSD_BLANKING
CLAMP_GATE	14	15	B_CLAMP(+)



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

 **TEXAS  
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265


Copyright © 1996, Texas Instruments Incorporated

**TLS1255**  
**VIDEO PREAMPLIFIER SYSTEM**  
**WITH ON-SCREEN DISPLAY (OSD) MIXER**

SLVS142 – DECEMBER 1996

**TLS1255Y chip information**

This chip, when properly assembled, displays characteristics similar to the TLS1255. Thermal compression or ultrasonic bonding may be used on the doped-aluminum bonding pads. The chips may be mounted with conductive epoxy or a gold silicon preform.



**absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†**

Supply voltage, V <sub>CC</sub> (see Note 1)	13.5 V
Input voltage range, V <sub>I</sub> (see Note 1)	0 V to V <sub>CC</sub>
Video output current, I <sub>O</sub> (per channel)	28 mA
Total power dissipation at (or below) 25°C free-air temperature (see Note 2)	2.37 W
Operating virtual junction temperature range, T <sub>J</sub>	150°C
Operating free-air temperature range, T <sub>A</sub>	0°C to 70°C
Storage temperature range, T <sub>stg</sub>	-65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds	260°C

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES: 1. All V<sub>CC</sub> terminals must be externally wired together to prevent internal damage during V<sub>CC</sub> power-on/-off cycles.  
 2. For operation above 25°C free-air temperature, derate linearly to 1.52 W at the rate of 19 mW/°C.



**recommended operating conditions**

	MIN	NOM	MAX	UNIT	
Supply voltage, $V_{CC1}$ and $V_{CC2}$	11	12	13	V	
High-level input voltage range, $\overline{\text{CLAMP GATE}}$ , $V_{IH}$	Clamp comparators off		2.4	5	V
Low-level input voltage range, $\overline{\text{CLAMP GATE}}$ , $V_{IL}$	Clamp comparators on		0	0.8	V
High-level input voltage range, $\overline{\text{BLANKING}}$ , $V_{IH}$	Blanking circuit inactive		2.4	5	V
Low-level input voltage range, $\overline{\text{BLANKING}}$ , $V_{IL}$	Blanking circuit active		0	0.8	V
High-level input voltage range, $\overline{\text{OSD BLANKING}}$ , $V_{IH}$	OSD Blanking circuit inactive		2.4	5	V
Low-level input voltage range, $\overline{\text{OSD BLANKING}}$ , $V_{IL}$	OSD Blanking circuit active		0	0.8	V
Operating free-air temperature, $T_A$			0	70	°C

**electrical characteristics at 25°C free-air temperature range,  $\overline{\text{CLAMP GATE}} = \text{COLOR} = 0 \text{ V}$ ;  $\text{R,G,B CLAMP}(+) = 2 \text{ V}$ ;  $\overline{\text{BLANKING}} = \overline{\text{OSD BLANKING}} = 4 \text{ V}$ ;  $\text{CONTRAST} = \text{R, G, B GAIN ADJUST} = 4 \text{ V}$ ;  $V_{CC1} = V_{CC2} = 12 \text{ V}$  (unless otherwise noted)**

PARAMETER	ALTERNATE SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$I_{CC}$ Supply current		$V_{CC1} + V_{CC2}$		110	130	mA
$V_{ref}$ Video input reference voltage		Measure R,G,B VIDEO_IN voltage	1.6	1.8	2.1	V
$I_{IL}$ $\overline{\text{CLAMP GATE}}$ low input current		$\overline{\text{CLAMP GATE}} = 0 \text{ V}$		-0.5	-8	μA
$I_{IH}$ $\overline{\text{CLAMP GATE}}$ high input current		$\overline{\text{CLAMP GATE}} = 12 \text{ V}$		0.005	1	μA
Clamp-capacitor charge current	$I_{K(chg)}$	R,G,B CLAMP CAP = 0 V		850		μA
Clamp-capacitor discharge current	$I_{K(dschg)}$	R,G,B CLAMP CAP = 5 V		-850		μA
$V_{OL}$ Low-level output voltage		R,G,B CLAMP CAP = 0 V		0.2	0.6	V
$V_{OH}$ High-level output voltage		R,G,B CLAMP CAP = 5 V	6.7	7.6		V
Video output blanked voltage	$V_{O(BLANK)}$	$\overline{\text{BLANKING}} = 0 \text{ V}$ ; R,G,B CLAMP(+) = 3 V		0.2	0.35	V
High-level output voltage, OSD	$V_{O(OSD BLANK)}$	$\overline{\text{OSD BLANKING}} = 0 \text{ V}$ ; $V_{O(PP)(OSD)} = 4 \text{ V}$			0.8	V
Output voltage difference	$V_{ODIFF}$	Between any two channels			50	mV
Spot-killer voltage	$V_{SPOT}$	$V_{CC}$ adjusted to active	8.2		10.3	V

**TLS1255**  
**VIDEO PREAMPLIFIER SYSTEM**  
**WITH ON-SCREEN DISPLAY (OSD) MIXER**


SLVS142 – DECEMBER 1996

operating characteristics at 25°C free-air temperature,  $\overline{\text{CLAMP GATE}} = \text{COLOR} = 0 \text{ V}$ ;  $\text{R,G,B CLAMP}(+) = 2 \text{ V}$ ,  $\overline{\text{BLANKING}} = \text{OSD BLANKING} = 4 \text{ V}$ ;  $\text{CONTRAST} = \text{R,G,B GAIN ADJUST} = 4 \text{ V}$ ;  $V_{CC1} = V_{CC2} = 12 \text{ V}$  (unless otherwise noted)

PARAMETER	ALTERNATE SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
A <sub>V(max)</sub> (CONTRAST) Maximum voltage amplification	A <sub>VMAX</sub> (cont)	CONTRAST = 4 V, COLOR = 0 V, V <sub>I(PP)</sub> = 700 mV		7.6		V/V
		CONTRAST = 4 V, COLOR = 4 V, V <sub>I(PP)</sub> = 700 mV		7.6		V/V
t <sub>r</sub> (video) Rise time, video output	T <sub>r</sub> (video)	V <sub>O(PP)</sub> = 4 V		3.5		ns
t <sub>f</sub> (video) Fall time, video output	T <sub>f</sub> (video)	V <sub>O(PP)</sub> = 4 V		3.5		ns
t <sub>r</sub> (BLANK) Rise time, blank output	T <sub>r</sub> (BLANK)	BLANKING = 0 V, Blanking output V <sub>I(PP)</sub> = 1 V		7		ns
t <sub>f</sub> (BLANK) Fall time, blank output	T <sub>f</sub> (BLANK)	BLANKING = 0 V, Blanking output V <sub>O(PP)</sub> = 1 V		7		ns
t <sub>r</sub> (OSD_BLANK) Rise time, OSD blank output	T <sub>r</sub> (OSD BLANK)	$\overline{\text{OSD\_BLANKING}} = 0 \text{ V}$ ; OSD_ADJUST = 0 V		7		ns
t <sub>f</sub> (OSD_BLANK) Fall time, OSD blank output	T <sub>f</sub> (OSD BLANK)	$\overline{\text{OSD\_BLANKING}} = 0 \text{ V}$ ; OSD_ADJUST = 0 V		7		ns
t <sub>r</sub> (OSD_MIXER) Rise time, OSD mixer	T <sub>r</sub> (OSD MIXER)	$\overline{\text{OSD\_BLANKING}} = 0 \text{ V}$ ; V <sub>O(PP)</sub> (OSD) = 4 V		7		ns
t <sub>f</sub> (OSD_MIXER) Fall time, OSD mixer	T <sub>f</sub> (OSD MIXER)	$\overline{\text{OSD\_BLANKING}} = 0 \text{ V}$ ; V <sub>O(PP)</sub> (OSD) = 4 V		7		ns
t <sub>pd</sub> Propagation delay, video to OSD MIXER	T <sub>rprop</sub> (OSD)	$\overline{\text{OSD\_BLANKING}} = 0 \text{ V}$ ; V <sub>O(PP)</sub> (OSD) = 4 V		15		ns
	T <sub>fprop</sub> (OSD)	$\overline{\text{OSD\_BLANKING}} = 0 \text{ V}$ ; V <sub>O(PP)</sub> (OSD) = 4 V		15		ns
BW Bandwidth, amplifier	bw (-3dB)	V <sub>O(PP)</sub> = 4 V, CLAMP+ = 2 V		100		MHz



**APPLICATION INFORMATION**



† Minimum pulse width = 300 ns

**Figure 1. Application and Test Circuit**

**TLS1255**  
**VIDEO PREAMPLIFIER SYSTEM**  
**WITH ON-SCREEN DISPLAY (OSD) MIXER**


SLVS142 – DECEMBER 1996

**MECHANICAL DATA**

**N (R-PDIP-T\*\*)**

**PLASTIC DUAL-IN-LINE PACKAGE**

24 PIN SHOWN



4040053/B 04/95

- NOTES: A. All linear dimensions are in inches (millimeters).  
 B. This drawing is subject to change without notice.  
 C. Falls within JEDEC MS-011  
 D. Falls within JEDEC MS-015 (32 pin only)

## IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.