

# TC74HC151AP, TC74HC151AF, TC74HC151AFN

## 8 - CHANNEL MULTIPLEXER

The TC74HC151A is a high speed CMOS 8 - CHANNEL MULTIPLEXER fabricated with silicon gate C<sup>2</sup>MOS technology.

It achieves the high speed operation similar to equivalent LSTTL while maintaining the CMOS low power dissipation.

One of eight data input signals (D0 - D7) is selected by decoding of the three - bit address input (A, B, C). The selected data appears on two outputs: non - inverting (Y) and inverting (W).

The strobe input provides two output conditions; a low level on the strobe input transfers the selected data to the outputs. A high level on the strobe input sets the Y output low and the W output high without regard to the data or select input conditions.

All inputs are equipped with protection circuits against static discharge or transient excess voltage.

### FEATURES:


- High Speed..... $t_{pd} = 15\text{ns}(\text{typ.})$  at  $V_{CC} = 5\text{V}$
- Low Power Dissipation..... $I_{CC} = 4\mu\text{A}(\text{Max.})$  at  $T_a = 25^\circ\text{C}$
- High Noise Immunity..... $V_{NIH} = V_{NIL} = 28\% V_{CC}(\text{Min.})$
- Output Drive Capability..... 10 LSTTL Loads
- Symmetrical Output Impedance...  $|I_{OH}| = I_{OL} = 4\text{mA}(\text{Min.})$
- Balanced Propagation Delays.....  $t_{PLH} = t_{PHL}$
- Wide Operating Voltage Range....  $V_{CC}(\text{opr.}) = 2\text{V} \sim 6\text{V}$
- Pin and Function Compatible with 74LS151

### TRUTH TABLE


| INPUTS |   |   |                 | OUTPUTS |                 |
|--------|---|---|-----------------|---------|-----------------|
| SELECT |   |   | STROBE          | Y       | W               |
| C      | B | A | $\overline{ST}$ |         |                 |
| X      | X | X | H               | L       | H               |
| L      | L | L | L               | D0      | $\overline{D0}$ |
| L      | L | H | L               | D1      | $\overline{D1}$ |
| L      | H | L | L               | D2      | $\overline{D2}$ |
| L      | H | H | L               | D3      | $\overline{D3}$ |
| H      | L | L | L               | D4      | $\overline{D4}$ |
| H      | L | H | L               | D5      | $\overline{D5}$ |
| H      | H | L | L               | D6      | $\overline{D6}$ |
| H      | H | H | L               | D7      | $\overline{D7}$ |

X : Don't Care


(Note) The JEDEC SOP (FN) is not available in Japan.



P (DIP16-P-300-2.54A)  
Weight : 1.00g (Typ.)




F (SOP16-P-300-1.27)  
Weight : 0.18g (Typ.)




FN (SOL16-P-150-1.27)  
Weight : 0.13g (Typ.)

### PIN ASSIGNMENT




### IEC LOGIC SYMBOL



961001EBA2

● TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.

## SYSTEM DIAGRAM



961001EBA2'

- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

## ABSOLUTE MAXIMUM RATINGS

| PARAMETER                    | SYMBOL    | VALUE                    | UNIT |
|------------------------------|-----------|--------------------------|------|
| Supply Voltage Range         | $V_{CC}$  | $-0.5 \sim 7$            | V    |
| DC Input Voltage             | $V_{IN}$  | $-0.5 \sim V_{CC} + 0.5$ | V    |
| DC Output Voltage            | $V_{OUT}$ | $-0.5 \sim V_{CC} + 0.5$ | V    |
| Input Diode Current          | $I_{IK}$  | $\pm 20$                 | mA   |
| Output Diode Current         | $I_{OK}$  | $\pm 20$                 | mA   |
| DC Output Current            | $I_{OUT}$ | $\pm 25$                 | mA   |
| DC $V_{CC}$ / Ground Current | $I_{CC}$  | $\pm 50$                 | mA   |
| Power Dissipation            | $P_D$     | 500 (DIP)* / 180 (SOP)   | mW   |
| Storage Temperature          | $T_{stg}$ | $-65 \sim 150$           | °C   |

\*500mW in the range of  $T_a = -40^\circ\text{C} \sim 65^\circ\text{C}$ . From  $T_a = 65^\circ\text{C}$  to  $85^\circ\text{C}$  a derating factor of  $-10\text{mW}/^\circ\text{C}$  shall be applied until 300mW.

## RECOMMENDED OPERATING CONDITIONS

| PARAMETER                | SYMBOL     | VALUE                                                                                                                          | UNIT |
|--------------------------|------------|--------------------------------------------------------------------------------------------------------------------------------|------|
| Supply Voltage           | $V_{CC}$   | $2 \sim 6$                                                                                                                     | V    |
| Input Voltage            | $V_{IN}$   | $0 \sim V_{CC}$                                                                                                                | V    |
| Output Voltage           | $V_{OUT}$  | $0 \sim V_{CC}$                                                                                                                | V    |
| Operating Temperature    | $T_{opr}$  | $-40 \sim 85$                                                                                                                  | °C   |
| Input Rise and Fall Time | $t_r, t_f$ | $0 \sim 1000$ ( $V_{CC} = 2.0\text{V}$ )<br>$0 \sim 500$ ( $V_{CC} = 4.5\text{V}$ )<br>$0 \sim 400$ ( $V_{CC} = 6.0\text{V}$ ) | ns   |

## DC ELECTRICAL CHARACTERISTICS

| PARAMETER                   | SYMBOL   | TEST CONDITION                       | $V_{CC}$<br>(V)            | $T_a = 25^\circ\text{C}$ |                   |                      | $T_a = -40 \sim 85^\circ\text{C}$ |                      | UNIT          |
|-----------------------------|----------|--------------------------------------|----------------------------|--------------------------|-------------------|----------------------|-----------------------------------|----------------------|---------------|
|                             |          |                                      |                            | MIN.                     | TYP.              | MAX.                 | MIN.                              | MAX.                 |               |
| High - Level Input Voltage  | $V_{IH}$ |                                      | 2.0<br>4.5<br>6.0          | 1.50<br>3.15<br>4.20     | —<br>—<br>—       | —<br>—<br>—          | 1.50<br>3.15<br>4.20              | —<br>—<br>—          | V             |
| Low - Level Input Voltage   | $V_{IL}$ |                                      | 2.0<br>4.5<br>6.0          | —<br>—<br>—              | —<br>—<br>—       | 0.50<br>1.35<br>1.80 | —<br>—<br>—                       | 0.50<br>1.35<br>1.80 | V             |
| High - Level Output Voltage | $V_{OH}$ | $V_{IN} = V_{IH} \text{ or } V_{IL}$ | $I_{OH} = -20\mu\text{A}$  | 2.0<br>4.5<br>6.0        | 1.9<br>4.4<br>5.9 | 2.0<br>4.5<br>6.0    | —<br>—<br>—                       | 1.9<br>4.4<br>5.9    | V             |
|                             |          |                                      | $I_{OH} = -4 \text{ mA}$   | 4.5                      | 4.18              | 4.31                 | —                                 | 4.13                 |               |
|                             |          |                                      | $I_{OH} = -5.2 \text{ mA}$ | 6.0                      | 5.68              | 5.80                 | —                                 | 5.63                 |               |
| Low - Level Output Voltage  | $V_{OL}$ | $V_{IN} = V_{IH} \text{ or } V_{IL}$ | $I_{OL} = 20\mu\text{A}$   | 2.0<br>4.5<br>6.0        | —<br>—<br>—       | 0.0<br>0.0<br>0.0    | 0.1<br>0.1<br>0.1                 | —<br>—<br>—          | V             |
|                             |          |                                      | $I_{OL} = 4 \text{ mA}$    | 4.5                      | —                 | 0.17                 | 0.26                              | —                    |               |
|                             |          |                                      | $I_{OL} = 5.2 \text{ mA}$  | 6.0                      | —                 | 0.18                 | 0.26                              | —                    |               |
| Input Leakage Current       | $I_{IN}$ | $V_{IN} = V_{CC} \text{ or GND}$     | 6.0                        | —                        | —                 | $\pm 0.1$            | —                                 | $\pm 1.0$            | $\mu\text{A}$ |
| Quiescent Supply Current    | $I_{CC}$ | $V_{IN} = V_{CC} \text{ or GND}$     | 6.0                        | —                        | —                 | 4.0                  | —                                 | 40.0                 |               |

AC ELECTRICAL CHARACTERISTICS (  $C_L = 15\text{pF}$ ,  $V_{CC} = 5\text{V}$ ,  $T_a = 25^\circ\text{C}$ , Input  $t_r = t_f = 6\text{ns}$  )

| PARAMETER                                       | SYMBOL                 | TEST CONDITION | MIN. | TYP. | MAX. | UNIT |
|-------------------------------------------------|------------------------|----------------|------|------|------|------|
| Output Transition Time                          | $t_{TLH}$<br>$t_{THL}$ |                | —    | 4    | 8    | ns   |
| Propagation Delay Time<br>(D—Y)                 | $t_{PLH}$<br>$t_{PHL}$ |                | —    | 15   | 24   |      |
| Propagation Delay Time<br>(D—W)                 | $t_{PLH}$<br>$t_{PHL}$ |                | —    | 15   | 24   |      |
| Propagation Delay Time<br>( $\overline{ST}$ —Y) | $t_{PLH}$<br>$t_{PHL}$ |                | —    | 10   | 17   |      |
| Propagation Delay Time<br>( $\overline{ST}$ —W) | $t_{PLH}$<br>$t_{PHL}$ |                | —    | 10   | 17   |      |
| Propagation Delay Time<br>(A, B, C—Y)           | $t_{PLH}$<br>$t_{PHL}$ |                | —    | 19   | 31   |      |
| Propagation Delay Time<br>(A, B, C—W)           | $t_{PLH}$<br>$t_{PHL}$ |                | —    | 19   | 31   |      |

AC ELECTRICAL CHARACTERISTICS (  $C_L = 50\text{pF}$ , Input  $t_r = t_f = 6\text{ns}$  )

| PARAMETER                             | SYMBOL                               | TEST CONDITION | Ta = 25°C           |      |      | Ta = -40~85°C |      | UNIT |      |
|---------------------------------------|--------------------------------------|----------------|---------------------|------|------|---------------|------|------|------|
|                                       |                                      |                | V <sub>CC</sub> (V) | MIN. | TYP. | MAX.          | MIN. |      | MAX. |
| Output Transition Time                | t <sub>TLH</sub><br>t <sub>THL</sub> |                | 2.0                 | —    | 30   | 75            | —    | 95   | ns   |
|                                       |                                      |                | 4.5                 | —    | 8    | 15            | —    | 19   |      |
|                                       |                                      |                | 6.0                 | —    | 7    | 13            | —    | 16   |      |
| Propagation Delay Time<br>(D—Y)       | t <sub>pLH</sub><br>t <sub>pHL</sub> |                | 2.0                 | —    | 65   | 140           | —    | 175  |      |
|                                       |                                      |                | 4.5                 | —    | 18   | 28            | —    | 35   |      |
|                                       |                                      |                | 6.0                 | —    | 15   | 24            | —    | 30   |      |
| Propagation Delay Time<br>(D—W)       | t <sub>pLH</sub><br>t <sub>pHL</sub> |                | 2.0                 | —    | 65   | 140           | —    | 175  |      |
|                                       |                                      |                | 4.5                 | —    | 18   | 28            | —    | 35   |      |
|                                       |                                      |                | 6.0                 | —    | 15   | 24            | —    | 30   |      |
| Propagation Delay Time<br>(ST—Y)      | t <sub>pLH</sub><br>t <sub>pHL</sub> |                | 2.0                 | —    | 36   | 100           | —    | 125  |      |
|                                       |                                      |                | 4.5                 | —    | 12   | 20            | —    | 25   |      |
|                                       |                                      |                | 6.0                 | —    | 10   | 17            | —    | 21   |      |
| Propagation Delay Time<br>(ST—W)      | t <sub>pLH</sub><br>t <sub>pHL</sub> |                | 2.0                 | —    | 36   | 100           | —    | 125  |      |
|                                       |                                      |                | 4.5                 | —    | 12   | 20            | —    | 25   |      |
|                                       |                                      |                | 6.0                 | —    | 10   | 17            | —    | 21   |      |
| Propagation Delay Time<br>(A, B, C—Y) | t <sub>pLH</sub><br>t <sub>pHL</sub> |                | 2.0                 | —    | 80   | 180           | —    | 225  |      |
|                                       |                                      |                | 4.5                 | —    | 23   | 36            | —    | 45   |      |
|                                       |                                      |                | 6.0                 | —    | 19   | 31            | —    | 38   |      |
| Propagation Delay Time<br>(A, B, C—W) | t <sub>pLH</sub><br>t <sub>pHL</sub> |                | 2.0                 | —    | 80   | 180           | —    | 225  |      |
|                                       |                                      |                | 4.5                 | —    | 23   | 36            | —    | 45   |      |
|                                       |                                      |                | 6.0                 | —    | 19   | 31            | —    | 38   |      |
| Input Capacitance                     | C <sub>IN</sub>                      |                | —                   | 5    | 10   | —             | 10   | pF   |      |
| Power Dissipation Capacitance         | C <sub>PD</sub> (1)                  |                | —                   | 69   | —    | —             | —    |      |      |


Note (1)  $C_{PD}$  is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load.

Average operating current can be obtained by the equation :

$$I_{CC}(\text{opr}) = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC}$$

DIP 16PIN OUTLINE DRAWING (DIP16-P-300-2.54A )


Unit in mm



Weight : 1.00g (Typ.)

SOP 16PIN ( 200mil BODY ) OUTLINE DRAWING ( SOP16-P-300-1.27 )

Unit in mm




Weight : 0.18g (Typ.)

SOP 16PIN ( 150mil BODY ) OUTLINE DRAWING ( SOL14-P-150 -1.27)

Unit in mm

(Note) This package is not available in Japan.



Weight : 0.13g (Typ.)