

TLE214x, TLE214xA, TLE214xY EXCALIBUR LOW-NOISE HIGH-SPEED PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

- **Low Noise**
10 Hz . . . 15 nV/ $\sqrt{\text{Hz}}$
1 kHz . . . 10.5 nV/ $\sqrt{\text{Hz}}$
- **10000-pF Load Capability**
- **20-mA Min Short-Circuit Output Current**
- **27-V/ μs Min Slew Rate**
- **High Gain-Bandwidth Product . . . 5.9 MHz**
- **Low V_{IO} . . . 500 μV Max at 25°C**
- **Single or Split Supply . . . 4 V to 44 V**
- **Fast Settling Time**
340 ns to 0.1%
400 ns to 0.01%
- **Saturation Recovery . . . 150 ns**
- **Large Output Swing**
 $V_{CC-} + 0.1 \text{ V}$ to $V_{CC+} - 1 \text{ V}$

description

The TLE214x and TLE214xA devices are high-performance, internally compensated operational amplifiers built using Texas Instruments complementary bipolar Excalibur process. The TLE214xA is a tighter offset voltage grade of the TLE214x. Both are pin-compatible upgrades to standard industry products.

The design incorporates an input stage that simultaneously achieves low audio-band noise of 10.5 nV/ $\sqrt{\text{Hz}}$ with a 10-Hz 1/f corner and symmetrical 40-V/ μs slew rate typically with loads up to 800 pF. The resulting low distortion and high power bandwidth are important in high-fidelity audio applications. A fast settling time of 340 ns to 0.1% of a 10-V step with a 2-k Ω /100-pF load is useful in fast actuator/positioning drivers. Under similar test conditions, settling time to 0.01% is 400 ns.

The devices are stable with capacitive loads up to 10 nF, although the 6-MHz bandwidth decreases to 1.8 MHz at this high loading level. As such, the TLE214x and TLE214xA are useful for low-droop sample-and-holds and direct buffering of long cables, including 4-mA to 20-mA current loops.

The special design also exhibits an improved insensitivity to inherent integrated circuit component mismatches as is evidenced by a 500- μV maximum offset voltage and 1.7- $\mu\text{V}/^\circ\text{C}$ typical drift. Minimum common-mode rejection ratio and supply-voltage rejection ratio are 85 dB and 90 dB, respectively.

Device performance is relatively independent of supply voltage over the $\pm 2\text{-V}$ to $\pm 22\text{-V}$ range. Inputs can operate between $V_{CC-} - 0.3$ to $V_{CC+} - 1.8 \text{ V}$ without inducing phase reversal, although excessive input current may flow out of each input exceeding the lower common-mode input range. The all-npn output stage provides a nearly rail-to-rail output swing of $V_{CC-} - 0.1$ to $V_{CC+} - 1 \text{ V}$ under light current-loading conditions. The device can sustain shorts to either supply since output current is internally limited, but care must be taken to ensure that maximum package power dissipation is not exceeded.

Both versions can also be used as comparators. Differential inputs of $V_{CC\pm}$ can be maintained without damage to the device. Open-loop propagation delay with TTL supply levels is typically 200 ns. This gives a good indication as to output stage saturation recovery when the device is driven beyond the limits of recommended output swing.

Both the TLE214x and TLE214xA are available in a wide variety of packages, including both the industry-standard 8-pin small-outline version and chip form for high-density system applications. The C-suffix devices are characterized for operation from 0°C to 70°C, I-suffix devices from -40°C to 105°C, and M-suffix devices over the full military temperature range of -55°C to 125°C.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1998, Texas Instruments Incorporated



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141 AVAILABLE OPTIONS

TA	V _{I0} max AT 25°C	PACKAGED DEVICES				CHIP FORM‡ (Y)
		SMALL OUT- LINE† (D)	CHIP CARRIER (FK)	CERAMIC DIP (JG)	PLASTIC DIP (P)	
0°C to 70°C	500 µV 900 µV	TLE2141ACD TLE2141CD	—	—	TLE2141ACP TLE2141CP	—
-40°C to 105°C	500 µV 900 µV	TLE2141AID TLE2141ID	—	—	TLE2141AIP TLE2141IP	TLE2141Y
-55°C to 125°C	500 µV 900 µV	TLE2141AMD TLE2141MD	TLE2141AMFK TLE2141MFK	TLE2141AMJG TLE2141MJG	TLE2141AMP TLE2141MP	—

† The D packages are available taped and reeled. Add R suffix to device type (e.g., TLE2141ACDR).

‡ Chip forms are tested at TA = 25°C only.

TLE2142 AVAILABLE OPTIONS

PACKAGED DEVICES							CHIP FORM§ (Y)
TA	V _{I0} max AT 25°C	SMALL OUTLINE† (D)	CHIP CARRIER (FK)	CERAMIC DIP (JG)	PLASTIC DIP (P)	TSSOP‡ (PW)	
0°C to 70°C	750 µV 1200 µV	TLE2142ACD TLE2142CD	— —	— —	TLE2142ACP TLE2142CP	— TLE2142CPWLE	—
-40°C to 105°C	750 µV 1200 µV	TLE2142AID TLE2142ID	— —	— —	TLC2142AIP TLC2142IP	— —	TLE2142Y
-55°C to 125°C	750 µV 1200 µV	TLE2142AMD TLE2142MD	TLE2142AMFK TLE2142MFK	TLE2142AMJG TLE2142MJG	TLC2142AMP TLC2142MP	— —	—

† The D packages are available taped and reeled. Add R suffix to device type (e.g., TLC2142ACDR).

‡ The PW packages are available left-ended taped and reeled. Add LE the suffix to device type (e.g., TLC2142CPWLE).

§ Chip forms are tested at TA = 25°C only.

TLE2144 AVAILABLE OPTIONS

TA	V _{I0} max AT 25°C	PACKAGED DEVICES				CHIP FORM‡ (Y)
		SMALL OUTLINE† (DW)	CHIP CARRIER (FK)	CERAMIC DIP (J)	PLASTIC DIP (N)	
0°C to 70°C	1.5 mV 2.4 mV	— TLE2144CDW	— —	— —	TLE2144ACN TLE2144CN	—
-40°C to 105°C	1.5 mV 2.4 mV	— TLE2144IDW	— —	— —	TLE2144AIN TLE2144IN	TLE2144Y
-55°C to 125°C	1.5 mV 2.5 mV	— TLE2144MDW	TLE2144AMFK TLE2144MFK	TLE2144AMJ TLE2144MJ	TLE2144AMN TLE2144MN	—

† The DW packages are available taped and reeled. Add R suffix to device type (e.g., TLE2144CDWR).


‡ Chip forms are tested at TA = 25°C only.




POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**


SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998




TLE2141
FK PACKAGE
(TOP VIEW)




TLE2144
DW PACKAGE
(TOP VIEW)




TLE2142
PW PACKAGE
(TOP VIEW)




TLE2142
D, JG, OR P PACKAGE
(TOP VIEW)




TLE2142
FK PACKAGE
(TOP VIEW)



TLE2144
J OR N PACKAGE
(TOP VIEW)



TLE2144
FK PACKAGE
(TOP VIEW)




NC – No internal connection

TLE214x, TLE214xA, TLE214xY EXCALIBUR LOW-NOISE HIGH-SPEED PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998


symbol



NOTES: A. OFFSET N1 AND OFFSET N2
are only available on the
TLE2241x devices.

TLE2141Y chip information


This chip, when properly assembled, displays characteristics similar to the TLE2141. Thermal compression or ultrasonic bonding may be used on the doped-aluminum bonding pads. Chips may be mounted with conductive epoxy or a gold-silicon preform.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

TLE2142Y chip information

This chip, when properly assembled, displays characteristics similar to the TLE2142. Thermal compression or ultrasonic bonding may be used on the doped-aluminum bonding pads. Chips may be mounted with conductive epoxy or a gold-silicon preform.




TLE214x, TLE214xA, TLE214xY EXCALIBUR LOW-NOISE HIGH-SPEED PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998


TLE2144Y chip information

This chip, when properly assembled, displays characteristics similar to the TLE2144. Thermal compression or ultrasonic bonding may be used on the doped-aluminum bonding pads. Chips may be mounted with conductive epoxy or a gold-silicon preform.



**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**
SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

equivalent schematic



NOTE A: OFFSET N1 AND OFFSET N2 are only available on the TLE2241x devices.

OFFSET N1
(see Note A)
OFFSET N2
(see Note A)

ACTUAL DEVICE COMPONENT COUNT		
COMPONENT	TLE2241	TLE2242
Transistors	46	65
Resistors	24	43
Diodes	8	14
Capacitors	4	8
Epi-FET	1	1
		130
		86
		28
		16
		2

TLE214x, TLE214xA, TLE214xY EXCALIBUR LOW-NOISE HIGH-SPEED PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)[†]

Supply voltage, V_{CC+} (see Note 1)	22 V
Supply voltage, V_{CC-}	-22 V
Differential input voltage, V_{ID} (see Note 2)	± 44 V
Input voltage range, V_I (any input)	V_{CC+} to V_{CC-} -0.3 V
Input current, I_I (each input)	± 1 mA
Output current, I_O	± 80 mA
Total current into V_{CC+}	80 mA
Total current out of V_{CC-}	80 mA
Duration of short-circuit current at (or below) 25°C (see Note 3)	unlimited
Continuous total dissipation	See Dissipation Rating Table
Operating free-air temperature range, T_A : C suffix	0°C to 70°C
I suffix	-40°C to 105°C
M suffix	-55°C to 125°C
Storage temperature range	-65°C to 150°C
Case temperature for 60 seconds: FK package	260°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds: D, DW, N, P, or PW package	260°C
Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds: J or JG package	300°C

[†] Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES:
1. All voltage values, except differential voltages, are with respect to the midpoint between V_{CC+} and V_{CC-} .
 2. Differential voltages are at IN+ with respect to IN-. Excessive current flows if input is brought below V_{CC-} -0.3 V.
 3. The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.

DISSIPATION RATING TABLE

PACKAGE	$T_A \leq 25^\circ\text{C}$ POWER RATING	DERATING FACTOR ABOVE $T_A = 25^\circ\text{C}$	$T_A = 70^\circ\text{C}$ POWER RATING	$T_A = 105^\circ\text{C}$ POWER RATING	$T_A = 125^\circ\text{C}$ POWER RATING
D	725 mW	5.8 mW/°C	464 mW	261 mW	145 mW
DW	1025 mW	8.2 mW/°C	656 mW	369 mW	205 mW
FK	1375 mW	11.0 mW/°C	880 mW	495 mW	275 mW
J	1375 mW	11.0 mW/°C	880 mW	495 mW	275 mW
JG	1050 mW	8.4 mW/°C	672 mW	378 mW	210 mW
N	1150 mW	9.2 mW/°C	736 mW	414 mW	230 mW
P	1000 mW	8.0 mW/°C	640 mW	360 mW	200 mW
PW	525 mW	4.2 mW/°C	336 mW	—	—

recommended operating conditions

		C SUFFIX		I SUFFIX		M SUFFIX		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
Supply voltage, $V_{CC\pm}$		± 2	± 22	± 2	± 22	± 2	± 22	V
Common-mode input voltage, V_{IC}	$V_{CC} = 5$ V	0	2.9	0	2.7	0	2.7	V
	$V_{CC\pm} = \pm 15$ V	-15	12.9	-15	12.7	-15	12.7	
Operating free-air temperature, T_A		0	70	-40	105	-55	125	°C

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141C electrical characteristics at specified free-air temperature, $V_{CC} = 5\text{ V}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2141C			TLE2141AC			UNIT		
			MIN	TYP	MAX	MIN	TYP	MAX			
V_{IO}	$V_O = 2.5\text{ V}$ $V_{IC} = 2.5\text{ V}$	$R_S = 50\ \Omega$	25°C	225	1400	200	1000		μV		
			Full range		1700			1300			
			Full range		1.7			1.7	$\mu\text{V}/^\circ\text{C}$		
			25°C	8	100	8	100				
			Full range		150			150	nA		
			25°C	-0.8	-2	-0.8	-2				
I_{IB}			Full range		-2.1			-2.1	μA		
V_{ICR}	$R_S = 50\ \Omega$	25°C	0	-0.3	0	-0.3		V			
		to	to		to	to					
		3	3.2		3	3.2		V			
		Full range	0		0						
V_{OH}	$I_{OH} = -150\ \mu\text{A}$ $I_{OH} = -1.5\ \text{mA}$ $I_{OH} = -15\ \text{mA}$		25°C	3.9	4.1	3.9	4.1		V		
			Full range	3.8		3.8					
			25°C	3.8	4	3.8	4				
			Full range	3.7		3.7					
			25°C	3.2	3.7	3.2	3.7				
			Full range	3.2		3.2					
V_{OL}	$I_{OL} = 150\ \mu\text{A}$ $I_{OL} = 1.5\ \text{mA}$ $I_{OL} = 15\ \text{mA}$		25°C	75	125	75	125		mV		
			Full range		150		150				
			25°C	150	225	150	225				
			Full range		250		250				
			25°C	1.2	1.6	1.2	1.6		V		
			Full range		1.7		1.7				
A_{VD}	Large-signal differential voltage amplification	$V_{CC} = \pm 2.5\text{ V}, R_L = 2\ \text{k}\Omega, V_O = 1\text{ V to }-1.5\text{ V}$	25°C	50	220	50	220		V/mV		
			Full range	25		25					
r_i	Input resistance		25°C	70		70			$\text{M}\Omega$		
c_i	Input capacitance		25°C	2.5		2.5			pF		
z_o	Open-loop output impedance	$f = 1\ \text{MHz}$	25°C	30		30			Ω		
$CMRR$	Common-mode rejection ratio	$V_{IC} = V_{ICR\min}, R_S = 50\ \Omega$	25°C	85	118	85	118		dB		
			Full range	80		80					
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	$V_{CC\pm} = \pm 2.5\text{ V to } \pm 15\text{ V}, R_S = 50\ \Omega$	25°C	90	106	90	106		dB		
			Full range	85		85					
I_{CC}	Supply current	$V_O = 2.5\text{ V}, V_{IC} = 2.5\text{ V}$	No load,	25°C	3.4	4.4	3.4	4.4	mA		
				Full range		4.6		4.6			

† Full range is 0°C to 70°C.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141C operating characteristics, $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2141C			TLE2141AC			UNIT	
		MIN	TYP	MAX	MIN	TYP	MAX		
SR+	Positive slew rate	AVD = -1, $R_L = 2 \text{ k}\Omega$, $C_L = 500 \text{ pF}$ [†] ,	To 0.1% To 0.01%	45	45	42	42	$\text{V}/\mu\text{s}$	
SR-	Negative slew rate			42					
t_s	Settling time	AVD = -1, 2.5-V step	To 0.1% To 0.01%	0.16	0.16	0.22	0.22	μs	
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$, $f = 10 \text{ Hz}$		15	15	10.5	10.5	$\text{nV}/\sqrt{\text{Hz}}$	
				10.5					
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$	0.48	0.48	0.51	0.51	μV		
			$f = 0.1 \text{ Hz to } 10 \text{ Hz}$						
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$	1.92	1.92	0.5	0.5	$\text{pA}/\sqrt{\text{Hz}}$		
			$f = 1 \text{ kHz}$						
THD + N	Total harmonic distortion plus noise	$V_O = 1 \text{ V to } 3 \text{ V}$, AVD = 2, $f = 10 \text{ kHz}$	0.0052%	0.0052%	660	660	kHz		
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$			5.9	5.9	MHz		
	Gain-bandwidth product	$R_L = 2 \text{ k}\Omega$, $f = 100 \text{ kHz}$	$C_L = 100 \text{ pF}$	5.8	5.8	MHz			
B_{OM}	Maximum output-swing bandwidth	$V_O(PP) = 2 \text{ V}$, AVD = 1, $C_L = 100 \text{ pF}$	57°	57°	57°	57°	57°		
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$							

[†] R_L and C_L terminated to 2.5 V.

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS
SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141C electrical characteristics at specified free-air temperature, $V_{CC\pm} = \pm 15$ V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2141C			TLE2141AC			UNIT		
			MIN	TYP	MAX	MIN	TYP	MAX			
V_{IO}	$V_{IC} = 0$, $V_O = 0$	$R_S = 50 \Omega$	25°C	200	900	175	500		μV		
			Full range		1300			800			
			Full range		1.7			1.7	$\mu V/^\circ C$		
			25°C	7	100	7	100				
			Full range		150			150	nA		
			25°C	-0.7	-1.5	-0.7	-1.5				
I_{IB}			Full range		-1.6			-1.6	μA		
			25°C	-15	-15.3	-15	-15.3		V		
				to	to	to	to				
				13	13.2	13	13.2		V		
			Full range	-15	-15.3	-15	-15.3				
V_{OM+}	$I_O = -150 \mu A$	25°C	13.8	14.1		13.8	14.1		V		
			Full range	13.7		13.7					
		$I_O = -1.5 mA$	25°C	13.7	14	13.7	14				
			Full range	13.6		13.6					
		$I_O = -15 mA$	25°C	13.1	13.7	13.1	13.7		V		
			Full range	13		13					
V_{OM-}	$I_O = 150 \mu A$	25°C	-14.7	-14.9		-14.7	-14.9		V		
			Full range	-14.6		-14.6					
		$I_O = 1.5 mA$	25°C	-14.5	-14.8	-14.5	-14.8				
			Full range	-14.4		-14.4					
		$I_O = 15 mA$	25°C	-13.4	-13.8	-13.4	-13.8		V		
			Full range	-13.3		-13.3					
AVD	$V_O = \pm 10 V$	25°C	100	450		100	450		V/mV		
			Full range	75		75					
r_i	Input resistance	$R_L = 2 k\Omega$	25°C	65		65			$M\Omega$		
c_i	Input capacitance		25°C	2.5		2.5			pF		
z_o	Open-loop output impedance	$f = 1 MHz$	25°C	30		30			Ω		
$CMRR$	Common-mode rejection ratio	$V_{IC} = V_{ICR\min}, R_S = 50 \Omega$	25°C	85	108	85	108		dB		
			Full range	80		80					
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	$V_{CC\pm} = \pm 2.5 V$ to $\pm 15 V$, $R_S = 50 \Omega$	25°C	90	106	90	106		dB		
			Full range	85		85					
I_{OS}	Short-circuit output current	$V_O = 0$	$V_{ID} = 1 V$	25°C	-25	-50	-25	-50	mA		
				20	31	20	31				
I_{CC}	Supply current	$V_O = 0$, No load		25°C	3.5	4.5	3.5	4.5	mA		
				Full range		4.7		4.7			

[†] Full range is 0°C to 70°C.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141C operating characteristics, $V_{CC\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2141C			TLE2141AC			UNIT
		MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	$A_{VD} = -1$, $C_L = 500$ pF	$R_L = 2$ k Ω ,	27	45	27	45	V/ μ s
SR-	Negative slew rate			27	42	27	42	
t_s	Settling time	$A_{VD} = -1$, 10-V step	To 0.1%	0.34	0.34	0.34	0.34	μ s
			To 0.01%	0.4	0.4	0.4	0.4	
V_n	Equivalent input noise voltage	$R_S = 20$ Ω ,	f = 10 Hz	15	15	15	15	nV/ $\sqrt{\text{Hz}}$
			$R_S = 20$ Ω ,	f = 1 kHz	10.5	10.5	10.5	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1$ Hz to 1 Hz		0.48	0.48	0.48	0.48	μ V
			$f = 0.1$ Hz to 10 Hz	0.51	0.51	0.51	0.51	
I_n	Equivalent input noise current	$f = 10$ Hz		1.89	1.89	1.89	1.89	pA/ $\sqrt{\text{Hz}}$
			$f = 1$ kHz	0.47	0.47	0.47	0.47	
THD + N	Total harmonic distortion plus noise	$V_{O(PP)} = 20$ V, $A_{VD} = 10$,	$R_L = 2$ k Ω , $f = 10$ kHz	0.01%	0.01%	0.01%	0.01%	
B_1	Unity-gain bandwidth	$R_L = 2$ k Ω ,	$C_L = 100$ pF	6	6	6	6	MHz
	Gain-bandwidth product		$R_L = 2$ k Ω , $f = 100$ kHz	5.9	5.9	5.9	5.9	MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)} = 20$ V, $A_{VD} = 1$,	$R_L = 2$ k Ω , $C_L = 100$ pF	668	668	668	668	kHz
ϕ_m	Phase margin at unity gain	$R_L = 2$ k Ω ,	$C_L = 100$ pF	58°	58°	58°	58°	

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142C electrical characteristics at specified free-air temperature, $V_{CC} = 5\text{ V}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2142C			TLE2142AC			UNIT	
			MIN	TYP	MAX	MIN	TYP	MAX		
V_{IO}	$V_O = 2.5\text{ V}$, $V_{IC} = 2.5\text{ V}$	25°C	220	1900		200	1500		μV	
			Full range		2200			1800		
		Full range		1.7			1.7		$\mu\text{V}/^\circ\text{C}$	
		25°C	8	100		8	100		nA	
			Full range		150			150		
		25°C	-0.8	-2		-0.8	-2		μA	
			Full range		-2.1			-2.1		
V_{ICR}	$R_S = 50\Omega$	25°C	0	-0.3		0	-0.3		V	
			to	to		to	to			
		Full range	3	3.2		3	3.2			
			0		0	0				
V_{OH}	$I_{OH} = -150\text{ }\mu\text{A}$	25°C	3.9	4.1		3.9	4.1		V	
		Full range	3.8			3.8				
		25°C	3.8	4		3.8	4			
			Full range	3.7		3.7				
		25°C	3.4	3.7		3.4	3.7			
			Full range	3.4		3.4				
V_{OL}	$I_{OL} = 150\text{ }\mu\text{A}$	25°C	75	125		75	125		mV	
		Full range		150			150			
		25°C	150	225		150	225			
			Full range	250			250			
		25°C	1.2	1.4		1.2	1.4			
			Full range	1.5			1.5			
A_{VD}	$V_{CC} = \pm 2.5\text{ V}$, $R_L = 2\text{ k}\Omega$, $V_O = 1\text{ V}$ to -1.5 V	25°C	50	220		50	220		V/mV	
		Full range	25			25				
r_i	Input resistance	25°C	70			70			$\text{M}\Omega$	
c_i	Input capacitance	25°C		2.5			2.5		pF	
z_o	Open-loop output impedance	$f = 1\text{ MHz}$	25°C		30		30		Ω	
CMRR	Common-mode rejection ratio		25°C	85	118		85	118	dB	
			Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	$V_{CC\pm} = \pm 2.5\text{ V}$ to $\pm 15\text{ V}$, $R_S = 50\Omega$	25°C	90	106		90	106	dB	
			Full range	85			85			
I_{CC}	Supply current	$V_O = 2.5\text{ V}$, No load, $V_{IC} = 2.5\text{ V}$	25°C	6.6	8.8		6.6	8.8	mA	
			Full range		9.2			9.2		

† Full range is 0°C to 70°C.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142C operating characteristics, $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2142C			TLE2142AC			UNIT	
		MIN	TYP	MAX	MIN	TYP	MAX		
SR+	Positive slew rate	AVD = -1, $R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 500 \text{ pF}$			45			45	$\text{V}/\mu\text{s}$
SR-	Negative slew rate				42			42	
t_s	Settling time	AVD = -1, 2.5-V step	To 0.1%		0.16			0.16	μs
			To 0.01%		0.22			0.22	
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$, $f = 10 \text{ Hz}$			15			15	$\text{nV}/\sqrt{\text{Hz}}$
			$R_S = 20 \Omega$,	$f = 1 \text{ kHz}$	10.5			10.5	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$			0.48			0.48	μV
		$f = 0.1 \text{ Hz to } 10 \text{ Hz}$			0.51			0.51	
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$			1.92			1.92	$\text{pA}/\sqrt{\text{Hz}}$
		$f = 1 \text{ kHz}$			0.5			0.5	
THD + N	Total harmonic distortion plus noise	$V_O = 1 \text{ V to } 3 \text{ V}$, $R_L = 2 \text{ k}\Omega^\dagger$, $AVD = 2$, $f = 10 \text{ kHz}$		0.0052%		0.0052%			
B1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 100 \text{ pF}$		5.9		5.9		MHz	
	Gain-bandwidth product	$R_L = 2 \text{ k}\Omega^\dagger$, $f = 100 \text{ kHz}$		5.8		5.8		MHz	
BOM	Maximum output-swing bandwidth	$V_O(PP) = 2 \text{ V}$, $AVD = 1$, $R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 100 \text{ pF}$		660		660		kHz	
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 100 \text{ pF}$		57°		57°			

† R_L terminates at 2.5 V.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**
SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142C electrical characteristics at specified free-air temperature, $V_{CC\pm} = \pm 15$ V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2142C			TLE2142AC			UNIT		
			MIN	TYP	MAX	MIN	TYP	MAX			
V_{IO}	$V_{IC} = 0$, $V_O = 0$	$R_S = 50 \Omega$	25°C	290	1200	275	750		μV		
			Full range		1600			1200			
			Full range		1.7			1.7	$\mu V/^\circ C$		
			25°C	7	100	7	100				
			Full range		150			150	nA		
			25°C	-0.7	-1.5	-0.7	-1.5				
I_{IB}			Full range		-1.6			-1.6	μA		
			25°C	-15	-15.3	-15	-15.3		V		
				to	to	to	to				
				13	13.2	13	13.2		V		
			Full range	-15	-15.3	-15	-15.3				
V_{OM+}	$I_O = -150 \mu A$	25°C	13.8	14.1		13.8	14.1		V		
			Full range	13.7		13.7					
		25°C	13.7	14		13.7	14				
			Full range	13.6		13.6					
		25°C	13.3	13.7		13.3	13.7		V		
			Full range	13.2		13.2					
V_{OM-}	$I_O = 150 \mu A$	25°C	-14.7	-14.9		-14.7	-14.9		V		
			Full range	-14.6		-14.6					
		25°C	-14.5	-14.8		-14.5	-14.8				
			Full range	-14.4		-14.4					
		25°C	-13.4	-13.8		-13.4	-13.8		V		
			Full range	-13.3		-13.3					
A_{VD}	$V_O = \pm 10$ V	25°C	100	450		100	450		V/mV		
		Full range	75			75					
r_i	Input resistance	$R_L = 2 k\Omega$	25°C		65		65		$M\Omega$		
c_i	Input capacitance		25°C		2.5		2.5		pF		
z_o	Open-loop output impedance	$f = 1$ MHz	25°C		30		30		Ω		
$CMRR$	Common-mode rejection ratio	$V_{IC} = V_{ICR\min}$, $R_S = 50 \Omega$	25°C	85	108		85	108	dB		
			Full range	80			80				
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	$V_{CC\pm} = \pm 2.5$ V to ± 15 V, $R_S = 50 \Omega$	25°C	90	106		90	106	dB		
			Full range	85			85				
I_{OS}	Short-circuit output current	$V_O = 0$	$V_{ID} = 1$ V	25°C	-25	-50	-25	-50	mA		
				20	31		20	31			
I_{CC}	Supply current	$V_O = 0$,	No load	25°C	6.9	9	6.9	9	mA		
						9.4		9.4			

† Full range is 0°C to 70°C.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142C operating characteristics, $V_{CC\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2142C			TLE2142AC			UNIT
		MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	$A_{VD} = -1$, $R_L = 2 \text{ k}\Omega$, $C_L = 500 \text{ pF}$	27	45	27	45	27	$\text{V}/\mu\text{s}$
SR-	Negative slew rate		27	42	27	42	27	
t_s	Settling time	$A_{VD} = -1$, 10-V step	To 0.1%	0.34	0.34	0.34	0.34	μs
			To 0.01%	0.4	0.4	0.4	0.4	
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$, $f = 10 \text{ Hz}$	15	15	15	15	15	$\text{nV}/\sqrt{\text{Hz}}$
			$R_S = 20 \Omega$, $f = 1 \text{ kHz}$	10.5	10.5	10.5	10.5	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$	0.48	0.48	0.48	0.48	0.48	μV
			$f = 0.1 \text{ Hz to } 10 \text{ Hz}$	0.51	0.51	0.51	0.51	
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$	1.89	1.89	1.89	1.89	1.89	$\text{pA}/\sqrt{\text{Hz}}$
			$f = 1 \text{ kHz}$	0.47	0.47	0.47	0.47	
THD + N	Total harmonic distortion plus noise	$V_{O(PP)} = 20 \text{ V}$, $A_{VD} = 10$, $f = 10 \text{ kHz}$	0.01%	0.01%	0.01%	0.01%	0.01%	
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$	6	6	6	6	6	MHz
	Gain-bandwidth product	$R_L = 2 \text{ k}\Omega$, $f = 100 \text{ kHz}$	5.9	5.9	5.9	5.9	5.9	
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)} = 20 \text{ V}$, $A_{VD} = 1$, $C_L = 100 \text{ pF}$	668	668	668	668	668	kHz
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$	58°	58°	58°	58°	58°	

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144C electrical characteristics at specified free-air temperature, $V_{CC} = 5\text{ V}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2144C			TLE2144AC			UNIT	
			MIN	TYP	MAX	MIN	TYP	MAX		
V_{IO}	$V_O = 2.5\text{ V}$, $V_{IC} = 2.5\text{ V}$	25°C	0.5	3.8		0.5	3		mV	
			Full range		4.4			3.6		
		Full range		1.7			1.7		μV/°C	
		25°C	8	100		8	100		nA	
			Full range		150			150		
		25°C	-0.8	-2		-0.8	-2		μA	
			Full range		-2.1			-2.1		
V_{ICR}	$R_S = 50\Omega$	25°C	0	-0.3		0	-0.3		V	
			to	to		to	to			
			3	3.2		3	3.2			
		Full range	0			0				
			to			to				
			2.9			2.9				
V_{OH}	$I_{OH} = -150\mu\text{A}$	25°C	3.9	4.1		3.9	4.1		V	
		Full range	3.8			3.8				
	$I_{OH} = -1.5\text{ mA}$	25°C	3.8	4		3.8	4			
		Full range	3.7			3.7				
	$I_{OH} = -15\text{ mA}$	25°C	3.4	3.7		3.4	3.7			
		Full range	3.4			3.4				
V_{OL}	$I_{OL} = 150\mu\text{A}$	25°C	75	125		75	125		mV	
		Full range		150			150			
	$I_{OL} = 1.5\text{ mA}$	25°C	150	225		150	225			
		Full range		250			250			
	$I_{OL} = 15\text{ mA}$	25°C	1.2	1.6		1.2	1.6			
		Full range		1.7			1.7			
A_{VD}	$V_{CC} = \pm 2.5\text{ V}$, $R_L = 2\text{ k}\Omega$, $V_O = 1\text{ V}$ to -1.5 V	25°C	50	95		50	95		V/mV	
		Full range	25			25				
r_i	Input resistance	25°C		70			70		MΩ	
c_i	Input capacitance	25°C		2.5			2.5		pF	
z_o	Open-loop output impedance	f = 1 MHz	25°C		30		30		Ω	
$CMRR$	$V_{IC} = V_{ICR\min}$, $R_S = 50\Omega$	25°C	85	118		85	118		dB	
		Full range	80			80				
k_{SVR}	$V_{CC\pm} = \pm 2.5\text{ V}$ to $\pm 15\text{ V}$, $R_S = 50\Omega$	25°C	90	106		90	106		dB	
		Full range	85			85				
I_{CC}	$V_O = 2.5\text{ V}$, $V_{IC} = 2.5\text{ V}$	No load,	25°C		13.2	17.6		13.2	17.6	mA
			Full range			18.5			18.5	

† Full range is 0°C to 70°C.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144C operating characteristics, $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2144C			TLE2144AC			UNIT	
		MIN	TYP	MAX	MIN	TYP	MAX		
SR+	Positive slew rate	AVD = -1, $R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 500 \text{ pF}$		45			45	$\text{V}/\mu\text{s}$	
SR-	Negative slew rate			42			42		
t_s	Settling time	AVD = -1, 2.5-V step	To 0.1%	0.16			0.16	μs	
			To 0.01%	0.22			0.22		
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$,	$f = 10 \text{ Hz}$	15			15	$\text{nV}/\sqrt{\text{Hz}}$	
		$R_S = 20 \Omega$,	$f = 1 \text{ kHz}$	10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$		0.48			0.48	μV	
		$f = 0.1 \text{ Hz to } 10 \text{ Hz}$		0.51			0.51		
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$		1.92			1.92	$\text{pA}/\sqrt{\text{Hz}}$	
		$f = 1 \text{ kHz}$		0.5			0.5		
THD + N	Total harmonic distortion plus noise	$V_O = 1 \text{ V to } 3 \text{ V}$, AVD = 2,	$R_L = 2 \text{ k}\Omega^\dagger$, $f = 10 \text{ kHz}$	0.0052%	0.0052%				
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega^\dagger$,	$C_L = 100 \text{ pF}$	5.9			5.9	MHz	
	Gain-bandwidth product	$R_L = 2 \text{ k}\Omega^\dagger$, $f = 100 \text{ kHz}$	$C_L = 100 \text{ pF}$	5.8			5.8		
B_{OM}	Maximum output-swing bandwidth	$V_O(PP) = 2 \text{ V}$, AVD = 1,	$R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 100 \text{ pF}$	660	660			kHz	
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega^\dagger$,	$C_L = 100 \text{ pF}$	57°	57°				

† R_L terminates at 2.5 V

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS
 SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144C electrical characteristics at specified free-air temperature, $V_{CC\pm} = \pm 15$ V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2144C			TLE2144AC			UNIT	
			MIN	TYP	MAX	MIN	TYP	MAX		
V_{IO} Input offset voltage	$V_{IC} = 0$, $V_O = 0$	25°C Full range	0.6	2.4		0.5	1.5		mV	
				3.2			2.4			
			Full range	1.7		1.7			$\mu V/^\circ C$	
αV_{IO} Temperature coefficient of input offset voltage		25°C	7	100		7	100		nA	
		Full range	150			150				
		25°C	-0.7	-1.5		-0.7	-1.5		μA	
I_{IB} Input bias current		Full range		-1.6			-1.6			
V_{ICR} Common-mode input voltage range	$R_S = 50 \Omega$	25°C Full range	-15 to 13	-15.3 to 13.2		-15 to 13	-15.3 to 13.2		V	
			-15 to 12.9	-15.3 to 13.1		-15 to 12.9	-15 to 13.1			
V_{OM+} Maximum positive peak output voltage swing	$I_O = -150 \mu A$	25°C	13.8	14.1		13.8	14.1		V	
		Full range	13.7			13.7				
		$I_O = -1.5 \text{ mA}$	25°C	13.7	14	13.7	14			
			Full range	13.6		13.6				
		$I_O = -15 \text{ mA}$	25°C	13.1	13.7	13.1	13.7		V	
			Full range	13		13				
V_{OM-} Maximum negative peak output voltage swing	$I_O = 150 \mu A$	25°C	-14.7	-14.9		-14.7	-14.9		V	
		Full range	-14.6			-14.6				
		$I_O = 1.5 \text{ mA}$	25°C	-14.5	-14.8	-14.5	-14.8			
			Full range	-14.4		-14.4				
		$I_O = 15 \text{ mA}$	25°C	-13.4	-13.8	-13.4	-13.8		V	
			Full range	-13.3		-13.3				
AVD Large-signal differential voltage amplification	$V_O = \pm 10 \text{ V}$	25°C	100	170		100	170		V/mV	
		Full range	75			75				
r_i Input resistance	$R_L = 2 \text{ k}\Omega$	25°C		65			65		$M\Omega$	
c_i Input capacitance		25°C		2.5			2.5		pF	
z_o Open-loop output impedance	$f = 1 \text{ MHz}$	25°C		30			30		Ω	
$CMRR$ Common-mode rejection ratio	$V_{IC} = V_{ICR\min}, R_S = 50 \Omega$	25°C	85	108		85	108		dB	
		Full range	80			80				
k_{SVR} Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	$V_{CC\pm} = \pm 2.5 \text{ V to } \pm 15 \text{ V}, R_S = 50 \Omega$	25°C	90	106		90	106		dB	
		Full range	85			85				
I_{OS} Short-circuit output current	$V_O = 0$	$V_{ID} = 1 \text{ V}$ $V_{ID} = -1 \text{ V}$	25°C	-25	-50		-25	-50	mA	
				20	31		20	31		
I_{CC} Supply current	$V_O = 0$	No load	25°C	13.8	18		13.8	18	mA	
			Full range		18.8			18.8		

[†] Full range is 0°C to 70°C.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144C operating characteristics, $V_{CC\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2144C			TLE2144AC			UNIT
		MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	$\text{AVD} = -1$, $R_L = 2 \text{ k}\Omega$, $C_L = 500 \text{ pF}$	27	45	27	45	27	$\text{V}/\mu\text{s}$
SR-	Negative slew rate		27	42	27	42	27	
t_s	Settling time	$\text{AVD} = -1$, 10-V step	To 0.1%	0.34	0.34	0.34	0.34	μs
			To 0.01%	0.4	0.4	0.4	0.4	
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$,	$f = 10 \text{ Hz}$	15	15	15	15	$\text{nV}/\sqrt{\text{Hz}}$
		$R_S = 20 \Omega$,	$f = 1 \text{ kHz}$	10.5	10.5	10.5	10.5	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$		0.48	0.48	0.48	0.48	μV
		$f = 0.1 \text{ Hz to } 10 \text{ Hz}$		0.51	0.51	0.51	0.51	
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$		1.89	1.89	1.89	1.89	$\text{pA}/\sqrt{\text{Hz}}$
		$f = 1 \text{ kHz}$		0.47	0.47	0.47	0.47	
THD + N	Total harmonic distortion plus noise	$V_{O(PP)} = 20 \text{ V}$, $\text{AVD} = 10$,	$R_L = 2 \text{ k}\Omega$, $f = 10 \text{ kHz}$	0.01%	0.01%	0.01%	0.01%	
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega$,	$C_L = 100 \text{ pF}$	6	6	6	6	MHz
	Gain-bandwidth product	$R_L = 2 \text{ k}\Omega$, $f = 100 \text{ kHz}$	$C_L = 100 \text{ pF}$	5.9	5.9	5.9	5.9	MHz
BOM	Maximum output-swing bandwidth	$V_{O(PP)} = 20 \text{ V}$, $\text{AVD} = 1$,	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$	668	668	668	668	kHz
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega$,	$C_L = 100 \text{ pF}$	58°	58°	58°	58°	

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141I electrical characteristics at specified free-air temperature, $V_{CC} = 5$ V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2141I			TLE2141AI			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	$V_O = 2.5$ V, $V_{IC} = 2.5$ V	$R_S = 50 \Omega$	25°C	225	1400	200	1000		μV
			Full range		1900			1500	
			Full range		1.7			1.7	$\mu\text{V}/^\circ\text{C}$
			25°C	8	100	8	100		nA
			Full range		200			200	
			25°C	-0.8	-2	-0.8	-2		μA
I_{IB}			Full range		-2.2			-2.2	
$R_S = 50 \Omega$	25°C	0	-0.3		0	-0.3		V	
		to	to		to	to			
	Full range	3	3.2		3	3.2			
		0	-0.3		0	-0.3		V	
		to	to		to	to			
V_{ICR}	V_{ICR} Common-mode input voltage range	$R_S = 50 \Omega$	2.7	2.9		2.7	2.9		V
			3.9	4.1		3.9	4.1		
			3.8	4		3.8	4		
			3.2	3.7		3.2	3.7		
			3.8			3.8			
			3.7			3.7			
V_{OH}	V_{OH} High-level output voltage	25°C	3.3			3.3			V
			3.9	4.1		3.9	4.1		
			3.8	4		3.8	4		
		Full range	3.2	3.7		3.2	3.7		
			3.8			3.8			
			3.7			3.7			
V_{OL}	V_{OL} Low-level output voltage	25°C	3.3			3.3			mV
			75	125		75	125		
			150	225		150	225		
		Full range	1.2	1.6		1.2	1.6		
			175			175			
			225			225			
A_{VD}	A_{VD} Large-signal differential voltage amplification	$V_{CC} = \pm 2.5$ V, $R_L = 2 \text{ k}\Omega$, $V_O = 1$ V to -1.5 V	25°C	50	220	50	220		V/mV
			Full range	10		10			
r_i	Input resistance		25°C		70		70		$\text{M}\Omega$
c_i	Input capacitance		25°C		2.5		2.5		pF
z_o	Open-loop output impedance	$f = 1$ MHz	25°C		30		30		Ω
CMRR	Common-mode rejection ratio		25°C	85	118	85	118		dB
k_{SVR}	k_{SVR} Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	$V_{IC} = V_{ICR\min}$, $R_S = 50 \Omega$	25°C	80		80			
			Full range	90	106	90	106		dB
I_{CC}	I_{CC} Supply current	$V_O = 2.5$ V, $V_{IC} = 2.5$ V	25°C		3.4	4.4	3.4	4.4	mA
			Full range			4.6		4.6	

† Full range is -40°C to 105°C.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141I operating characteristics, $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2141I			TLE2141AI			UNIT
		MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	AVD = -1, $R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 500 \text{ pF}$		45			45	$\text{V}/\mu\text{s}$
SR-	Negative slew rate			42			42	
t_s	Settling time	AVD = -1, 2.5-V step	To 0.1%	0.16			0.16	μs
			To 0.01%	0.22			0.22	
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$, $f = 10 \text{ Hz}$		15			15	$\text{nV}/\sqrt{\text{Hz}}$
		$R_S = 20 \Omega$, $f = 1 \text{ kHz}$		10.5			10.5	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$		0.48			0.48	μV
		$f = 0.1 \text{ Hz to } 10 \text{ Hz}$		0.51			0.51	
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$		1.92			1.92	$\text{pA}/\sqrt{\text{Hz}}$
		$f = 1 \text{ kHz}$		0.5			0.5	
THD + N	Total harmonic distortion plus noise	$V_O = 1 \text{ V to } 3 \text{ V}$, $AVD = 2$,		$R_L = 2 \text{ k}\Omega^\dagger$, $f = 10 \text{ kHz}$	0.0052%	0.0052%		
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega^\dagger$,		$C_L = 100 \text{ pF}^\dagger$	5.9	5.9		MHz
	Gain-bandwidth product	$R_L = 2 \text{ k}\Omega^\dagger$, $f = 100 \text{ kHz}$		$C_L = 100 \text{ pF}^\dagger$	5.8	5.8		MHz
BOM	Maximum output-swing bandwidth	$V_O(PP) = 2 \text{ V}$, $AVD = 1$,		$R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 100 \text{ pF}^\dagger$	660	660		kHz
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega^\dagger$,		$C_L = 100 \text{ pF}^\dagger$	57°	57°		

† R_L and C_L terminated to 2.5 V.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**
SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141I electrical characteristics at specified free-air temperature, $V_{CC\pm} = \pm 15$ V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2141I			TLE2141AI			UNIT		
			MIN	TYP	MAX	MIN	TYP	MAX			
V_{IO}	$V_{IC} = 0$, $V_O = 0$	$R_S = 50 \Omega$	25°C	200	900	175	500		μV		
			Full range		1500			1000			
			Full range		1.7			1.7	$\mu V/^\circ C$		
			25°C	7	100	7	100				
			Full range		200			200	nA		
			25°C	-0.7	-1.5	-0.7	-1.5				
I_{IB}			Full range		-1.7			-1.7	μA		
$R_S = 50 \Omega$	25°C	-15	-15.3		-15	-15.3		V			
		to	to		to	to					
	Full range	13	13.2		13	13.2					
		-15	-15.3		-15	-15.3					
		V_{ICR}			to	to			to	to	
					12.7	12.9			12.7	12.9	
V_{OM+}	Maximum positive peak output voltage swing	25°C	$I_O = -150 \mu A$	13.8	14.1	13.8	14.1		V		
			$I_O = -1.5 mA$	13.7	14	13.7	14				
			$I_O = -15 mA$	13.1	13.7	13.1	13.7				
		Full range	$I_O = -100 \mu A$	13.7		13.7					
			$I_O = -1 mA$	13.6		13.6					
			$I_O = -10 mA$	13.1		13.1					
V_{OM-}	Maximum negative peak output voltage swing	25°C	$I_O = 150 \mu A$	-14.7	-14.9	-14.7	-14.9		V		
			$I_O = 1.5 mA$	-14.5	-14.8	-14.5	-14.8				
			$I_O = 15 mA$	-13.4	-13.8	-13.4	-13.8				
		Full range	$I_O = 100 \mu A$	-14.6		-14.6					
			$I_O = 1 mA$	-14.5		-14.5					
			$I_O = 10 mA$	-13.4		-13.4					
AVD	Large-signal differential voltage amplification	$V_O = \pm 10 V$, $R_L = 2 k\Omega$	25°C	100	450	100	450		V/mV		
			Full range	40		40					
r_i	Input resistance		25°C		65		65		$M\Omega$		
c_i	Input capacitance		25°C		2.5		2.5		pF		
z_o	Open-loop output impedance	$f = 1 MHz$	25°C		30		30		Ω		
$CMRR$	Common-mode rejection ratio	$V_{IC} = V_{ICR\min}$, $R_S = 50 \Omega$	25°C	85	108	85	108		dB		
			Full range	80		80					
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	$V_{CC\pm} = \pm 2.5 V$ to $\pm 15 V$, $R_S = 50 \Omega$	25°C	90	106	90	106		dB		
			Full range	85		85					
I_{OS}	Short-circuit output current	$V_O = 0$	25°C	-25	-50	-25	-50		mA		
				20	31	20	31				
I_{CC}	Supply current	$V_O = 0$, No load	25°C		3.5	4.5	3.5	4.5	mA		
			Full range			4.7		4.7			

[†] Full range is $-40^\circ C$ to $105^\circ C$.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141I operating characteristics, $V_{CC\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2141I			TLE2141AI			UNIT
		MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	$\text{AVD} = -1$, $R_L = 2 \text{ k}\Omega$, $C_L = 500 \text{ pF}$	27	45	27	45		$\text{V}/\mu\text{s}$
SR-	Negative slew rate		27	42	27	42		
t_s	Settling time	$\text{AVD} = -1$, 10-V step	To 0.1%	0.34	0.34		μs	
			To 0.01%	0.4	0.4			
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$, $f = 10 \text{ Hz}$		15	15		$\text{nV}/\sqrt{\text{Hz}}$	
		$R_S = 20 \Omega$, $f = 1 \text{ kHz}$		10.5	10.5			
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$		0.48	0.48		μV	
		$f = 0.1 \text{ Hz to } 10 \text{ Hz}$		0.51	0.51			
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$		1.89	1.89		$\text{pA}/\sqrt{\text{Hz}}$	
		$f = 1 \text{ kHz}$		0.47	0.47			
THD + N	Total harmonic distortion plus noise	$V_{O(PP)} = 20 \text{ V}$, $\text{AVD} = 10$, $f = 10 \text{ kHz}$		0.01%	0.01%			
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$		6	6	MHz		
	Gain-bandwidth product	$R_L = 2 \text{ k}\Omega$, $f = 100 \text{ kHz}$		5.9	5.9	MHz		
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)} = 20 \text{ V}$, $\text{AVD} = 1$, $C_L = 100 \text{ pF}$		668	668	kHz		
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$		58°	58°			

TLE214x, TLE214xA, TLE214xY
**EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**
SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142I electrical characteristics at specified free-air temperature, $V_{CC} = 5\text{ V}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2142I			TLE2142AI			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	$V_O = 2.5\text{ V}, V_{IC} = 2.5\text{ V}$ $R_S = 50\Omega$	25°C	220	1900		220	1500		μV
		Full range		2400				2000	
		Full range		1.7			1.7		$\mu\text{V}/^\circ\text{C}$
		25°C	8	100		8	100		nA
		Full range		200			200		
		25°C	-0.8	-2		-0.8	-2		μA
I_{IB}		Full range		-2.2				-2.2	
V_{ICR}	$R_S = 50\Omega$	25°C	0 to 3	-0.3 3.2		0 to 3	-0.3 3.2		V
		Full range	0 to 2.7	-0.3 2.9		0 to 2.7	-0.3 2.9		
		25°C	3.9	4.1		3.9	4.1		V
		25°C	3.8	4		3.8	4		
		25°C	3.4	3.7		3.4	3.7		
V_{OH}	High-level output voltage	$I_{OH} = -150\mu\text{A}$	3.8			3.8			mV
		$I_{OH} = -1.5\text{ mA}$	3.7			3.7			
		$I_{OH} = -15\text{ mA}$	3.5			3.5			
		$I_{OH} = 100\mu\text{A}$	75	125		75	125		
		$I_{OH} = 1\text{ mA}$	150	225		150	225		
		$I_{OH} = 10\text{ mA}$	1.2	1.4		1.2	1.4		
V_{OL}	Low-level output voltage	25°C	175			175			mV
		25°C	225			225			
		25°C	1.2			1.2			
		Full range	175			175			
		Full range	225			225			
		Full range	1.2			1.2			
A_{VD}	$V_{IC} = \pm 2.5\text{ V}, R_L = 2\text{ k}\Omega, V_O = 1\text{ V to }-1.5\text{ V}$	25°C	50	220		50	220		V/mV
		Full range	10			10			
r_i	Input resistance	25°C	70			70			$\text{M}\Omega$
c_i	Input capacitance	25°C	2.5			2.5			pF
z_o	Open-loop output impedance	$f = 1\text{ MHz}$	25°C	30		30			Ω
CMRR	Common-mode rejection ratio	$V_{IC} = V_{ICR\min}, R_S = 50\Omega$	25°C	85	118		85	118	dB
			Full range	80		80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	$V_{CC\pm} = \pm 2.5\text{ V to } \pm 15\text{ V}, R_S = 50\Omega$	25°C	90	106		90	106	dB
			Full range	85		85			
I_{CC}	Supply current	$V_O = 2.5\text{ V}, V_{IC} = 2.5\text{ V}$	25°C	6.6	8.8		6.6	8.8	mA
			Full range		9.2		9.2		

[†] Full range is -40°C to 105°C .

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142I operating characteristics, $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2142I			TLE2142AI			UNIT	
		MIN	TYP	MAX	MIN	TYP	MAX		
SR+	Positive slew rate	$A_{VD} = -1$, $R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 500 \text{ pF}$		45			45	$\text{V}/\mu\text{s}$	
SR-	Negative slew rate			42			42		
t_s	Settling time	$A_{VD} = -1$, 2.5-V step	To 0.1%	0.16			0.16	μs	
			To 0.01%	0.22			0.22		
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$, $f = 10 \text{ Hz}$		15			15	$\text{nV}/\sqrt{\text{Hz}}$	
				10.5			10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$		0.48			0.48	μV	
				0.51			0.51		
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$		1.92			1.92	$\text{pA}/\sqrt{\text{Hz}}$	
				0.5			0.5		
THD + N	Total harmonic distortion plus noise	$V_O = 1 \text{ V to } 3 \text{ V}$, $A_{VD} = 2$,	$R_L = 2 \text{ k}\Omega^\dagger$, $f = 10 \text{ kHz}$	0.0052%	0.0052%				
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega^\dagger$,	$C_L = 100 \text{ pF}$	5.9			5.9	MHz	
	Gain-bandwidth product			5.8			5.8		
B_{OM}	Maximum output-swing bandwidth	$V_O(PP) = 2 \text{ V}$, $A_{VD} = 1$,	$R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 100 \text{ pF}$	660	660			kHz	
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega^\dagger$,	$C_L = 100 \text{ pF}$	57°	57°				

† R_L terminates at 2.5 V.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**
SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142I electrical characteristics at specified free-air temperature, $V_{CC\pm} = \pm 15$ V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2142I			TLE2142I			UNIT			
			MIN	TYP	MAX	MIN	TYP	MAX				
V_{IO} Input offset voltage	$V_{IC} = 0$, $V_O = 0$	$R_S = 50 \Omega$	25°C	290	1200	275	750		μV			
			Full range		1800			1400				
			Full range		1.7			1.7	$\mu V/^\circ C$			
			25°C	7	100	7	100					
			Full range		200			200	nA			
			25°C	-0.7	-1.5	-0.7	-1.5					
I_{IB} Input bias current			Full range		-1.7			-1.7	μA			
			25°C	-15	-15.3	-15	-15.3		V			
				to	to	to	to					
				13	13.2	13	13.2		V			
			Full range	-15	-15.3	-15	-15.3					
V_{ICR} Common-mode input voltage range	$R_S = 50 \Omega$			to	to	to	to		V			
				12.7	12.9	12.7	12.9					
			25°C	13.8	14.1	13.8	14.1		V			
				13.7	14	13.7	14					
				13.3	13.7	13.3	13.7					
			Full range	13.7		13.7						
V_{OM+} Maximum positive peak output voltage swing				13.6		13.6			V			
				13.3		13.3						
			25°C	13.7		13.7						
				13.7		13.7						
			Full range	13.6		13.6						
				13.3		13.3						
V_{OM-} Maximum negative peak output voltage swing			25°C	-14.7	-14.9	-14.7	-14.9		V			
				-14.5	-14.8	-14.5	-14.8					
				-13.4	-13.8	-13.4	-13.8					
			Full range	-14.6		-14.6						
				-14.5		-14.5						
				-13.4		-13.4						
AVD Large-signal differential voltage amplification	$V_O = \pm 10$ V, $R_L = 2 \text{ k}\Omega$	25°C	100	450		100	450		V/mV			
		Full range	40			40						
r_i	Input resistance		25°C		65		65		$M\Omega$			
c_i	Input capacitance		25°C		2.5		2.5		pF			
z_o	Open-loop output impedance	$f = 1$ MHz	25°C		30		30		Ω			
CMRR	Common-mode rejection ratio	$V_{IC} = V_{ICR\min}$	25°C	85	108		85	108	dB			
		$R_S = 50 \Omega$	Full range	80			80					
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	$V_{CC\pm} = \pm 2.5$ V to ± 15 V, $R_S = 50 \Omega$	25°C	90	106		90	106	dB			
			Full range	85			85					
I_{OS}	Short-circuit output current	$V_O = 0$	$V_{ID} = 1$ V	-25	-50		-25	-50	mA			
			$V_{ID} = -1$ V	20	31		20	31				
I_{CC}	Supply current	$V_O = 0$,	No load	25°C	6.9	9	6.9	9	mA			
						9.4		9.4				

[†] Full range is $-40^\circ C$ to $105^\circ C$.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142I operating characteristics, $V_{CC\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2142I			TLE2142AI			UNIT	
		MIN	TYP	MAX	MIN	TYP	MAX		
SR+	Positive slew rate	AVD = -1, $R_L = 2\text{ k}\Omega$, $C_L = 500\text{ pF}$	30	45	30	45	30	$\text{V}/\mu\text{s}$	
SR-	Negative slew rate		30	42	30	42	30		
t_s	Settling time	AVD = -1, 10-V step	To 0.1%	0.34	0.34	0.34	0.4	μs	
			To 0.01%	0.4	0.4	0.4	0.4		
V_n	Equivalent input noise voltage	$R_S = 20\text{ }\Omega$,	$f = 10\text{ Hz}$	15	15	15	15	$\text{nV}/\sqrt{\text{Hz}}$	
			$f = 1\text{ kHz}$	10.5	10.5	10.5	10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1\text{ Hz to }1\text{ Hz}$		0.48	0.48	0.48	0.48	μV	
		$f = 0.1\text{ Hz to }10\text{ Hz}$		0.51	0.51	0.51	0.51		
I_n	Equivalent input noise current	$f = 10\text{ Hz}$		1.89	1.89	1.89	1.89	$\text{pA}/\sqrt{\text{Hz}}$	
		$f = 1\text{ kHz}$		0.47	0.47	0.47	0.47		
THD + N	Total harmonic distortion plus noise	$V_{O(PP)} = 20\text{ V}$, AVD = 10, $f = 10\text{ kHz}$	0.01%		0.01%				
B_1	Unity-gain bandwidth	$R_L = 2\text{ k}\Omega$, $C_L = 100\text{ pF}$	6		6		MHz		
	Gain-bandwidth product	$R_L = 2\text{ k}\Omega$, $f = 100\text{ kHz}$	5.9		5.9		MHz		
BOM	Maximum output-swing bandwidth	$V_{O(PP)} = 20\text{ V}$, AVD = 1, $C_L = 100\text{ pF}$	668		668		kHz		
ϕ_m	Phase margin at unity gain	$R_L = 2\text{ k}\Omega$, $C_L = 100\text{ pF}$	58°		58°				

TLE214x, TLE214xA, TLE214xY
**EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**
SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144I electrical characteristics at specified free-air temperature, $V_{CC} = 5\text{ V}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2144I			TLE2144AI			UNIT		
			MIN	TYP	MAX	MIN	TYP	MAX			
V_{IO}	$V_{IC} = 0, V_O = 0$	$R_S = 50\ \Omega$	25°C	0.5	3.8	0.5	3	4	mV		
			Full range		4.8			4			
			Full range		1.7			1.7	$\mu\text{V}/^\circ\text{C}$		
			25°C	8	100	8	100	200			
			Full range		200			200	nA		
			25°C	-0.8	-2	-0.8	-2	-2.2			
I_{IB}			Full range		-2.2			-2.2	μA		
V_{ICR}	$R_S = 50\ \Omega$	25°C	0	-0.3	0	-0.3	3	V			
			to	to	to	to	3.2				
		Full range	0	-0.3	0	-0.3	3.2				
			to	to	to	to	2.9				
V_{OH}	High-level output voltage	25°C	3.9	4.1	3.9	4.1			V		
			3.8	4	3.8	4					
			3.4	3.7	3.4	3.7					
		Full range	3.8		3.8						
			3.7		3.7						
			3.5		3.5						
V_{OL}	Low-level output voltage	25°C	75	125	75	125			mV		
			150	225	150	225					
			1.2	1.6	1.2	1.6					
		Full range	175		175				mV		
			225		225						
			1.4		1.4						
A_{VD}	Large-signal differential voltage amplification	$V_{IC} = \pm 2.5\text{ V}, R_L = 2\text{ k}\Omega, V_O = 1\text{ V to }-1.5\text{ V}$	25°C	50	95	50	95		V/mV		
			Full range	10		10					
r_i	Input resistance		25°C		70		70		MΩ		
c_i	Input capacitance		25°C		2.5		2.5		pF		
z_o	Open-loop output impedance	f = 1 MHz	25°C		30		30		Ω		
CMRR	Common-mode rejection ratio	$V_{IC} = V_{ICR\min}, R_S = 50\ \Omega$	25°C	85	118	85	118		dB		
			Full range	80		80					
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	$V_{CC\pm} = \pm 2.5\text{ V to } \pm 15\text{ V}, R_S = 50\ \Omega$	25°C	90	106	90	106		dB		
			Full range	85		85					
I_{CC}	Supply current	$V_O = 2.5\text{ V}, V_{IC} = 2.5\text{ V}$	25°C	13.2	17.6	13.2	17.6		mA		
			Full range		18.4			18.4			

† Full range is -40°C to 105°C .

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144I operating characteristics, $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2144I			TLE2144AI			UNIT		
		MIN	TYP	MAX	MIN	TYP	MAX			
SR+	Positive slew rate	$A_{VD} = -1$, $R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 500 \text{ pF}$		45		45		$\text{V}/\mu\text{s}$		
SR-	Negative slew rate			42						
t_s	Settling time	$A_{VD} = -1$, 2.5-V step	To 0.1%	0.16		0.16		μs		
			To 0.01%	0.22						
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$, $f = 10 \text{ Hz}$		15		15		$\text{nV}/\sqrt{\text{Hz}}$		
				10.5						
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$		0.48		0.48		μV		
				0.51						
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$		1.92		1.92		$\text{pA}/\sqrt{\text{Hz}}$		
				0.5						
THD + N	Total harmonic distortion plus noise	$V_O = 1 \text{ V to } 3 \text{ V}$, $A_{VD} = 2$,	$R_L = 2 \text{ k}\Omega^\dagger$, $f = 10 \text{ kHz}$	0.0052%	0.0052%					
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega^\dagger$,	$C_L = 100 \text{ pF}$	5.9		5.9		MHz		
	Gain-bandwidth product			5.8						
B_{OM}	Maximum output-swing bandwidth	$V_O(PP) = 2 \text{ V}$, $A_{VD} = 1$,	$R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 100 \text{ pF}$	660	660			kHz		
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega^\dagger$,	$C_L = 100 \text{ pF}$	57°	57°					

† R_L terminates at 2.5 V



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144I electrical characteristics at specified free-air temperature, $V_{CC\pm} = \pm 15$ V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2144I			TLE2144AI			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	$V_{IC} = 0$, $V_O = 0$	$R_S = 50 \Omega$	25°C	0.6	2.4	0.5	1.5		mV
			Full range		3.2			2.8	
			Full range		1.7			1.7	$\mu V/^\circ C$
			25°C	7	100	7	100		
			Full range		200			200	nA
			25°C	-0.7	-1.5	-0.7	-1.5		
I_{IB}			Full range		-1.7			-1.7	μA
			25°C	-15	-15.3	-15	-15.3		V
				to	to	to	to		
				13	13.2	13	13.2		
			Full range	-15	-15.3	-15	-15.3		
V_{ICR}	$R_S = 50 \Omega$			to	to	to	to		
				12.7	12.9	12.7	12.9		
			25°C	13.8	14.1	13.8	14.1		
				13.7	14	13.7	14		
				13.1	13.7	13.1	13.7		
V_{OM+}	Maximum positive peak output voltage swing	$I_O = -150 \mu A$	13.7			13.7			V
			13.7			13.6			
			13.6			13.1			
		Full range	13.1			13.1			
V_{OM-}	Maximum negative peak output voltage swing	$I_O = 150 \mu A$	-14.7	-14.9		-14.7	-14.9		V
			-14.5	-14.8		-14.5	-14.8		
			-13.4	-13.8		-13.4	-13.8		
		Full range	-14.6			-14.6			
			-14.5			-14.5			
			-13.4			-13.4			
AVD	Large-signal differential voltage amplification	$V_O = \pm 10$ V, $R_L = 2 \text{ k}\Omega$	25°C	100	170	100	170		V/mV
			Full range	40		40			
r_i	Input resistance		25°C		65		65		MΩ
c_i	Input capacitance		25°C		2.5		2.5		pF
z_o	Open-loop output impedance	f = 1 MHz	25°C		30		30		Ω
$CMRR$	Common-mode rejection ratio	$V_{IC} = V_{ICR\min}$, $R_S = 50 \Omega$	25°C	85	108	85	108		dB
			Full range	80		80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	$V_{CC\pm} = \pm 2.5$ V to ± 15 V, $R_S = 50 \Omega$	25°C	90	106	90	106		dB
			Full range	85		85			
I_{OS}	Short-circuit output current	$V_O = 0$	$V_{ID} = 1$ V	25°C	-25	-50	-25	-50	mA
				20	31	20	31		
I_{CC}	Supply current	$V_O = 0$,	No load	25°C	13.8	18	13.8	18	mA
				Full range		18.8		18.8	

† Full range is -40°C to 105°C.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144I operating characteristics, $V_{CC\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2144I			TLE2144AI			UNIT
		MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	$\text{AVD} = -1$, $R_L = 2 \text{ k}\Omega$, $C_L = 500 \text{ pF}$	27	45	27	45	27	$\text{V}/\mu\text{s}$
SR-	Negative slew rate		27	42	27	42	27	
t_s	Settling time	$\text{AVD} = -1$, 10-V step	To 0.1%	0.34	0.34	0.34	0.4	μs
			To 0.01%	0.4	0.4	0.4	0.4	
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$, $f = 10 \text{ Hz}$	15	15	15	15	15	$\text{nV}/\sqrt{\text{Hz}}$
			$R_S = 20 \Omega$, $f = 1 \text{ kHz}$	10.5	10.5	10.5	10.5	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$	0.48	0.48	0.48	0.48	0.48	μV
			$f = 0.1 \text{ Hz to } 10 \text{ Hz}$	0.51	0.51	0.51	0.51	
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$	1.89	1.89	1.89	1.89	1.89	$\text{pA}/\sqrt{\text{Hz}}$
			$f = 1 \text{ kHz}$	0.47	0.47	0.47	0.47	
THD + N	Total harmonic distortion plus noise	$V_{O(PP)} = 20 \text{ V}$, $\text{AVD} = 10$,	$R_L = 2 \text{ k}\Omega$, $f = 10 \text{ kHz}$	0.01%	0.01%	0.01%	0.01%	
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$	6	6	6	6	6	MHz
	Gain-bandwidth product		$R_L = 2 \text{ k}\Omega$, $f = 100 \text{ kHz}$	5.9	5.9	5.9	5.9	
BOM	Maximum output-swing bandwidth	$V_{O(PP)} = 20 \text{ V}$, $\text{AVD} = 1$,	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$	668	668	668	668	kHz
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$	58°	58°	58°	58°	58°	

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**
SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141M electrical characteristics at specified free-air temperature, $V_{CC} = 5\text{ V}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2141M			TLE2141AM			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	$V_O = 2.5\text{ V}$ $V_{IC} = 2.5\text{ V}$	$R_S = 50\ \Omega$	25°C	225	1400	200	1000		μV
			Full range		2100			1700	
			Full range		1.7			1.7	$\mu\text{V}/^\circ\text{C}$
			25°C	8	100	8	100		nA
			Full range		250			250	
			25°C	-0.8	-2	-0.8	-2		μA
I_{IB}			Full range		-2.3			-2.3	
V_{ICR}	$R_S = 50\ \Omega$	25°C	0	-0.3	0	-0.3		V	
			to	to	to	to			
			3	3.2	3	3.2		V	
		Full range	0	-0.3	0	-0.3			
			to	to	to	to			
V_{OH}	$I_{OH} = -150\ \mu\text{A}$ $I_{OH} = -1.5\text{ mA}$ $I_{OH} = -15\text{ mA}$ $I_{OH} = -100\ \mu\text{A}$ $I_{OH} = -1\text{ mA}$ $I_{OH} = -10\text{ mA}$	25°C	3.9	4.1		3.9	4.1		V
			3.8	4		3.8	4		
			3.2	3.7		3.2	3.7		
		Full range	3.75			3.75			
			3.65			3.65			
			3.25			3.25			
V_{OL}	$I_{OL} = 150\ \mu\text{A}$ $I_{OL} = 1.5\ \mu\text{A}$ $I_{OL} = 15\text{ mA}$ $I_{OL} = 100\ \mu\text{A}$ $I_{OL} = 1\text{ mA}$ $I_{OL} = 10\text{ mA}$	25°C	75	125		75	125		mV
			150	225		150	225		
			1.2	1.4		1.2	1.4		
		Full range	200			200			mV
			250			225			
			1.25			1.25			
AVD	$V_{IC} = \pm 2.5\text{ V}, R_L = 2\text{ k}\Omega, V_O = 1\text{ V to }-1.5\text{ V}$	25°C	50	220		50	220		V/mV
		Full range	5			5			
r_i	Input resistance	25°C	70			70			$\text{M}\Omega$
c_i	Input capacitance	25°C	2.5			2.5			pF
z_o	Open-loop output impedance	25°C	30			30			Ω
$CMRR$	$V_{IC} = V_{ICR\min}, R_S = 50\ \Omega$	25°C	85	118		85	118		dB
		Full range	80			80			
k_{SVR}	$V_{CC\pm} = \pm 2.5\text{ V to } \pm 15\text{ V}, R_S = 50\ \Omega$	25°C	90	106		90	106		dB
		Full range	85			85			
I_{CC}	$V_O = 2.5\text{ V}, V_{IC} = 2.5\text{ V}$	25°C	3.4	4.4		3.4	4.4		mA
		Full range			4.6			4.6	

[†] Full range is -55°C to 125°C .

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141M operating characteristics, $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2141M			TLE2141AM			UNIT		
		MIN	TYP	MAX	MIN	TYP	MAX			
SR+	Positive slew rate	$A_{VD} = -1$, $C_L = 500 \text{ pF}$	$R_L = 2 \text{ k}\Omega^\dagger$,	45	45	45	45	$\text{V}/\mu\text{s}$		
SR-	Negative slew rate			42						
t_s	Settling time	$A_{VD} = -1$, 2.5-V step	To 0.1%	0.16	0.16	0.16	0.16	μs		
			To 0.01%	0.22						
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$,	$f = 10 \text{ Hz}$	15	15	15	15	$\text{nV}/\sqrt{\text{Hz}}$		
		$R_S = 20 \Omega$,	$f = 1 \text{ kHz}$	10.5						
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$		0.48	0.48	0.48	0.48	μV		
		$f = 0.1 \text{ Hz to } 10 \text{ Hz}$		0.51						
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$		1.92	1.92	1.92	1.92	$\text{pA}/\sqrt{\text{Hz}}$		
		$f = 1 \text{ kHz}$		0.5						
THD + N	Total harmonic distortion plus noise	$V_O = 1 \text{ V to } 3 \text{ V}$, $A_{VD} = 2$,	$R_L = 2 \text{ k}\Omega^\dagger$, $f = 10 \text{ kHz}$	0.0052%	0.0052%					
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega^\dagger$,	$C_L = 100 \text{ pF}^\dagger$	5.9	5.9	5.9	5.9	MHz		
	Gain-bandwidth product	$R_L = 2 \text{ k}\Omega^\dagger$, $f = 100 \text{ kHz}$	$C_L = 100 \text{ pF}^\dagger$,	5.8						
B_{OM}	Maximum output-swing bandwidth	$V_O(PP) = 2 \text{ V}$, $A_{VD} = 1$	$R_L = 2 \text{ k}\Omega^\dagger$,	660	660			kHz		
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega^\dagger$,	$C_L = 100 \text{ pF}^\dagger$	57°	57°					

† R_L and C_L terminated to 2.5 V.

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS
SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141M electrical characteristics at specified free-air temperature, $V_{CC\pm} = \pm 15$ V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2141M			TLE2141AM			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	$V_{IC} = 0$, $R_S = 50 \Omega$	25°C	200	900	900	175	500	500	μV
		Full range			1700			1200	
		Full range		1.7			1.7		$\mu V/^\circ C$
		25°C	7	100	100	7	100	100	nA
		Full range		250			250		
		25°C	-0.7	-1.5	-1.5	-0.7	-1.5	-1.5	μA
I_{IB}		Full range		-1.8			-1.8		
V_{ICR}	$R_S = 50 \Omega$	25°C	-15 to 13	-15.3 to 13.2	-15.3 to 13.2	-15 to 13	-15.3 to 13.2	-15.3 to 13.2	V
		Full range	-15 to 12.7	-15.3 to 12.9	-15.3 to 12.9	-15 to 12.7	-15.3 to 12.9	-15.3 to 12.9	
		25°C	13.8	14.1	14.1	13.8	14.1	14.1	V
			13.7	14	14	13.7	14	14	
			13.1	13.7	13.7	13.1	13.7	13.7	
V_{OM+}	Maximum positive peak output voltage swing	25°C	13.7		13.7				V
			13.6		13.6				
			13.1		13.1				
		Full range							
V_{OM-}	Maximum negative peak output voltage swing	25°C	-14.7	-14.9	-14.9	-14.7	-14.9	-14.9	V
			-14.5	-14.8	-14.8	-14.5	-14.8	-14.8	
			-13.4	-13.8	-13.8	-13.4	-13.8	-13.8	
		Full range	-14.6		-14.6				
			-14.5		-14.5				
			-13.4		-13.4				
AVD	Large-signal differential voltage amplification	$V_O = \pm 10$ V, $R_L = 2 k\Omega$	25°C	100	450	100	450	450	V/mV
			Full range	20		20			
r_i	Input resistance		25°C		65		65		$M\Omega$
c_i	Input capacitance		25°C		2.5		2.5		pF
z_o	Open-loop output impedance	$f = 1$ MHz	25°C		30		30		Ω
$CMRR$	Common-mode rejection ratio	$V_{IC} = V_{ICR\min}$, $R_S = 50 \Omega$	25°C	85	108	85	108	108	dB
			Full range	80		80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	$V_{CC\pm} = \pm 2.5$ V to ± 15 V, $R_S = 50 \Omega$	25°C	90	106	90	106	106	dB
			Full range	85		85			
I_{OS}	Short-circuit output current	$V_O = 0$	$V_{ID} = 1$ V	25°C	-25	-50	-25	-50	mA
				20	31		20	31	
I_{CC}	Supply current	$V_O = 0$, $V_{IC} = 2.5$ V	No load,	25°C	3.5	4.5	3.5	4.5	mA
				Full range		4.7		4.7	

[†] Full range is $-55^\circ C$ to $125^\circ C$.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141M operating characteristics, $V_{CC\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2141M			TLE2141AM			UNIT
		MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	$A_{VD} = -1$, $R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$	27	45	27	45	27	$\text{V}/\mu\text{s}$
SR-	Negative slew rate		27	42	27	42	27	
t_s	Settling time	$A_{VD} = -1$, 10-V step	To 0.1%	0.34	0.34	0.34	0.34	μs
			To 0.01%	0.4	0.4	0.4	0.4	
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$, $f = 10 \text{ Hz}$		15	15	15	15	$\text{nV}/\sqrt{\text{Hz}}$
		$R_S = 20 \Omega$, $f = 1 \text{ kHz}$		10.5	10.5	10.5	10.5	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$		0.48	0.48	0.48	0.48	μV
		$f = 0.1 \text{ Hz to } 10 \text{ Hz}$		0.51	0.51	0.51	0.51	
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$		1.89	1.89	1.89	1.89	$\text{pA}/\sqrt{\text{Hz}}$
		$f = 1 \text{ kHz}$		0.47	0.47	0.47	0.47	
THD + N	Total harmonic distortion plus noise	$V_{O(PP)} = 20 \text{ V}$, $A_{VD} = 10$,		0.01%	0.01%	0.01%	0.01%	
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$						
Gain-bandwidth product		$R_L = 2 \text{ k}\Omega$, $f = 100 \text{ kHz}$		5.9	5.9	5.9	5.9	MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)} = 20 \text{ V}$, $A_{VD} = 1$,		668	668	668	668	kHz
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$		58°	58°	58°	58°	

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142M electrical characteristics at specified free-air temperature, $V_{CC} = 5\text{ V}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2142M			TLE2142AM			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	$V_O = 2.5\text{ V}$, $V_{IC} = 2.5\text{ V}$	$R_S = 50\Omega$	25°C	220	1900	200	1500		μV
			Full range		2600			2200	
			Full range		1.7			1.7	$\mu\text{V}/^\circ\text{C}$
			25°C	8	100	8	100		nA
			Full range		200			200	
			25°C	-0.8	-2	-0.8	-2		μA
			Full range		-2.3			-2.3	
V_{ICR}	$R_S = 50\Omega$		25°C	0	-0.3	0	-0.3		V
				to	to	to	to		
				3	3.2	3	3.2		
			Full range	0	-0.3	0	-0.3		V
				to	to	to	to		
				2.7	2.9	2.7	2.9		
V_{OH}	High-level output voltage	25°C	$I_{OH} = -150\text{ }\mu\text{A}$	3.9	4.1	3.9	4.1		V
			$I_{OH} = -1.5\text{ mA}$	3.8	4	3.8	4		
			$I_{OH} = -15\text{ mA}$	3.4	3.7	3.4	3.7		
		Full range	$I_{OH} = 100\text{ }\mu\text{A}$	3.75		3.75			
			$I_{OH} = 1\text{ mA}$	3.65		3.65			
			$I_{OH} = 10\text{ mA}$	3.45		3.45			
V_{OL}	Low-level output voltage	25°C	$I_{OL} = 150\text{ }\mu\text{A}$	75	125	75	125		mV
			$I_{OL} = 1.5\text{ mA}$	150	225	150	225		
			$I_{OL} = 15\text{ mA}$	1.2	1.4	1.2	1.4		
		Full range	$I_{OL} = 100\text{ }\mu\text{A}$	200		200			
			$I_{OL} = 1\text{ mA}$	250		250			
			$I_{OL} = 10\text{ mA}$	1.25		1.25			
A_{VD}	$V_{IC} = \pm 2.5\text{ V}, R_L = 2\text{ k}\Omega, V_O = 1\text{ V to }-1.5\text{ V}$	25°C	50	220		50	220		V/mV
		Full range	5			5			
r_i	Input resistance		25°C		70		70		$\text{M}\Omega$
c_i	Input capacitance		25°C		2.5		2.5		pF
z_o	Open-loop output impedance	$f = 1\text{ MHz}$	25°C		30		30		Ω
CMRR	Common-mode rejection ratio	$V_{IC} = V_{ICR\min}, R_S = 50\Omega$	25°C	85	118	85	118		dB
			Full range	80		80			
k_{SVR}	$V_{CC\pm} = \pm 2.5\text{ V to } \pm 15\text{ V}, R_S = 50\Omega$		25°C	90	106	90	106		dB
			Full range	85		85			
I_{CC}	Supply current	$V_O = 2.5\text{ V}, V_{IC} = 2.5\text{ V}$	25°C		6.6	8.8	6.6	8.8	mA
			Full range			9.2		9.2	

† Full range is -55°C to 125°C .

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142M operating characteristics, $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2142M			TLE2142AM			UNIT		
		MIN	TYP	MAX	MIN	TYP	MAX			
SR+	Positive slew rate	$A_{VD} = -1$, $R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 500 \text{ pF}$		45		45		$\text{V}/\mu\text{s}$		
SR-	Negative slew rate			42						
t_s	Settling time	$A_{VD} = -1$, 2.5-V step	To 0.1%	0.16		0.16		μs		
			To 0.01%	0.22						
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$, $f = 10 \text{ Hz}$		15		15		$\text{nV}/\sqrt{\text{Hz}}$		
				10.5						
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$		0.48		0.48		μV		
				0.51						
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$		1.92		1.92		$\text{pA}/\sqrt{\text{Hz}}$		
				0.5						
THD + N	Total harmonic distortion plus noise	$V_O = 1 \text{ V to } 3 \text{ V}$, $A_{VD} = 2$,	$R_L = 2 \text{ k}\Omega^\dagger$, $f = 10 \text{ kHz}$	0.0052%	0.0052%					
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega^\dagger$,	$C_L = 100 \text{ pF}$	5.9		5.9		MHz		
	Gain-bandwidth product			5.8						
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)} = 2 \text{ V}$, $A_{VD} = 1$,	$R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 100 \text{ pF}$	660	660			kHz		
ϕ_m	Phase margin	$R_L = 2 \text{ k}\Omega^\dagger$,	$C_L = 100 \text{ pF}$	57°	57°					

† R_L terminates at 2.5 V.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS
SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142M electrical characteristics at specified free-air temperature, $V_{CC\pm} = \pm 15$ V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2142M			TLE2142AM			UNIT	
			MIN	TYP	MAX	MIN	TYP	MAX		
V_{IO} Input offset voltage	$V_{IC} = 0$, $R_S = 50\Omega$	25°C	290	1200		275	750		μV	
		Full range		2000			1600			
αV_{IO} Temperature coefficient of input offset voltage		Full range		1.7			1.7		$\mu V/\text{ }^\circ C$	
		25°C	7	100		7	100		nA	
I_{IO} Input offset current		Full range		250			250			
		25°C	-0.7	-1.5		-0.7	-1.5		μA	
		Full range		-1.8			-1.8			
V_{ICR} Common-mode input voltage range	$R_S = 50\Omega$	25°C	-15 to 13	-15.3 to 13.2		-15 to 13	-15.3 to 13.2		V	
		Full range	-15 to 12.7	-15.3 to 12.9		-15 to 12.7	-15.3 to 12.9			
V_{OM+} Maximum positive peak output voltage swing		$I_O = -150\mu A$	13.8	14.1		13.8	14.1		V	
		$I_O = -1.5mA$	13.7	14		13.7	14			
		$I_O = -15mA$	13.3	13.7		13.3	13.7			
		$I_O = -100\mu A$	13.7			13.7				
		$I_O = -1mA$	13.6			13.6				
		$I_O = -10mA$	13.3			13.3				
		$I_O = 150\mu A$	-14.7	-14.9		-14.7	-14.9			
V_{OM-} Maximum negative peak output voltage swing	$V_O = \pm 10V$, $R_L = 2k\Omega$	25°C	-14.5	-14.8		-14.5	-14.8		V	
		$I_O = 1.5mA$	-13.4	-13.8		-13.4	-13.8			
		$I_O = 15mA$	-14.6			-14.6				
		$I_O = 100\mu A$	-14.5			-14.5				
		$I_O = 1mA$	-13.4			-13.4				
		$I_O = 10mA$	-14.7	-14.9		-14.7	-14.9			
		$I_O = 15mA$	-14.5	-14.8		-14.5	-14.8			
AVD Large-signal differential voltage amplification	$V_O = \pm 10V$, $R_L = 2k\Omega$	25°C	100	450		100	450		V/mV	
		Full range	20			20				
r_i	Input resistance	25°C		65			65		$M\Omega$	
c_i	Input capacitance	25°C		2.5			2.5		pF	
z_o	Open-loop output impedance	$f = 1MHz$	25°C		30		30		Ω	
$CMRR$ Common-mode rejection ratio	$V_{IC} = V_{ICR\min}$, $R_S = 50\Omega$	25°C	85	108		85	108		dB	
		Full range	80			80				
k_{SVR} Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm} = \pm 2.5V$ to $\pm 15V$, $R_S = 50\Omega$	25°C	90	106		90	106		dB	
		Full range	85			85				
I_{OS} Short-circuit output current	$V_O = 0$	$V_{ID} = 1V$	25°C	-25	-50		-25	-50	mA	
		$V_{ID} = -1V$	20	31		20	31			
I_{CC} Supply current	$V_O = 0$, $V_{IC} = 2.5V$	No load,	25°C		6.9	9	6.9	9	mA	
			Full range			9.4		9.4		

[†] Full range is $-55^\circ C$ to $125^\circ C$.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142M operating characteristics, $V_{CC\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2142M			TLE2142AM			UNIT
		MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	$R_L = 2 \text{ k}\Omega$, $A_{VD} = -1$, $C_L = 100 \text{ pF}$	27	45	27	45	27	$\text{V}/\mu\text{s}$
SR-	Negative slew rate		27	42	27	42	27	
t_s	Settling time	$A_{VD} = -1$, 10-V step	To 0.1%	0.34	0.34	0.34	0.34	μs
			To 0.01%	0.4	0.4	0.4	0.4	
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$, $f = 10 \text{ Hz}$	15	15	15	15	15	$\text{nV}/\sqrt{\text{Hz}}$
			$R_S = 20 \Omega$, $f = 1 \text{ kHz}$	10.5	10.5	10.5	10.5	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$	0.48	0.48	0.48	0.48	0.48	μV
			$f = 0.1 \text{ Hz to } 10 \text{ Hz}$	0.51	0.51	0.51	0.51	
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$	1.89	1.89	1.89	1.89	1.89	$\text{pA}/\sqrt{\text{Hz}}$
			$f = 1 \text{ kHz}$	0.47	0.47	0.47	0.47	
THD + N	Total harmonic distortion plus noise	$V_{O(PP)} = 20 \text{ V}$, $A_{VD} = 10$,	$R_L = 2 \text{ k}\Omega$, $f = 10 \text{ kHz}$	0.01%	0.01%	0.01%	0.01%	
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega$,	$C_L = 100 \text{ pF}$	6	6	6	6	MHz
	Gain-bandwidth product	$R_L = 2 \text{ k}\Omega$, $f = 100 \text{ kHz}$	$C_L = 100 \text{ pF}$	5.9	5.9	5.9	5.9	MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)} = 20 \text{ V}$, $A_{VD} = 1$,	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$	668	668	668	668	kHz
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega$,	$C_L = 100 \text{ pF}$	58°	58°	58°	58°	

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144M electrical characteristics at specified free-air temperature, $V_{CC} = 5\text{ V}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2144M			TLE2144AM			UNIT		
			MIN	TYP	MAX	MIN	TYP	MAX			
V_{IO}	$V_O = 2.5\text{ V}$, $V_{IC} = 2.5\text{ V}$	$R_S = 50\Omega$	25°C	0.5	3.8	0.5	3	4.4	mV		
			Full range		5.2						
			Full range		1.7		1.7		$\mu\text{V}/^\circ\text{C}$		
αV_{IO}			25°C	8	100	8	100		nA		
			Full range		250		250				
			25°C	-0.8	-2	-0.8	-2		μA		
I_{IB}			Full range		-2.3			-2.3			
V_{ICR}	$R_S = 50\Omega$	25°C	0	-0.3		0	-0.3		V		
			to	to		to	to				
			3	3.2		3	3.2				
		Full range	0	-0.3		0	-0.3				
			to	to		to	to				
			2.7	2.9		2.7	2.9				
V_{OH}	High-level output voltage	25°C	3.9	4.1		3.9	4.1		V		
			3.8	4		3.8	4				
			3.4	3.7		3.4	3.7				
		Full range	3.75			3.75					
			3.65			3.65					
			3.45			3.45					
V_{OL}	Low-level output voltage	25°C	75	125		75	125		mV		
			150	225		150	225				
			1.2	1.6		1.2	1.6				
		Full range	200			200					
			250			250					
			1.45			1.45					
A_{VD}	$V_{IC} = \pm 2.5\text{ V}$, $R_L = 2\text{ k}\Omega$, $V_O = 1\text{ V}$ to -1.5 V	25°C	50	95		50	95		V/mV		
		Full range	5			5					
r_i	Input resistance	25°C		70		70			$M\Omega$		
c_i	Input capacitance	25°C		2.5		2.5			pF		
z_o	Open-loop output impedance	$f = 1\text{ MHz}$	25°C		30		30		Ω		
CMRR	$V_{IC} = V_{ICR\min}$, $R_S = 50\Omega$	25°C	85	118		85	118		dB		
		Full range	80			80					
k_{SVR}	$V_{CC\pm} = \pm 2.5\text{ V}$ to $\pm 15\text{ V}$, $R_S = 50\Omega$	25°C	90	106		90	106		dB		
		Full range	85			85					
I_{CC}	$V_O = 2.5\text{ V}$, $V_{IC} = 2.5\text{ V}$	No load,	25°C		13.2	17.6		13.2	mA		
			Full range			18.4		18.4			

[†] Full range is -55°C to 125°C .

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144M operating characteristics, $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2144M			TLE2144AM			UNIT
		MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	$A_{VD} = -1$, $R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 500 \text{ pF}$	45	42	45	42		V/ μs
SR-	Negative slew rate							
t_s	Settling time	$A_{VD} = -1$, 2.5-V step	To 0.1%	0.16	0.16	0.22	0.22	μs
			To 0.01%	0.22				
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$, $f = 10 \text{ Hz}$	15	15	15	10.5	10.5	$\text{nV}/\sqrt{\text{Hz}}$
		$R_S = 20 \Omega$, $f = 1 \text{ kHz}$	10.5	10.5	10.5			
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$	0.48	0.48	0.48	0.51	0.51	μV
		$f = 0.1 \text{ Hz to } 10 \text{ Hz}$	0.51	0.51	0.51			
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$	1.92	1.92	1.92	0.5	0.5	$\text{pA}/\sqrt{\text{Hz}}$
		$f = 1 \text{ kHz}$	0.5	0.5	0.5			
THD + N	Total harmonic distortion plus noise	$V_O = 1 \text{ V to } 3 \text{ V}$, $A_{VD} = 2$, $f = 10 \text{ kHz}$	0.0052%	0.0052%	0.0052%			
B_1	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 100 \text{ pF}$	5.9	5.9	5.9			MHz
	Gain-bandwidth product	$R_L = 2 \text{ k}\Omega^\dagger$, $f = 100 \text{ kHz}$	5.8	5.8	5.8			MHz
B_{OM}	Maximum output-swing bandwidth	$V_O(PP) = 2 \text{ V}$, $A_{VD} = 1$	660	660	660			kHz
ϕ_m	Phase margin	$R_L = 2 \text{ k}\Omega^\dagger$, $C_L = 100 \text{ pF}$	57°	57°	57°			

† R_L terminates at 2.5 V



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**
SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144M electrical characteristics at specified free-air temperature, $V_{CC\pm} = \pm 15$ V (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T_A^\dagger	TLE2144M			TLE2144AM			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	$V_{IC} = 0$, $R_S = 50\Omega$	25°C	0.6	2.4		0.5	1.5		mV
		Full range		4			3.2		
		Full range		1.7			1.7		$\mu\text{V}/^\circ\text{C}$
		25°C	7	100		7	100		nA
		Full range		250			250		
		25°C	-0.7	-1.5		-0.7	-1.5		μA
I_{IB}		Full range		-1.8			-1.8		
V_{ICR}	$R_S = 50\Omega$	25°C	-15 to 13	-15.3 to 13.2		-15 to 13	-15.3 to 13.2		V
		Full range	-15 to 12.7	-15.3 to 12.9		-15 to 12.7	-15.3 to 12.9		
		25°C	13.8	14.1		13.8	14.1		V
		25°C	13.7	14		13.7	14		
		25°C	13.1	13.7		13.1	13.7		
V_{OM+}	Maximum positive peak output voltage swing	25°C	13.7			13.7			V
		Full range	13.6			13.6			
		Full range	13.1			13.1			
		25°C	-14.7	-14.9		-14.7	-14.9		V
		25°C	-14.5	-14.8		-14.5	-14.8		
		25°C	-13.4	-13.8		-13.4	-13.8		
V_{OM-}	Maximum negative peak output voltage swing	25°C	-14.6			-14.6			V
		Full range	-14.5			-14.5			
		Full range	-13.4			-13.4			
		25°C	100	170		100	170		V/mV
		Full range	20			20			
		25°C	65			65			$\text{M}\Omega$
c_i	Input capacitance	25°C	2.5			2.5			pF
z_o	Open-loop output impedance	25°C	30			30			Ω
CMRR	Common-mode rejection ratio	25°C	85	108		85	108		dB
		Full range	80			80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm} / \Delta V_{IO}$)	25°C	90	106		90	106		dB
		Full range	85			85			
I_{OS}	Short-circuit output current	$V_O = 0$	$V_{ID} = 1\text{ V}$	25°C	-25	-50	-25	-50	mA
				25°C	20	31	20	31	
I_{CC}	Supply current	$V_O = 0$, $V_{IC} = 2.5\text{ V}$	No load,	25°C	13.8	18	13.8	18	mA
				Full range		18.8		18.8	

[†] Full range is -55°C to 125°C



**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144M operating characteristics, $V_{CC\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2144M			TLE2144AM			UNIT
		MIN	TYP	MAX	MIN	TYP	MAX	
SR+	Positive slew rate	$R_L = 2 \text{ k}\Omega$, $A_{VD} = -1$, $C_L = 100 \text{ pF}$	27	45	27	45	27	$\text{V}/\mu\text{s}$
SR-	Negative slew rate		27	42	27	42	27	
t_s	Settling time	$A_{VD} = -1$,	To 0.1%	0.34	0.34	0.34	0.34	μs
		10-V step	To 0.01%	.4	.4	.4	.4	
V_n	Equivalent input noise voltage	$R_S = 20 \Omega$,	$f = 10 \text{ Hz}$	15	15	15	15	$\text{nV}/\sqrt{\text{Hz}}$
		$R_S = 20 \Omega$,	$f = 1 \text{ kHz}$	10.5	10.5	10.5	10.5	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	$f = 0.1 \text{ Hz to } 1 \text{ Hz}$		0.48	0.48	0.48	0.48	μV
		$f = 0.1 \text{ Hz to } 10 \text{ Hz}$		0.51	0.51	0.51	0.51	
I_n	Equivalent input noise current	$f = 10 \text{ Hz}$		1.89	1.89	1.89	1.89	$\text{pA}/\sqrt{\text{Hz}}$
		$f = 10 \text{ kHz}$		0.47	0.47	0.47	0.47	
THD + N	Total harmonic distortion plus noise	$V_{O(PP)} = 20 \text{ V}$, $A_{VD} = 10$,	$R_L = 2 \text{ k}\Omega$, $f = 10 \text{ kHz}$	0.01%	0.01%	0.01%	0.01%	
B ₁	Unity-gain bandwidth	$R_L = 2 \text{ k}\Omega$,	$C_L = 100 \text{ pF}$	6	6	6	6	MHz
	Gain-bandwidth product	$R_L = 2 \text{ k}\Omega$,	$C_L = 100 \text{ pF}$,	5.9	5.9	5.9	5.9	MHz
B _{OM}	Maximum output-swing bandwidth	$V_{O(PP)} = 20 \text{ V}$, $A_{VD} = 1$,	$R_L = 2 \text{ k}\Omega$, $C_L = 100 \text{ pF}$	668	668	668	668	kHz
ϕ_m	Phase margin at unity gain	$R_L = 2 \text{ k}\Omega$,	$C_L = 100 \text{ pF}$	58°	58°	58°	58°	

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2141Y electrical characteristics at specified free-air temperature, $V_{CC\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	TLE2141Y			UNIT
		MIN	TYP	MAX	
V_{IO}	$V_{IC} = 0$, $V_O = 0$	$R_S = 50 \Omega$	200	1000	μV
I_{IO}			7	100	nA
I_{IB}			-0.7	-1.5	μA
V_{ICR}	$R_S = 50 \Omega$		-15	-15.3	V
			to 13	to 13.2	
V_{OM+}		$I_O = -150 \mu\text{A}$	13.8	14.1	V
		$I_O = -1.5 \text{ mA}$	13.7	14	
		$I_O = -15 \text{ mA}$	13.3	13.7	
V_{OM-}		$I_O = 150 \mu\text{A}$	-14.7	-14.9	V
		$I_O = 1.5 \text{ mA}$	-14.5	-14.8	
		$I_O = 15 \text{ mA}$	-13.4	-13.8	
A_{VD}	$V_O = \pm 10 \text{ V}$, $R_L = 2 \text{ k}\Omega$		100	450	V/mV
r_i				65	
c_i				2.5	pF
z_o			f = 1 MHz	30	
$CMRR$	$V_{IC} = V_{ICR\min}$, $R_S = 50 \Omega$		80	108	dB
k_{SVR}			$V_{CC\pm} = \pm 2.5 \text{ V}$ to $\pm 15 \text{ V}$, $R_S = 50 \Omega$	85	
I_{OS}	$V_O = 0$	$V_{ID} = 1 \text{ V}$	-25	-50	mA
		$V_{ID} = -1 \text{ V}$	20	31	
I_{CC}	$V_O = 0$, No load		3.5	4.5	mA

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2142Y electrical characteristics at specified free-air temperature, $V_{CC\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TLE2142Y			UNIT
		MIN	TYP	MAX	
V_{IO}	$V_{IC} = 0$, $V_O = 0$	$R_S = 50 \Omega$,	150	875	μV
I_{IO}			7	100	nA
I_{IB}			-0.7	-1.5	μA
V_{ICR}	$R_S = 50 \Omega$	-15 to 13	-15.3 to 13.2	V	
V_{OM+}					
V_{OM-}	$I_O = -150 \mu\text{A}$	13.8	14.1		V
	$I_O = -1.5 \text{ mA}$	13.7	14		
	$I_O = -15 \text{ mA}$	13.3	13.7		
AVD	$I_O = 150 \mu\text{A}$	-14.7	-14.9		V
	$I_O = 1.5 \text{ mA}$	-14.5	-14.8		
	$I_O = 15 \text{ mA}$	-13.4	-13.8		
r_i	$V_O = \pm 10 \text{ V}$, $R_L = 2 \text{ k}\Omega$	100	450	V/mV	
c_i					
z_0	$f = 1 \text{ MHz}$	30	Ω		
$CMRR$					
k_{SVR}	$V_{CC\pm} = \pm 2.5 \text{ V to } \pm 15 \text{ V}$, $R_S = 50 \Omega$	80	108	dB	
I_{OS}					
I_{CC}	$V_O = 0$, No load	-25 20	-50 31	mA	

TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TLE2144Y electrical characteristics at $V_{CC\pm} = \pm 15$ V, $T_A = 25^\circ\text{C}$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	TLE2144Y			UNIT	
		MIN	TYP	MAX		
V_{IO}	$V_{IC} = 0$, $V_O = 0$ $R_S = 50 \Omega$,		0.3	1.8	mV	
I_{IO}			7	100	nA	
I_{IB}			-0.7	-1.5	μA	
V_{ICR}	$R_S = 50 \Omega$		-15 to 13	-15.3 to 13.2	V	
V_{OM+}		$I_O = -150 \mu\text{A}$	13.8	14.1		
V_{OM-}	$I_O = -1.5 \text{ mA}$		13.7	14	V	
	$I_O = -15 \text{ mA}$		13.3	13.7		
	$I_O = 150 \mu\text{A}$		-14.7	-14.9		
A_{VD}	$I_O = 1.5 \text{ mA}$		-14.5	-14.8	V	
	$I_O = 15 \text{ mA}$		-13.4	-13.8		
	$V_O = \pm 10 \text{ V}$, $R_L = 2 \text{ k}\Omega$		100	450		
r_i				65	$\text{M}\Omega$	
c_i				2.5	pF	
z_o	$f = 1 \text{ MHz}$			30	Ω	
CMRR	$V_{IC} = V_{ICR\min}$, $R_S = 50 \Omega$		80	108	dB	
k_{SVR}	$V_{CC\pm} = \pm 2.5 \text{ V to } \pm 15 \text{ V}$, $R_S = 50 \Omega$		85	106	dB	
I_{OS}	$V_O = 0$	$V_{ID} = 1 \text{ V}$	-25	-50	mA	
		$V_{ID} = -1 \text{ V}$	20	31		
I_{CC}	$V_O = 0$, No load			13.8	18	mA



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TYPICAL CHARACTERISTICS

Table of Graphs

			FIGURE
V _{IO}	Input offset voltage	Distribution	1, 2, 3
I _{IO}	Input offset current	vs Free-air temperature	4
I _{IB}	Input bias current	vs Common-mode input voltage vs Free-air temperature	5 6
V _{OM+}	Maximum positive peak output voltage	vs Supply voltage vs Free-air temperature vs Output current vs Settling time	7 8 9 11
V _{OM-}	Maximum negative peak output voltage	vs Supply voltage vs Free-air temperature vs Output current vs Settling time	7 8 10 11
V _{O(PP)}	Maximum peak-to-peak output voltage	vs Frequency	12
V _{OH}	High-level output voltage	vs Output current	13
V _{OL}	Low-level output voltage	vs Output current	14
A _{VD}	Large-signal differential voltage amplification	vs Frequency vs Free-air temperature	15 16
z _o	Closed-loop output impedance	vs Frequency	17
I _{OS}	Short-circuit output current	vs Free-air temperature	18
CMRR	Common-mode rejection ratio	vs Frequency vs Free-air temperature	19 20
k _{SVR}	Supply-voltage rejection ratio	vs Frequency vs Free-air temperature	21 22
I _{CC}	Supply current	vs Supply voltage vs Free-air temperature	23 24
V _n	Equivalent input noise voltage	vs Frequency	25
V _n	Input noise voltage	Over a 10-second period	26
I _n	Noise current	vs Frequency	27
THD + N	Total harmonic distortion plus noise	vs Frequency	28
SR	Slew rate	vs Free-air temperature vs Load capacitance	29 30
Pulse response	Noninverting large signal	vs Time	31
	Inverting large signal	vs Time	32
	Small signal	vs Time	33
B ₁	Unity-gain bandwidth	vs Load capacitance	34
	Gain margin	vs Load capacitance	35
φ _m	Phase margin	vs Load capacitance	36
	Phase shift	vs Frequency	15

TYPICAL CHARACTERISTICS

TLE2141
DISTRIBUTION OF
INPUT OFFSET VOLTAGE




Figure 1

TLE2142
DISTRIBUTION OF
INPUT OFFSET VOLTAGE




Figure 2

TLE2144
DISTRIBUTION OF
INPUT OFFSET VOLTAGE




Figure 3

**INPUT OFFSET CURRENT[†]
vs
FREE-AIR TEMPERATURE**




Figure 4

[†] Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TLE214x, TLE214xA, TLE214xY EXCALIBUR LOW-NOISE HIGH-SPEED PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TYPICAL CHARACTERISTICS




Figure 5




Figure 6




Figure 7




Figure 8

[†] Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS




Figure 9




Figure 10




Figure 11




Figure 12

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TLE214x, TLE214xA, TLE214xY EXCALIBUR LOW-NOISE HIGH-SPEED PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TYPICAL CHARACTERISTICS

HIGH-LEVEL OUTPUT VOLTAGE†
vs
OUTPUT CURRENT




Figure 13

LOW-LEVEL OUTPUT VOLTAGE†
vs
OUTPUT CURRENT




Figure 14

LARGE-SIGNAL DIFFERENTIAL VOLTAGE
AMPLIFICATION AND PHASE SHIFT
vs
FREQUENCY




Figure 15

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS




Figure 16




Figure 17




Figure 18

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TLE214x, TLE214xA, TLE214xY EXCALIBUR LOW-NOISE HIGH-SPEED PRECISION OPERATIONAL AMPLIFIERS

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TYPICAL CHARACTERISTICS




Figure 19




Figure 20




Figure 21




Figure 22

[†] Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS




Figure 23




Figure 24




Figure 25




Figure 26

[†] Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TYPICAL CHARACTERISTICS




Figure 27




Figure 28




Figure 29




Figure 30

[†] Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS




Figure 31




Figure 32




Figure 33




Figure 34

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

TYPICAL CHARACTERISTICS




Figure 35




Figure 36

[†] Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

APPLICATION INFORMATION

input offset voltage nulling

The TLE2141 series offers external null pins that can be used to further reduce the input offset voltage. If this feature is desired, connect the circuit of Figure 37 as shown. If external nulling is not needed, the null pins may be left unconnected.




Figure 37. Input Offset Voltage Null Circuit

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**


SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

MECHANICAL INFORMATION

D (R-PDSO-G)**

14 PIN SHOWN

PLASTIC SMALL-OUTLINE PACKAGE




- NOTES: A. All linear dimensions are in inches (millimeters).
 B. This drawing is subject to change without notice.
 C. Body dimensions do not include mold flash or protrusion, not to exceed 0.006 (0.15).
 D. Falls within JEDEC MS-012

MECHANICAL INFORMATION

DW (R-PDSO-G**)

PLASTIC SMALL-OUTLINE PACKAGE

16 PIN SHOWN



- NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
D. Falls within JEDEC MS-013

**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**


SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

MECHANICAL INFORMATION

FK (S-CQCC-N)**

28 TERMINAL SHOWN

LEADLESS CERAMIC CHIP CARRIER



4040140/D 10/96


- NOTES: A. All linear dimensions are in inches (millimeters).
 B. This drawing is subject to change without notice.
 C. This package can be hermetically sealed with a metal lid.
 D. The terminals are gold plated.
 E. Falls within JEDEC MS-004

MECHANICAL INFORMATION


J (R-GDIP-T**)

CERAMIC DUAL-IN-LINE PACKAGE

14 PIN SHOWN



PINS ** DIM	14	16	18	20
A MAX	0.310 (7,87)	0.310 (7,87)	0.310 (7,87)	0.310 (7,87)
A MIN	0.290 (7,37)	0.290 (7,37)	0.290 (7,37)	0.290 (7,37)
B MAX	0.785 (19,94)	0.785 (19,94)	0.910 (23,10)	0.975 (24,77)
B MIN	0.755 (19,18)	0.755 (19,18)	—	0.930 (23,62)
C MAX	0.280 (7,11)	0.300 (7,62)	0.300 (7,62)	0.300 (7,62)
C MIN	0.245 (6,22)	0.245 (6,22)	0.245 (6,22)	0.245 (6,22)



4040083/C 08/96

- NOTES:
- A. All linear dimensions are in inches (millimeters).
 - B. This drawing is subject to change without notice.
 - C. This package can be hermetically sealed with a ceramic lid using glass frit.
 - D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
 - E. Falls within MIL-STD-1835 GDIP1-T14, GDIP1-T16, GDIP1-T18, and GDIP1-T20


**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

MECHANICAL INFORMATION

JG (R-GDIP-T8)

CERAMIC DUAL-IN-LINE PACKAGE




- NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
E. Falls within MIL-STD-1835 GDIP1-T8

MECHANICAL INFORMATION

N (R-PDIP-T**)

16 PIN SHOWN

PLASTIC DUAL-IN-LINE PACKAGE



- NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS-001 (20 pin package is shorter than MS-001.)


**TLE214x, TLE214xA, TLE214xY
EXCALIBUR LOW-NOISE HIGH-SPEED
PRECISION OPERATIONAL AMPLIFIERS**

SLOS183A – FEBRUARY 1997 – REVISED MARCH 1998

MECHANICAL INFORMATION

P (R-PDIP-T8)

PLASTIC DUAL-IN-LINE PACKAGE




- NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS-001

MECHANICAL INFORMATION

PW (R-PDSO-G**)

PLASTIC SMALL-OUTLINE PACKAGE

14 PIN SHOWN



- NOTES: A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.
D. Falls within JEDEC MO-153

IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.

Copyright © 1999, Texas Instruments Incorporated