

TPS2320, TPS2321 DUAL HOT SWAP POWER CONTROLLERS WITH INDEPENDENT CIRCUIT BREAKER

SLVS276C – MARCH 2000 – REVISED MARCH 2001

features

- Dual-Channel High-Side MOSFET Drivers
- IN1: 3 V to 13 V; IN2: 3 V to 5.5 V
- Inrush Current Limiting With dv/dt Control
- Independent Circuit-Breaker Control With Programmable Current Limit and Transient Timer
- CMOS- and TTL-Compatible Enable Input
- Low, 5- μ A Standby Supply Current . . . Max
- Available in 16-Pin SOIC and TSSOP Package
- -40°C to 85°C Ambient Temperature Range
- Electrostatic Discharge Protection

applications


- Hot-Swap/Plug/Dock Power Management
- Hot-Plug PCI, Device Bay
- Electronic Circuit Breaker

description

The TPS2320 and TPS2321 are dual-channel hot-swap controllers that use external N-channel MOSFETs as high-side switches in power applications. Features of these devices, such as overcurrent protection (OCP), inrush-current control, and separation of load transients from actual load increases, are critical requirements for hot-swap applications.


The TPS2320/21 devices incorporate undervoltage lockout (UVLO) to ensure the device is off at startup. Each internal charge pump, capable of driving multiple MOSFETs, provides enough gate-drive voltage to fully enhance the N-channel MOSFETs. The charge pumps control both the rise times and fall times (dv/dt) of the MOSFETs, reducing power transients during power up/down. The circuit-breaker functionality combines the ability to sense overcurrent conditions with a timer function; this allows designs such as DSPs, that may have high peak currents during power-state transitions, to disregard transients for a programmable period.

D OR PW PACKAGE
(TOP VIEW)



NOTE: Terminal 14 is active high on TPS2321.

typical application



AVAILABLE OPTIONS

T _A	HOT-SWAP CONTROLLER DESCRIPTION	PIN COUNT	PACKAGES	
			ENABLE	ENABLE
-40°C to 85°C	Dual-channel with independent OCP and adjustable PG	20	TPS2300IPW	TPS2301IPW
	Dual-channel with interdependent OCP and adjustable PG	20	TPS2310IPW	TPS2311IPW
	Dual-channel with independent OCP	16	TPS2320ID TPS2320IPW	TPS2321ID TPS2321IPW
	Single-channel with OCP and adjustable PG	14	TPS2330ID TPS2330IPW	TPS2331ID TPS2331IPW

† The packages are available left-end taped and reeled (indicated by the R suffix on the device type; e.g., TPS2321IPWR).



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS
INSTRUMENTS**


POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 2001, Texas Instruments Incorporated

TPS2320, TPS2321 DUAL HOT SWAP POWER CONTROLLERS WITH INDEPENDENT CIRCUIT BREAKER

SLVS276C – MARCH 2000 – REVISED MARCH 2001

functional block diagram



Terminal Functions

TERMINAL NAME	NO.	I/O	DESCRIPTION
AGND	6	I	Analog ground, connects to DGND as close as possible
DGND	3	I	Digital ground
DISCH1	16	O	Discharge transistor 1
DISCH2	15	O	Discharge transistor 2
ENABLE/ ENAB \bar{L}	14	I	Active low (TPS2320) or active high enable (TPS2321)
FAULT	13	O	Overcurrent fault, open-drain output
GATE1	1	O	Connects to gate of channel 1 high-side MOSFET
GATE2	2	O	Connects to gate of channel 2 high-side MOSFET
IN1	9	I	Input voltage for channel 1
IN2	10	I	Input voltage for channel 2
ISENSE1	8	I	Current-sense input channel 1
ISENSE2	7	I	Current-sense input channel 2
ISET1	12	I	Adjusts circuit-breaker threshold with resistor connected to IN1
ISET2	11	I	Adjusts circuit-breaker threshold with resistor connected to IN2
TIMER	4	O	Adjusts circuit-breaker deglitch time
VREG	5	O	Connects to bypass capacitor, for stable operation

detailed description

DISCH1, DISCH2 – DISCH1 and DISCH2 should be connected to the sources of the external N-channel MOSFET transistors connected to GATE1 and GATE2, respectively. These pins discharge the loads when the MOSFET transistors are disabled. They also serve as reference-voltage connections for internal gate voltage-clamp circuitry.

ENABLE or ENABLER – $\overline{\text{ENABLE}}$ for TPS2320 is active low. ENABLE for TPS2321 is active high. When the controller is enabled, both GATE1 and GATE2 voltages will power up to turn on the external MOSFETs. When the $\overline{\text{ENABLE}}$ pin is pulled high for TPS2320 or the ENABLE pin is pulled low for TPS2321 for more than 50 μs , the gate of the MOSFET is discharged at a controlled rate by a current source, and a transistor is enabled to discharge the output bulk capacitance. In addition, the device turns on the internal regulator PREREG (see VREG) when enabled and shuts down PREREG when disabled so that total supply current is much less than 5 μA .

FAULT – FAULT is an open-drain overcurrent flag output. When an overcurrent condition in either channel is sustained long enough to charge TIMER to 0.5 V, the overcurrent channel latches off and pulls FAULT low. The other channel will run normally if not in overcurrent. In order to turn the channel back on, either the enable pin has to be toggled or the input power has to be cycled.

GATE1, GATE2 – GATE1 and GATE2 connect to the gates of external N-channel MOSFET transistors. When the device is enabled, internal charge-pump circuitry pulls these pins up by sourcing approximately 15 μA to each. The turnon slew rates depend upon the capacitance present at the GATE1 and GATE2 terminals. If desired, the turnon slew rates can be further reduced by connecting capacitors between these pins and ground. These capacitors also reduce inrush current and protect the device from false overcurrent triggering during powerup. The charge-pump circuitry will generate gate-to-source voltages of 9 V–12 V across the external MOSFET transistors.

IN1, IN2 – IN1 and IN2 should be connected to the power sources driving the external N-channel MOSFET transistors connected to GATE1 and GATE2, respectively. The TPS2320/TPS2321 draws its operating current from IN1, and both channels will remain disabled until the IN1 power supply has been established. The IN1 channel has been constructed to support 3-V, 5-V, or 12-V operation, while the IN2 channel has been constructed to support 3-V or 5-V operation.

ISENSE1, ISENSE2, ISET1, ISET2 – ISENSE1 and ISENSE2, in combination with ISET1 and ISET2, implement overcurrent sensing for GATE1 and GATE2. ISET1 and ISET2 set the magnitude of the current that generates an overcurrent fault, through external resistors connected to ISET1 and ISET2. An internal current source draws 50 μA from ISET1 and ISET2. With a sense resistor from IN1 to ISENSE1 or from IN2 to ISENSE2, which is also connected to the drains of external MOSFETs, the voltage on the sense resistor reflects the load current. An overcurrent condition is assumed to exist if ISENSE1 is pulled below ISET1 or if ISENSE2 is pulled below ISET2.

TIMER – A capacitor on TIMER sets the time during which the power switch can be in overcurrent before turning off. When the overcurrent protection circuits sense an excessive current, a current source is enabled which charges the capacitor on TIMER. Once the voltage on TIMER reaches approximately 0.5 V, the circuit-breaker latch is set and the power switch is latched off. Power must be recycled or the ENABLE pin must be toggled to restart the controller. In high-power or high-temperature applications, a minimum 50-pF capacitor is strongly recommended from TIMER to ground, to prevent any false triggering.

TPS2320, TPS2321
DUAL HOT SWAP POWER CONTROLLERS
WITH INDEPENDENT CIRCUIT BREAKER

SLVS276C – MARCH 2000 – REVISED MARCH 2001

detailed description (continued)

VREG – VREG is the output of an internal low-dropout voltage regulator, where IN1 is the input. The regulator is used to generate a regulated voltage source, less than 5.5 V, for the device. A 0.1- μ F ceramic capacitor should be connected between VREG and ground to aid in noise rejection. In this configuration, upon disabling the device, the internal low-dropout regulator will also be disabled, which removes power from the internal circuitry and allows the device to be placed in low-quiescent-current mode. In applications where IN1 is less than 5.5 V, VREG and IN1 may be connected together. However, under these conditions, disabling the device will not place the device in low-quiescent-current mode, because the internal low-dropout voltage regulator is being bypassed, thereby keeping internal circuitry operational. If VREG and IN1 are connected together, a 0.1- μ F ceramic capacitor between VREG and ground is not needed if IN1 already has a bypass capacitor of 1 μ F to 10 μ F.

absolute maximum ratings over operating free-air temperature (unless otherwise noted)†

Input voltage range:	$V_I(IN1), V_I(ISENSE1), V_I(ISET1), V_I(ENABLE)$	-0.3 V to 15 V
	$V_I(IN2), V_I(ISENSE2), V_I(ISET2), V_I(VREG)$	-0.3 V to 7 V
Output voltage range:	$V_O(GATE1)$	-0.3 V to 30 V
	$V_O(GATE2)$	-0.3 V to 22V
	$V_O(DISCH1), V_O(FAULT), V_O(DISCH2), V_O(TIMER)$	-0.3 V to 15V
Sink current range:	$I_{GATE1}, I_{GATE2}, I_{DISCH1}, I_{DISCH2}$	0 mA to 100 mA
	I_{TIMER}, I_{FAULT}	0 mA to 10 mA
Operating virtual junction temperature range, T_J		-40°C to 100°C
Storage temperature range, T_{stg}		-55°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds		260°C

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: All voltages are respect to DGND.

DISSIPATION RATING TABLE

PACKAGE	$T_A \leq 25^\circ\text{C}$	DERATING FACTOR	$T_A = 70^\circ\text{C}$	$T_A = 85^\circ\text{C}$
	POWER RATING	ABOVE $T_A = 25^\circ\text{C}$	POWER RATING	POWER RATING
PW-16	823 mW	10.98 mW/°C	329 mW	165 mW
D-16	674 mW	8.98 mW/°C	270 mW	135 mW

recommended operating conditions

		MIN	NOM	MAX	UNIT
Input voltage, V_I	$V_I(IN1), V_I(ISENSE1), V_I(ISET1)$	3		13	V
	$V_I(IN2), V_I(ISENSE2), V_I(ISET2), V_I(VREG)$	3		5.5	
Operating virtual junction temperature, T_J		-40		100	°C



TPS2320, TPS2321
DUAL HOT SWAP POWER CONTROLLERS
WITH INDEPENDENT CIRCUIT BREAKER

SLVS276C – MARCH 2000 – REVISED MARCH 2001

**electrical characteristics over recommended operating temperature range ($-40^{\circ}\text{C} < T_A < 85^{\circ}\text{C}$),
 $3\text{ V} \leq V_{I(IN1)} \leq 13\text{ V}$, $3\text{ V} \leq V_{I(IN2)} \leq 5.5\text{ V}$ (unless otherwise noted)**

general

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$I_{I(IN1)}$	Input current, IN1	$V_{I(ENABLE)} = 5\text{ V}$ (TPS2321),		0.5	1	mA
$I_{I(IN2)}$	Input current, IN2	$V_{I(ENABLE)} = 0\text{ V}$ (TPS2320)		75	200	μA
$I_{I(stby)}$	Standby current (sum of currents into IN1, IN2, ISENSE1, ISENSE2, ISET1, and ISET2)	$V_{I(ENABLE)} = 0\text{ V}$ (TPS2321), $V_{I(ENABLE)} = 5\text{ V}$ (TPS2320)			5	μA

GATE1

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
$V_{G(GATE1_3V)}$	Gate voltage	$I_{I(GATE1)} = 500\text{ nA}$, DISCH1 open	$V_{I(IN1)} = 3\text{ V}$	9	11.5		V
$V_{G(GATE1_4.5V)}$			$V_{I(IN1)} = 4.5\text{ V}$	10.5	14.5		
$V_{G(GATE1_10.8V)}$			$V_{I(IN1)} = 10.8\text{ V}$	16.8	21		
$V_{C(GATE1)}$	Clamping voltage, GATE1 to DISCH1			9	10	12	V
$I_{S(GATE1)}$	Source current, GATE1	$3\text{ V} \leq V_{I(IN1)} \leq 13.2\text{ V}$, $3\text{ V} \leq V_{O(VREG)} \leq 5.5\text{ V}$, $V_{I(GATE1)} = V_{I(IN1)} + 6\text{ V}$		10	14	20	μA
	Sink current, GATE1	$3\text{ V} \leq V_{I(IN1)} \leq 13.2\text{ V}$, $3\text{ V} \leq V_{O(VREG)} \leq 5.5\text{ V}$, $V_{I(GATE1)} = V_{I(IN1)}$		50	75	100	μA
$t_r(GATE1)$	Rise time, GATE1	C_g to GND = 1 nF (see Note 2)	$V_{I(IN1)} = 3\text{ V}$		0.5		ms
			$V_{I(IN1)} = 4.5\text{ V}$		0.6		
			$V_{I(IN1)} = 10.8\text{ V}$		1		
$t_f(GATE1)$	Fall time, GATE1	C_g to GND = 1 nF (see Note 2)	$V_{I(IN1)} = 3\text{ V}$		0.1		ms
			$V_{I(IN1)} = 4.5\text{ V}$		0.12		
			$V_{I(IN1)} = 10.8\text{ V}$		0.2		

GATE2

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
$V_{G(GATE2_3V)}$	Gate voltage	$I_{I(GATE2)} = 500\text{ nA}$, DISCH2 open	$V_{I(IN2)} = 3\text{ V}$	9	11.7		V
$V_{G(GATE2_4.5V)}$			$V_{I(IN2)} = 4.5\text{ V}$	10.5	14.7		
$V_{C(GATE2)}$	Clamping voltage, GATE2 to DISCH2			9	10	12	V
$I_{S(GATE2)}$	Source current, GATE2	$3\text{ V} \leq V_{I(IN2)} \leq 5.5\text{ V}$, $3\text{ V} \leq V_{O(VREG)} \leq 5.5\text{ V}$, $V_{I(GATE2)} = V_{I(IN2)} + 6\text{ V}$		10	14	20	μA
	Sink current, GATE2	$3\text{ V} \leq V_{I(IN2)} \leq 5.5\text{ V}$, $3\text{ V} \leq V_{O(VREG)} \leq 5.5\text{ V}$, $V_{I(GATE2)} = V_{I(IN2)}$		50	75	100	μA
$t_r(GATE2)$	Rise time, GATE2	C_g to GND = 1 nF (see Note 2)	$V_{I(IN2)} = 3\text{ V}$		0.5		ms
			$V_{I(IN2)} = 4.5\text{ V}$		0.6		
$t_f(GATE2)$	Fall time, GATE2	C_g to GND = 1 nF (see Note 2)	$V_{I(IN2)} = 3\text{ V}$		0.1		ms
			$V_{I(IN2)} = 4.5\text{ V}$		0.12		

NOTE 2: Specified, but not production tested.



TPS2320, TPS2321 DUAL HOT SWAP POWER CONTROLLERS WITH INDEPENDENT CIRCUIT BREAKER

SLVS276C – MARCH 2000 – REVISED MARCH 2001

electrical characteristics over recommended operating temperature range ($-40^{\circ}\text{C} < T_A < 85^{\circ}\text{C}$),
 $3\text{ V} \leq V_{I(IN1)} \leq 13\text{ V}$, $3\text{ V} \leq V_{I(IN2)} \leq 5.5\text{ V}$ (unless otherwise noted) (continued)

TIMER

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{OT(TIMER)}$ Threshold voltage, TIMER		0.4	0.5	0.6	V
Charge current, TIMER	$V_{I(TIMER)} = 0\text{ V}$	35	50	65	μA
Discharge current, TIMER	$V_{I(TIMER)} = 1\text{ V}$	1	2.5		mA

circuit breaker

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{IT(CB)}$ Undervoltage voltage, circuit breaker	$R_{ISETx} = 1\text{ k}\Omega$	40	50	60	mV
$I_{IB(ISENSEx)}$ Input bias current, I_{SENSEx}			0.1	5	μA
Discharge current, $GATEx$	$V_{O(GATEx)} = 4\text{ V}$	400	800		mA
	$V_{O(GATEx)} = 1\text{ V}$	25	150		
$t_{pd(CB)}$ Propagation (delay) time, comparator inputs to gate output	$C_g = 50\text{ pF}$, 10 mV overdrive, (50% to 10%) $C_{TIMER} = 50\text{ pF}$		1.3		μs

ENABLE, active low (TPS2320)

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{IH(ENABLE)}$ High-level input voltage, \overline{ENABLE}		2			V
$V_{IL(ENABLE)}$ Low-level input voltage, \overline{ENABLE}				0.8	V
$R_{I(ENABLE)}$ Input pullup resistance, \overline{ENABLE}	See Note 3	100	200	300	$\text{k}\Omega$
$t_{d_off(ENABLE)}$ Turnoff delay time, \overline{ENABLE}	$V_{I(ENABLE)}$ increasing above stop threshold; 100 ns rise time, 20 mV overdrive (see Note 2)		60		μs
$t_{d_on(ENABLE)}$ Turnon delay time, \overline{ENABLE}	$V_{I(ENABLE)}$ decreasing below start threshold; 100 ns fall time, 20 mV overdrive (see Note 2)		125		μs

NOTES: 2. Specified, but not production tested.

3. Test I_O of \overline{ENABLE} at $V_{I(ENABLE)} = 1\text{ V}$ and 0 V , then $R_{I(ENABLE)} = \frac{1\text{ V}}{I_{O_0V} - I_{O_1V}}$

ENABLE, active high (TPS2321)

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{IH(ENABLE)}$ High-level input voltage, $ENABLE$		2			V
$V_{IL(ENABLE)}$ Low-level input voltage, $ENABLE$				0.7	V
$R_{I(ENABLE)}$ Input pulldown resistance, $ENABLE$		100	150	300	$\text{k}\Omega$
$t_{d_on(ENABLE)}$ Turnon delay time, $ENABLE$	$V_{I(ENABLE)}$ increasing above start threshold; 100 ns rise time, 20 mV overdrive (see Note 2)		85		μs
$t_{d_off(ENABLE)}$ Turnoff delay time, $ENABLE$	$V_{I(ENABLE)}$ decreasing below stop threshold; 100 ns fall time, 20 mV overdrive (see Note 2)		100		μs

NOTE 2: Specified, but not production tested.

PREREG

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{REG} PREREG output voltage	$4.5 \leq V_{I(IN1)} \leq 13\text{ V}$	3.5	4.1	5.5	V
V_{drop_PREREG} PREREG dropout voltage	$V_{I(IN1)} = 3\text{ V}$			0.1	V



TPS2320, TPS2321
DUAL HOT SWAP POWER CONTROLLERS
WITH INDEPENDENT CIRCUIT BREAKER

SLVS276C – MARCH 2000 – REVISED MARCH 2001

electrical characteristics over recommended operating temperature range ($-40^{\circ}\text{C} < T_A < 85^{\circ}\text{C}$),
 $3\text{ V} \leq V_{I(IN1)} \leq 13\text{ V}$, $3\text{ V} \leq V_{I(IN2)} \leq 5.5\text{ V}$ (unless otherwise noted) (continued)

VREG UVLO

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{OT(UVLOstart)}$	Output threshold voltage, start		2.75	2.85	2.95	V
$V_{OT(UVLOstop)}$	Output threshold voltage, stop		2.65	2.78		V
$V_{hys(UVLO)}$	Hysteresis		50	75		mV
	UVLO sink current, GATEx	$V_{I(GATEx)} = 2\text{ V}$	10			mA

FAULT output

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{O(sat)(FAULT)}$	Output saturation voltage, FAULT	$I_O = 2\text{ mA}$			0.4	V
$I_{kg(FAULT)}$	Leakage current, FAULT	$V_{O(FAULT)} = 13\text{ V}$			1	μA

DISCH1 and DISCH2

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
I_{DISCH}	Discharge current, DISCHx	$V_{I(DISCHx)} = 1.5\text{ V}$, $V_{I(VIN1)} = 5\text{ V}$	5	10		mA
$V_{IH(DISCH)}$	Discharge on high-level input voltage		2			V
$V_{IL(DISCH)}$	Discharge on low-level input voltage				1	V



**TPS2320, TPS2321
DUAL HOT SWAP POWER CONTROLLERS
WITH INDEPENDENT CIRCUIT BREAKER**

SLVS276C – MARCH 2000 – REVISED MARCH 2001

PARAMETER MEASUREMENT INFORMATION




Figure 1. Turnon Voltage Transition of Channel 1




Figure 2. Turnoff Voltage Transition of Channel 1




Figure 3. Turnon Voltage Transition of Channel 2




Figure 4. Turnoff Voltage Transition of Channel 2

PARAMETER MEASUREMENT INFORMATION




Figure 5. Channel 1 Overcurrent Response: Enabled Into Overcurrent Load




Figure 6. Channel 1 Overcurrent Response: an Overcurrent Load Plugged Into the Enabled Board




Figure 7. Channel 2 Overcurrent Response: Enabled Into Overcurrent Load




Figure 8. Channel 2 Overcurrent Response: an Overcurrent Load Plugged Into the Enabled Board

TPS2320, TPS2321
DUAL HOT SWAP POWER CONTROLLERS
WITH INDEPENDENT CIRCUIT BREAKER

SLVS276C – MARCH 2000 – REVISED MARCH 2001

PARAMETER MEASUREMENT INFORMATION




Figure 9. Channel 1 – Enabled Into Short Circuit




Figure 10. Channel 2 – Enabled Into Short Circuit




Figure 11. Channel 1 – Hot Plug




Figure 12. Channel 1 – Hot Removal

PARAMETER MEASUREMENT INFORMATION




Figure 13. Channel 2 – Hot Plug




Figure 14. Channel 2 – Hot Removal

TPS2320, TPS2321
DUAL HOT SWAP POWER CONTROLLERS
WITH INDEPENDENT CIRCUIT BREAKER

SLVS276C – MARCH 2000 – REVISED MARCH 2001

TYPICAL CHARACTERISTICS

SUPPLY CURRENT (ENABLED)
vs
VOLTAGE




Figure 15

SUPPLY CURRENT (ENABLED)
vs
VOLTAGE




Figure 16

SUPPLY CURRENT (DISABLED)
vs
VOLTAGE




Figure 17

SUPPLY CURRENT (DISABLED)
vs
VOLTAGE








Figure 18



TYPICAL CHARACTERISTICS



TPS2320, TPS2321
DUAL HOT SWAP POWER CONTROLLERS
WITH INDEPENDENT CIRCUIT BREAKER

SLVS276C – MARCH 2000 – REVISED MARCH 2001

TYPICAL CHARACTERISTICS

CIRCUIT-BREAKER RESPONSE
vs
TIMER CAPACITANCE




Figure 23

LOAD VOLTAGE 1 DISCHARGE TIME
vs
LOAD CAPACITANCE




Figure 24

UVLO START AND STOP THRESHOLDS
vs
TEMPERATURE




Figure 25



APPLICATION INFORMATION

typical application diagram

Figure 26 shows a typical dual hot-swap application. The pullup resistor at FAULT should be relatively large (e.g., 100 k Ω) to reduce power loss, unless it is required to drive a large load.




Figure 26. Typical Dual Hot-Swap Application

input capacitor

A 0.1- μF ceramic capacitor in parallel with a 1- μF ceramic capacitor should be placed on the input power terminals near the connector on the hot-plug board to help stabilize the voltage rails on the cards. The TPS2320/01 does not need to be mounted near the connector or to these input capacitors. For applications with more severe power environments, a 2.2- μF , or higher, ceramic capacitor is recommended near the input terminals of the hot-plug board. A bypass capacitor for IN1 and for IN2 should be placed close to the device.

output capacitor

A 0.1- μF ceramic capacitor is recommended per load on the TPS2320/21; these capacitors should be placed close to the external FETs and to TPS2320/21. A larger bulk capacitor is also recommended on the load. The value of the bulk capacitor should be selected based on the power requirements and the transients generated by the application.

external FET

To deliver power from the input sources to the loads, each channel needs an external N-channel MOSFET. A few widely used MOSFETs are shown in Table 1. But many other MOSFETs on the market can also be used with TPS23xx in hot-swap systems.

TPS2320, TPS2321
DUAL HOT SWAP POWER CONTROLLERS
WITH INDEPENDENT CIRCUIT BREAKER

SLVS276C – MARCH 2000 – REVISED MARCH 2001

APPLICATION INFORMATION

Table 1. Some Available N-Channel MOSFETs

CURRENT RANGE (A)	PART NUMBER	DESCRIPTION	MANUFACTURER
0 to 2	IRF7601	N-channel, $r_{DS(on)} = 0.035 \Omega$, 4.6 A, Micro-8	International Rectifier
	MTSF3N03HDR2	N-channel, $r_{DS(on)} = 0.040 \Omega$, 4.6 A, Micro-8	ON Semiconductor
	MMSF5N02HDR2	Dual N-channel, $r_{DS(on)} = 0.04 \Omega$, 5 A, SO-8	ON Semiconductor
2 to 5	IRF7401	N-channel, $r_{DS(on)} = 0.022 \Omega$, 7 A, SO-8	International Rectifier
	MMSF5N02HDR2	N-channel, $r_{DS(on)} = 0.025 \Omega$, 5 A, SO-8	ON Semiconductor
	IRF7313	Dual N-channel, $r_{DS(on)} = 0.029 \Omega$, 5.2 A, SO-8	International Rectifier
	SI4410	N-channel, $r_{DS(on)} = 0.020 \Omega$, 8 A, SO-8	Vishay Dale
5 to 10	IRLR3103	N-channel, $r_{DS(on)} = 0.019 \Omega$, 29 A, d-Pak	International Rectifier
	IRLR2703	N-channel, $r_{DS(on)} = 0.045 \Omega$, 14 A, d-Pak	International Rectifier

timer

For most applications, a minimum capacitance of 50 pF is recommended to prevent false triggering. A capacitor should be connected between TIMER and ground. The presence of an overcurrent condition on either channel of the TPS2320/TPS2321 causes a 50- μ A current source to begin charging this capacitor. If the overcurrent condition persists until the capacitor has been charged to approximately 0.5 V, the TPS2320/TPS2321 will latch off the offending channels and will pull the FAULT pin low. The timer capacitor can be made as large as desired to provide additional time delay before registering a fault condition. PWRGDx will not correctly report power conditions when the device is disabled. The time delay is approximately: $dt = C_{TIMER} \times 10,000$.

output-voltage slew-rate control

When enabled, the TPS2320/TPS2321 controllers supply the gates of each external MOSFET transistor with a current of approximately 15 μ A. The slew rate of the MOSFET source voltage is thus limited by the gate-to-drain capacitance C_{gd} of the external MOSFET capacitor to a value approximating:

$$\frac{dvs}{dt} = \frac{15 \mu A}{C_{gd}}$$

If a slower slew rate is desired, an additional capacitance can be connected between the gate of the external MOSFET and ground.

VREG capacitor

The internal voltage regulator connected to VREG requires an external capacitor to ensure stability. A 0.1- μ F or 0.22- μ F ceramic capacitor is recommended.



APPLICATION INFORMATION

gate-drive circuitry

The TPS2320/TPS2321 includes four separate features associated with each gate-drive terminal:

- A charging current of approximately 15 μA is applied to enable the external MOSFET transistor. This current is generated by an internal charge pump that can develop a gate-to-source potential (referenced to DISCH1 or DISCH2) of 9 V–12 V. DISCH1 and DISCH2 must be connected to the respective external MOSFET source terminals to ensure proper operation of this circuitry.
- A discharge current of approximately 75 μA is applied to disable the external MOSFET transistor. Once the transistor gate voltage has dropped below approximately 1.5 V, this current is disabled and the UVLO discharge driver is enabled instead. This feature allows the part to enter a low-current shutdown mode while ensuring that the gates of the external MOSFET transistors remain at a low voltage.
- During a UVLO condition, the gates of both MOSFET transistors are pulled down by internal PMOS transistors. These transistors continue to operate even if IN1 and IN2 are both at 0 V. This circuitry also helps hold the external MOSFET transistors off when power is suddenly applied to the system.
- During an overcurrent fault condition, the external MOSFET transistor that exhibited an overcurrent condition will be rapidly turned off by an internal pulldown circuit capable of pulling in excess of 400 mA (at 4 V) from the pin. Once the gate has been pulled below approximately 1.5 V, this driver is disengaged and the UVLO driver is enabled instead. If one channel experiences an overcurrent condition and the other does not, then only the channel that is conducting excessive current will be turned off rapidly. The other channel will continue to operate normally.

setting the current-limit circuit-breaker threshold

Using channel 1 as an example, the current sensing resistor R_{ISENSE1} and the current-limit-setting resistor R_{ISET1} determine the current limit of the channel, and can be calculated by the following equation:

$$I_{\text{LMT1}} = \frac{R_{\text{ISET1}} \times 50 \times 10^{-6}}{R_{\text{ISENSE1}}}$$

Typically R_{ISENSE1} is very small (0.001 Ω to 0.1 Ω). If the trace and solder-junction resistances between the junction of R_{ISENSE1} and ISENSE1 and the junction of R_{ISENSE1} and R_{ISET1} are greater than 10% of the R_{ISENSE1} value, then these resistance values should be added to the R_{ISENSE1} value used in the calculation above.

The above information and calculation also apply to channel 2. Table 2 shows some of the current sense resistors available in the market.

Table 2. Some Current Sense Resistors

CURRENT RANGE (A)	PART NUMBER	DESCRIPTION	MANUFACTURER
0 to 1	WSL-1206, 0.05 1%	0.05 Ω , 0.25 W, 1% resistor	Vishay Dale
1 to 2	WSL-1206, 0.025 1%	0.025 Ω , 0.25 W, 1% resistor	
2 to 4	WSL-1206, 0.015 1%	0.015 Ω , 0.25 W, 1% resistor	
4 to 6	WSL-2010, 0.010 1%	0.010 Ω , 0.5 W, 1% resistor	
6 to 8	WSL-2010, 0.007 1%	0.007 Ω , 0.5 W, 1% resistor	
8 to 10	WSR-2, 0.005 1%	0.005 Ω , 0.5 W, 1% resistor	

TPS2320, TPS2321 DUAL HOT SWAP POWER CONTROLLERS WITH INDEPENDENT CIRCUIT BREAKER

SLVS276C – MARCH 2000 – REVISED MARCH 2001

APPLICATION INFORMATION

undervoltage lockout (UVLO)

The TPS2320/TPS2321 includes an undervoltage lockout (UVLO) feature that monitors the voltage present on the VREG pin. This feature will disable both external MOSFETs if the voltage on VREG drops below 2.78 V (nominal) and will re-enable normal operation when it rises above 2.85 V (nominal). Since VREG is fed from IN1 through a low-dropout voltage regulator, the voltage on VREG will track the voltage on IN1 within 50 mV. While the undervoltage lockout is engaged, both GATE1 and GATE2 are held low by internal PMOS pulldown transistors, ensuring that the external MOSFET transistors remain off at all times, even if all power supplies have fallen to 0 V.

single-channel operation

Some applications may require only a single external MOS transistor. Such applications should use GATE1 and the associated circuitry (IN1, ISENSE1, ISET1, DISCH1). The IN2 pin should be grounded to disable the circuitry associated with the GATE2 pin.

power-up control

The TPS2320/TPS2321 includes a 500 μ s (nominal) startup delay that ensures that internal circuitry has sufficient time to start before the device begins turning on the external MOSFETs. This delay is triggered only upon the rapid application of power to the circuit. If the power supply ramps up slowly, the undervoltage lockout circuitry will provide adequate protection against undervoltage operation.

3-channel hot-swap application

Some applications require hot-swap control of up to three voltage rails, but may not explicitly require the sensing of the status of the output power on all three of the voltage rails. One such application is device bay, where dv/dt control of 3.3 V, 5 V, and 12 V is required. By using Channel 2 to drive both the 3.3-V and 5-V power rails and Channel 1 to drive the 12-V power rail, as is shown below, TPS2320/01 can deliver three different voltages to three loads while monitoring the status of two of the loads.



APPLICATION INFORMATION




Figure 27. Three-Channel Application

Figure 28 shows ramp-up waveforms of the three output voltages.




Figure 28

TPS2320, TPS2321
DUAL HOT SWAP POWER CONTROLLERS
WITH INDEPENDENT CIRCUIT BREAKER


SLVS276C – MARCH 2000 – REVISED MARCH 2001

MECHANICAL DATA

D (R-PDSO-G)**

PLASTIC SMALL-OUTLINE PACKAGE

14 PINS SHOWN



- NOTES: A. All linear dimensions are in inches (millimeters).
 B. This drawing is subject to change without notice.
 C. Body dimensions do not include mold flash or protrusion, not to exceed 0.006 (0,15).
 D. Falls within JEDEC MS-012

TPS2320, TPS2321
 DUAL HOT SWAP POWER CONTROLLERS
 WITH INDEPENDENT CIRCUIT BREAKER


SLVS276C – MARCH 2000 – REVISED MARCH 2001

MECHANICAL DATA

PW (R-PDSO-G**)

PLASTIC SMALL-OUTLINE PACKAGE

14 PINS SHOWN



- NOTES: A. All linear dimensions are in millimeters.
 B. This drawing is subject to change without notice.
 C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.
 D. Falls within JEDEC MO-153

IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgment, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Customers are responsible for their applications using TI components.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, license, warranty or endorsement thereof.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations and notices. Representation or reproduction of this information with alteration voids all warranties provided for an associated TI product or service, is an unfair and deceptive business practice, and TI is not responsible nor liable for any such use.

Resale of TI's products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service, is an unfair and deceptive business practice, and TI is not responsible nor liable for any such use.

Also see: [Standard Terms and Conditions of Sale for Semiconductor Products](http://www.ti.com/sc/docs/stdterms.htm). www.ti.com/sc/docs/stdterms.htm

Mailing Address:

Texas Instruments
Post Office Box 655303
Dallas, Texas 75265