

TMS464409, TMS464409P, TMS465409, TMS465409P

16 777 216 BY 4-BIT EXTENDED DATA OUT

DYNAMIC RANDOM-ACCESS MEMORIES

SMKS895A – MAY 1997 – REVISED OCTOBER 1997

- Organization . . . 16777216 by 4 Bits
- Single 3.3-V Power Supply (± 0.3 -V Tolerance)
- Performance Ranges:


	ACCESS TIME	ACCESS TIME	ACCESS TIME	EDO CYCLE
	t_{RAC} (MAX)	t_{CAC} (MAX)	t_{AA} (MAX)	t_{HPC} (MIN)
'46x409/P-40	40 ns	11 ns	20 ns	16 ns
'46x409/P-50	50 ns	13 ns	25 ns	20 ns
'46x409/P-60	60 ns	15 ns	30 ns	25 ns

- Extended-Data-Out (EDO) Operation
- \overline{CAS} -Before- \overline{RAS} (CBR) Refresh
- Long Refresh Period (See Available Options Table)
- Low-Power, Self-Refresh Version (TMS46x409P)
- 3-State Unlatched Output
- All Inputs/Outputs and Clocks Are Low-Voltage TTL (LVTTTL) Compatible
- High-Reliability Plastic 32-Lead 400-Mil-Wide Thin Small-Outline (TSOP) Package (DGC Suffix)
- Operating Free-Air Temperature Range 0°C to 70°C

AVAILABLE OPTIONS

DEVICE	SELF-REFRESH BATTERY BACKUP	\overline{RAS} -ONLY REFRESH CYCLES	CBR REFRESH CYCLES
TMS464409	—	8 192 in 64 ms	4 096 in 64 ms
TMS464409P	YES	8 192 in 128 ms	4 096 in 128 ms
TMS465409	—	4 096 in 64 ms	4 096 in 64 ms
TMS465409P	YES	4 096 in 128 ms	4 096 in 128 ms

DGC PACKAGE
(TOP VIEW)



† A12 is NC for TMS465409 and TMS465409P.

PIN NOMENCLATURE

A0–A12	Address Inputs
\overline{CAS}	Column-Address Strobe
DQ1–DQ4	Data In/Data Out
NC	No Internal Connection
\overline{OE}	Output Enable
\overline{RAS}	Row-Address Strobe
\overline{W}	Write Enable
VCC	3.3-V Supply
VSS	Ground

description

The TMS464409 and TMS465409 series are low-voltage, 67 108 864-bit dynamic random-access memories (DRAMs), organized as 16 777 216 words of 4 bits each. The TMS464409P and TMS465409P series are high-speed, low-voltage, low-power, self-refresh, 67 108 864-bit DRAMs, organized as 16 777 216 words of 4 bits each. Both sets of devices employ state-of-the-art technology for high performance, reliability, and low power.

These devices feature maximum \overline{RAS} access times of 40, 50, and 60 ns. All inputs and outputs, including clocks, are compatible with LVTTTL. All addresses and data-in lines are latched on chip to simplify system design. Data out is unlatched to allow greater system flexibility.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.

**TEXAS
INSTRUMENTS**

POST OFFICE BOX 1443 • HOUSTON, TEXAS 77251-1443

Copyright © 1997, Texas Instruments Incorporated

PRODUCT PREVIEW


TMS464409, TMS464409P, TMS465409, TMS465409P
 16 777 216 BY 4-BIT EXTENDED DATA OUT
 DYNAMIC RANDOM-ACCESS MEMORIES

SMKS895A – MAY 1997 – REVISED OCTOBER 1997

description (continued)


The TMS46x409 and TMS46x409P series are offered in a 400-mil, 32-lead plastic surface mount TSOP package (DGC suffix). This package is designed for operation from 0°C to 70°C.

logic symbol (TMS464409 and TMS464409P)†



† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

logic symbol (TMS465409 and TMS465409P)[†]



[†] This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

PRODUCT PREVIEW

TMS464409, TMS464409P, TMS465409, TMS465409P


16 777 216 BY 4-BIT EXTENDED DATA OUT

DYNAMIC RANDOM-ACCESS MEMORIES


SMKS895A – MAY 1997 – REVISED OCTOBER 1997

functional block diagram

TMS464409, TMS464409P



TMS465409, TMS465409P



operation

extended data out

Extended data out (EDO) allows data output rates up to 66 MHz for 40-ns devices. When keeping the same row address while selecting random column addresses, the time for row-address setup and hold and for address multiplex is eliminated. The maximum number of columns that can be accessed is determined by t_{RAS} , the maximum RAS low time.

Extended data out does not place the data in/data out pins (DQ pins) into the high-impedance state with the rising edge of \overline{CAS} during \overline{RAS} low. The output remains valid for the system to latch the data. After \overline{CAS} goes high, the DRAM decodes the next address. \overline{OE} and \overline{W} can control the output impedance. Descriptions of \overline{OE} and \overline{W} further explain EDO operation benefit.

address: A0–A11 (TMS465409/P) and A0–A12 (TMS464409/P)

Twenty-four address bits are required to decode each one of 16 777 216 storage cell locations. For the TMS465409 and TMS465409P, 12 row-address bits are set up on A0 through A11 and latched onto the chip by the row-address strobe (RAS). Twelve column-address bits are set up on A0 through A11. For the TMS464409 and TMS464409P, 13 row-address bits are set up on inputs A0 through A12 and latched onto the chip by RAS. Eleven column-address bits are set up on A0 through A10. All addresses must be stable on or before the falling edge of RAS and CAS. RAS is similar to a chip enable because it activates the sense amplifiers as well as the row decoder. CAS is used as a chip select, activating the output buffers and latching the address bits into the column-address buffers.

output enable (\overline{OE})

\overline{OE} controls the impedance of the output buffers. While \overline{CAS} and \overline{RAS} are low and \overline{W} is high, \overline{OE} can be brought low or high and the DQs transition between valid data and high impedance (see Figure 8). There are two methods for placing the DQs into the high-impedance state and maintaining that state during \overline{CAS} high time. The first method is to transition \overline{OE} high before CAS transitions high and keep \overline{OE} high for t_{CHO} (hold time, \overline{OE} from \overline{CAS}) past the CAS transition. This disables the DQs and they remain disabled, regardless of \overline{OE} , until \overline{CAS} falls again. The second method is to have \overline{OE} low as \overline{CAS} transitions high. Then \overline{OE} can pulse high for a minimum of t_{OEP} (precharge time, \overline{OE}) anytime during \overline{CAS} high time, disabling the DQs regardless of further transitions on \overline{OE} until CAS falls again (see Figure 8).

write enable (\overline{W})

The read or write mode is selected through \overline{W} . A logic high on \overline{W} selects the read mode, and a logic low selects the write mode. The data inputs are disabled when the read mode is selected. When \overline{W} goes low prior to \overline{CAS} (early write), data out remains in the high-impedance state for the entire cycle, permitting a write operation with \overline{OE} grounded. If \overline{W} goes low in an extended-data-out read cycle, the DQs are disabled so long as CAS is high (see Figure 9).

data in/data out (DQ1–DQ4)

Data is written during a write or read-modify-write cycle. Depending on the mode of operation, the later falling edge of \overline{CAS} or \overline{W} strobes data into the on-chip data latch with setup and hold times referenced to the later edge. The DQs drive valid data after all access times are met and remain valid except in cases described in the \overline{W} and \overline{OE} descriptions.

\overline{RAS} -only refresh

A refresh operation must be performed at least once every 64 ms (128 ms for TMS46x409P) to retain data by strobing each of the 4096 rows for TMS465409/P or 8192 rows for TMS464409/P. A normal read or write cycle refreshes all bits in each row that is selected. A \overline{RAS} -only operation can be used by holding CAS at the high (inactive) level, conserving power as the output buffers remain in the high-impedance state. Externally generated addresses must be used for a \overline{RAS} -only refresh.

TMS464409, TMS464409P, TMS465409, TMS465409P

16 777 216 BY 4-BIT EXTENDED DATA OUT

DYNAMIC RANDOM-ACCESS MEMORIES

SMKS895A – MAY 1997 – REVISED OCTOBER 1997

hidden refresh

A hidden refresh can be performed while maintaining valid data at the output pin. This is accomplished by holding $\overline{\text{CAS}}$ at V_{IL} after a read operation and cycling $\overline{\text{RAS}}$ after a specified precharge period, similar to a $\overline{\text{RAS}}$ -only refresh cycle. The external address is ignored, and the refresh address is generated internally.

$\overline{\text{CAS}}$ -before- $\overline{\text{RAS}}$ (CBR) refresh

CBR refresh is performed by bringing $\overline{\text{CAS}}$ low earlier than $\overline{\text{RAS}}$ (see parameter t_{CSR}) and holding it low after $\overline{\text{RAS}}$ falls (see parameter t_{CHR}). For successive CBR refresh cycles, $\overline{\text{CAS}}$ can remain low while cycling $\overline{\text{RAS}}$. The external address is ignored, and the refresh address is generated internally.

battery-backup refresh

A low-power battery-backup refresh mode that requires less than 250 μA of refresh current is available on the TMS464409P and TMS465409P. Data integrity is maintained using CBR refresh with a period of 31.25 μs while holding $\overline{\text{RAS}}$ low for less than 300 ns. To minimize current consumption, all input levels must be at LVCMOS levels ($V_{\text{IL}} < 0.2 \text{ V}$, $V_{\text{IH}} > V_{\text{CC}} - 0.2 \text{ V}$).

self-refresh (TMS46x409P)

The self-refresh mode is entered by dropping $\overline{\text{CAS}}$ low prior to $\overline{\text{RAS}}$ going low. Then $\overline{\text{CAS}}$ and $\overline{\text{RAS}}$ are both held low for a minimum of 100 μs . The chip is then refreshed internally by an on-board oscillator. No external address is required because the CBR counter is used to keep track of the address. To exit the self-refresh mode, both $\overline{\text{RAS}}$ and $\overline{\text{CAS}}$ are brought high to satisfy t_{CHS} . Upon exiting self-refresh mode, a burst refresh (refreshes a full set of row addresses) must be executed before continuing with normal operation. The burst refresh ensures the DRAM is fully refreshed.

power up


To achieve proper device operation, an initial pause of 200 μs followed by a minimum of eight initialization cycles is required after power up to the full V_{CC} level. These eight initialization cycles must include at least one refresh ($\overline{\text{RAS}}$ -only or CBR) cycle.

test mode

The test mode (see Figure 1) is initiated with a CBR-refresh cycle while simultaneously holding the $\overline{\text{W}}$ input low. The entry cycle performs an internal refresh cycle while internally setting the device to perform parallel read or write on subsequent cycles. While in the test mode, any data sequence can be performed. The device exits test mode if a CBR refresh cycle with $\overline{\text{W}}$ held high or a $\overline{\text{RAS}}$ -only refresh cycle is performed.

In the test mode, the device is configured as 1024K bits \times 4 bits for each DQ. Each DQ pin has a separate 4-bit parallel read and write data bus that ignores column addresses A0 and A1. During a read cycle, the four internal bits are compared for each DQ pin. If the four bits agree, DQ goes high; if not, DQ goes low. During a write cycle, the data states of all four DQs must be the same to ensure proper function of the test mode. Test time is reduced by a factor of four for this series.

test mode (continued)



NOTE A: The states of \overline{W} , data in, and address are defined by the type of cycle used during test mode.

Figure 1. Test-Mode Cycle

PRODUCT PREVIEW

TMS464409, TMS464409P, TMS465409, TMS465409P
 16 777 216 BY 4-BIT EXTENDED DATA OUT
 DYNAMIC RANDOM-ACCESS MEMORIES

SMKS895A – MAY 1997 – REVISED OCTOBER 1997

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage range on V_{CC}	– 0.5 V to 4.6 V
Voltage range on any pin (see Note 1)	– 0.5 V to 4.6 V
Short-circuit output current	50 mA
Power dissipation	1 W
Operating free-air temperature range, T_A	0°C to 70°C
Storage temperature range, T_{stg}	– 55°C to 125°C

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: All voltage values are with respect to V_{SS} .

recommended operating conditions

	MIN	NOM	MAX	UNIT
V_{CC} Supply voltage	3	3.3	3.6	V
V_{IH} High-level input voltage	2		$V_{CC} + 0.3$	V
V_{IL} Low-level input voltage (see Note 2)	– 0.3		0.8	V
T_A Operating free-air temperature	0		70	°C

NOTE 2: The algebraic convention, where the more negative (less positive) limit is designated as minimum, is used for logic voltage levels only.



electrical characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted)

TMS464409/P

PARAMETER	TEST CONDITIONS†	'464409-40 '464409P-40		'464409-50 '464409P-50		'464409-60 '464409P-60		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
V_{OH} High-level output voltage	$I_{OH} = -2 \text{ mA}$ LVTTL	2.4		2.4		2.4		V
	$I_{OH} = -100 \mu\text{A}$ LVCMOS	$V_{CC}-0.2$		$V_{CC}-0.2$		$V_{CC}-0.2$		
V_{OL} Low-level output voltage	$I_{OL} = 2 \text{ mA}$ LVTTL		0.4		0.4		0.4	V
	$I_{OL} = 100 \mu\text{A}$ LVCMOS		0.2		0.2		0.2	
I_I Input current (leakage)	$V_{CC} = 3.6 \text{ V}$, $V_I = 0 \text{ V to } 3.9 \text{ V}$, All others = $0 \text{ V to } V_{CC}$		± 10		± 10		± 10	μA
I_O Output current (leakage)	$V_{CC} = 3.6 \text{ V}$, $V_O = 0 \text{ V to } V_{CC}$, CAS high		± 10		± 10		± 10	μA
$I_{CC1}^{\ddagger\S}$ Average read- or write-cycle current	$V_{CC} = 3.6 \text{ V}$, Minimum cycle		125		100		90	mA
I_{CC2} Average standby current	After one memory cycle, RAS and CAS high, $V_{IH} = 2 \text{ V (LVTTL)}$		1		1		1	mA
	After one memory cycle, RAS and CAS high, $V_{IH} = V_{CC} - 0.2 \text{ V}$ (LVCMOS)	'464409	500		500		500	μA
		'464409P	150		150		150	μA
I_{CC3}^{\S} Average RAS-only refresh current	$V_{CC} = 3.6 \text{ V}$, Minimum cycle, RAS cycling, CAS high (RAS only)		125		100		90	mA
$I_{CC4}^{\ddagger\P}$ Average EDO current	$V_{CC} = 3.6 \text{ V}$, $t_{PC} = \text{minimum}$, RAS low, CAS cycling		140		110		90	mA
I_{CC5} Average CBR refresh current	$V_{CC} = 3.6 \text{ V}$, Minimum cycle, RAS low after CAS low		160		130		110	mA
$I_{CC6}^{\#}$ Average self-refresh current	$\overline{\text{CAS}} < 0.2 \text{ V}$, $\overline{\text{RAS}} < 0.2 \text{ V}$, Measured after t_{RASS} minimum		300		300		300	μA
$I_{CC10}^{\#}$ Average battery-backup operating current, CBR only	$t_{RAS} \leq 300 \text{ ns}$, $t_{RC} = 31.25 \mu\text{s}$ $V_{CC} - 0.2 \text{ V} \leq V_{IH} \leq 3.9 \text{ V}$, $0 \text{ V} \leq V_{IL} \leq 0.2 \text{ V}$, \overline{W} and $\overline{OE} = V_{IH}$, Address and data stable		400		400		400	μA

† For conditions shown as MIN/MAX, use the appropriate value specified in the timing requirements.

‡ Measured with outputs open

§ Measured with a maximum of one address change while $\overline{\text{RAS}} = V_{IL}$

¶ Measured with a maximum of one address change per EDO cycle, t_{HPC}

For TMS464409P only

PRODUCT PREVIEW

electrical characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (continued)

TMS465409/P

PARAMETER		TEST CONDITIONS†		'465409-40 '465409P-40		'465409-50 '465409P-50		'465409-60 '465409P-60		UNIT
				MIN	MAX	MIN	MAX	MIN	MAX	
V _{OH}	High-level output voltage	I _{OH} = − 2 mA	LVTTTL	2.4		2.4		2.4		V
		I _{OH} = − 100 μA	LVC MOS	V _{CC} − 0.2		V _{CC} − 0.2		V _{CC} − 0.2		
V _{OL}	Low-level output voltage	I _{OL} = 2 mA	LVTTTL	0.4		0.4		0.4		V
		I _{OL} = 100 μA	LVC MOS	0.2		0.2		0.2		
I _I	Input current (leakage)	V _{CC} = 3.6 V, V _I = 0 V to 3.9 V, All others = 0 V to V _{CC}		± 10		± 10		± 10		μA
I _O	Output current (leakage)	V _{CC} = 3.6 V, V _O = 0 V to V _{CC} , CAS high		± 10		± 10		± 10		μA
I _{CC1} ‡§	Average read- or write-cycle current	V _{CC} = 3.6 V, Minimum cycle		160		130		110		mA
I _{CC2}	Average standby current	After one memory cycle, RAS and CAS high, V _{IH} = 2 V (LVTTTL)		1		1		1		mA
		After one memory cycle, RAS and CAS high, V _{IH} = V _{CC} − 0.2 V (LVC MOS)	'465409	500		500		500		μA
			'465409P	150		150		150		μA
I _{CC3} §	Average RAS-only refresh current	V _{CC} = 3.6 V, Minimum cycle, RAS cycling, CAS high (RAS only)		160		130		110		mA
I _{CC4} ‡¶	Average EDO current	V _{CC} = 3.6 V, RAS low, t _{PC} = minimum, CAS cycling		150		120		100		mA
I _{CC5}	Average CBR refresh current	V _{CC} = 3.6 V, Minimum cycle, RAS low after CAS low		160		130		110		mA
I _{CC6} #	Average self-refresh current	CAS < 0.2 V, RAS < 0.2 V, Measured after t _{RASS} minimum		300		300		300		μA
I _{CC10} #	Average battery-backup operating current, CBR only	t _{RAS} ≤ 300 ns, t _{RC} = 31.25 μs V _{CC} − 0.2 V ≤ V _{IH} ≤ 3.9 V, 0 V ≤ V _{IL} ≤ 0.2 V, W and OE = V _{IH} , Address and data stable		400		400		400		μA

† For conditions shown as MIN/MAX, use the appropriate value specified in the timing requirements.

‡ Measured with outputs open

§ Measured with a maximum of one address change while RAS = V_{IL}

¶ Measured with a maximum of one address change per EDO cycle, t_{HPC}

For TMS465409P only

capacitance over recommended ranges of supply voltage and operating free-air temperature, $f = 1 \text{ MHz}$ (see Note 3)

PARAMETER		MIN	MAX	UNIT
$C_{i(A)}$	Input capacitance, A0–A12†		5	pF
$C_{i(OE)}$	Input capacitance, \overline{OE}		7	pF
$C_{i(RC)}$	Input capacitance, \overline{CAS} and \overline{RAS}		7	pF
$C_{i(W)}$	Input capacitance, \overline{W}		7	pF
C_o	Output capacitance‡		7	pF

† A12 is NC (no internal connection) for TMS465409 and TMS465409P.

‡ \overline{CAS} and $\overline{OE} = V_{IH}$ to disable outputs

NOTE 3: $V_{CC} = 3.3 \text{ V} \pm 10\%$, and the bias on pins under test is 0 V.

switching characteristics over recommended ranges of supply voltage and operating free-air temperature (see Note 4)

PARAMETER	'46x409-40 '46x409P-40		'46x409-50 '46x409P-50		'46x409-60 '46x409P-60		UNIT
	MIN	MAX	MIN	MAX	MIN	MAX	
t_{AA}	Access time from column address (see Note 5)		20	25	30		ns
t_{CAC}	Access time from \overline{CAS} (see Note 5)		11	13	15		ns
t_{CPA}	Access time from \overline{CAS} precharge (see Note 5)		22	28	35		ns
t_{RAC}	Access time from \overline{RAS} (see Note 5)		40	50	60		ns
t_{OEA}	Access time from \overline{OE} (see Note 5)		11	13	15		ns
t_{CLZ}	Delay time, \overline{CAS} to output in low impedance		0	0	0		ns
t_{REZ}	Output buffer turn off delay from \overline{RAS} (see Note 6)		3	11	3	15	ns
t_{CEZ}	Output buffer turn off delay from \overline{CAS} (see Note 6)		3	11	3	15	ns
t_{OEZ}	Output buffer turn off delay from \overline{OE} (see Note 6)		3	11	3	15	ns
t_{WEZ}	Output buffer turn off delay from \overline{W} (see Note 6)		3	11	3	15	ns

NOTES: 4. With ac parameters, it is assumed that $t_T = 2 \text{ ns}$.

5. Access times are measured with output reference levels of $V_{OH} = 2 \text{ V}$ and $V_{OL} = 0.8 \text{ V}$.

6. The maximum values of t_{REZ} , t_{CEZ} , t_{OEZ} , and t_{WEZ} are specified when the output is no longer driven. Data in should not be driven until one of the applicable maximum specs is satisfied.

EDO timing requirements over recommended ranges of supply voltage and operating free-air temperature (see Note 4)

	'46x409-40 '46x409P-40		'46x409-50 '46x409P-50		'46x409-60 '46x409P-60		UNIT
	MIN	MAX	MIN	MAX	MIN	MAX	
t_{HPC}	Cycle time, EDO page mode, read-write		16	20	25		ns
t_{PRWC}	Cycle time, EDO read-write		47	57	68		ns
t_{CSH}	Delay time, \overline{RAS} active to \overline{CAS} precharge		32	40	48		ns
t_{CHO}	Hold time, \overline{OE} from \overline{CAS}		5	5	5		ns
t_{DOH}	Hold time, output from \overline{CAS}		5	5	5		ns
t_{CAS}	Pulse duration, \overline{CAS} active (see Note 7)		6	10 000	8	10 000	ns
t_{WPE}	Pulse duration, \overline{W} active (output disable only)		5	5	5		ns
t_{OCH}	Setup time, \overline{OE} before \overline{CAS}		5	5	5		ns
t_{CP}	Pulse duration, \overline{CAS} precharge		6	8	10		ns
t_{OEP}	Precharge time, \overline{OE}		5	5	5		ns

NOTES: 4. With ac parameters, it is assumed that $t_T = 2 \text{ ns}$.

7. In a read-write cycle, t_{CWD} and t_{CWL} must be observed.

timing requirements (see Note 4)

		'46x409-40 '46x409P-40		'46x409-50 '46x409P-50		'46x409-60 '46x409P-60		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
t _{RC}	Cycle time, random read or write	69		84		104		ns
t _{RWC}	Cycle time, read-write	92		111		135		ns
t _{RASP}	Pulse duration, $\overline{\text{RAS}}$ active, fast page mode (see Note 8)	40	100 000	50	100 000	60	100 000	ns
t _{RAS}	Pulse duration, $\overline{\text{RAS}}$ active, non-page mode (see Note 8)	40	10 000	50	10 000	60	10 000	ns
t _{RP}	Pulse duration, $\overline{\text{RAS}}$ precharge	25		30		40		ns
t _{WP}	Pulse duration, write command	6		8		10		ns
t _{RASS}	Pulse duration, $\overline{\text{RAS}}$ active, self refresh (see Note 9)	100		100		100		μs
t _{RPS}	Pulse duration, $\overline{\text{RAS}}$ precharge after self refresh	70		90		110		ns
t _{ASC}	Setup time, column address	0		0		0		ns
t _{ASR}	Setup time, row address	0		0		0		ns
t _{DS}	Setup time, data in (see Note 9)	0		0		0		ns
t _{RCS}	Setup time, read command	0		0		0		ns
t _{CWL}	Setup time, write command before $\overline{\text{CAS}}$ precharge	6		8		10		ns
t _{RWL}	Setup time, write command before $\overline{\text{RAS}}$ precharge	6		8		10		ns
t _{WCS}	Setup time, write command before $\overline{\text{CAS}}$ active (early-write only)	0		0		0		ns
t _{WRP}	Setup time, $\overline{\text{W}}$ high before $\overline{\text{RAS}}$ low (CBR refresh only)	5		5		5		ns
t _{WTS}	Setup time, $\overline{\text{W}}$ low before $\overline{\text{RAS}}$ low (test mode only)	5		5		5		ns
t _{CSR}	Setup time, $\overline{\text{CAS}}$ referenced to $\overline{\text{RAS}}$ (CBR refresh only)	5		5		5		ns
t _{CAH}	Hold time, column address	6		8		10		ns
t _{DH}	Hold time, data in (see Note 10)	6		8		10		ns
t _{RAH}	Hold time, row address	6		8		10		ns
t _{RCH}	Hold time, read command referenced to $\overline{\text{CAS}}$ (see Note 11)	0		0		0		ns
t _{RRH}	Hold time, read command referenced to $\overline{\text{RAS}}$ (see Note 11)	0		0		0		ns
t _{WCH}	Hold time, write command during $\overline{\text{CAS}}$ active (early-write only)	6		8		10		ns
t _{ROH}	Hold time, $\overline{\text{RAS}}$ referenced to $\overline{\text{OE}}$	6		8		10		ns
t _{WRH}	Hold time, $\overline{\text{W}}$ high after $\overline{\text{RAS}}$ low (CBR refresh)	6		8		10		ns
t _{WTH}	Hold time, $\overline{\text{W}}$ low after $\overline{\text{RAS}}$ low (test mode only)	6		8		10		ns
t _{CHR}	Hold time, $\overline{\text{CAS}}$ referenced to $\overline{\text{RAS}}$ (CBR refresh only)	6		8		10		ns
t _{OEH}	Hold time, $\overline{\text{OE}}$ command	11		13		15		ns
t _{CHS}	Hold time, $\overline{\text{CAS}}$ active after $\overline{\text{RAS}}$ precharge (self-refresh)	–50		–50		–50		ns
t _{RHCP}	Hold time, $\overline{\text{RAS}}$ active from $\overline{\text{CAS}}$ precharge	22		28		35		ns


NOTES: 4. With ac parameters, it is assumed that $t_T = 2$ ns.8. In a read-write cycle, t_{RWD} and t_{RWL} must be observed.9. During the period of $10 \mu\text{s} \leq t_{\text{RASS}} \leq 100 \mu\text{s}$, the device is in transition state from normal operation mode to self-refresh mode.10. Referenced to the later of $\overline{\text{CAS}}$ or $\overline{\text{W}}$ in write operations11. Either t_{RRH} or t_{RCH} must be satisfied for a read cycle.

timing requirements (see Note 4) (continued)

		'46x409-40 '46x409P-40		'46x409-50 '46x409P-50		'46x409-60 '46x409P-60		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
t _{AWD}	Delay time, column address to write command (read-write only)	35		42		49		ns
t _{CPW}	Delay time, \overline{W} low after xCAS precharge (read-write only)	37		45		54		ns
t _{CRP}	Delay time, \overline{CAS} precharge to \overline{RAS}	5		5		5		ns
t _{CWD}	Delay time, \overline{CAS} to write command (read-write only)	26		30		34		ns
t _{OED}	Delay time, \overline{OE} to data in	11		13		15		ns
t _{RAD}	Delay time, \overline{RAS} to column address (see Note 12)	8	20	10	25	12	30	ns
t _{RAL}	Delay time, column address to \overline{RAS} precharge	20		25		30		ns
t _{CAL}	Delay time, column address to \overline{CAS} precharge	12		15		18		ns
t _{RCD}	Delay time, \overline{RAS} to \overline{CAS} (see Note 12)	10	29	12	37	14	45	ns
t _{RPC}	Delay time, \overline{RAS} precharge to \overline{CAS}	5		5		5		ns
t _{RSR}	Delay time, \overline{CAS} active to \overline{RAS} precharge	6		8		10		ns
t _{RWD}	Delay time, \overline{RAS} to write command (read-write only)	55		67		79		ns
t _{TAA}	Access time from address (test mode)	25		30		35		ns
t _{TCPA}	Access time, from column precharge (test mode)	30		35		40		ns
t _{TRAC}	Access time, from \overline{RAS} (test mode)	45		55		65		ns
t _T	Transition time	1	50	1	50	1	50	ns
t _{REF}	Refresh time interval	'46x409	64	'46x409	64	'46x409	64	ms
		'46x409P	128	'46x409P	128	'46x409P	128	ms

NOTES: 4. With ac parameters, it is assumed that $t_T = 2$ ns.
12. The maximum value is specified only to ensure access time.


PARAMETER MEASUREMENT INFORMATION



NOTE A: C_L includes probe and fixture capacitance.

Figure 2. Load Circuits for Timing Parameters

PARAMETER MEASUREMENT INFORMATION



NOTE A: Output can go from the high-impedance state to an invalid-data state prior to the specified access time.

Figure 3. Read-Cycle Timing

PRODUCT PREVIEW

PARAMETER MEASUREMENT INFORMATION




Figure 4. Early-Write-Cycle Timing

PARAMETER MEASUREMENT INFORMATION





Figure 5. Write-Cycle Timing

PRODUCT PREVIEW


PARAMETER MEASUREMENT INFORMATION



NOTE A: Output can go from the high-impedance state to an invalid-data state prior to the specified access time.

Figure 6. Read-Write-Cycle Timing

PARAMETER MEASUREMENT INFORMATION




- NOTES: A. Output can go from the high-impedance state to an invalid-data state prior to the specified access time.
 B. Access time is t_{CPA} , t_{AA} , or t_{CAC} -dependent.
 C. Output is turned off by t_{CEZ} if RAS goes high during \overline{CAS} low.

Figure 7. EDO Read Cycle

PRODUCT PREVIEW

PARAMETER MEASUREMENT INFORMATION



NOTE A: Output is turned off by t_{CEZ} if \overline{RAS} goes high during \overline{CAS} low.


Figure 8. EDO Read-Cycle With \overline{OE} Control

PARAMETER MEASUREMENT INFORMATION



Figure 9. EDO Read-Cycle With \overline{W} Control

PARAMETER MEASUREMENT INFORMATION




NOTE A: A read cycle or a read-write cycle can be intermixed with write cycles as long as read and read-write timing specifications are not violated.

Figure 10. EDO Early-Write-Cycle Timing (see Note A)

PRODUCT PREVIEW



PARAMETER MEASUREMENT INFORMATION



- NOTES: A. Output can go from the high-impedance state to an invalid-data state prior to the specified access time.
 B. A read or write cycle can be intermixed with read-write cycles as long as the read- and write-timing specifications are not violated.

Figure 12. EDO Read-Write-Cycle Timing (see Note B)

PARAMETER MEASUREMENT INFORMATION




Figure 13. $\overline{\text{RAS}}$ -Only Refresh-Cycle Timing

PRODUCT PREVIEW

PARAMETER MEASUREMENT INFORMATION




Figure 14. Automatic-CBR-Refresh-Cycle Timing

PARAMETER MEASUREMENT INFORMATION




Figure 15. Self-Refresh-Cycle Timing

PRODUCT PREVIEW

PARAMETER MEASUREMENT INFORMATION




Figure 16. Hidden-Refresh-Cycle (Read) Timing

PARAMETER MEASUREMENT INFORMATION




Figure 17. Hidden-Refresh-Cycle (Write) Timing

PRODUCT PREVIEW

PARAMETER MEASUREMENT INFORMATION




Figure 18. Test-Mode-Entry-Cycle Timing





Figure 19. Test-Mode-Exit-Cycle CBR-Refresh-Cycle Timing

MECHANICAL DATA


DGC (R-PDSO-G32)

PLASTIC SMALL-OUTLINE PACKAGE



- NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Body dimensions do not include mold flash or protrusion.

device symbolization (TMS464409 illustrated)



TMS464409, TMS464409P, TMS465409, TMS465409P
16 777 216 BY 4-BIT EXTENDED DATA OUT
DYNAMIC RANDOM-ACCESS MEMORIES

SMKS895A – MAY 1997 – REVISED OCTOBER 1997

PRODUCT PREVIEW



IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.