

# TPIC5403

## 4-CHANNEL INDEPENDENT GATE-PROTECTED POWER DMOS ARRAY

SLIS038A – SEPTEMBER 1994 – REVISED SEPTEMBER 1995

- Low  $r_{DS(on)}$  . . . 0.23  $\Omega$  Typ
- High Voltage Output . . . 60 V
- Extended ESD Capability . . . 4000 V
- Pulsed Current . . . 11.25 A Per Channel
- Fast Commutation Speed

### description


The TPIC5403 is a monolithic gate-protected power DMOS array that consists of four independent electrically isolated N-channel enhancement-mode DMOS transistors. Each transistor features integrated high-current zener diodes ( $Z_{CXa}$  and  $Z_{CXb}$ ) to prevent gate damage in the event that an overstress condition occurs. These zener diodes also provide up to 4000 V of ESD protection when tested using the human-body model of a 100-pF capacitor in series with a 1.5-k $\Omega$  resistor.

The TPIC5403 is offered in a 24-pin wide-body surface-mount (DW) package and is characterized for operation over the case temperature range of  $-40^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ .

DW PACKAGE  
(TOP VIEW)

DRAIN1	1	24	DRAIN3
DRAIN1	2	23	DRAIN3
GATE1	3	22	GATE3
GND	4	21	GND
SOURCE1	5	20	SOURCE3
SOURCE1	6	19	SOURCE3
SOURCE2	7	18	SOURCE4
SOURCE2	8	17	SOURCE4
GND	9	16	GND
GATE2	10	15	GATE4
DRAIN2	11	14	DRAIN4
DRAIN2	12	13	DRAIN4

### schematic



NOTE A: For correct operation, no terminal may be taken below GND.

# TPIC5403

## 4-CHANNEL INDEPENDENT GATE-PROTECTED POWER DMOS ARRAY

SLIS038A – SEPTEMBER 1994 – REVISED SEPTEMBER 1995

### absolute maximum ratings over operating case temperature range (unless otherwise noted)<sup>†</sup>

Drain-to-source voltage, $V_{DS}$	60 V
Source-to-GND voltage	100 V
Drain-to-GND voltage	100 V
Gate-to-source voltage range, $V_{GS}$	–9 V to 18 V
Continuous drain current, each output, $T_C = 25^\circ\text{C}$	2.25 A
Continuous source-to-drain diode current, $T_C = 25^\circ\text{C}$	2.25 A
Pulsed drain current, each output, $I_{max}$ , $T_C = 25^\circ\text{C}$ (see Note 1 and Figure 15)	11.25 A
Continuous gate-to-source zener diode current, $T_C = 25^\circ\text{C}$	$\pm 50$ mA
Pulsed gate-to-source zener diode current, $T_C = 25^\circ\text{C}$	$\pm 500$ mA
Single-pulse avalanche energy, $E_{AS}$ , $T_C = 25^\circ\text{C}$ (see Figures 4, 15, and 16)	17.2 mJ
Continuous total power dissipation, $T_C = 25^\circ\text{C}$ (see Figure 15)	1.39 W
Operating virtual junction temperature range, $T_J$	–40°C to 150°C
Operating case temperature range, $T_C$	–40°C to 125°C
Storage temperature range, $T_{stg}$	–65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds	260°C

<sup>†</sup> Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: Pulse duration = 10 ms, duty cycle = 2%



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

**TPIC5403**  
**4-CHANNEL INDEPENDENT GATE-PROTECTED**  
**POWER DMOS ARRAY**

SLIS038A – SEPTEMBER 1994 – REVISED SEPTEMBER 1995

**electrical characteristics,  $T_C = 25^\circ\text{C}$  (unless otherwise noted)**

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
$V_{(BR)DSX}$	Drain-to-source breakdown voltage	$I_D = 250\ \mu\text{A}$ ,	$V_{GS} = 0$	60			V
$V_{GS(th)}$	Gate-to-source threshold voltage	$I_D = 1\ \text{mA}$ , See Figure 5	$V_{DS} = V_{GS}$	1.5	1.75	2.2	V
$V_{(BR)GS}$	Gate-to-source breakdown voltage	$I_{GS} = 250\ \mu\text{A}$		18			V
$V_{(BR)SG}$	Source-to-gate breakdown voltage	$I_{SG} = 250\ \mu\text{A}$		9			V
$V_{(BR)}$	Reverse drain-to-GND breakdown voltage (across D1, D2, D3, and D4)	Drain-to-GND current = $250\ \mu\text{A}$		100			V
$V_{DS(on)}$	Drain-to-source on-state voltage	$I_D = 2.25\ \text{A}$ , See Notes 2 and 3	$V_{GS} = 10\ \text{V}$		0.5	0.62	V
$V_{F(SD)}$	Forward on-state voltage, source-to-drain	$I_S = 2.25\ \text{A}$ , $V_{GS} = 0$ (Z1, Z2, Z3, Z4), See Notes 2 and 3 and Figure 12			0.9	1.1	V
$V_F$	Forward on-state voltage, GND-to-drain	$I_D = 2.25\ \text{A}$ (D1, D2, D3, D4), See Notes 2 and 3			2.5		V
$I_{DSS}$	Zero-gate-voltage drain current	$V_{DS} = 48\ \text{V}$ , $V_{GS} = 0$	$T_C = 25^\circ\text{C}$		0.05	1	$\mu\text{A}$
			$T_C = 125^\circ\text{C}$		0.5	10	
$I_{GSSF}$	Forward gate current, drain short circuited to source	$V_{GS} = 15\ \text{V}$ ,	$V_{DS} = 0$		20	200	nA
$I_{GSSR}$	Reverse gate current, drain short circuited to source	$V_{SG} = 5\ \text{V}$ ,	$V_{DS} = 0$		10	100	nA
$I_{lkg}$	Leakage current, drain-to-GND	$V_{DGND} = 48\ \text{V}$	$T_C = 25^\circ\text{C}$		0.05	1	$\mu\text{A}$
			$T_C = 125^\circ\text{C}$		0.5	10	
$r_{DS(on)}$	Static drain-to-source on-state resistance	$V_{GS} = 10\ \text{V}$ , $I_D = 2.25\ \text{A}$ , See Notes 2 and 3 and Figures 6 and 7	$T_C = 25^\circ\text{C}$		0.23	0.27	$\Omega$
			$T_C = 125^\circ\text{C}$		0.35	0.4	
$g_{fs}$	Forward transconductance	$V_{DS} = 15\ \text{V}$ , See Notes 2 and 3 and Figure 9	$I_D = 1.125\ \text{A}$	1.6	2.1		S
$C_{iss}$	Short-circuit input capacitance, common source	$V_{DS} = 25\ \text{V}$ , $f = 1\ \text{MHz}$ ,	$V_{GS} = 0$ , See Figure 11		200	250	pF
$C_{oss}$	Short-circuit output capacitance, common source				100	175	
$C_{rss}$	Short-circuit reverse-transfer capacitance, common source				60	75	

NOTES: 2. Technique should limit  $T_J - T_C$  to  $10^\circ\text{C}$  maximum.

3. These parameters are measured with voltage-sensing contacts separate from the current-carrying contacts.

**source-to-drain and GND-to-drain diode characteristics,  $T_C = 25^\circ\text{C}$**

PARAMETER		TEST CONDITIONS		MIN	TYP	MAX	UNIT
t <sub>rr</sub>	Reverse-recovery time	I <sub>S</sub> = 1.125 A, V <sub>GS</sub> = 0, See Figures 1 and 14	V <sub>DS</sub> = 48 V, di/dt = 100 A/μs, Z1, Z2, Z3, and Z4		80		ns
			D1, D2, D3, and D4		160		
Q <sub>RR</sub>	Total diode charge		Z1, Z2, Z3, and Z4		0.12		μC
			D1, D2, D3, and D4		0.5		

# TPIC5403

## 4-CHANNEL INDEPENDENT GATE-PROTECTED POWER DMOS ARRAY

SLIS038A – SEPTEMBER 1994 – REVISED SEPTEMBER 1995

### resistive-load switching characteristics, $T_C = 25^\circ\text{C}$


PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$t_{d(on)}$ Turn-on delay time	$V_{DD} = 25\text{ V}$ , $R_L = 20\ \Omega$ , $t_{r1} = 10\text{ ns}$ , See Figure 2		32	55	ns
$t_{d(off)}$ Turn-off delay time			27	50	
$t_{r2}$ Rise time			14	30	
$t_{f2}$ Fall time			7	15	
$Q_g$ Total gate charge	$V_{DS} = 48\text{ V}$ , $I_D = 1.125\text{ A}$ , $V_{GS} = 10\text{ V}$ , See Figure 3		6.6	8	nC
$Q_{gs(th)}$ Threshold gate-to-source charge			0.6	0.7	
$Q_{gd}$ Gate-to-drain charge			2.8	3.2	
$L_D$ Internal drain inductance			5		nH
$L_S$ Internal source inductance			5		
$R_g$ Internal gate resistance			0.25		$\Omega$

### thermal resistance

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$R_{\theta JA}$ Junction-to-ambient thermal resistance	See Notes 4 and 7		90		$^\circ\text{C/W}$
$R_{\theta JB}$ Junction-to-board thermal resistance	See Notes 5 and 7		49		$^\circ\text{C/W}$
$R_{\theta JP}$ Junction-to-pin thermal resistance	See Notes 6 and 7		28		$^\circ\text{C/W}$

NOTES: 4. Package mounted on an FR4 printed-circuit board with no heatsink  
5. Package mounted on a 24 inch<sup>2</sup>, 4-layer FR4 printed-circuit board  
6. Package mounted in intimate contact with infinite heatsink  
7. All outputs with equal power


## PARAMETER MEASUREMENT INFORMATION



†  $I_{RM}$  = maximum recovery current

‡ The above waveform is representative of D1, D2, D3, and D4 in shape only.

**Figure 1. Reverse-Recovery-Current Waveform of Source-to-Drain Diode**



NOTE A:  $C_L$  includes probe and jig capacitance.

**Figure 2. Resistive-Switching Test Circuit and Voltage Waveforms**

# TPIC5403

## 4-CHANNEL INDEPENDENT GATE-PROTECTED POWER DMOS ARRAY

SLIS038A – SEPTEMBER 1994 – REVISED SEPTEMBER 1995

### PARAMETER MEASUREMENT INFORMATION





Figure 3. Gate-Charge Test Circuit and Voltage Waveform



NOTES: A. The pulse generator has the following characteristics:  $t_r \leq 10$  ns,  $t_f \leq 10$  ns,  $Z_0 = 50 \Omega$ .  
B. Input pulse duration ( $t_w$ ) is increased until peak current  $I_{AS} = 11.25$  A.

$$\text{Energy test level is defined as } E_{AS} = \frac{I_{AS} \times V_{(BR)DSX} \times t_{av}}{2} = 17.2 \text{ mJ.}$$

Figure 4. Single-Pulse Avalanche-Energy Test Circuit and Waveforms

## TYPICAL CHARACTERISTICS




Figure 5




Figure 6




Figure 7




Figure 8

# TPIC5403

## 4-CHANNEL INDEPENDENT GATE-PROTECTED POWER DMOS ARRAY

SLIS038A – SEPTEMBER 1994 – REVISED SEPTEMBER 1995

### TYPICAL CHARACTERISTICS




Figure 9




Figure 10




Figure 11




Figure 12



## TYPICAL CHARACTERISTICS

DRAIN-TO-SOURCE VOLTAGE AND  
GATE-TO-SOURCE VOLTAGE  
vs  
GATE CHARGE




Figure 13

REVERSE-RECOVERY TIME  
vs  
REVERSE  $di/dt$





Figure 14

**TPIC5403**  
**4-CHANNEL INDEPENDENT GATE-PROTECTED**  
**POWER DMOS ARRAY**

SLIS038A – SEPTEMBER 1994 – REVISED SEPTEMBER 1995

**THERMAL INFORMATION**

**MAXIMUM DRAIN CURRENT  
 vs  
 DRAIN-TO-SOURCE VOLTAGE**




† Less than 2% duty cycle

‡ Device mounted in intimate contact with infinite heatsink.

§ Device mounted on FR4 printed circuit board with no heatsink.

**Figure 15**


**MAXIMUM PEAK AVALANCHE CURRENT  
 vs  
 TIME DURATION OF AVALANCHE**



**Figure 16**

## THERMAL INFORMATION

### DW PACKAGE† JUNCTION-TO-BOARD THERMAL RESISTANCE VS PULSE DURATION



† Device mounted on 24in<sup>2</sup>, 4-layer FR4 printed-circuit board with no heatsink.

NOTE A:  $Z_{\theta JB}(t) = r(t) R_{\theta JB}$   
 $t_W$  = pulse duration  
 $t_C$  = cycle time  
 $d$  = duty cycle =  $t_W/t_C$

Figure 17

## **IMPORTANT NOTICE**

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.