


REV. Status

PRELIMINARY
05/30/00 MPPRELIMINARY 1
ADDED
DESCRIPTION.
11/29/00 MP

HDSL2 transformer for Conexant CN8980 chipset


A. Electrical Specifications (@ 25°C)

1. Primary (Line side) Impedance; 135 Ω
2. Secondary (IC side) Impedance; 5.4 Ω
3. Total Harmonic Distortion; -85dB TYP, 100KHz, 5Vp-p
4. Primary Open Circuit Inductance; 2.0mH $\pm 10\%$ @ 10KHz, 0.1Vrms, 0/150mAdc, measured (1-5) with 2 and 4 shorted
5. Leakage Inductance; 500nH MAX @ 100KHz, 10mVrms Measured (7-9) with 2 & 4, and 1 & 5 shorted
6. DC Current; 150mA
7. DC Resistance; (1-4) (2-5)=0.57 Ω $\pm 10\%$
(7-9)=0.25 Ω $\pm 10\%$
8. Turns Ratio; (1-4):(2-5)=1:1.00 $\pm 1\%$
(7-9):(1-5)=1:5.00 $\pm 1\%$, 2 & 4 shorted
9. Dielectric Strength; 1500Vrms 1 second @ Pri to Sec


Date
CodeWhite dot
indicates
Pin 1

B. Marking; TTC-4056, TAMURA, date code and country of origin

C. Schematic;



D. Mechanical Specifications;



PREPARED BY:

D. Rund

ENGINEER:

L. Le

QUALITY CONTROL:

D. Kelley

APPROVED:

J. Coleman

DWG CONTROL NO.
P-A1-12501
ACAD\TTC\A1125011.DWGREV
PR1HDSL2
TRANSFORMER
TAMURA CORPORATION OF AMERICA
 43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624
 (909) 699-1270 FAX 9096769482

TTC-4056

MODEL SPECIFICATION

DIM: mm(In) SCL: 2/1 SH: 1 OF 1

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.

MODEL NUMBER

TTC-4056