


# ISDN U-INTERFACE TRANSFORMERS SMALL SURFACE MOUNT PACKAGE For Applications in 2B1Q and 4B3T Coding



- ☛ Matched to leading transceiver ICs
- ☛ Meets ANSI T1.601-1992 and ETSI ETR 080 standards for longitudinal balance, linearity and return loss
- ☛ Small compact footprint and minimum Isolation: 1500 Vrms

**Small Surface  
Mount Package**

## Electrical Specifications @ 25°C

| Part Number | Turns Ratio<br>Line:Chip<br>(±2%) | Line Side<br>Pins | OCL<br>Line side<br>(mH) | DCR<br>Line Side<br>(Ω) | DCR<br>Chip Side<br>(Ω) | Isolation<br>Voltage<br>(Vrms MIN) | Idc<br>(mA) | Schematic |
|-------------|-----------------------------------|-------------------|--------------------------|-------------------------|-------------------------|------------------------------------|-------------|-----------|
| T4031       | 1.65CS:1CT                        | (1-5)             | 13-18                    | 7.40 MAX                | 4.4 MAX                 | 1500                               | 50          | A         |
| T4032       | 1.25CS:1CT                        | (1-5)             | 11.9-16.1                | 6.40 MAX                | 4.4 MAX                 | 1500                               | 50          | A         |
| T4033       | 1.25CS:1CT                        | (1-5)             | 25.5-30.5                | 15.66 MAX               | 11 MAX                  | 1500                               | 40          | B         |
| T4043*      | 2CS:1CS                           | (1-5)             | 13.5-16.5                | 7.80 MAX                | 4.0 MAX                 | 1500                               | 50          | C         |
| T4067       | 1.32CS:1                          | (1-5)             | 7.5-8.3                  | 1.60 MAX                | 2.5 MAX                 | 1500                               | 55          | D         |

## Additional Specifications

| Part Number | Return Loss                  | Longitudinal Balance          |
|-------------|------------------------------|-------------------------------|
| T4031       | 10 kHz to 25 kHz @ 20 dB MIN | 281 Hz to 40 kHz @ 55 dB MIN  |
| T4032       | 15 kHz to 50 kHz @ 16 dB MIN | 20 kHz to 150 kHz @ 40 dB MIN |
| T4033       | 10 kHz to 25 kHz @ 20 dB MIN | 281 Hz to 40 kHz @ 55 dB MIN  |
| T4043*      | 10 kHz to 25 kHz @ 20 dB MIN | 281 Hz to 40 kHz @ 55 dB MIN  |
| T4067       | 15 kHz to 50 kHz @ 16 dB MIN | 15 kHz to 50 kHz @ 40 dB MIN  |

NOTES: Common Mode Chokes for EMI reduction are also available. Recommended part numbers are either **PE-68624** (Surface Mount) or **PE-65944** (Through Hole) — see data sheet **G002**. Six Sigma analysis has substantiated that **T4033** line side inductance may range from 25.5 to 30.5 mH. Optional Tape & Reel packaging can be ordered by adding a "T" suffix to the part number (ex: T4031T).


### \*Provisional Specifications

## Transformer Selection


| Company  | Chip            | Transformer |
|----------|-----------------|-------------|
| Motorola | MC145572        | T4033       |
| Infineon | PEB 2091        | T4031       |
|          | PEB 8091/8191   | T4031       |
|          | PEB 24902/24911 | T4031       |
|          | PSB 21910/21911 | T4031       |
|          | PEB 2491        | T4032       |
| Alcatel  | PEB 20901       | T4067       |
|          | MTC 20276       | T4043       |

## Mechanical

### T40XX



## Schematics



## For More Information :

### UNITED STATES

(Worldwide)  
12220 World Trade Drive  
San Diego, CA 92128  
U.S.A.  
<http://www.pulseeng.com>  
TEL: 858 674 8100  
FAX: 858 674 8262

### UNITED KINGDOM

(Northern Europe)  
1 & 2 Huxley Road  
The Surrey Research Park  
Guildford, Surrey GU2 5RE  
United Kingdom  
TEL: 44 1483 401700  
FAX: 44 1483 401701

### FRANCE

(Southern Europe)  
Zone Industrielle  
F-39270  
Orgelet  
France  
TEL: 33 3 84 35 04 04  
FAX: 33 3 84 25 46 41

### SINGAPORE

(Southern Asia)  
150 Kampong Ampat  
#07-01/02  
KA Centre  
Singapore 368324  
TEL: 65 287 8998  
FAX: 65 280 0080

### TAIWAN, R.O.C.

(Northern Asia)  
3F-4, No. 81, Sec. 1  
HsinTai Wu Road  
Hsi-Chih, Taipei Hsien  
Taiwan, R.O.C.  
Tel: 886 2 2698 0228  
FAX: 886 2 2698 0948

### DISTRIBUTOR

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.