

- 2.5-V Virtual Ground for 5-V/GND Analog Systems
- Self-Contained in Small-Outline, Dual-In-Line or 3-Terminal TO-226AA Packages
- High Output-Current Capability Sink or Source . . . 20 mA Typ
- Micropower Operation . . . 170  $\mu$ A Typ

### description

In signal-conditioning applications using a single power source, a reference voltage is required for termination of all signal grounds. To accomplish this, engineers have typically used solutions consisting of resistors, capacitors, operational amplifiers, and voltage references. Texas Instruments has eliminated all of those components with one easy-to-use 3-terminal device. That device is the TLE2425 precision virtual ground.


Use of the TLE2425 over other typical circuit solutions gives the designer increased dynamic signal range, improved signal-to-noise ratio, lower distortion, improved signal accuracy, and easier interfacing to ADCs and DACs. These benefits are the result of combining a precision micropower voltage reference and a high-performance precision operational amplifier in a single silicon chip. It is the precision and performance of these two circuit functions together that yield such dramatic system-level performance.

The TLE2425 improves input regulation as well as output regulation and, in addition, reduces output impedance and power dissipation in a majority of virtual-ground-generation circuits. Both input regulation and load regulation exceed 12 bits of accuracy on a single 5-V system. Signal-conditioning front ends of data acquisition systems that push 12 bits and beyond can use the TLE2425 to eliminate a major source of system error.

The TLE2425C is characterized for operation from 0°C to 70°C. The TLE2425I is characterized for operation from -40°C to 85°C. The TLE2425M is characterized for operation over the full military temperature range of -55°C to 125°C.

- Excellent Regulation Characteristics
  - Output Regulation
    - 45  $\mu$ V Typ at  $I_O = 0$  to -10 mA
    - +15  $\mu$ V Typ at  $I_O = 0$  to +10 mA
  - Input Regulation = 1.5  $\mu$ V/V Typ
- Low-Impedance Output . . . 0.0075  $\Omega$  Typ
- Macromodel Included

### OUTPUT REGULATION



### AVAILABLE OPTIONS

$T_A$	PACKAGED DEVICES			CHIP FORM (Y)
	SMALL OUTLINE (D)	CERAMIC DIP (JG)	PLASTIC TO-226AA (LP)	
0°C to 70°C	TLE2425CD	—	TLE2425CD	TLE2425Y
-40°C to 85°C	TLE2425ID	—	TLE2425ID	—
-55°C to 125°C	TLE2425MD	TLE2425MD	TLE2425MD	—

<sup>†</sup>The D and LP packages are available taped and reeled in the commercial temperature range only. Add R suffix to the device type (e.g., TLE2425CDR). The chip form is tested at 25°C.

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.



PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1998, Texas Instruments Incorporated



# TLE2425, TLE2425Y PRECISION VIRTUAL GROUND


SLOS065C – MARCH 1991 – REVISED MAY 1998



NC – No internal connection

## TLE2425Y chip information

This chip, properly assembled, displays characteristics similar to the TLE2425C. Thermal compression or ultrasonic bonding may be used on the doped aluminum bonding pads. The chip may be mounted with conductive epoxy or a gold-silicon preform.



**absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†**

Continuous input voltage, $V_I$ .....	40 V
Output current, $I_O$ .....	±80 mA
Duration of short-circuit current at (or below) 25°C (see Note 1) .....	unlimited
Continuous total power dissipation .....	See Dissipation Rating Table
Operating free-air temperature range, $T_A$ :	
C-suffix .....	0°C to 70°C
I-suffix .....	-40°C to 85°C
M-suffix .....	-55°C to 125°C
Storage temperature range, $T_{stg}$ .....	-65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds: D package .....	260°C
Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds: JG or LP package .....	300°C

† Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTE 1: The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.

**DISSIPATION RATING TABLE**

PACKAGE	$T_A \leq 25^\circ\text{C}$ POWER RATING	DERATING FACTOR ABOVE $T_A = 25^\circ\text{C}$	$T_A = 70^\circ\text{C}$	$T_A = 85^\circ\text{C}$	$T_A = 125^\circ\text{C}$
			POWER RATING	POWER RATING	POWER RATING
D	725 mV	5.8 mW/°C	464 mW	377 mW	145 mW
JG	1050 mV	8.4 mW/°C	672 mW	546 mW	210 mW
LP	775 mV	6.2 mW/°C	496 mW	403 mW	155 mW

**recommended operating conditions**

	C-SUFFIX		I-SUFFIX		M-SUFFIX		UNIT
	MIN	MAX	MIN	MAX	MIN	MAX	
Input voltage, $V_I$	4	40	4	40	4	40	V
Operating free-air temperature, $T_A$	0	70	-40	85	-55	125	°C

# TLE2425, TLE2425Y PRECISION VIRTUAL GROUND

SLOS065C – MARCH 1991 – REVISED MAY 1998

## electrical characteristics at specified free-air temperature, $V_I = 5 \text{ V}$ , $I_O = 0$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	$T_A^\dagger$	TLE2425C			UNIT
			MIN	TYP	MAX	
Output voltage		25°C	2.48	2.5	2.52	V
		Full range	2.47		2.53	
Temperature coefficient of output voltage		25°C		20		ppm/°C
Bias current	$I_O = 0$	25°C		170	250	$\mu\text{A}$
		Full range			250	
Input voltage regulation	$V_I = 4.5 \text{ V to } 5.5 \text{ V}$	25°C		1.5	20	$\mu\text{V}$
		Full range			25	
	$V_I = 4 \text{ V to } 40 \text{ V}$	25°C		1.5	20	$\mu\text{V/V}$
		Full range			25	
Ripple rejection	$f = 120 \text{ Hz}$ , $\Delta V_I(\text{PP}) = 1 \text{ V}$	25°C		80		dB
Output voltage regulation (source current) <sup>‡</sup>	$I_O = 0 \text{ to } -10 \text{ mA}$	25°C	-160	-45	160	$\mu\text{V}$
		Full range	-250		250	
	$I_O = 0 \text{ to } -20 \text{ mA}$	25°C	-450	-150	450	
Output voltage regulation (sink current) <sup>‡</sup>	$I_O = 0 \text{ to } 10 \text{ mA}$	25°C	-160	15	160	$\mu\text{V}$
		Full range	-250		250	
	$I_O = 0 \text{ to } 20 \text{ mA}$	25°C	-235	65	235	
Long-term drift of output voltage	$\Delta t = 1000 \text{ h}$ , Noncumulative	25°C		15		ppm
Output impedance		25°C		7.5	22.5	$\text{m}\Omega$
Short-circuit output current (sink current)	$V_O = 5 \text{ V}$	25°C	30	55		$\text{mA}$
Short-circuit output current (source current)	$V_O = 0$		-30	-50		
Output noise voltage, rms	$f = 10 \text{ Hz to } 10 \text{ kHz}$	25°C		100		$\mu\text{V}$
Output voltage response to output current step	$V_O$ to 0.1%, $I_O = \pm 10 \text{ mA}$	25°C		110		$\mu\text{s}$
	$C_L = 0$			115		
	$C_L = 100 \text{ pF}$			180		
	$V_O$ to 0.01%, $I_O = \pm 10 \text{ mA}$			180		
Output voltage response to input voltage step	$V_I = 4.5 \text{ to } 5.5 \text{ V}$ , $V_O$ to 0.1%	25°C		12		$\mu\text{s}$
	$V_I = 4.5 \text{ to } 5.5 \text{ V}$ , $V_O$ to 0.01%			30		
Output voltage turn-on response	$V_I = 0 \text{ to } 5 \text{ V}$ , $V_O$ to 0.1%	25°C		125		$\mu\text{s}$
	$V_I = 0 \text{ to } 5 \text{ V}$ , $V_O$ to 0.01%			210		

<sup>†</sup> Full range is 0°C to 70°C.

<sup>‡</sup> The listed values are not production tested.

**electrical characteristics at specified free-air temperature,  $V_I = 5 \text{ V}$ ,  $I_O = 0$  (unless otherwise noted)**

PARAMETER	TEST CONDITIONS	$T_A^{\dagger}$	TLE2425I			UNIT	
			MIN	TYP	MAX		
Output voltage		25°C	2.48	2.5	2.52	V	
		Full range	2.47		2.53		
Temperature coefficient of output voltage		25°C		20		ppm/°C	
Bias current	$I_O = 0$	25°C		170	250	$\mu\text{A}$	
		Full range			250		
Input voltage regulation	$V_I = 4.5 \text{ V to } 5.5 \text{ V}$		25°C	1.5	20	$\mu\text{V}$	
			Full range		75		
	$V_I = 4 \text{ V to } 40 \text{ V}$		25°C	1.5	20	$\mu\text{V/V}$	
			Full range		75		
Ripple rejection	$f = 120 \text{ Hz}$ , $\Delta V_{I(PP)} = 1 \text{ V}$	25°C		80		dB	
Output voltage regulation (source current) <sup>‡</sup>	$I_O = 0 \text{ to } -10 \text{ mA}$		25°C	-160	-45	160	$\mu\text{V}$
			Full range	-250		250	
	$I_O = 0 \text{ to } -20 \text{ mA}$		25°C	-450	-150	450	
Output voltage regulation (sink current) <sup>‡</sup>	$I_O = 0 \text{ to } 8 \text{ mA}$		25°C	-160	15	160	$\mu\text{V}$
			Full range	-250		250	
	$I_O = 0 \text{ to } 20 \text{ mA}$		25°C	-235	65	235	
Long-term drift of output voltage	$\Delta t = 1000 \text{ h}$ , Noncumulative	25°C		15		ppm	
Output impedance		25°C		7.5	22.5	$\text{m}\Omega$	
Short-circuit output current (sink current)	$V_O = 5 \text{ V}$	25°C		30	55	$\text{mA}$	
Short-circuit output current (source current)	$V_O = 0$			-30	-50		
Output noise voltage, rms	$f = 10 \text{ Hz to } 10 \text{ kHz}$	25°C		100		$\mu\text{V}$	
Output voltage response to output current step	$V_O$ to 0.1%, $I_O = \pm 10 \text{ mA}$	25°C		110		$\mu\text{s}$	
	$C_L = 0$			115			
	$C_L = 100 \text{ pF}$			180			
	$V_O$ to 0.01%, $I_O = \pm 10 \text{ mA}$			180			
Output voltage response to input voltage step	$V_I = 4.5 \text{ to } 5.5 \text{ V}$ , $V_O$ to 0.1%	25°C		12		$\mu\text{s}$	
	$V_I = 4.5 \text{ to } 5.5 \text{ V}$ , $V_O$ to 0.01%			30			
Output voltage turn-on response	$V_I = 0 \text{ to } 5 \text{ V}$ , $V_O$ to 0.1%	25°C		125		$\mu\text{s}$	
	$V_I = 0 \text{ to } 5 \text{ V}$ , $V_O$ to 0.01%			210			

<sup>†</sup> Full range is  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$ .

<sup>‡</sup> The listed values are not production tested.

# TLE2425, TLE2425Y PRECISION VIRTUAL GROUND

SLOS065C – MARCH 1991 – REVISED MAY 1998

## electrical characteristics at specified free-air temperature, $V_I = 5 \text{ V}$ , $I_O = 0$ (unless otherwise noted)

PARAMETER	TEST CONDITIONS	$T_A^\dagger$	TLE2425M			UNIT
			MIN	TYP	MAX	
Output voltage		25°C	2.48	2.5	2.52	V
		Full range	2.47		2.53	
Temperature coefficient of output voltage		25°C		20		ppm/°C
Bias current	$I_O = 0$	25°C		170	250	$\mu\text{A}$
		Full range			250	
Input voltage regulation	$V_I = 4.5 \text{ V to } 5.5 \text{ V}$	25°C		1.5	20	$\mu\text{V}$
		Full range			100	
	$V_I = 4.5 \text{ V to } 40 \text{ V}$	25°C		1.5	20	$\mu\text{V/V}$
		Full range			100	
Ripple rejection	$f = 120 \text{ Hz}$ , $\Delta V_I(\text{PP}) = 1 \text{ V}$	25°C		80		dB
Output voltage regulation (source current) $^\ddagger$	$I_O = 0 \text{ to } -10 \text{ mA}$	25°C	-160	-45	160	$\mu\text{V}$
		Full range	-250		250	
	$I_O = 0 \text{ to } -20 \text{ mA}$	25°C	-450	-150	450	
Output voltage regulation (sink current) $^\ddagger$	$I_O = 0 \text{ to } 3 \text{ mA}$	25°C	-160	15	160	$\mu\text{V}$
		Full range	-250		250	
	$I_O = 0 \text{ to } 20 \text{ mA}$	25°C	-235	65	235	
Long-term drift of output voltage	$\Delta t = 1000 \text{ h}$ , Noncumulative	25°C		15		ppm
Output impedance		25°C		7.5	22.5	$\text{m}\Omega$
Short-circuit output current (sink current)	$V_O = 5 \text{ V}$	25°C	30	55		$\text{mA}$
Short-circuit output current (source current)	$V_O = 0$		-30	-50		
Output noise voltage, rms	$f = 10 \text{ Hz to } 10 \text{ kHz}$	25°C		100		$\mu\text{V}$
Output voltage response to output current step	$V_O \text{ to } 0.1\%$ , $I_O = \pm 10 \text{ mA}$	25°C		110		$\mu\text{s}$
	$C_L = 0$			115		
	$C_L = 100 \text{ pF}$			180		
	$V_O \text{ to } 0.01\%$ , $I_O = \pm 10 \text{ mA}$			180		
Output voltage response to input voltage step	$V_I = 4.5 \text{ to } 5.5 \text{ V}$ , $V_O \text{ to } 0.1\%$	25°C		12		$\mu\text{s}$
	$V_I = 4.5 \text{ to } 5.5 \text{ V}$ , $V_O \text{ to } 0.01\%$			30		
Output voltage turn-on response	$V_I = 0 \text{ to } 5 \text{ V}$ , $V_O \text{ to } 0.1\%$	25°C		125		$\mu\text{s}$
	$V_I = 0 \text{ to } 5 \text{ V}$ , $V_O \text{ to } 0.01\%$			210		

$^\dagger$  Full range is  $-55^\circ\text{C}$  to  $125^\circ\text{C}$ .

$^\ddagger$  The listed values are not production tested.

**electrical characteristics  $V_I = 5 \text{ V}$ ,  $I_O = 0$ ,  $T_A = 25^\circ\text{C}$  (unless otherwise noted)**

PARAMETER	TEST CONDITIONS	TLE2425Y			UNIT
		MIN	TYP	MAX	
Output voltage			2.5		V
Temperature coefficient of output voltage			20		ppm/ $^\circ\text{C}$
Bias current	$I_O = 0$		170		$\mu\text{A}$
Input voltage regulation	$V_I = 4.5 \text{ V to } 5.5 \text{ V}$		1.5		$\mu\text{V}$
	$V_I = 4 \text{ V to } 40 \text{ V}$		1.5		$\mu\text{V/V}$
Ripple rejection	$f = 120 \text{ Hz}$ , $\Delta V_I(\text{PP}) = 1 \text{ V}$		80		dB
Output voltage regulation (source current) <sup>†</sup>	$I_O = 0 \text{ to } -10 \text{ mA}$		-45		$\mu\text{V}$
	$I_O = 0 \text{ to } -20 \text{ mA}$		-150		
Output voltage regulation (sink current) <sup>†</sup>	$I_O = 0 \text{ to } 10 \text{ mA}$		15		$\mu\text{V}$
	$I_O = 0 \text{ to } 20 \text{ mA}$		65		
Output impedance			7.5		$\text{m}\Omega$
Short-circuit output current (sink current)	$V_O = 5 \text{ V}$		55		$\text{mA}$
Short-circuit output current (source current)	$V_O = 0$		-50		
Output noise voltage, rms	$f = 10 \text{ Hz to } 10 \text{ kHz}$		100		$\mu\text{V}$
Output voltage response to output current step	$V_O \text{ to } 0.1\%$ , $I_O = \pm 10 \text{ mA}$	$C_L = 0$	110		$\mu\text{s}$
		$C_L = 100 \text{ pF}$	115		
	$V_O \text{ to } 0.01\%$ , $I_O = \pm 10 \text{ mA}$	$C_L = 0$	180		
		$C_L = 100 \text{ pF}$	180		
Output voltage response to input voltage step	$V_I = 4.5 \text{ to } 5.5 \text{ V}$ , $V_O \text{ to } 0.1\%$		12		$\mu\text{s}$
	$V_I = 4.5 \text{ to } 5.5 \text{ V}$ , $V_O \text{ to } 0.01\%$		30		
Output voltage turn-on response	$V_I = 0 \text{ to } 5 \text{ V}$ , $V_O \text{ to } 0.1\%$		125		$\mu\text{s}$
	$V_I = 0 \text{ to } 5 \text{ V}$ , $V_O \text{ to } 0.01\%$		210		

<sup>†</sup>The listed values are not production tested.

# TLE2425, TLE2425Y PRECISION VIRTUAL GROUND

SLOS065C – MARCH 1991 – REVISED MAY 1998

## TYPICAL CHARACTERISTICS

Table Of Graphs

		FIGURE
Output voltage	Distribution	1
	vs Free-air temperature	2
Output voltage hysteresis	vs Free-air temperature	3
	vs Input voltage	4
Input bias current	vs Free-air temperature	5
	6	
Input voltage regulation	vs Frequency	7
Output voltage regulation		8
Output impedance	vs Frequency	9
Short-circuit output current	vs Free-air temperature	10
Spectral noise voltage density	vs Frequency	11
Wide-band noise voltage	vs Frequency	12
Output voltage change with current step	vs Time	13
Output voltage change with voltage step	vs Time	14
Output voltage power-up response	vs Time	15
Output current	vs Load capacitance	16



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

TYPICAL CHARACTERISTICS<sup>†</sup>




Figure 1




Figure 2




Figure 3




Figure 4

<sup>†</sup> Data at high and low temperatures are applicable within rated operating free-air temperature ranges of the various devices.

# TLE2425, TLE2425Y PRECISION VIRTUAL GROUND

SLOS065C – MARCH 1991 – REVISED MAY 1998

## TYPICAL CHARACTERISTICS<sup>†</sup>




Figure 5




Figure 6




Figure 7




Figure 8

<sup>†</sup> Data at high and low temperatures are applicable within rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS




Figure 9




Figure 10




Figure 11




Figure 12

# TLE2425, TLE2425Y PRECISION VIRTUAL GROUND

SLOS065C – MARCH 1991 – REVISED MAY 1998

## TYPICAL CHARACTERISTICS




Figure 13




Figure 14




Figure 15




Figure 16

---

## macromodel information

```

*   TLE2425 OPERATIONAL AMPLIFIER "MACROMODEL" SUBCIRCUIT
*   CREATED USING PARTS RELEASE 4.03 ON 08/21/90 AT 13:51
*   REV (N/A)      SUPPLY VOLTAGE: 5 V
*   CONNECTIONS: INPUT
*           | COMMON
*           | OUTPUT
*           |
*           3   4   5
*.SUBCKT TLE2425
*
```

---

```

*   OPAMP SECTION
C1    11 12 21.66E-12
C2    6  7  30.00E-12
C3    87 0  10.64E-9
CPSR  85 86 15.9E-9
DCM+  81 82 DX
DCM-  83 81 DX
DC    5  53 DX
DE    54 5  DX
DLN   92 90 DX
DLP   90 91 DX
DP    4  3  DX
ECMR  84 99 (2,99) 1
EGND  99 0  POLY(2)  (3,0)  (4,0)  0   .5  .5
EPSR  85 0  POLY(1)  (3,4)  -16.22E-6 3.24E-6
ENSE  89 2  POLY(1)  (88,0) 120E-6 1
FB    7  99  POLY(6)  VB  VC  VE  VLP VLNVPSR  O  74.8E6 -10E6  10E6  10E6
+ -10E6 74E6
GA    6  0  11 12 320.4E-6
GCM   0  6  10 99 1.013E-9
GPSR  85 86 (85,86) 100E-6
GRC1  4  11 (4,11) 3.204E-4
GRC2  4  12 (4,12) 3.204E-4
GRE1  13 10 (13,10) 1.038E-3
GRE2  14 10 (14,10) 1.038E-3
HLIM  90 0  VLIM  1K
HCMR  80 1  POLY(2)  VCM+  VCM-  0  1E2 1E2
IRP   3  4  146E-6
IEE   3  10 DC  24.05E-6
IIO   2  0  .2E-9
I1    88 0  1E-21
Q1    11 89 13 QX
Q2    12 80 14 QX
R2    6  9  100.0E3
RCM   84 81 1K
REE   10 99 8.316E6
RN1   87 0  2.55E8
RN2   87 88 11.67E3

```

---

# TLE2425, TLE2425Y PRECISION VIRTUAL GROUND

SLOS065C – MARCH 1991 – REVISED MAY 1998

## macromodel information (continued)


```
RO1      8  5   63
RO2      7  99  62
VCM+    82 99  1.0
VCM-    83 99 -2.3
VB       9  0   DC  0
VC       3  53  DC  1.400
VE       54  4   DC  1.400
VLIM     7  8   DC  0
VLP      91  0   DC  30
VLN      0  92  DC  30
VPSR     0  86  DC  0
RFB      5  2   1K
RIN      30  1   1K
RCOM     34  4   .1
*REGULATOR SECTION
RG1      30  0   20MEG
RG2      30  31  .2
RG3      31  35  400K
RG4      35  34  411K
RG5      31  36  25MEG
HREG     31  32  POLY(2)  VPSET  VNSET  0  1E2 1E2
VREG     32  33  DC  0V
EREG     33  34  POLY(1)  (36,34)  1.23  1
VADJ     36  34  1.27V
HPSET    37  0   VREG   1.030E3
VPSET    38  0   DC  20V
HNSET    39  0   VREG   6.11E5
VNSET    40  0   DC  -20V
DSUB     4  34  DX
DPOS     37  38  DX
DNNEG    40  39  DX
.MODEL DX D(IS=800.0E-18)
.MODEL QX PNP(IS=800.0E-18 BF=480)
.ENDS
```

## MECHANICAL INFORMATION

D (R-PDSO-G\*\*)

PLASTIC SMALL-OUTLINE PACKAGE

14 PIN SHOWN



- NOTES: A. All linear dimensions are in inches (millimeters).  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion, not to exceed 0.006 (0,15).  
 D. Falls within JEDEC MS-012


# TLE2425, TLE2425Y PRECISION VIRTUAL GROUND

SLOS065C – MARCH 1991 – REVISED MAY 1998

## MECHANICAL INFORMATION

JG (R-GDIP-T8)

CERAMIC DUAL-IN-LINE PACKAGE




- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. This package can be hermetically sealed with a ceramic lid using glass frit.
  - D. Index point is provided on cap for terminal identification only on press ceramic glass frit seal only.
  - E. Falls within MIL-STD-1835 GDIP1-T8

**MECHANICAL INFORMATION**

LP (O-PBCY-W3)

PLASTIC CYLINDRICAL PACKAGE



- NOTES:
- All linear dimensions are in inches (millimeters).
  - This drawing is subject to change without notice.
  - Lead dimensions are not controlled within this area.
  - Falls within JEDEC TO-226AA (TO-226AA replaces TO-92)

### **IMPORTANT NOTICE**

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.