





TG12864C(L)

TINSHARP ELECTRONICS CO.LTD

EXTERNAL DIMENSIONS AND DISPLAY PATTERN



TYPE	A	B
LED B/L	12.0	7.50
Without B/L	9.10	4.60



A-DETAL
Unit:mm

MECHANICAL DATA (Nominal dimensions)

ITEM	SPECIFICATION	UNIT
Module Size(WxH)	78.0x70.0	mm
Viewing Area(WxH)	62.0x44.0	mm
Internal Area(WxH)	56.27x38.35	mm
Dot pitch(WxH)	0.60x0.44	mm
Dot Size(WxH)	0.55x0.39	mm
DOTS	128X64	dot

Absolute Maximum Ratings

Item	Symbol	Condition	Standard Value		unit
			min	max	
Supply Voltage for Logic	$V_{DD}-V_{SS}$	$T_a=25^{\circ}\text{C}$	0	6.5	V
Supply Voltage for LCD	$V_{DD}-V_E$		0	18.0	V
Input Voltage	V_i		0	V_{DD}	V


PIN CONFIGURATION

ITEM	SYMBOL	Level	DESCRIPTION
1	/CS1	L	Chip select signal for IC1
2	/CS2	L	Chip select signal for IC2
3	GND	0V	Ground(LED-)
4	VDD	+5V	(LED+)
5	V0	-	For LCD driving voltage (variable)
6	D/I	H/L	H:Display data L:Display instruction
7	R/W	H/L	H:Read signal L:Write signal
8	E	H/L	Enable signal
9-16	DB0-DB7	-	Data bus

ELECTRICAL CHARACTERISTICS

Item	Symbol	Condition	Standard value			Unit
			min.	typ.	max.	
Supply Voltage for Logic	$V_{DD}-V_{SS}$	-	4.75	5.0	5.25	V
Supply Voltage for LCD	$V_{DD}-V_0$	-	-	13.0	-	V
Input high Voltage	V_{IH}	-	$0.7V_{DD}$	-	V_{DD}	V
Input low Voltage	V_{IL}	-	0	-	$0.3V_{DD}$	V
Supply Current for Logic	V_{OH}	$-I_{OH}=0.2\text{mA}$	-	4.0	-	mA
Supply Current for LCD	V_{OL}	$I_{OL}=1.2\text{mA}$	-	3.0	-	mA
With B/L	I_{LED}	$V_{DD}=5.0\text{V}$	-	150	-	mA
Drive method	1/64Duty 1/9Bias					

Power supply



Block diagram

