

BIPOLAR ANALOG INTEGRATED CIRCUIT

μ PC78L00 SERIES

THREE TERMINAL POSITIVE VOLTAGE REGULATORS

DESCRIPTION

The μ PC78L00 series are monolithic three terminal positive regulators which employ internally current limiting, thermal shut down, output transistor safe area protection make them essentially indestructible.

They are intended as fixed voltage regulators in a wide range of application including local on card regulation for elimination of distribution problems associated with single point regulation.

FEATURES


- Output current in excess of 100 mA.
- Low noise.
- High Ripple Rejection.
- Internal output transistor safe area protection.
- Internal thermal overload protection.
- Internal short circuit current limiting.

ORDER INFORMATION


Type Number	Output Voltage	Package	Quality Grade
μ PC78L05J	5 V	TO-92	Standard
μ PC78L05T		SOT-89	
μ PC78L06J	6 V	TO-92	
μ PC78L06T		SOT-89	
μ PC78L07J	7 V	TO-92	
μ PC78L07T		SOT-89	
μ PC78L08J	8 V	TO-92	
μ PC78L08T		SOT-89	
μ PC78L10J	10 V	TO-92	
μ PC78L10T		SOT-89	
μ PC78L12J	12 V	TO-92	
μ PC78L12T		SOT-89	
μ PC78L15J	15 V	TO-92	
μ PC78L15T		SOT-89	

CONNECTION DIAGRAM


μ PC78L00J Series



μ PC78L00T Series




EQUIVALENT CIRCUIT

ABSOLUTE MAXIMUM RATINGS ($T_a = 25^\circ\text{C}$)

PARAMETER	SYMBOL	RATINGS		UNIT
		μ PC78L00J Series	μ PC78L00T Series	
Input Voltage	V_{IN}	30/35 (Note1)		V
Internal Power Dissipation	P_T	700	400/2000 (Note2)	mW
Operating Ambient Temperature Range	T_{opt}	-20 to +85		°C
Operating Junction Temperature Range	$T_{opt(j)}$	-20 to +150		°C
Storage Temperature Range	T_{stg}	-55 to +150		°C
Thermal Resistance (junction to ambient)	$R_{th(j-a)}$	180	315/62.5 (Note2)	°C/W

(Note 1) μ PC78L05, 06, 07, 08 : 30 V, μ PC78L10, 12, 15 : 35 V(Note 2) with $2.5 \text{ cm}^2 \times 0.7 \text{ mm}$ ceramic substrate

TYPICAL CONNECTION



C1: Required if regulator is located an appreciable distance from power supply filter

C2: More than $0.1 \mu\text{F}$ D1: Needed for $V_{IN} < V_o$ D2: Needed for $V_o < \text{GND}$

RECOMMENDED OPERATING CONDITIONS

CHARACTERISTIC	SYMBOL	TYPE NUMBER	MIN.	TYP.	MAX.	UNIT
Input Voltage	V_{IN}	μ PC78L05	7	10	20	V
		μ PC78L06	8.5	11	21	
		μ PC78L07	9.5	12	22	
		μ PC78L08	10.5	14	23	
		μ PC78L10	12.5	17	25	
		μ PC78L12	14.5	19	27	
		μ PC78L15	17.5	23	30	
Output Current	I_o	All	0	40	70	mA
Operating Temperature Range	T_{opt}	All	-20		+85	°C
Operating Junction Temperature Range	$T_{opt(i)}$	All	-20		+125	°C

ELECTRICAL CHARACTERISTICS μ PC78L05(V_{IN} = 10 V, I_o = 40 mA, 0 °C ≤ T_j ≤ +125 °C, C_{IN} = 0.33 μF, C_{OUT} = 0.1 μF)

CHARACTERISTIC	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Output Voltage	V_o	T _j = 25 °C	4.8	5.0	5.2	V
		7 V ≤ V _{IN} ≤ 20 V, 1 mA ≤ I _o ≤ 40 mA	4.75		5.25	
		V _{IN} = 10 V, 1 mA ≤ I _o ≤ 70 mA	4.75		5.25	
Line Regulation	REG_{IN}	T _j = 25 °C, 7 V ≤ V _{IN} ≤ 20 V		6	150	mV
		T _j = 25 °C, 8 V ≤ V _{IN} ≤ 20 V		4	100	
Load Regulation	REG_L	T _j = 25 °C, 1 mA ≤ I _o ≤ 100 mA		9	60	mV
		T _j = 25 °C, 1 mA ≤ I _o ≤ 40 mA		4	30	
Quiescent Current	I _{BIAS}	T _j = 25 °C		2.3	5.5	mA
Quiescent Current Change	ΔI_{BIAS}	8 V ≤ V _{IN} ≤ 20 V, I _o = 40 mA			1.5	mA
		V _{IN} = 10 V, 1 mA ≤ I _o ≤ 40 mA			0.1	
Output Noise Voltage	V _n	T _j = 25 °C, 10 Hz ≤ f ≤ 100 kHz		45	120	μ V _{r.m.s.}
Ripple Rejection	R · R	T _j = 25 °C, f = 120 Hz, 8 V ≤ V _{IN} ≤ 18 V	55	75		dB
Dropout Voltage	V _{DIF}	T _j = 25 °C		1.7		V
Short Circuit Current	I _{short}	T _j = 25 °C, V _{IN} = 20 V		88		mA
Peak Output Current	I _{peak}	T _j = 25 °C	125	160	205	mA
Temperature coefficient of Output Voltage	$\Delta V_o/\Delta T$	I _o = 5 mA		0.4		mV/°C

ELECTRICAL CHARACTERISTICS μ PC78L06(V_{IN} = 11 V, I_O = 40 mA, 0 °C ≤ T_j ≤ + 125 °C, C_{IN} = 0.33 μF, C_{OUT} = 0.1 μF)

CHARACTERISTIC	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Output Voltage	V _O	T _j = 25 °C	5.76	6.0	6.24	V
		8.5 V ≤ V _{IN} ≤ 21 V, 1 mA ≤ I _O ≤ 40 mA	5.70		6.30	
		V _{IN} = 11 V, 1 mA ≤ I _O ≤ 70 mA	5.70		6.30	
Line Regulation	REG _{IN}	T _j = 25 °C, 8.5 V ≤ V _{IN} ≤ 21 V		6	155	mV
		T _j = 25 °C, 9 V ≤ V _{IN} ≤ 21 V		4	105	
Load Regulation	REG _L	T _j = 25 °C, 1 mA ≤ I _O ≤ 100 mA		10	65	mV
		T _j = 25 °C, 1 mA ≤ I _O ≤ 40 mA		4	35	
Quiescent Current	I _{BIAS}	T _j = 25 °C		2.3	5.5	mA
Quiescent Current Change	ΔI _{BIAS}	9 V ≤ V _{IN} ≤ 21 V, I _O = 40 mA			1.5	mA
		V _{IN} = 11 V, 1 mA ≤ I _O ≤ 40 mA			0.1	
Output Noise Voltage	V _n	T _j = 25 °C, 10 Hz ≤ f ≤ 100 kHz		55	145	μV _{r.m.s.}
Ripple Rejection	R · R	T _j = 25 °C, f = 120 Hz, 9 V ≤ V _{IN} ≤ 19 V	54	75		dB
Dropout Voltage	V _{DIF}	T _j = 25 °C		1.7		V
Short Circuit Current	I _{Oshort}	T _j = 25 °C, V _{IN} = 21 V		85		mA
Peak Output Current	I _{Opeak}	T _j = 25 °C	125	160	205	mA
Temperature coefficient of Output Voltage	ΔV _O /ΔT	I _O = 5 mA		0.5		mV/°C

ELECTRICAL CHARACTERISTICS μ PC78L07(V_{IN} = 12 V, I_O = 40 mA, 0 °C ≤ T_j ≤ + 125 °C, C_{IN} = 0.33 μF, C_{OUT} = 0.1 μF)

CHARACTERISTIC	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Output Voltage	V _O	T _j = 25 °C	6.72	7.0	7.28	V
		9.5 V ≤ V _{IN} ≤ 22 V, 1 mA ≤ I _O ≤ 40 mA	6.65		7.35	
		V _{IN} = 12 V, 1 mA ≤ I _O ≤ 70 mA	6.65		7.35	
Line Regulation	REG _{IN}	T _j = 25 °C, 9.5 V ≤ V _{IN} ≤ 22 V		8	165	mV
		T _j = 25 °C, 10 V ≤ V _{IN} ≤ 22 V		5	115	
Load Regulation	REG _L	T _j = 25 °C, 1 mA ≤ I _O ≤ 100 mA		12	75	mV
		T _j = 25 °C, 1 mA ≤ I _O ≤ 40 mA		5	35	
Quiescent Current	I _{BIAS}	T _j = 25 °C		2.3	5.5	mA
Quiescent Current Change	ΔI _{BIAS}	10 V ≤ V _{IN} ≤ 22 V, I _O = 40 mA			1.5	mA
		V _{IN} = 12 V, 1 mA ≤ I _O ≤ 40 mA			0.1	
Output Noise Voltage	V _n	T _j = 25 °C, 10 Hz ≤ f ≤ 100 kHz		70	180	μV _{r.m.s.}
Ripple Rejection	R · R	T _j = 25 °C, f = 120 Hz, 10 V ≤ V _{IN} ≤ 20 V	52	74		dB
Dropout Voltage	V _{DIF}	T _j = 25 °C		1.7		V
Short Circuit Current	I _{Oshort}	T _j = 25 °C, V _{IN} = 22 V		83		mA
Peak Output Current	I _{Opeak}	T _j = 25 °C	125	160	205	mA
Temperature coefficient of Output Voltage	ΔV _O /ΔT	I _O = 5 mA		0.6		mV/°C

ELECTRICAL CHARACTERISTICS μ PC78L08(V_{IN} = 14 V, I_O = 40 mA, 0 °C ≤ T_j ≤ + 125 °C, C_{IN} = 0.33 μF, C_{OUT} = 0.1 μF)

CHARACTERISTIC	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Output Voltage	V _O	T _j = 25 °C	7.7	8.0	8.3	V
		10.5 V ≤ V _{IN} ≤ 23 V, 1 mA ≤ I _O ≤ 40 mA	7.6		8.4	
		V _{IN} = 14 V, 1 mA ≤ I _O ≤ 70 mA	7.6		8.4	
Line Regulation	REG _{IN}	T _j = 25 °C, 10.5 V ≤ V _{IN} ≤ 23 V		10	175	mV
		T _j = 25 °C, 11 V ≤ V _{IN} ≤ 23 V		6	125	
Load Regulation	REG _L	T _j = 25 °C, 1 mA ≤ I _O ≤ 100 mA		14	80	mV
		T _j = 25 °C, 1 mA ≤ I _O ≤ 40 mA		6	40	
Quiescent Current	I _{BIAS}	T _j = 25 °C		2.4	5.5	mA
Quiescent Current Change	ΔI _{BIAS}	12 V ≤ V _{IN} ≤ 23 V, I _O = 40 mA			1.5	mA
		V _{IN} = 14 V, 1 mA ≤ I _O ≤ 40 mA			0.1	
Output Noise Voltage	V _n	T _j = 25 °C, 10 Hz ≤ f ≤ 100 kHz		85	190	μV _{r.m.s.}
Ripple Rejection	R · R	T _j = 25 °C, f = 120 Hz, 12 V ≤ V _{IN} ≤ 22 V	51	73		dB
Dropout Voltage	V _{DIF}	T _j = 25 °C		1.7		V
Short Circuit Current	I _{Oshort}	T _j = 25 °C, V _{IN} = 23 V		80		mA
Peak Output Current	I _{Opeak}	T _j = 25 °C	125	160	205	mA
Temperature coefficient of Output Voltage	ΔV _O /ΔT	I _O = 5 mA		0.6		mV/°C

ELECTRICAL CHARACTERISTICS μ PC78L10(V_{IN} = 17 V, I_O = 40 mA, 0 °C ≤ T_j ≤ + 125 °C, C_{IN} = 0.33 μF, C_{OUT} = 0.1 μF)







CHARACTERISTIC	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Output Voltage	V _O	T _j = 25 °C	9.6	10	10.4	V
		12.5 V ≤ V _{IN} ≤ 25 V, 1 mA ≤ I _O ≤ 40 mA	9.5		10.5	
		V _{IN} = 17 V, 1 mA ≤ I _O ≤ 70 mA	9.5		10.5	
Line Regulation	REG _{IN}	T _j = 25 °C, 12.5 V ≤ V _{IN} ≤ 25 V		12	200	mV
		T _j = 25 °C, 13 V ≤ V _{IN} ≤ 25 V		8	150	
Load Regulation	REG _L	T _j = 25 °C, 1 mA ≤ I _O ≤ 100 mA		18	90	mV
		T _j = 25 °C, 1 mA ≤ I _O ≤ 40 mA		8	45	
Quiescent Current	I _{BIAS}	T _j = 25 °C		2.5	5.5	mA
Quiescent Current Change	ΔI _{BIAS}	13 V ≤ V _{IN} ≤ 25 V, I _O = 40 mA			1.5	mA
		V _{IN} = 17 V, 1 mA ≤ I _O ≤ 40 mA			0.1	
Output Noise Voltage	V _n	T _j = 25 °C, 10 Hz ≤ f ≤ 100 kHz		100	230	μV _{r.m.s.}
Ripple Rejection	R · R	T _j = 25 °C, f = 120 Hz, 14 V ≤ V _{IN} ≤ 24 V	49	69		dB
Dropout Voltage	V _{DIF}	T _j = 25 °C		1.7		V
Short Circuit Current	I _{Oshort}	T _j = 25 °C, V _{IN} = 25 V		70		mA
Peak Output Current	I _{Opeak}	T _j = 25 °C	125	160	205	mA
Temperature coefficient of Output Voltage	ΔV _O /ΔT	I _O = 5 mA		0.8		mV/°C





ELECTRICAL CHARACTERISTICS μ PC78L12(V_{IN} = 19 V, I_O = 40 mA, 0 °C ≤ T_j ≤ +125 °C, C_{IN} = 0.33 μF, C_{OUT} = 0.1 μF)


CHARACTERISTIC	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Output Voltage	V _O	T _j = 25 °C	11.5	12	12.5	V
		14 V ≤ V _{IN} ≤ 27 V, 1 mA ≤ I _O ≤ 40 mA	11.4		12.6	
		V _{IN} = 19 V, 1 mA ≤ I _O ≤ 70 mA	11.4		12.6	
Line Regulation	REG _{IN}	T _j = 25 °C, 14.5 V ≤ V _{IN} ≤ 27 V		14	250	mV
		T _j = 25 °C, 16 V ≤ V _{IN} ≤ 27 V		10	200	
Load Regulation	REG _L	T _j = 25 °C, 1 mA ≤ I _O ≤ 100 mA		20	100	mV
		T _j = 25 °C, 1 mA ≤ I _O ≤ 40 mA		10	50	
Quiescent Current	I _{BIAS}	T _j = 25 °C		2.6	5.5	mA
Quiescent Current Change	ΔI _{BIAS}	16 V ≤ V _{IN} ≤ 27 V, I _O = 40 mA			1.5	mA
		V _{IN} = 19 V, 1 mA ≤ I _O ≤ 40 mA			0.1	
Output Noise Voltage	V _n	T _j = 25 °C, 10 Hz ≤ f ≤ 100 kHz		115	280	μV _{r.m.s.}
Ripple Rejection	R · R	T _j = 25 °C, f = 120 Hz, 15 V ≤ V _{IN} ≤ 25 V	47	66		dB
Dropout Voltage	V _{DIF}	T _j = 25 °C		1.7		V
Short Circuit Current	I _{Oshort}	T _j = 25 °C, V _{IN} = 27 V		64		mA
Peak Output Current	I _{Opeak}	T _j = 25 °C	125	160	205	mA
Temperature coefficient of Output Voltage	ΔV _O /ΔT	I _O = 5 mA		1.1		mV/°C

ELECTRICAL CHARACTERISTICS μ PC78L15(V_{IN} = 23 V, I_O = 40 mA, 0 °C ≤ T_j ≤ +125 °C, C_{IN} = 0.33 μF, C_{OUT} = 0.1 μF)

CHARACTERISTIC	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Output Voltage	V _O	T _j = 25 °C	14.4	15	15.6	V
		17.5 V ≤ V _{IN} ≤ 30 V, 1 mA ≤ I _O ≤ 40 mA	14.25		15.75	
		V _{IN} = 23 V, 1 mA ≤ I _O ≤ 70 mA	14.25		15.75	
Line Regulation	REG _{IN}	T _j = 25 °C, 17.5 V ≤ V _{IN} ≤ 30 V		18	300	mV
		T _j = 25 °C, 20 V ≤ V _{IN} ≤ 30 V		13	250	
Load Regulation	REG _L	T _j = 25 °C, 1 mA ≤ I _O ≤ 100 mA		25	150	mV
		T _j = 25 °C, 1 mA ≤ I _O ≤ 40 mA		12	75	
Quiescent Current	I _{BIAS}	T _j = 25 °C		2.7	5.5	mA
Quiescent Current Change	ΔI _{BIAS}	20 V ≤ V _{IN} ≤ 30 V, I _O = 40 mA			1.5	mA
		V _{IN} = 23 V, 1 mA ≤ I _O ≤ 40 mA			0.1	
Output Noise Voltage	V _n	T _j = 25 °C, 10 Hz ≤ f ≤ 100 kHz		135	350	μV _{r.m.s.}
Ripple Rejection	R · R	T _j = 25 °C, f = 120 Hz, 18.5 V ≤ V _{IN} ≤ 28.5 V	45	61		dB
Dropout Voltage	V _{DIF}	T _j = 25 °C		1.7		V
Short Circuit Current	I _{Oshort}	T _j = 25 °C, V _{IN} = 30 V		53		mA
Peak Output Current	I _{Opeak}	T _j = 25 °C	125	160	205	mA
Temperature coefficient of Output Voltage	ΔV _O /ΔT	I _O = 5 mA		1.4		mV/°C

TYPICAL CHARACTERISTICS ($T_a = 25^\circ\text{C}$)




PACKAGE DIMENSIONS (Unit: mm) μ PC78L00J Series**3 PIN PLASTIC SIP (TO-92)****NOTE**

Each lead centerline is located within 0.12 mm (0.005 inch) of its true position (T.P.) at maximum material condition.

P3J-127B

ITEM	MILLIMETERS	INCHES
A	5.2 MAX.	0.205 MAX.
F	$0.5^{+0.1}$	$0.02^{+0.005}$
G	0.12	0.005
H	1.27	0.05
J	1.33 MAX.	0.053 MAX.
M	5.5 MAX.	0.217 MAX.
N	4.2 MAX.	0.166 MAX.
U	2.8 MAX.	0.111 MAX.
V	$0.5^{+0.1}$	$0.02^{+0.005}$
Y	$15.0^{+0.7}$	$0.591^{+0.028}$

μ PC78L00T Series

RECOMMENDED SOLDERING CONDITIONS

The following conditions (see table below) must be met when soldering this product.

Please consult with our sales offices in case other soldering process is used, or in case soldering is done under different conditions.

<TYPES OF SURFACE MOUNT DEVICE>

For more details, refer to our document "SMT MANUAL" (IEI-1207).

[μ PC78L00T Series]

Soldering process	Soldering condition	Symbol
Infrared ray reflow	Peak package's surface temperature: 230 °C or below, Reflow time: 30 seconds or below (210 °C or higher), Number of reflow process: 1, Exposure limit*: None	IR30-00
VPS	Peak package's surface temperature: 215 °C or below, Reflow time: 40 seconds or below (200 °C or higher), Number of reflow process: 1, Exposure limit*: None	VP15-00

*: Exposure limit before soldering after dry-pack package is opened. Storage conditions: 25 °C and relative humidity at 65% or less.

Note: Do not apply more than a single process at once, except for "Partial heating method".

<TYPES OF THROUGH HOLE MOUNT DEVICE>

[μ PC78L00J Series]

Soldering process	Soldering condition	Symbol
Wave soldering	Solder temperature: 260 °C or below, Flow time: 10 seconds or below	

Reference

Application note name	No.
Quality control of NEC semiconductor devices	TEI-1202
Quality control guide of semiconductor devices	MEI-1202
Assembly manual of semiconductor devices	IEI-1207
NEC semiconductor device reliability/quality control system	IEI-1212

No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Corporation. NEC Corporation assumes no responsibility for any errors which may appear in this document.

NEC Corporation does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from use of a device described herein or any other liability arising from use of such device. No license, either express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Corporation or others.

The devices listed in this document are not suitable for use in aerospace equipment, submarine cables, nuclear reactor control systems and life support systems. If customers intend to use NEC devices for above applications or they intend to use "Standard" quality grade NEC devices for applications not intended by NEC, please contact our sales people in advance.

Application examples recommended by NEC Corporation.

Standard: Computer, Office equipment, Communication equipment, Test and Measurement equipment, Machine tools, Industrial robots, Audio and Visual equipment, Other consumer products, etc.

Special: Automotive and Transportation equipment, Traffic control systems, Antidisaster systems, Anticrime systems, etc.