


ULTRA-FAST GLASS PASSIVATED RECTIFIER
VOLTAGE RANGE 50 TO 1000 Volts Current 1 Ampere

FEATURES

- * Ultra-fast recovery time for high efficiency
- * Glass Passivated Chip junction
- * Excellent high temperature switching
- * Low leakage
- * High temperature soldering guaranteed
260 °C/10 seconds, 0.375"(9.5 mm) lead length
at 5 lbs(2.3kg) tension

MECHANICAL DATA

- * Case : Transfer Molded Plastic
- * Epoxy: UL94V-O rate flame retardant
- * Terminals : Solderable Per MIL-STD-202 Method 208
- * Polarity : Color band denotes cathode end
- * Mounting position: Any
- * Weight : 0.012 ounce. 0.33 gram (approx)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- * Rating at 25 °C ambient temperature unless otherwise specified
* Single phase-half wave. 60Hz, resistive or inductive load.
* For capacitive load derate current by 20 %

[illegible]

UF1001 Thru UF1007

FIG-1 TYPICAL FORWARD CHARACTERISTICS




FIG-3 FORWARD CURRENT DERATING CURVE




FIG-2 TYPICAL REVERSE CHARACTERISTICS




FIG-4 TYPICAL JUNCTION CAPACITANCE







FIG-5 PEAK FORWARD SURGE CURRENT



- Notes:
 1. Rise Time = 7 ns max. Input Impedance = 1 M Ω , 22 pF
 2. Rise Time = 10 ns max. Input Impedance = 50 Ω



Set time base for 20/50 ns/cm

FIG-6 Reverse Recovery Time Characteristic and Test Circuit Diagram