

	Ausgabe	1	Erstellt	22.11.99 Sz																																
	1. Änderung		2. Änderung																																	
Top view dimensions: 86.5 max, 49 max, 38±0.4, 71 max, 52 max, 36.5 ±0.3, 15 ±0.3. A circular arrow indicates rotation. A screw is labeled M4. Side view dimension: 27 max. <table><tr><td>Frequency</td><td>:</td><td>1680...1920MHz</td><td></td></tr><tr><td>Temperature range</td><td>:</td><td>0 ...+50°C</td><td>-20...+60°C</td></tr><tr><td>Isolation</td><td>:</td><td>min 25dB</td><td>min 23dB</td></tr><tr><td>Insertion loss</td><td>:</td><td>max 0.35dB</td><td>max 0.4dB</td></tr><tr><td>VSWR</td><td>:</td><td>max 1.12</td><td>max 1.15</td></tr><tr><td>Power</td><td>:</td><td>50W cw</td><td>50W cw</td></tr><tr><td>Connectors</td><td>:</td><td>N (3xfemale)</td><td></td></tr><tr><td>Dimensions</td><td>:</td><td>49x52x27 mm</td><td></td></tr></table>					Frequency	:	1680...1920MHz		Temperature range	:	0 ...+50°C	-20...+60°C	Isolation	:	min 25dB	min 23dB	Insertion loss	:	max 0.35dB	max 0.4dB	VSWR	:	max 1.12	max 1.15	Power	:	50W cw	50W cw	Connectors	:	N (3xfemale)		Dimensions	:	49x52x27 mm	
Frequency	:	1680...1920MHz																																		
Temperature range	:	0 ...+50°C	-20...+60°C																																	
Isolation	:	min 25dB	min 23dB																																	
Insertion loss	:	max 0.35dB	max 0.4dB																																	
VSWR	:	max 1.12	max 1.15																																	
Power	:	50W cw	50W cw																																	
Connectors	:	N (3xfemale)																																		
Dimensions	:	49x52x27 mm																																		
	Art	Circulator	Artikel-Nr. 2722 162 03911																																	
	Typ	VAS 391	Blatt-Nr.																																	
bearbeitet :		geprüft :	VALVO Bauelemente GmbH, Hamburg																																	