


## VOLTAGE-CONTROLLED CRYSTAL OSCILLATOR

**VG-1011JA series**

- High accuracy and high reliability due to trimmerless design.
- Built-in heat resistive AT-cut crystal provides heat resistance equivalent to that of general-purpose ICs.
- Use of C-MOS IC assures low current consumption.
- Excellent shock resistance and environmental capability.
- Supply voltage: 5V




## ■ Specifications (characteristics)

Item	Symbol	Specifications	Remarks
Output frequency range	$f_o$	1.5000 MHz to 28.63636 MHz	
Power source voltage	Max. supply voltage	$V_{DD-GND}$	-0.5V to +7.0V
	Operating voltage	$V_{DD}$	5.0V $\pm$ 0.5V
Temperature range	Storage temperature	$T_{STG}$	-55°C to +125°C
	Operating temperature	$T_{OPR}$	As per below table
Soldering condition	$T_{SOL}$	Twice at under 260°C within 10 sec.	
Frequency stability	$\Delta f/f_o$	As per below table	
Current consumption	$I_{OP}$	10mA max.	No load condition
Pull range	$\Delta f_c$	As per below table	$V_c=2.5\pm 2.0V$
Input resistance	$Z_{IN}$	10M $\Omega$ min.	DC Level
Frequency change polarity		Positive polarity	$V_c=0.5$ to 4.5V
Duty	$t_w/t$	40% to 60%	1.4V or 1/2VDD level
Output voltage	$V_{OH}$	$V_{DD}-0.4V$ min.	$I_{OH}= -0.8mA$
	$V_{OL}$	0.4V max.	$I_{OL}=1.6mA$
Output load condition (fan out)	N/CL	2TTL or 15pF max.	TTL load/C-MOS load
Output rise time	$t_{TLH}$	8ns. max.	C-MOS load: 20% $\rightarrow$ 80% $V_{DD}$
		5ns. max.	TTL load: 0.4V $\rightarrow$ 2.4V
Output fall time	$t_{THL}$	8ns. max.	C-MOS load: 80% $\rightarrow$ 20% $V_{DD}$
		5ns. max.	TTL load: 2.4V $\rightarrow$ 0.4V
Oscillation start up time	$t_{OSC}$	4ms. max.	Time at 4.5V to be 0 sec.
Aging	$f_a$	$\pm 5ppm$ max.	$T_a=25^\circ C$ , $V_{DD}=5V$ , first year
Shock resistance	S.R.	$\pm 5ppm$ max.	Three drops on a hard board from 75 cm or excitation test with 3000G x 0.3ms x 1/2sine wave in 3 directions

Note: • Please contact us for inquiries about operating temperature, frequency stability, pull range.

## ■ External dimensions

(Unit: mm)



## ■ Stability / Temperature range


## ■ Pull range

Stability	No.	Temperature range			No.	Pull range
		-20°C to 70°C	-30°C to 75°C	-40°C to 85°C		
$\pm 15ppm$	S	-	B	-	B	$\pm 20ppm$ min.
$\pm 20ppm$	A	G, K, N	-	-	G	$\pm 50ppm$ min.
$\pm 25ppm$	B	-	-	G, K, N	K	$\pm 75ppm$ min.
					N	$\pm 100ppm$ min.

Please consult us for AVN type device.

## ■ Recommended soldering pattern

(Unit: mm)



# THE CRYSTALMASTER




## ENERGY SAVING EPSON

EPSON offers effective savings to its customers through a wide range of electronic devices, such as semiconductors, liquid crystal display (LCD) modules, and crystal devices. These savings are achieved through a sophisticated melding of three different efficiency technologies.

Power saving technology provides low power consumption at low voltages.

Space saving technology provides further reductions in product size and weight through super-precise processing and high-density assembly technology.

Time saving technology shortens the time required for design and development on the customer side and shortens delivery times.



Our concept of Energy Saving technology conserves resources by blending the essence of these three efficiency technologies. The essence of these technologies is represented in each of the products that we provide to our customers.

In the industrial sector, leading priorities include measures to counter the greenhouse effect by reducing CO<sub>2</sub>, measures to preserve the global environment, and the development of energy-efficient products. Environmental problems are of global concern, and although the contribution of energy-saving technology developed by EPSON may appear insignificant, we seek to contribute to the development of energy-saving products by our customers through the utilization of our electronic devices. EPSON is committed to the conservation of energy, both for the sake of people and of the planet on which we live.

**Resource Saving**



**SEIKO EPSON CORP. QUARTZ DEVICE DIVISION acquired ISO9001 and ISO14001 certification by B.V.Q.I. (Bureau Veritas Quality International) .**

**ISO9001 in October, 1992.**

**ISO14001 in November, 1997.**

### NOTICE

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. This material or portions thereof may contain technology or the subject relating to strategic products under the control of the Foreign Exchange and Foreign Trade Control Law of Japan and may require an export license from the Ministry of International Trade and Industry or other approval from another government agency.