





VCSEL/LD Division



Unit: mm
Bottom View

- 1.Case
- 2.VCSEL Anode
- 3.VCSEL Cathode
- 4.NC

850nm VCSEL in To-46 Package

1. Feature:

- a. Ion-implant process
- b. Ball Lens Window
- c. High speed ≥ 1.25 Gbps

2. Application:

- a. High-speed data communications and telecommunications applications
- b. Gigabit Ethernet
- c. Fiber Channel
- d. ATM transceiver modules and system

3. Part Number: **VX-TI11-4BO1**

4. Optical and Electrical Characteristics

Parameter	Symbol	Min.	TYP.	Max.	Unit	Test Condition
Peak Wavelength	λ_p	830	845	860	nm	$I_f = 12\text{mA@RT}$
Spectral Width (RMS)	$\Delta\lambda$			0.85	nm	$I_f = 12\text{mA@RT}$
Beam Divergence	Θ		15	20	Deg	Full width at $1/e^2$; $I_f = 12\text{mA@RT}$
Forward Voltage	V_f	1.7	2.0	2.4	V	$I_f = 12\text{mA@RT}$
Threshold Current	I_{th}	2.0	4.5	7	mA	
Slope Efficiency	dP/dI	0.12	0.18	0.32	W/A	$I_f = 12\text{mA@RT}$
Optical output power	P_{out}		1.32		mW	$I_f = 12\text{mA@RT}$
Dynamic Resistance	dV/dI	15	35	45	Ω	$I_f = 12\text{mA@RT}$
Rise / Fall Time	t_r / t_f		100	200	ps	20%-80%
Jitter p-p	t_j		40		ps	
λ_p Temperature Coefficient	$\delta\lambda_p/\delta T$		0.06		nm/ $^{\circ}\text{C}$	$T_A = 0 \sim 70^{\circ}\text{C}$, $I_f = 12\text{mA}$

5. Maximum Ratings

Parameter	Min.	Max.	Unit	Condition
Storage Temperature	-40	100	$^{\circ}\text{C}$	
Operating Temperature	0	70	$^{\circ}\text{C}$	
Continuous Forward Current		15	mA	
Continuous Reverse Voltage		5	V	@10 μA

Note. These specifications are subject to change without notice.

Tel: 323-278-0820
Website: www.axt.com/vcsl

Fax: 323-278-0096
Email: vcsl@axt.com