




VDSGLD @ 38.88 MHz

Voltage Controlled Crystal Oscillator

Pin Information

Table 1. Pin Function

Pin	Symbol	Function
1	V _C	Control Voltage
2	Tri-State	TTL logic low disables output TTL logic high enables output waveform
3	GND	Case Ground
4	Output	Output waveform
5	TTL/CMOS	TTL logic low for CMOS optimized symmetry TTL logic high or no connection for TTL optimized symmetry
6	V _{CC}	Power Supply Voltage (3.3 V ±10%)



Performance Characteristics

Table 2. Electrical Performance

Parameter	Symbol	Minimum	Typical	Maximum	Units
Nominal Output Frequency	f ₀	-	38.88	-	MHz
Supply Voltage ¹	V _{DD}	2.97	3.3	3.63	V
Operating Temperature Range	T _O	-40		85	°C
Supply Current	I _{DD}			20	mA
Output Voltage Levels Output Logic High Output Logic Low	V _{OH} V _{OL}	0.9*V _{DD}		0.1*V _{DD}	V
Output Rise/Fall Time ²	T _R /T _F			5	nS
Output Duty Cycle or Symmetry ³	D	45	50	55	%
Absolute Pull Range, V _C = 1.0 to 2.0 V	APR	±5			ppm
Absolute Pull Range, V _C = 0.3 to 3.0 V	APR	±50			ppm
Initial Accuracy (V _C = 1.65V @25°C)		-20		+20	ppm
Linearity				20	%
Start up time (To reach 90% of final amplitude)				10	ms
Control Voltage Input Impedance		10			MΩ
Control Voltage Leakage Current				100	nA
Control Voltage Bandwidth (-3 dB, V _C = 1.65 V)	BW	10			KHz
Output Load				15	pf

1. A 0.1 μF low frequency tantalum bypass capacitor in parallel with a 0.01 μF high frequency ceramic capacitor is recommended.

2. Figure 1 defines these parameters. Figure 2 illustrates the operating conditions.

3. Duty cycle is defined as (on time/period) per Figure 1.

4. Maximum control Voltage Leakage Current is by design.




Figure 1. Output Waveform




Figure 2. Output Test Conditions (25±5°C)

Outline Diagram




Figure 3. Outline Diagram

Table 3. Ordering Information

V	D	S	G	L	D	38.88
Package	Supply Voltage (V)	Oscillator Type & Special Requirements	APR	Operating Temperature	Duty Cycle Min/Max	Frequency (MHz)
6 Pin Ceramic Leadless Chip Carrier	3.3 ± 10%	Initial Accuracy Vc = 1.65V @ 25°C	±50ppm	-40°C to +85°C	45/55% Tri-State on Pin # 2	Nominal Output Frequency

For Additional Information Please Contact:



USA: Vectron International • 166 Glover Avenue, Norwalk, CT 06856 • Tel: 1-888-VECTRON-1 • Fax: 1-888-FAX-VECTRON
 EUROPE: In Denmark, Finland, Ireland, Italy, Israel, Norway, Spain, UK: Tel: 44 (0) 1703 766 288 • Fax: 44 (0) 1703 766 822
 In Austria, Belgium, France, Germany, Luxembourg, Netherlands, Sweden, Switzerland: Tel: 49(0)7263 6480 • Fax: 49(0)7263 6196
 ASIA: In China, Taiwan, Japan: Tel: 01 603 598 0070 • Fax: 01 603 598 0075
 In Korea, Singapore, Australia, India: Tel: 01 203 853 4433 • Fax: 01 203 853 1423

Vectron International reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information. 4/19/02