



Three Phase Rectifier Bridge with IGBT and Fast Recovery Diode for Braking System

$$V_{RRM} = 1200-1600 \text{ V}$$

$$I_{dAVM} = 70 \text{ A}$$

V_{RRM} V	Type
1200	VUB 71-12 NO1
1600	VUB 71-16 NO1



Symbol	Test Conditions	Maximum Ratings
V_{RRM} I_{dAV} I_{dAVM}	$T_H = 110^\circ\text{C}$, sinusoidal 120° limited by leads	1200 / 1600 V 59 A 70 A
I_{FSM}	$T_{VJ} = 45^\circ\text{C}$, $t = 10 \text{ ms}$, $V_R = 0 \text{ V}$ $T_{VJ} = 150^\circ\text{C}$, $t = 10 \text{ ms}$, $V_R = 0 \text{ V}$	530 A 475 A
I^2t	$T_{VJ} = 45^\circ\text{C}$, $t = 10 \text{ ms}$, $V_R = 0 \text{ V}$ $T_{VJ} = 150^\circ\text{C}$, $t = 10 \text{ ms}$, $V_R = 0 \text{ V}$	1400 A 1130 A
P_{tot}	$T_H = 25^\circ\text{C}$ per diode	90 W
V_{CES} V_{GE}	$T_{VJ} = 25^\circ\text{C}$ to 150°C Continuous	1200 V $\pm 20 \text{ V}$
I_{C25} I_{C80}	$T_H = 25^\circ\text{C}$, DC $T_H = 80^\circ\text{C}$, DC	43 A 29 A
I_{CM}	$t_p = \text{Pulse width limited by } T_{VJM}$	90 A
P_{tot}	$T_H = 80^\circ\text{C}$	160 W
V_{RRM} I_{FAV} I_{FRMS} I_{FRM}	$T_H = 80^\circ\text{C}$, rectangular $d = 0.5$ $T_H = 80^\circ\text{C}$, rectangular $d = 0.5$ $T_H = 80^\circ\text{C}$, $t_p = 10 \mu\text{s}$, $f = 5 \text{ kHz}$	1200 V 9 A 14 A 90 A
I_{FSM}	$T_{VJ} = 45^\circ\text{C}$, $t = 10 \text{ ms}$ $T_{VJ} = 150^\circ\text{C}$, $t = 10 \text{ ms}$	75 A 60 A
P_{tot}	$T_H = 25^\circ\text{C}$	40 W
T_{VJ} T_{VJM} T_{stg}		$-40 \dots +150^\circ\text{C}$ 150 $^\circ\text{C}$ $-40 \dots +125^\circ\text{C}$
V_{ISOL}	50/60 Hz $I_{ISOL} \leq 1 \text{ mA}$ $t = 1 \text{ min}$ $t = 1 \text{ s}$	3000 V~ 3600 V~
M_d	Mounting torque (M5) (10-32 unf)	2-2.5 Nm 18-22 lb.in.
Weight	typ.	35 g

Features

- Soldering connections for PCB mounting
- Isolation voltage 3600 V~
- Ultrafast freewheeling diode
- Convenient package outline
- UL registered E 72873
- Thermistor



Applications

- Drive Inverters with brake system

Advantages

- 2 functions in one package
- No external isolation necessary
- Easy to mount with two screws
- Suitable for wave soldering
- High temperature and power cycling capability

Dimensions in mm (1 mm = 0.0394")



Data according to IEC 60747
IXYS reserves the right to change limits, test conditions and dimensions.

Symbol	Test Conditions	Characteristic Values ($T_{VJ} = 25^{\circ}\text{C}$, unless otherwise specified)		
		min.	typ.	max.
I_R	$V_R = V_{RRM}^1$ $T_{VJ} = 25^{\circ}\text{C}$ $V_R = V_{RRM}^1$ $T_{VJ} = 150^{\circ}\text{C}$			0.1 mA 3 mA
V_F	$I_F = 25 \text{ A}$, $T_{VJ} = 25^{\circ}\text{C}$			1.3 V
V_{T0} r_T	For power-loss calculations only $T_{VJ} = 150^{\circ}\text{C}$			0.85 V 8.5 m Ω
R_{thJH}	per diode			1.42 K/W
$V_{BR(CES)}$ $V_{GE(th)}$	$V_{GS} = 0 \text{ V}$, $I_C = 3 \text{ mA}$ $I_C = 10 \text{ mA}$	1200 5		V V
I_{GES}	$V_{GE} = \pm 20 \text{ V}$			500 nA
I_{CES}	$T_{VJ} = 25^{\circ}\text{C}$, $V_{CE} = V_{CES}$ $T_{VJ} = 125^{\circ}\text{C}$, $V_{CE} = 0.8 V_{CES}$			700 μA 1.5 mA
V_{CEsat}	$V_{GE} = 15 \text{ V}$, $I_C = 25 \text{ A}$			2.9 V
t_{SC} (SCSOA)	$V_{GE} = 15 \text{ V}$, $V_{CE} = 600 \text{ V}$, $T_{VJ} = 125^{\circ}\text{C}$, $R_G = 22 \Omega$, non repetitive			10 μs
RBSOA	$V_{GE} = 15 \text{ V}$, $V_{CE} = 800 \text{ V}$, $T_{VJ} = 125^{\circ}\text{C}$, $R_G = 22 \Omega$, Clamped Inductive load, $L = 100 \mu\text{H}$			50 A
C_{ies}	$V_{CE} = 25 \text{ V}$, $f = 1 \text{ MHz}$, $V_{GE} = 0 \text{ V}$	4.5		nF
$t_{d(on)}$ $t_{d(off)}$ t_{fi} E_{on} E_{off}	$V_{CE} = 600 \text{ V}$, $I_C = 25 \text{ A}$ $V_{GE} = 15 \text{ V}$, $R_G = 22 \Omega$ Inductive load; $L = 100 \mu\text{H}$ $T_{VJ} = 125^{\circ}\text{C}$	300 350 1600 6 8		ns ns ns mJ mJ
R_{thJH}				0.8 K/W
I_R	$V_R = V_{RRM}^1$ $T_{VJ} = 25^{\circ}\text{C}$ $V_R = 800 \text{ V}$, $T_{VJ} = 150^{\circ}\text{C}$		4	0.2 mA 6 mA
V_F	$I_F = 12 \text{ A}$, $T_{VJ} = 25^{\circ}\text{C}$			2.7 V
V_{T0} r_T	For power-loss calculations only $T_{VJ} = 150^{\circ}\text{C}$			1.65 V 46 m Ω
I_{RM}	$I_F = 25 \text{ A}$, $-di_F/dt = 100 \text{ A}/\mu\text{s}$ $V_R = 100 \text{ V}$	6.5		7 A
t_{rr}	$I_F = 1 \text{ A}$, $-di_F/dt = 100 \text{ A}/\mu\text{s}$ $V_R = 30 \text{ V}$	50		70 ns
R_{thJH}				3.12 K/W
R_{25}	NTC Siemens Typ S 891/2,2k/+9			2,2 k Ω
d_s d_A a	Creep distance on surface Strike distance in air Maximum allowable acceleration			12.7 mm 9.4 mm 50 m/s ²