


Features

- 184 Pin Unbuffered 33,554,432 x 64 bit Organization DDR SDRAM Modules
- Utilizes High Performance 32M x 8 DDR SDRAM in TSOPII-66 Packages
- Single +2.5V ($\pm 0.2V$) Power Supply
- Single +2.6V ($\pm 0.1V$) Power Supply for DDR400
- Programmable CAS Latency, Burst Length, and Wrap Sequence (Sequential & Interleave)
- Auto Refresh (CBR) and Self Refresh
- All Inputs, Outputs are SSTL-2 Compatible
- 8192 Refresh Cycles every 64 ms
- Serial Presence Detect (SPD)


Description


The V826632K24S memory module is organized 33,554,432 x 64 bits in a 184 pin memory module. The 32M x 64 memory module uses 8 Mosel-Vitellic 32M x 8 DDR SDRAM. The x64 modules are ideal for use in high performance computer systems where increased memory density and fast access times are required.

	Module Speed	D4	D3	D0	C0	B1	B0	A1	Units
t_{CK}	Clock Frequency (max.)	200 (PC400C)	200 (PC400B)	200 (PC400A)	166 (PC333)	143 (PC266A)	133 (PC266B)	125 (PC200)	MHz
t_{AC}	Clock Cycle Time CAS Latency = 2	7.5	7.5	7.5	7.5	7.5	10	10	ns
t_{AC}	Clock Cycle Time CAS Latency = 2.5	6	6	5	6	7	7.5	8	ns
t_{AC}	Clock Cycle Time CAS Latency = 3	5	5	5	-	-	-	-	ns
t_{RCD}	t_{RP} parameter	4	3	3	3	2	3	2	CLK
t_{RP}	t_{RCD} parameter	4	3	3	3	2	3	2	CLK



Part Number Information



Block Diagram

Pin Configurations (Front Side/Back Side)

Pin	Front	Pin	Front	Pin	Front	Pin	Back	Pin	Back	Pin	Back
1	VREF	32	A5	62	VDDQ	93	VSS	124	VSS	154	RAS
2	DQ0	33	DQ24	63	WE	94	DQ4	125	A6	155	DQ45
3	VSS	34	VSS	64	DQ41	95	DQ5	126	DQ28	156	VDDQ
4	DQ1	35	DQ25	65	CAS	96	VDDQ	127	DQ29	157	CS0
5	DQS0	36	DQS3	66	VSS	97	DM0	128	VDDQ	158	CS1
6	DQ2	37	A4	67	DQS5	98	DQ6	129	DM3	159	DM5
7	VDD	38	VDD	68	DQ42	99	DQ7	130	A3	160	VSS
8	DQ3	39	DQ26	69	DQ43	100	VSS	131	DQ30	161	DQ46
9	NC	40	DQ27	70	VDD	101	NC	132	VSS	162	DQ47
10	NC	41	A2	71	NC	102	NC	133	DQ31	163	NC
11	VSS	42	Vss	72	DQ48	103	A13*	134	CB4*	164	VDDQ
12	DQ8	43	A1	73	DQ49	104	VDDQ	135	CB5*	165	DQ52
13	DQ9	44	CB0*	74	VSS	105	DQ12	136	VDDQ	166	DQ53
14	DQS1	45	CB1*	75	CK2	106	DQ13	137	CK0*	167	NC
15	VDDQ	46	VDD	76	CK2	107	DM1	138	CK0*	168	VDD
16	CK1	47	DQS8*	77	VDDQ	108	VDD	139	VSS	169	DM6
17	CK1	48	A0	78	DQS6	109	DQ14	140	DM8*	170	DQ54
18	VSS	49	CB2*	79	DQ50	110	DQ15	141	A10	171	DQ55
19	DQ10	50	VSS	80	DQ51	111	CKE1	142	CB6*	172	VDDQ
20	DQ11	51	CB3*	81	VSS	112	VDDQ	143	VDDQ	173	NC
21	CKE0	52	BA1	82	VDDID	113	BA2*	144	CB7*	174	DQ60
22	VDDQ	Key		83	DQ56	114	DQ20	Key		175	DQ61
23	DQ16	53	DQ32	84	DQ57	115	A12	145	VSS	176	VSS
24	DQ17	54	VDDQ	85	VDD	116	VSS	146	DQ36	177	DM7
25	DQS2	55	DQ33	86	DQS7	117	DQ21	147	DQ37	178	DQ62
26	VSS	56	DQS4	87	DQ58	118	A11	148	VDD	179	DQ63
27	A9	57	DQ34	88	DQ59	119	DM2	149	DM4	180	VDDQ
28	DQ18	58	VSS	89	VSS	120	VDD	150	DQ38	181	SA0
29	A7	59	BA0	90	NC	121	DQ22	151	DQ39	182	SA1
30	VDDQ	60	DQ35	91	SDA	122	A8	152	VSS	183	SA2
31	DQ19	61	DQ40	92	SCL	123	DQ23	153	DQ44	184	VDDSPD

Notes:

* These pins are not used in this module.

Pin Names

Pin	Pin Description
CK1, CK1, CK2, CK2	Differential Clock Inputs
CS0	Chip Select Input
CKE0	Clock Enable Input
RAS, CAS, WE	Command Sets Inputs
A0 ~ A12	Address
BA0, BA1	Bank Address
DQ0~DQ63	Data Inputs/Outputs
DQS0~DQS7	Data Strobe Inputs/Outputs
DM0~DM7	Data-in Mask
VDD	Power Supply

Pin	Pin Description
VDDQ	DQs Power Supply
VSS	Ground
VREF	Reference Power Supply
VDDSPD	Power Supply for SPD
SA0~SA2	E ² PROM Address Inputs
SCL	E ² PROM Clock
SDA	E ² PROM Data I/O
VDDID	VDD Identification Flag
DU	Do not Use
NC	No Connection

Serial Presence Detect Information

Bin Sort:

A1 (PC1600 @ 2-2-2)

B0 (PC2100B @ 2.5-3-3)

B1 (PC2100A @ 2-2-2)

C0 (PC2700 @ 2.5-3-3)

D0 (PC3200 @ 2.5-3-3)

D3 (PC3200 @ 3-3-3)

D4 (PC3200 @ 3-4-4)

Byte #	Function described	Function Supported							Hex value						
		A1	B0	B1	C0	D0	D3	D4	A1	B0	B1	C0	D0	D3	D4
0	Defines # of Bytes written into serial memory at module manufacturer	128bytes							80h						
1	Total # of Bytes of SPD memory device	256bytes							08h						
2	Fundamental memory type	SDRAM DDR							07h						
3	# of row address on this assembly	13							0Dh						
4	# of column address on this assembly	10							0Ah						
5	# of module Rows on this assembly	1 Bank							01h						
6	Data width of this assembly	64 bits							40h						
7	Data width of this assembly	-							00h						
8	VDDQ and interface standard of this assembly	SSTL 2.5V							04h						
9	DDR SDRAM cycle time at highest CAS Latency	8ns	7.5ns	7ns	6ns	5ns	5ns	5ns	80h	75h	70h	60h	50h	50h	50h
10	DDR SDRAM Access time from clock at highest CL	±0.8 ns	±0.75 ns	±0.75 ns	±0.70 ns	±0.65 ns	±0.65 ns	±0.65 ns	80h	75h	75h	70h	65h	65h	65h
11	DIMM configuration type(Non-parity, Parity, ECC)	Non-parity, ECC							00h						
12	Refresh rate & type	7.8us & Self refresh							82h						
13	Primary DDR SDRAM width	x8							08h						
14	Error checking DDR SDRAM data width	N/A							00h						
15	Minimum clock delay for back-to-back random column address	t _{CCD} =1CLK							01h						
16	DDR SDRAM device attributes : Burst lengths supported	2,4,8							0Eh						
17	DDR SDRAM device attributes : # of banks on each DDR SDRAM	4 banks							04h						
18	DDR SDRAM device attributes : CAS Latency supported	2,2.5,3							0Ch	0Ch	0Ch	0Ch	1Ch	1Ch	1Ch
19	DDR SDRAM device attributes : CS Latency	0CLK							01h						
20	DDR SDRAM device attributes : WE Latency	1CLK							02h						
21	DDR SDRAM module attributes	Differential clock / non Registered							20h						
22	DDR SDRAM device attributes : General	+/-0.2V voltage tolerance							00h						
23	DDR SDRAM cycle time at second highest CL	10ns	10ns	7.5ns	7.5ns	5.0ns	6.0ns	6.0ns	A0h	A0h	75h	75h	50h	60h	60h
24	DDR SDRAM Access time from clock at highest CL	±0.8 ns	±0.75 ns	±0.75 ns	±0.70 ns	±0.65 ns	±0.70 ns	±0.70 ns	80h	75h	75h	70h	65h	70h	70h

Serial Presence Detect Information (cont.)

Byte #	Function described	Function Supported							Hex value						
		A1	B0	B1	C0	D0	D3	D4	A1	B0	B1	C0	D0	D3	D4
25	DDR SDRAM cycle time at third highest CL	-	-	-	-	7.5ns	7.5ns	7.5ns	00h	00h	00h	00h	75h	75h	75h
26	DDR SDRAM Access time from clock at third highest CL	-	-	-	-	±0.75 ns	±0.75 ns	±0.75 ns	00h	00h	00h	00h	75h	75h	75h
27	Minimum row precharge time (=t _{RP})	20ns	20ns	15ns	18ns	15ns	15ns	20ns	50h	50h	3Ch	48h	3Ch	3Ch	50h
28	Minimum row activate to row active delay(=t _{R RD})	15ns	15ns	15ns	12ns	10ns	10ns	10ns	3Ch	3Ch	3Ch	30h	28h	28h	28h
29	Minimum RAS to CAS delay(=t _{R CD})	20ns	20ns	15ns	18ns	15ns	15ns	20ns	50h	50h	3Ch	48h	3Ch	3Ch	50h
30	Minimum active to precharge time(=t _{R AS})	50ns	45ns	45ns	42ns	40ns	40ns	40ns	32h	2Dh	2Dh	2Ah	28h	28h	28h
31	Module ROW density	256MB							40h						
32	Command and address signal input setup time	1.1ns	0.9ns	0.9ns	0.75 ns	0.6ns	0.6ns	0.6ns	B0h	90h	90h	75h	60h	60h	60h
33	Command and address signal input hold time	1.1ns	0.9ns	0.9ns	0.75 ns	0.6ns	0.6ns	0.6ns	B0h	90h	90h	75h	60h	60h	60h
34	Data signal input setup time	0.6ns	0.5ns	0.5ns	0.45 ns	0.4ns	0.4ns	0.4ns	60h	50h	50h	45h	40h	40h	40h
35	Data signal input hold time	0.6ns	0.5ns	0.5ns	0.45 ns	0.4ns	0.4ns	0.4ns	60h	50h	50h	45h	40h	40h	40h
36-40	Superset information (may be used in future)								00h						
41	SDRAM device minimum active to active/auto-refresh time (=t _{RC})	70ns	65ns	65ns	60ns	60ns	60ns	60ns	46h	41h	41h	3Ch	3Ch	3Ch	3Ch
42	SDRAM device minimum active to autorefresh to active/auto-refresh time (=t _{R FC})	80ns	75ns	75ns	72ns	70ns	70ns	70ns	50h	4Bh	4Bh	48h	46h	46h	46h
43	SDRAM device maximum device cycle time (=t _{CK MAX})	12ns	12ns	12ns	12ns	12ns	12ns	12ns	30h	30h	30h	30h	30h	30h	30h
44	SDRAM device maximum skew between DQS and DQ signals (=t _{D QS Q})	0.6ns	0.5ns	0.5ns	0.45 ns	0.4ns	0.4ns	0.4ns	3Ch	32h	32h	2Dh	28h	28h	28h
45	SDRAM device maximum read datahold skew factor (=t _{Q HS})	1ns	0.75 ns	0.75 ns	0.60 ns	0.55 ns	0.55 ns	0.55 ns	A0h	75h	75h	60h	55h	55h	55h
46-61	Superset information (may be used in future)	-							00h						
62	SPD data revision code	Initial release							00h	00h	00h	00h	11h	11h	11h
63	Checksum for Bytes 0 ~ 62	-							E7h	22h	CAh	4Bh	A3h	BEh	E6h
64	Manufacturer JEDEC ID code	Mosel Vitelic							40h						
65 -71	 Manufacturer JEDEC ID code								00h						

Byte #	Function described	Function Supported							Hex value						
		A1	B0	B1	C0	D0	D3	D4	A1	B0	B1	C0	D0	D3	D4
72	Manufacturing location	02=Taiwan 05=China 0A=S-CH													
73-90	Module part number (ASCII)	V826632K24S													
91	Manufacturer revision code (For PCB)	0							00						
92	Manufacturer revision code (For component)	0							00						
93	Manufacturing date (Week)	-							-						
94	Manufacturing date (Year)	-							-						
95-98	Assembly serial #	-							-						
99-127	Manufacturer specific data (may be used in future)	Undefined							00h						
128-255	Open for customer use	Undefined							00h						

DC Operating Conditions

($T_A = 0$ to 70°C , Voltage referenced to $V_{SS} = 0\text{V}$)

Parameter	Symbol	Min	Typ.	Max	Unit	Note
Power Supply Voltage	V_{DD}	2.3	2.5	2.7	V	
Power Supply Voltage for DDR400	V_{DD}	2.5	2.6	2.7	V	
Power Supply Voltage	V_{DDQ}	2.3	2.5	2.7	V	1
Power Supply Voltage for DDR400	V_{DDQ}	2.5	2.6	2.7	V	1
Input High Voltage	V_{IH}	$V_{REF} + 0.15$	-	$V_{DDQ} + 0.3$	V	
Input Low Voltage	V_{IL}	-0.3	-	$V_{REF} - 0.15$	V	2
I/O Termination Voltage	V_{TT}	$V_{REF} - 0.04$	V_{REF}	$V_{REF} + 0.04$	V	
Reference Voltage	V_{REF}	$V_{DDQ/2} - 0.05$	-	$V_{DDQ/2} + 0.05$	V	
Input Leakage Current	I_I	-2	-	2	μA	
Output Leakage Current	IO_Z	-5	-	5	μA	
Output High Current ($V_{OUT} = 1.95\text{V}$)	IO_H	-16.8	-	-	mA	
Output Low Current ($V_{OUT} = 0.35\text{V}$)	IO_L	16.8	-	-	mA	

Notes: 1. V_{DDQ} must not exceed the level of V_{DD} .
2. V_{IL} (min) is acceptable -1.5V AC pulse width with $\leq 5\text{ns}$ of duration.


AC Operating Conditions(T_A = 0 to 70 °C, Voltage referenced to V_{SS} = 0V)

Parameter	Symbol	Min	Max	Unit	Note
Input High (Logic 1) Voltage, DQ, DQS and DM signals	V _{IH(AC)}	V _{REF} + 0.31		V	
Input Low (Logic 0) Voltage, DQ, DQS and DM signals	V _{IL(AC)}		V _{REF} - 0.31	V	
Input Differential Voltage, CK and $\overline{\text{CK}}$ inputs	V _{ID(AC)}	0.7	V _{DDQ} + 0.6	V	1
Input Crossing Point Voltage, CK and $\overline{\text{CK}}$ inputs	V _{IX(AC)}	0.5*V _{DDQ} -0.2	0.5*V _{DDQ} +0.2	V	2

Notes: 1. VID is the magnitude of the difference between the input level on CK and the input on $\overline{\text{CK}}$.
 2. The value of VIX is expected to equal 0.5*V_{DDQ} of the transmitting device and must track variations in the DC level of the same.

AC Operating Test Conditions (T_A = 0 to 70°C, Voltage referenced to V_{SS} = 0V)

Parameter	Value	Unit
Reference Voltage	V _{DDQ} × 0.5	V
Termination Voltage	V _{DDQ} × 0.5	V
AC Input High Level Voltage (V _{IH} , min)	V _{REF} + 0.31	V
AC Input Low Level Voltage (V _{IL} , max)	V _{REF} - 0.31	V
Input Timing Measurement Reference Level Voltage	V _{REF}	V
Output Timing Measurement Reference Level Voltage	V _{TT}	V
Input Signal maximum peak swing	1.5	V
Input minimum Signal Slew Rate	1	V/ns
Termination Resistor (R _T)	50	ohm
Series Resistor (R _S)	25	ohm
Output Load Capacitance for Access Time Measurement (C _L)	30	pF



Output Load Circuit (SSTL_2)

Input/Output Capacitance(V_{DD} = 2.5V, V_{DD} = 2.6V, V_{DDQ} = 2.5V, V_{DDQ} = 2.6V, T_A = 25°C, f = 1MHz)

Parameter	Symbol	Min	Max	Unit
Input capacitance (A ₀ ~ A ₁₁ , BA ₀ ~ BA ₁ , $\overline{\text{RAS}}$, $\overline{\text{CAS}}$, $\overline{\text{WE}}$)	CIN ₁	29	34	pF
Input capacitance (CKE ₀)	CIN ₂	29	34	pF
Input capacitance ($\overline{\text{CS}}_0$)	CIN ₃	26	30	pF
Input capacitance (CLK ₁ , CLK ₂)	CIN ₄	30	32	pF
Data & DQS input/output capacitance (DQ ₀ ~DQ ₆₃)	C _{OUT}	8	9	pF
Input capacitance (DM0~DM8)	CIN ₅	8	9	pF

DDR SDRAM Module I_{DD} Spec Table

Symbol		A1 PC1600@CL=2	B0 PC2100B@CL=2.5	B1 PC2100A@CL=2	C0 PC2700A@CL=2.5	D0/D3/D4 PC3200@CL=3	Unit
IDD0		720	800	800	880	960	mA
IDD1		800	960	960	1120	1280	mA
IDD2P		60	60	60	60	60	mA
IDD2F		200	250	250	280	330	mA
IDD2Q		130	170	170	190	220	mA
IDD3P		240	260	260	300	340	mA
IDD3N		360	380	380	480	580	mA
IDD4R		1200	1520	1520	1840	2160	mA
IDD4W		1040	1360	1360	1680	2000	mA
IDD5		1440	1520	1520	1600	1680	mA
IDD6	Normal	48	48	48	48	48	mA
	Low power	29	29	29	29	29	mA
IDD7		2000	2400	2400	2800	3200	mA

AC Characteristics (AC operating conditions unless otherwise noted)

Parameter		Sym- bol	(PC400A) D0		(PC400B) D3		(PC400C) D4		(PC333) C0		(PC266A) B1		(PC266B) B0		(PC200) A1		Units	Note
			Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
Row Cycle Time		t _{RC}	60	-	60	-	60	-	60	-	65	-	65	-	70	-	ns	
Auto Refresh Row Cycle Time		t _{RFC}	70	-	70	-	70	-	72	-	75	-	75	-	80	-	ns	
Row Active Time		t _{RAS}	40	120K	40	120K	40	120K	42	120K	45	120K	45	120K	50	120K	ns	
Row Address to Column Address Delay		t _{RCD}	15	-	15	-	20	-	18	-	15	-	20	-	20	-	ns	
Row Active to Row Active Delay		t _{RRD}	10	-	10	-	10	-	12	-	15	-	15	-	15	-	ns	
Column Address to Column Address Delay		t _{CCD}	1	-	1	-	1	-	1	-	1	-	1	-	1	-	tCK	
Row Precharge Time		t _{RP}	15	-	15	-	20	-	18	-	15	-	20	-	20	-	ns	
Write Recovery Time		t _{WR}	15	-	15	-	15	-	15	-	15	-	15	-	15	-	ns	
Last Data-In to Read Command		t _{DRL}	1	-	1	-	1	-	1	-	1	-	1	-	1	-	tCK	
Auto Precharge Write Recovery + Precharge Time		t _{DAL}	35	-	35	-	35	-	35	-	35	-	35	-	35	-	ns	
System Clock Cycle Time	$\overline{\text{CAS}}$ Latency = 3	t _{CK}	5	12	5	12	5	12	-	12	-	12	-	12	-	12	ns	
	$\overline{\text{CAS}}$ Latency = 2.5		5	12	6	12	6	12	6	12	7	12	7.5	12	8	12	ns	
	$\overline{\text{CAS}}$ Latency = 2		7.5	12	7.5	12	7.5	12	7.5	12	7.5	12	10	12	10	12	ns	
Clock High Level Width		t _{CH}	0.45	0.55	0.45	0.55	0.45	0.55	0.45	0.55	0.45	0.55	0.45	0.55	0.45	0.55	tCK	
Clock Low Level Width		t _{CL}	0.45	0.55	0.45	0.55	0.45	0.55	0.45	0.55	0.45	0.55	0.45	0.55	0.45	0.55	tCK	
Data-Out edge to Clock edge Skew		t _{AC}	-0.65	0.65	-0.65	0.65	-0.65	0.65	-0.75	0.75	-0.75	0.75	-0.75	0.75	-0.8	0.8	tCK	
DQS-Out edge to Clock edge Skew		t _{DQSK}	-0.60	0.60	-0.60	0.60	-0.60	0.60	-0.75	0.75	-0.75	0.75	-0.75	0.75	-0.8	0.8	tCK	
DQS-Out edge to Data-Out edge Skew		t _{DQSQ}	-	0.40	-	0.40	-	0.40	-	0.45	-	0.5	-	0.5	-	0.6	tCK	
Data-Out hold time from DQS		t _{QH}	t _{HPmin} - 0.75ns	-	t _{HPmin} - 0.75ns	-	t _{HPmin} - 0.75ns	-	t _{HPmin} - 0.75ns	-	t _{HPmin} - 0.75ns	-	t _{HPmin} - 0.75ns	-	t _{HPmin} - 0.75ns	-	tCK	1
Clock Half Period		t _{HP}	t _{CH/L} min	-	t _{CH/L} min	-	t _{CH/L} min	-	t _{CH/L} min	-	t _{CH/L} min	-	t _{CH/L} min	-	t _{CH/L} min	-	tCK	1
Input Setup Time (fast slew rate)		t _{IS}	0.6	-	0.6	-	0.6	-	0.75	-	0.9	-	0.9	-	1.1	-	tCK	2,3,5,6

AC Characteristics (cont.)

Parameter	Symbol	(PC400A) D0		(PC400B) D3		(PC400C) D4		(PC333) C0		(PC266A) B1		(PC266B) B0		(PC200) A1		Units	Note
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
Input Hold Time (fast slew rate)	t_{IH}	0.6	-	0.6	-	0.6	-	0.75	-	0.9	-	0.9	-	1.1	-	tCK	2,3,5,6
Input Setup Time (slow slew rate)	t_{IS}	0.75	-	0.75	-	0.75	-	0.8	-	1.0	-	1.0	-	1.1	-	tCK	2,4,5,6
Input Hold Time (slow slew rate)	t_{IH}	0.75	-	0.75	-	0.75	-	0.8	-	1.0	-	1.0	-	1.1	-	tCK	2,4,5,6
Input Pulse Width	t_{IPW}	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	2.2	-	2.2	-	-	-	tCK	6
Write DQS High Level Width	t_{DQSH}	0.35		0.35		0.35		0.35		0.35		0.35		0.35		tCK	
Write DQS Low Level Width	t_{DQSL}	0.35		0.35		0.35		0.35		0.35		0.35		0.35		tCK	
CLK to First Rising edge of DQS-In	t_{DQSS}	0.72	1.25	0.72	1.25	0.72	1.25	0.75	1.25	0.75	1.25	0.75	1.25	0.75	1.25	tCK	
Data-In Setup Time to DQS-In (DQ & DM)	t_{DS}	0.40	-	0.40	-	0.40	-	0.45	-	0.5	-	0.5	-	0.6	-	tCK	7
Data-in Hold Time to DQS-In (DQ & DM)	t_{DH}	0.40	-	0.40	-	0.40	-	0.45	-	0.5	-	0.5	-	0.6	-	tCK	7
DQ & DM Input Pulse Width	t_{DIPW}	1.75	-	1.75	-	1.75	-	1.75	-	1.75	-	1.75	-	2	-	tCK	
Read DQS Preamble Time	t_{RPRE}	0.9	1.1	0.9	1.1	0.9	1.1	0.9	1.1	0.9	1.1	0.9	1.1	0.9	1.1	tCK	
Read DQS Postamble Time	t_{RPST}	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	tCK	
Write DQS Preamble Setup Time	t_{WPRES}	0	-	0	-	0	-	0	-	0	-	0	-	0	-	tCK	
Write DQS Preamble Hold Time	t_{WPREH}	0.25	-	0.25	-	0.25	-	0.25	-	0.25	-	0.25	-	0.25	-	tCK	
Write DQS Postamble Time	t_{WPST}	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	tCK	
Mode Register Set Delay	t_{MRD}	2	-	2	-	2	-	2	-	2	-	2	-	2	-	tCK	
Power Down Exit Time to any command	t_{XPDN}	1	-	1	-	1	-	1	-	1	-	1	-	1	-	tCK	
Exit Self Refresh to Non-Read Command	t_{XSNR}	200	-	200	-	200	-	200	-	200	-	200	-	200	-	tCK	8
Average Periodic Refresh Interval	t_{REFI}	-	7.8	-	7.8	-	7.8	-	7.8	-	7.8	-	7.8	-	7.8	us	

Notes: 1. This calculation accounts for $t_{DQSQ}(\max)$, the pulse width distortion of on-chip circuit and jitter.

2. Data sampled at the rising edges of the clock : A0~A11, BA0~BA1, CKE, CS, RAS, CAS, WE.

3. For command/address input slew rate $\geq 1.0V/ns$

4. For command/address input slew rate $\geq 0.5V/ns$ and $< 1.0V/ns$

5. CK, CK slew rates are $\geq 1.0V/ns$

6. These parameters guarantee device timing, but they are not necessarily tested on each device, and they may be guaranteed by design or tester correlation.

7. Data latched at both rising and falling edges of Data Strobes(DQS) : DQ, DM


8. Minimum of 200 cycles of stable input clocks after Self Refresh Exit command, where CKE is held high, is required to complete Self Refresh Exit and lock the internal DLL circuit of DDR SDRAM.



Absolute Maximum Ratings

Parameter	Symbol	Rating	Unit
Ambient Temperature	T_A	0 ~ 70	°C
Storage Temperature	T_{STG}	-55 ~ 125	°C
Voltage on Any Pin relative to V_{SS}	V_{IN}, V_{OUT}	-0.5 ~ 3.6	V
Voltage on V_{DD} relative to V_{SS}	V_{DD}	-0.5 ~ 3.6	V
Voltage on V_{DDQ} relative to V_{SS}	V_{DDQ}	-0.5 ~ 3.6	V
Output Short Circuit Current	I_{OS}	50	mA
Power Dissipation	P_D	6	W
Soldering Temperature • Time	T_{SOLDER}	260 • 10	°C • Sec

Note: Operation at above absolute maximum rating can adversely affect device reliability

Units: Inches (Millimeters)





WORLDWIDE OFFICES**U.S.A.**

3910 NORTH FIRST STREET
SAN JOSE, CA 95134
PHONE: 408-433-6000
FAX: 408-433-0952

TAIWAN

7F, NO. 102
MIN-CHUAN E. ROAD, SEC. 3
TAIPEI
PHONE: 886-2-2545-1213
FAX: 886-2-2545-1209

SINGAPORE

10 ANSON ROAD #23-13
INTERNATIONAL PLAZA
SINGAPORE 079903
PHONE: 65-6323-1801
FAX: 65-6323-7013

UK & IRELAND

SUITE 50, GROVEWOOD
BUSINESS CENTRE
STRATHCLYDE BUSINESS
PARK
BELLSHILL, LANARKSHIRE,
SCOTLAND, ML4 3NQ
PHONE: 44-1698-748515
FAX: 44-1698-748516

NO 19 LI HSIN ROAD
SCIENCE BASED IND. PARK
HSIN CHU, TAIWAN, R.O.C.
PHONE: 886-3-579-5888
FAX: 886-3-566-5888

JAPAN

ONZE 1852 BUILDING 6F
2-14-6 SHINTOMI, CHUO-KU
TOKYO 104-0041
PHONE: 03-3537-1400
FAX: 03-3537-1402

U.S. SALES OFFICES**WEST**

3910 NORTH FIRST STREET
SAN JOSE, CA 95134
PHONE: 408-433-6000
FAX: 408-433-0952

CENTRAL / EAST

604 FIELDWOOD CIRCLE
RICHARDSON, TX 75081
PHONE: 214-352-3775
FAX: 214-904-9029

The information in this document is subject to change without notice.

MOSEL VITELIC makes no commitment to update or keep current the information contained in this document. No part of this document may be copied or reproduced in any form or by any means without the prior written consent of MOSEL-VITELIC.

MOSEL VITELIC subjects its products to normal quality control sampling techniques which are intended to provide an assurance of high quality products suitable for usual commercial applications. MOSEL VITELIC does not do testing appropriate to provide 100% product quality assurance and does not assume any liability for consequential or incidental arising from any use of its products. If such products are to be used in applications in which personal injury might occur from failure, purchaser must do its own quality assurance testing appropriate to such applications.