

Tuning Fork Quartz Crystal

The tuning fork crystal provides the circuit designer with the ultimate in size, performance, and economic trade-offs. This highly reliable, stable, and accurate device is available in two micro-miniature sizes for time base applications operating from a 32.768KHz reference frequency.

WX26B

- Very small, compact SM packaging
- Rugged, resistant to shock and vibration
- Low cost
- Ideal for time of watches and clocks


Specifications:

Frequency Range:	30.000 ~ 120.000 KHz 32.768 KHz Standard
Operating Temperature:	-0°C ~ +60°C -B -10°C ~ +70°C -C -40°C ~ +85°C -L
Storage Temperature:	-40°C ~ +85°C
Frequency Tolerance: (at 25°C)	± 100 ppm -100 ± 50 ppm -50 ± 30 ppm -30 ± 20 ppm -20
Temperature Coefficient:	-0.04 ppm/°C
Circuit Condition:	8 pF ~ 32 pF or series 12.5 pF (Standard) -None
Turnover Temperature:	25 ± 5 °C
Series Resistance:	Maximum resistance corresponds to frequency. Please see R table.
Drive Level:	1.0 µW max
Series Capacitance:	4.0 fF max
Parallel Capacitance:	2.0 pF max
Aging:	± 3 ppm max per year
Optional Features:	Tape & Reel -TR

Note:

1. Other frequencies, tolerances, stabilities, and operating temperature ranges available. Consult VTC Support for specific requirements.
2. Not all combinations of the above tolerances, stabilities, and temperature ranges are available. Consult VTC Support if your requirement is not standard.
3. All specifications subject to change without notice.

WX26B



All dimensions are in mm

Ordering Information

Product name + Temperature Range + CL + Frequency Tolerance + Other Specification Code + Frequency.

i.e. WX26BC50-32.768KHz