



Inductive sensor with analogue output Wi40-M18-LiU5



- threaded barrel, M18 x 1
- chrome-plated brass
- analogue output (current and voltage)
- actuation via short-circuiting ring, blind hole or the like
- 4-wire, 15...30 VDC
- cable connection


Wiring diagram



Function principles

Simple control tasks can be accomplished with inductive TURCK sensors with analogue output. They provide a current, voltage or frequency signal that is proportional to the target's distance. With TURCK's analogue sensors, this output signal is linear to the distance of the target over the entire sensing range.


Measuring range



Type	Wi40-M18-LiU5
Ident-No.	1536603
Measuring range [A...B]	0... 40 mm
Mounting mode	non-flush
Min. repeat accuracy	$\leq 1 \%$ of measuring range A - B
	$\leq 0.5 \%$, after a heating period of 0.5 h
Linearity tolerance	$\leq 2 \%$ of final value
Max. relative temperature drift	$\leq \pm 0.06 \%$ / °C
Operating temperature	-10 ... + 70 °C
Rated operational voltage (DC) U_B	15... 30 VDC
Max. ripple	$\leq 10 \%$ U_{pp}
No-load current I_0	≤ 8 mA
Rated insulation voltage	≤ 0.5 kV
Output function	4-wire, analogue output
Short-circuit protection	yes
Wire breakage / reverse polarity protection	yes / complete
Voltage output	0... 10 V
Current output	4... 20 mA
Voltage output load resistance	≥ 4.7 k Ω
Current output load resistance	≤ 0.4 k Ω
Reading rate frequency	40 Hz
Recovery time on output	≤ 12 ms
Housing style	threaded barrel; M18 x 1
Dimensions	107.5 mm
Housing material	metal, CuZn, chrome-plated
Active face	plastic, PA12-GF30
Max. fixing torque of coupling nut	25 Nm
Wiring	cable
Cable	$\varnothing 5.2$, LiYY, PVC, 2 m
Cable cross section	4 x 0.34 mm ²
Vibration resistance	55 Hz (1 mm)
Shock resistance	30 x g (11 ms)
Degree of protection	IP67


Inductive sensor with analogue output Wi40-M18-LiU5

Mounting instructions	minimum gap
Gap D	3 x B
Gap W	3 x Sn
Gap T	3 x B
Gap S	1,5 x B
Gap G	6 x Sn
Gap N	2 x Sn
Diameter of active face B	Ø 18 mm



Inductive sensor with analogue output Wi40-M18-LiU5

Accessories

Typ	Ident-No.	Description	Dimension drawing
IM43-13-SR	7540041	limit value monitor; single channel; input 0/4...20 mA or 0/2...10 V; supply of 2- or 3-wire transmitters/sensors; limit value adjustment via teach button; three relay outputs with one normally open contact each; removeable terminal blocks; 27 mm wide; universal voltage supply 20...250 VUC; further limit value monitors are described in our "Interface Technology" catalogue.	
QM-18	6945102	quick-mount fixing clamp with dead-stop; material: chrome-plated brass external thread M24 x 1,5.	
BST-18B	6947214	fixing clamp with dead-stop; material: PA6	